Assignment:NOSQL Assignment

1.Create a new database named CDAC and connect to it.

```
test> use CDAC
switched to db CDAC
```

2. Display the list of collections in the CDAC database.

```
CDAC> show collections;
```

3. Create a collection named LIBRARY.

```
CDAC> db.LIBRARY
CDAC.LIBRARY
```

4. Insert a document into LIBRARY with:
title: MongoDB programming, author: Amit, likes: 100

```
CDAC> db.LIBRARY.insertOne({title:'MongoDB programming',author:'Amit',likes:
100})
{
  acknowledged: true,
  insertedId: ObjectId('69b945115291cf48d14eeb86')
}
CDAC> db.LIBRARY.find()
[
  {
    _id: ObjectId('69b945115291cf48d14eeb86'),
    title: 'MongoDB programming',
    author: 'Amit',
    likes: 100
  }
]
CDAC> |
```

5. Display the inserted document and note the _id field.

```
CDAC> db.LIBRARY.find({},{_id:1,title:1,author:1,likes:1})
[
  {
    _id: ObjectId('69b945115291cf48d14eeb86'),
    title: 'MongoDB programming',
    author: 'Amit',
    likes: 100
  }
]
CDAC>
```

6. Insert another document into LIBRARY with:
title: MySQL programming, authors: [Jack, Jill], likes: 200

```
CDAC> db.LIBRARY.insertOne({title:'MYSQL programming',authors:['Jack','Jill'
],likes:200})
{
  acknowledged: true,
  insertedId: ObjectId('69b947025291cf48d14eeb87')
}
CDAC> db.LIBRARY.find()
[
  {
    _id: ObjectId('69b945115291cf48d14eeb86'),
    title: 'MongoDB programming',
    author: 'Amit',
    likes: 100
  },
  {
    _id: ObjectId('69b947025291cf48d14eeb87'),
    title: 'MYSQL programming',
    authors: [ 'Jack', 'Jill' ],
    likes: 200
  }
]
CDAC> |
```

7. Display all documents in the LIBRARY collection.

```
CDAC> db.LIBRARY.find()
[
  {
    _id: ObjectId('69b945115291cf48d14eeb86'),
    title: 'MongoDB programming',
    author: 'Amit',
    likes: 100
  },
  {
    _id: ObjectId('69b947025291cf48d14eeb87'),
    title: 'MYSQL programming',
    authors: [ 'Jack', 'Jill' ],
    likes: 200
  }
]
CDAC> |
```

8. Display only the first inserted document.

```
CDAC> db.LIBRARY.findOne();
{
  _id: ObjectId('69b945115291cf48d14eeb86'),
  title: 'MongoDB programming',
  author: 'Amit',
  likes: 100
}
CDAC> |
```

9. Display documents using the pretty() method.

```
CDAC> db.LIBRARY.find().pretty();
[
  {
    _id: ObjectId('69b945115291cf48d14eeb86'),
    title: 'MongoDB programming',
    author: 'Amit',
    likes: 100
  },
  {
    _id: ObjectId('69b947025291cf48d14eeb87'),
    title: 'MYSQL programming',
    authors: [ 'Jack', 'Jill' ],
    likes: 200
  }
]
CDAC>
```

10. Update the document where author = Amit to Amit Sharma.

```
CDAC> db.LIBRARY.updateOne({author:'Amit'},{$set:{author:'Amit Sharma'}})
{
  acknowledged: true,
  insertedId: null,
  matchedCount: 1,
  modifiedCount: 1,
  upsertedCount: 0
}
CDAC> db.LiBRARY.find()

CDAC> db.LIBRARY.find()
[
  {
    _id: ObjectId('69b945115291cf48d14eeb86'),
    title: 'MongoDB programming',
    author: 'Amit Sharma',
    likes: 100
  },
  {
    _id: ObjectId('69b947025291cf48d14eeb87'),
    title: 'MYSQL programming',
    authors: [ 'Jack', 'Jill' ],
    likes: 200
  }
]
CDAC>
```

11. Delete all documents with likes = 100.

```
CDAC> db.LIBRARY.deleteMany({likes:100})
{ acknowledged: true, deletedCount: 1 }
CDAC> db.LIBRARY.find()
[
  {
    _id: ObjectId('69b947025291cf48d14eeb87'),
    title: 'MYSQL programming',
    authors: [ 'Jack', 'Jill' ],
    likes: 200
  }
]
CDAC>
```

12. Drop the LIBRARY collection.

```
CDAC> db.LIBRARY.drop()
true
```

13. Drop the CDAC database.

```
CDAC> db.dropDatabase('CDAC')
{ ok: 1, dropped: 'CDAC' }
CDAC>
```