Assignment -1 Creating sample tables and inserting values.

Create the following tables with the given structures and insert sample data as specified: -

```
A) SALESPEOPLE

Snum int(4)

Sname varchar(10)

City varchar(10)

Comm float(3,2)

Queries:-

Create table salespeople

(

Snum int(4),

Sname varchar(10),

City varchar(10),

Comm float(3,2)

);
```

B) CUSTOMERS

```
C:\WINDOWS\system32\cmd. × + ~
D3_92975_siddarth> use dbt1;
Database changed
D3_92975_siddarth> select Snum , Sname, city,Comm from salespeople;
 Snum
         Sname
                   city
                                Comm
 1001
                                0.12
         peel
                   London
  1002
         Serres
                   San Jose
                                0.13
 1004
         Motika
                   London
                                0.11
         Rifkin
 1007
                   Barcelona
                                0.15
 1003
         Axelrod
                   New York
                                0.10
 rows in set (0.00 sec)
```

```
Cnum int(4)
Cname varchar(10)
City varchar(10)
```

Rating int(4)

```
Snum int(4)
Queries:-
   Create table customers
(
Cnum int(4),
Cname varchar(10),
City varchar(10),
Rating int(4),
Snum int(4)
);
 D3_92975_siddarth>use dbt1
 Database changed
                          select Cnum, Cname, city, Rating
 D3_92975_siddarth>
      -> Snum from costomers;
   Cnum
            Cname
                          city
                                        Snum
            Hoffman
    2001
                          London
                                         100
    2002
            Giovanni
                          Rome
                                         200
                                         200
    2003
            Lio
                          San Jose
    2004
            Grass
                          Barlin
                                         300
    2006
            Clemens
                          London
                                         100
                          San Jose
    2008
            Cisneros
                                         300
    2007
                          Rome
                                         100
 7 rows in set (0.00 sec)
C) ORDERS
    Onum int(4)
    Amt float(7,2)
    Odate date
   Cnum int(4)
   Snum int(4)
Queries :-
  Create table orders
(
```

```
Onum int(4)
```

Amt float(7,2)

Odate date

Cnum int(4)

Snum int(4)

);

D3_92975_siddarth> select Onum,Amt, Odate, -> Cnum,Snum from orders;				
Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003 3002	767.19 1900.10	1990-10-03 1990-10-03	2001 2007	1001 1004
3005 3006	5160.45 1098.16	1990-10-03 1990-10-03	2003 2008	1002 1007
3009 3007	1713.23 75.75	1990-10-04 1990-10-04	2002 2004	1003 1002
3008	4723.00	1990-10-05	2006	1001
3010 3011	1309.95 9891.88	1990-10-06 1990-10-06	2004 2006	1002 1001
++ 10 rows in set (0.00 sec)				