1. Create an index that will enable a user to pull orders for ‘1990-10-03’ out of the Orders table quickly.

```
D3_96509_Aditya> CREATE INDEX idx_orders_odate
    -> ON Orders(odate);
Query OK, 0 rows affected, 1 warning (0.03 sec)
Records: 0  Duplicates: 0  Warnings: 1

D3_96509_Aditya> |
```

2. If the Orders table has already been created, how can you force the onum field to be unique (assume all current values are unique)?

```
D3_96509_Aditya> CREATE UNIQUE INDEX idx_orders_onum
    -> ON Orders(onum);
Query OK, 0 rows affected, 1 warning (0.04 sec)
Records: 0  Duplicates: 0  Warnings: 1

D3_96509_Aditya> |
```

3. Create an index that would permit salesperson to retrieve his orders.

```
D3_96509_Aditya> CREATE INDEX idx_orders_snum
    -> ON Orders(snum);
Query OK, 0 rows affected, 1 warning (0.04 sec)
Records: 0  Duplicates: 0  Warnings: 1

D3_96509_Aditya> |
```

4. Let us assume that each salesperson is to have only one customer of a given rating, and this is currently the case. Create an index that enforces it.

```
D3_96509_Aditya> CREATE UNIQUE INDEX idx_customers_snum_rating
    -> ON Customers(snum, rating);
ERROR 1062 (23000): Duplicate entry '1001-100' for key 'customers.idx_custom
ers_snum_rating'
D3_96509_Aditya> |
```

5. Create an index to speed up searching order on a given date by given customer.

```
D3_96509_Aditya> CREATE UNIQUE INDEX idx_customers_snum_rating
    -> ON Customers(snum, rating);
ERROR 1062 (23000): Duplicate entry '1001-100' for key 'customers.idx_custom
ers_snum_rating'
D3_96509_Aditya> CREATE INDEX idx_orders_odate_cnum
    -> ON Orders(odate, cnum);
Query OK, 0 rows affected (0.03 sec)
Records: 0  Duplicates: 0  Warnings: 0

D3_96509_Aditya> |
```