1.Write a query that counts the number of salespeople registering orders for each day. (If a salesperson has more than one order on a given day, he or she should be counted only once.).

```
D3_96509_Aditya> SELECT odate, COUNT(DISTINCT snum) AS salesperson_count
    -> FROM orders
    -> GROUP BY odate;
+------------+--------------------+
| odate      | salesperson_count |
+------------+--------------------+
| 1990-10-03 |                  4 |
| 1990-10-04 |                  3 |
+------------+--------------------+
2 rows in set (0.00 sec)
```

2. Write a query on the Customers table that will find the highest rating in each city. Put the output in this form: For the city (city), the highest rating is: (rating).

```
D3_96509_Aditya> SELECT city ,MAX(rating) As result FROM customers GROUP BY city;
+----------+--------+
| city     | result |
+----------+--------+
| London   |    100 |
| Rome     |    200 |
| San Jose |    300 |
| Berlin   |    300 |
+----------+--------+
4 rows in set (0.00 sec)
```

3 Write an SQL query to calculate the total order amount for each day and display the results in descending order of total orders.

```
D3_96509_Aditya> SELECT odate, SUM(amt) AS Total FROM orders GROUP BY odate ORDER BY odate
DESC;
+------------+----------+
| odate      | Total    |
+------------+----------+
| 1990-10-04 | 16713.81 |
| 1990-10-03 |  8944.59 |
+------------+----------+
2 rows in set (0.00 sec)
```

3. Write a query that selects the total amount in orders for each salesperson for whom this total is greater than the average amount of the order in the table. (Note Use the average amount value directly →2565.84)

```
D3_96509_Aditya> SELECT snum, SUM(amt) AS total FROM orders GROUP BY snum HAVING total > 25
65.84;
+------+----------+
| snum | total    |
+------+----------+
| 1001 | 15382.07 |
| 1002 |  5546.15 |
+------+----------+
2 rows in set (0.00 sec)
```

4. Write a query that selects the highest rating in each city.

```
D3_96509_Aditya> SELECT city ,MAX(rating) As Rating FROM customers GROUP BY city;
+----------+--------+
| city     | Rating |
+----------+--------+
| London   |    100 |
| Rome     |    200 |
| San Jose |    300 |
| Berlin   |    300 |
+----------+--------+
4 rows in set (0.00 sec)
```

5. Retrieve the maximum order amount for each salesperson from the orders table, including only those orders whose value exceeds Rs. 3000.

```
D3_96509_Aditya> SELECT snum,MAX(amt) FROM orders GROUP BY snum HAVING  MAX(amt)>3000 ORDER
 BY MAX(amt) DESC;
+------+----------+
| snum | MAX(amt) |
+------+----------+
| 1001 |  9891.88 |
| 1002 |  5160.45 |
+------+----------+
2 rows in set (0.00 sec)
```

7. Write an SQL query to find the smallest order placed by every customer.

```
D3_96509_Aditya> SELECT cnum ,MIN(amt) FROM orders GROUP BY cnum ORDER BY cnum;
+------+----------+
| cnum | MIN(amt) |
+------+----------+
| 2001 |   767.19 |
| 2002 |  1713.23 |
| 2003 |  5160.45 |
| 2004 |    75.75 |
| 2006 |  4723.00 |
| 2007 |  1900.10 |
| 2008 |    18.69 |
+------+----------+
7 rows in set (0.00 sec)
```