this area, a grounded LCI, will be used for air-to-ground gunnery exercises.

(ii) A circular area immediately north of Marquesas Keys with a radius of two nautical miles having its center at latitude 24°38'20", longitude 82°06'25". The target located within this area, a grounded eagle boat, will be used for bombing exercises using water-filled bombs only.

(iii) A rectangular area immediately northeast of Key West bounded as follows: Beginning at latitude 24°40'14", longitude 81°35'12"; thence to latitude 24°38'25", longitude 81°34'38"; thence to latitude 24°37'10", longitude 81°38'46"; thence to latitude 24°38'50", longitude 81°39'23"; thence to the point of beginning. This area, an aircraft rocket range, will be used for air-to-ground rocket firing exercises.

(b) *The regulations.* (1) In advance of scheduled air or surface operations which, in the opinion of the enforcing agency, may be dangerous to watercraft, appropriate warnings will be issued to navigation interests through official government and civilian channels or in such other manner as the District Engineer, Corps of Engineers, Jacksonville, Florida, may direct. Such warnings will specify the location, type, time, and duration of operations, give such other pertinent information as may be required in the interests of safety, and state whether watercraft will be excluded from the zone of operations which is defined as that portion of a danger zone within which watercraft might be endangered by the operations in progress.

(2) Watercraft shall not be prohibited from passing through a danger zone except when the operations being conducted are of such a nature that the exclusion of watercraft from the zone of operations is required in the interests of safety or for accomplishment of the mission, or is considered important to the national security.

(3) When the warning to navigation interests states that watercraft will be excluded from the zone of operations, no vessel shall enter or remain in such area during the period the operations are in progress.

(4) Aircraft and naval vessels conducting operations in a danger zone will exercise caution in order not to endanger watercraft. Operations which may be dangerous to watercraft will not be conducted without first ascertaining that the zone of operations is clear. Any vessel in the zone of operations will be warned to leave, and upon being so warned the vessel shall leave the zone of operations immediately.

(5) The regulations in this section shall be enforced by the Commandant, Seventh Naval District, Jacksonville, Florida, and such agencies as he may designate.

[Regs. June 1, 1948, CE 800.2121 (Florida Straits)—ENGWR] (40 Stat. 266; 33 U. S. C. 1)

[SEAL] EDWARD F. WITSELL,
Major General,
The Adjutant General.

[F. R. Doc. 48-5531; Filed, June 21, 1948; 8:48 a. m.]

TITLE 43—PUBLIC LANDS: INTERIOR

Chapter I—Bureau of Land Management, Department of the Interior

Appendix—Public Land Orders

[Public Land Order 485]

FLORIDA

REVOKING EXECUTIVE ORDER NO. 4014 OF MAY 22, 1924

By virtue of the authority contained in the act of June 25, 1910, 36 Stat. 847, as amended by the act of August 24, 1912, 37 Stat. 497 (43 U. S. C. 141–143), and pursuant to Executive Order No. 9337 of April 24, 1943, it is ordered as follows:

Executive Order No. 4014 of May 22, 1924, withdrawing the unappropriated lands in the following-described areas in aid of legislation, is hereby revoked:

TALLAHASSEE MERIDIAN

T. 2 S., R. 17 W.,
Secs. 30, 31, and 32.
T. 3 S., R. 18 W.,
Secs. 25 and 36.

The areas described, including both public and nonpublic lands, aggregate 2,498.42 acres.

The public lands in the above-described areas will be made subject to disposition by the Director of the Bureau of Land Management under the appropriate public-land laws pursuant to an order to be published simultaneously herewith. Such order will provide for the preference rights to which veterans of World War II are entitled under the act of September 27, 1944, 58 Stat. 747 (43 U. S. C. 279–283).

Applications for lots 7, 8, 10, and 11, sec. 31, T. 2 S., R. 17 W., have been filed under the Color-of-Title Act of December 22, 1928, 45 Stat. 1069 (43 U. S. C. 1068, 1068a).

MASTIN G. WHITE,
Acting Assistant Secretary of the Interior.

JUNE 9, 1948.

[F. R. Doc. 48-5573; Filed, June 21, 1948; 9:45 a. m.]

TITLE 46—SHIPPING

Chapter I—Coast Guard: Inspection and Navigation

[CGFR 48-5]

MARINE ENGINEERING AND MATERIAL SPECIFICATIONS FOR MERCHANT VESSELS

By virtue of the authority vested in me by R. S. 4405, 4417a, 4418, 4426, 4427, 4429, 4430, 4431, 4432, 4433, 4434, 4453, 4491, sec. 14, 29 Stat. 690, 41 Stat. 305, 49 Stat. 1544, 54 Stat. 346, and sec. 5 (e), 55 Stat. 244, as amended (46 U. S. C. 363, 366, 367, 375, 391a, 392, 404, 405, 407, 408, 409, 410, 411, 412, 435, 1333, 50 U. S. C. 1275), and sec. 101 of Reorganization Plan No. 3 of 1946 (11 F. R. 7875), the following corrections shall be made and the following omissions shall be inserted in Coast Guard document CGFR 48-5, Federal Register document 48-2817, filed March 30, 1948, and published in the FEDERAL REGISTER dated March 31, 1948, 13 F. R. 1668, et seq.:

Subchapter F—Marine Engineering

PART 55—PIPING SYSTEMS

SUBPART 55.07—DETAILED REQUIREMENTS

Section 55.07–15 is corrected by changing the description for Figure 55.07–15 (f7) (13 F. R. 1736) to read as follows:

§ 55.07–15 *Joints and flange connections.* * * *

(f) * * *

Figure 55.07–15 (f7). Pipe may be attached to high hub flanges with screwed threads where the end of the pipe and the bore of the flange are machined to a snug fit and the hub screwed and welded to the pipe as shown by Figure 55.07–15 (f7).

PART 56—ARC WELDING, GAS WELDING, AND BRAZING

SUBPART 56.01—ARC WELDING AND GAS WELDING

The text of the regulations in 46 CFR 56.20–10 (g) was inadvertently omitted from the material published in Part 56 on March 31, 1948, and, therefore, Part 56 is amended by adding § 56.01–57 to follow 56.01–55, reading as follows:

§ 56.01–57 *Unreinforced holes in welded joints.* (a) Unreinforced holes may be machine-cut through welded seams which have been stress-relieved and radiographed. The joint efficiency as well as the ligament efficiency shall be considered in calculating the required thickness.

(b) Tubes may be rolled and expanded in such unreinforced holes, or such holes may be threaded: *Provided,* That in the portion of the welded joint in which the holes are cut the following additional requirements are fulfilled:

(1) The welds shall be examined by the paramagnetic powder method on both sides and found to be satisfactory.

(2) The weld shall contain no slag inclusion or defect longer than 0.15T (where T is the thickness of the weld), but in no case greater than ⅜ inch.

(c) If either or both paragraphs (b) (1) and (b) (2) of this section are not complied with, the unreinforced holes for threaded connections or for rolled or expanded tubes may not be placed closer than ¼ inch to the edge of the fused metal, and no deduction need be made in the maximum allowable pressure computed for the same tube layout without a circumferential weld.

(R. S. 4405, 4417a, 4418, 4426, 4427, 4429–4434, 4453, 4491, sec. 14, 29 Stat. 690, 41 Stat. 305, 49 Stat. 1544, 54 Stat. 346, sec. 5 (e), 55 Stat. 244, as amended; 46 U. S. C. 363, 366, 367, 375, 391a, 392, 404, 405, 407–412, 435, 1333, 50 U. S. C. 1275; sec. 101, Reorg. Plan of 1946, 11 F. R. 7875)

Dated: June 15, 1948.

[SEAL] MERLIN O'NEILL,
Rear Admiral, U. S. C. G.,
Acting Commandant.

[F. R. Doc. 48-5538; Filed, June 21, 1948; 8:49 a. m.]