TITLE 24—HOUSING AND HOUSING CREDIT

Chapter VIII—Office of Housing Expediter

PART 825—RENT REGULATIONS UNDER THE HOUSING AND RENT ACT OF 1947, AS AMENDED

COLORADO

Correction to the Controlled Housing Rent Regulation and the Rent Regulation for Controlled Rooms in Rooming Houses and Other Establishments.

Item 4 of Amendment 168 to the Controlled Housing Rent Regulation (§§ 825.1 to 825.12) [1] and of Amendment 166 to the Rent Regulation for Controlled Rooms in Rooming Houses and Other Establishments (§§ 825.81 to 825.92),[1] issued and effective September 21, 1949, is corrected to read as follows:

4. Schedule A, Item 41b, is amended to describe the counties in the Defense-Rental area as follows:

In Fremont County, the metropolitan area of Canon City consisting of the municipalities of Canon City, South Canon and East Canon.

This decontrols the entire Canon City, Colorado, Defense-Rental Area, except the metropolitan area of Canon City consisting of the municipalities of Canon City, South Canon and East Canon, all in the State of Colorado.

(Sec. 204 (d), 61 Stat. 197, as amended by 62 Stat. 37, 94 and by Pub. Law 31, 81st Cong.; 50 U. S. C. App. 1894 (d))

This correction shall be effective as of September 21, 1949.

Issued this 7th day of October 1949.

TIGHE E. WOODS,
Housing Expediter.

[F. R. Doc. 49-8137; Filed, Oct. 10, 1949; 8:48 a. m.]

TITLE 35—PANAMA CANAL

Chapter I—Canal Zone Regulations

Appendix—Canal Zone Orders

[Canal Zone Order 18]

FORT WILLIAM D. DAVIS MILITARY RESERVATION

ESTABLISHMENT OF NEW BOUNDARIES

SEPTEMBER 14, 1949.

By virtue of the authority vested in The President of the United States by section 5 of title 2 of the Canal Zone Code and delegated to me by Executive Order No. 9746 of July 1, 1946, it is ordered as follows:

SECTION 1. *Setting apart of reservation; boundaries.* The following-described areas of land situated in the Canal Zone are hereby reserved and set apart as, and assigned to the uses and purposes of, a military reservation, which shall be known as Fort William D. Davis Military Reservation, and which shall be under the control and jurisdiction of the Secretary of the Army, subject to the provisions of section 2 of this order:

PARCEL NO. I

Beginning at monument No. 41, which is an 8 inch square concrete post, and which is located 100 feet easterly of the centerline of the Panama Railroad right-of-way (centerline of track span towers) and 77 feet more or less north of track span tower 4-15, the geographic position of which monument referred to the Canal Zone triangulation system is in latitude 9°17' N., plus 4,854.0 feet and in longitude 79°54' W., plus 5,900.0 feet from Greenwich.

Thence from said initial point by metes and bounds:

S. 07°32'40" E., 903.3 feet parallel to, and 100.0 feet from, the centerline of the Panama Railroad right-of-way, to monument No. 42, which is an 8 inch square concrete post;

On a curve to the left, parallel to, and 100.0 feet from, the centerline of the Panama Railroad right-of-way, to monument No. 43, which is an 8 inch square concrete post (the chord distance and bearing between monuments No. 42 and No. 43 being 778.9 feet, S. 09°57'40" E.);

S. 12°19'40" E., 57.6 feet to monument No. 44, which is an iron rod in concrete;

N. 32°30'20" E., 262.8 feet to monument No. 44-A, which is an iron rod in concrete;

N. 32°29'20" E., 1252.9 feet to monument No. 44-B, which is an iron rod in concrete, and which is 75.0 feet northwesterly of the Bolivar Highway centerline;

N. 32°40'00" E., 305.6 feet, parallel to, and 75.0 feet from, the Bolivar Highway centerline, to monument No. 2-J, which is an 8 inch square concrete post;

N. 30°35'30" W., 569.7 feet to monument No. 23, which is an 8 inch square concrete post;

S. 72°13'50" W., 392.5 feet to monument No. 23-A, which is an iron rod in concrete;

S. 72°14'20" W., 554.5 feet to monument No. 23-B, which is an iron rod in concrete;

S. 71°32'50" W., 55.9 feet to monument No. 41, the point of beginning.

Parcel No. I as described, contains an area of 31 acres, more or less.

PARCEL NO. II

Beginning at monument No. 13, which is a 1½ inch galvanized iron pipe and which is located on the approximate 90 foot contour of the west shore of the Quebrada Ancha Arm at Gatun Lake, the geographic position of which monument, referred to the Canal Zone triangulation system, is in latitude 9°17' N., plus 4,792.3 feet, and in longitude 79°52' W., plus 4,757.3 feet from Greenwich.

Thence from said initial point by metes and bounds:

N. 89°57'00" W., 1377.9 feet through monuments No. 13-A, 13-B, NFC, 13-C and 13-D (monuments 13-A, 13-C, and 13-D are 2 inch galvanized iron pipes; monuments 13-B and NFC are 8 inch square concrete posts), to monument No. 14, which is a 1½ inch galvanized iron pipe, the distances being 176.7 feet, 116.8 feet, 444.0 feet, 164.8 feet, 325.6 feet and 150.0 feet, successively, from beginning of course; from monument NFC to monument 14, inclusive, the boundary is coincident with the U. S. Naval Reservation, Gatun Tank Farm boundary;

N. 89°58'30" W., 1,396.0 feet, coincident with the U. S. Naval Reservation, Gatun Tank Farm boundary, through monuments Nos. 14-A, 14-B, 14-C, and 14-D (monuments 14-A, 14-B and 14-D are 2 inch galvanized iron pipes; monument 14-C is a 1½ inch galvanized iron pipe) to monument No. 15, which is a 1½ inch galvanized iron pipe, the distances being 96.6 feet, 348.1 feet, 168.9 feet, 556.3 feet and 226.1 feet, successively, from beginning of course;

S. 89°57'40" W., 515.7 feet, through monuments Nos. 15-A, 15-B and 15-C, which are 2 inch galvanized iron pipes, to monument No. 16, which is an iron rod in concrete, the distances being 87.0 feet, 126.5 feet, 263.2 feet and 39.0 feet, successively, from beginning of course; from monument 15 to monument 15-C, the boundary is coincident with the U. S. Naval Reservation, Gatun Tank Farm boundary;

N. 89°54'40" W., 383.0 feet, to monument No. 16-1, which is an iron rod in concrete;

S. 89°54'50" W., 172.2 feet, to monument No. 17-A, which is an iron rod in concrete;

S. 89°10'40" W., 300.1 feet to monument No. 18, which is a 2 inch galvanized iron pipe;

S. 76°04'10" W., 388.5 feet to monument No. 18-1, which is an iron rod in concrete;

S. 74°35'30" W., 507.8 feet to monument No. 18-A, which is an iron rod in concrete;

S. 75°26'30" W., 387.1 feet, to monument No. 18-A 1, which is an iron rod in concrete;

S. 74°47'40" W., 470.1 feet to monument No. 18-B, which is an iron rod in concrete;

S. 75°01'20" W., 93.4 feet, to monument No. 18-B 1, which is an iron rod in concrete;

S. 75°05'10" W., 2268.1 feet, through monuments Nos. 18-B 2, 18-C and 18-D (monument 18-B 2 is an iron rod in concrete, monuments Nos. 18-C and 18-D are 2 inch galvanized iron pipes), to monument No. MR-1, which is an 8 inch square concrete post, the distances being 377.9 feet, 385.1 feet, 891.0 feet and 614.1 feet, successively, from beginning of course;

N. 14°54'50" W., 1369.4 feet, through monuments Nos. MR-1A, MR-1B, MR-1C and MR-1D, all of which are 8 inch square concrete posts, to monument No. MR-1E, which is an 8 inch square concrete post, the distances being 131.6 feet, 241.4 feet, 160.5 feet, 477.6 feet and 358.3 feet, successively, from beginning of course;

N. 14°50'10" W., 314.6 feet, to monument MR-2, which is an 8 inch square concrete post;

N. 89°59'00" W., 281.7 feet, through monument No. MR-2X, which is an 8 inch concrete post, to monument MR-2Y, which is an 8 inch square concrete post, the distance being 144.0 feet and 137.7 feet, successively, from beginning of course;

S. 89°59'40" W., 377.5 feet to monument No. MR-2A, which is an 8 inch square concrete post;

S. 87°12'00" W., 165.6 feet, to monument No. MR-2B, which is an 8 inch square concrete post;

S. 89°29'40" W., 451.4 feet, through monument No. MR-2C, which is an 8 inch square concrete post, to monument MR-2D, which is an 8 inch square concrete post, the distances being 105.1 feet and 346.3 feet, successively, from beginning of course;

N. 88°22'10" W., 403.5 feet, through monument No. MR-2E, which is an 8 inch square concrete post, to monument No. MR-2F, which is an 8 inch square concrete post, the distances being 335.0 feet and 68.5 feet, successively, from beginning of course;

N. 89°45'40" W., 127.5 feet to monument No. MR-3, which is an 8 inch square concrete post;

S. 00°00'30" W., 386.2 feet, to monument No. MR-3A, which is an 8 inch square concrete post;

S. 00°02'20" E., 326.5 feet, to monument No. MR-3B, which is an 8 inch square concrete post, and which monument is the northeast corner of the U. S. Naval Radio Station;

S. 00°01'20" E., 671.9 feet, along the U. S. Naval Radio Station boundary, to monument No. MR-3C, which an 8 inch square concrete post;

N. 89°59'30" W., 719.8, feet, along the U. S. Naval Radio Station boundary, to monument No. MR-3D, which is an 8 inch square concrete post and which is located 25.0 feet easterly from the centerline of Andrews Road;

[1] 14 F. R. 5830.

Parallel to, and 25.0 feet easterly of the centerline of Andrews Road, which curves slightly to the left, and along the U. S. Naval Radio Station boundary, to monument MR-3E, which is an 8 inch square concrete post, the direct bearing and distance being N. 07°55'20" W., 676.8 feet;

N. 88°49'50" E., 14.3 feet, along the northern boundary of the U. S. Naval Radio Station, to monument MR-4, which is a 10 inch square concrete post;

N. 09°28'00" W., 655.7 feet, parallel to, and 40.0 feet from, the centerline of Andrews Road, through monument Number 4-A, which is an 8 inch square concrete post, to monument No. 5, which is an 8 inch square concrete post, the distances being 281.5 feet and 374.2 feet, successively, from beginning of course;

N. 88°02'00" W., 70.0 feet to monument No. 6, which is an 8 inch square concrete post, located 75.0 feet easterly of the centerline of Bolivar Highway.

S. 32°31'30" W., 1,870.9 feet, parallel to, and 75.0 feet easterly of the centerline of Bolivar Highway, through monuments 6-A, 6-B, and 6-C, which are 8 inch square concrete posts, to monument No. 7, which is an 8 inch square concrete post, the distances being 603.4 feet, 304.1 feet, 253.7 feet and 704.7 feet, successively, from beginning of course;

On a curve to the left, parallel to, and 75.0 feet from, the centerline of Bolivar Highway, through monuments 7-A, 7-B and 7-C (monument 7-A is a ½ inch brass plug in curb, 7-B and 7-C are 8 inch square concrete posts), to monument No. 8, which is an 8 inch square concrete post, the chord distances and bearings between monuments being 241.9 feet S. 29°12'40" W., 521.0 feet S. 18°57'00" W., 71.9 feet S. 11°01'30" W., and 177.2 feet S. 07°57'00" W., successively, from beginning of curve;

S. 76°04'00" W., 191.1 feet to monument No. 9, which is an 8 inch square concrete post, located 50.0 feet easterly of the Panama Railroad (Quebrancha cut-off) right-of-way (centerline of track span towers);

S. 12°21'10" E., 2,027.0 feet, parallel to, and 50.0 feet from, the centerline of the Panama Railroad (Quebrancha cut-off) right-of-way, through monuments Nos. 9-A and 9-B, which are 8 inch square concrete posts, to monument No. 10, which is an 8 inch square concrete post, the distances being 1,000.7 feet, 500.3 feet and 526.0 feet, successively, from beginning of course;

Along a curve to the left, parallel to, and 50.0 feet from the centerline of the Panama Railroad (Quebrancha cut-off) right-of-way to monument No. 11, which is an 8 inch square concrete post (the chord distance and bearing between monuments 10 and 11 being 770.4 feet S. 17°02'20" E.);

N. 64°37'20" E., 57.7 feet, to monument No. 19—A, which is an 8 inch square concrete post;

S. 26°31'20" E., 100.9 feet, to monument No. 20-A, which is an 8 inch square concrete post;

S. 62°00'30" W., 57.7 feet, to monument No. 21-A, which is an 8 inch square concrete post, located 50.0 feet easterly of the centerline of the Panama Railroad (Quebrancha cut-off) right-of-way;

Along a curve to the left, parallel to, and 50.0 feet from, the centerline of the Panama Railroad (Quebrancha cut-off) right-of-way, through monuments Nos. 21-B and 21-C, which are 8 inch square concrete posts, to monument No. 22-K, which is an 8 inch square concrete post (the chord distance and bearings between monuments are 83.3 feet, S. 29°08'30" E., 75.8 feet S. 30°48'50" E., and 528.7 feet S. 38°24'20" E., successively, from beginning of curve);

N. 46°26'40" E., 75.0 feet, to monument No. 23-A, which is an 8 inch square concrete post, located 125.0 feet easterly of the centerline of the Panama Railroad (Quebrancha cut-off) right-of-way;

On a curve to the left, parallel to, and 125.0 feet from, the centerline of the Panama Railroad (Quebrancha cut-off) right-of-way, to monument No. 24, which is an 8 inch square concrete post (the chord distance and bearing between monuments 23-A and 24 is 477.2 feet S. 51°14'00" E.);

S. 32°34'00" W., 25.0 feet, to monument No. 25, which is an 8 inch square concrete post, located 100.0 feet easterly of the centerline of the Panama Railroad (Quebranche cut-off) right-of-way;

Along a curve to the left, parallel to, and 100.0 feet from, the centerline of the Panama Railroad (Quebrancha cut-off) right-of-way, through monuments 25-A, 25-B, 25-C, 25-D, 25-E, and 25-F, all of which are 8 inch square concrete posts, to monument No. 26, which is an 8 inch square concrete post, the chord distances and bearings between monuments are 241.3 feet S. 60°27'40" E., 893.2 feet S. 74°58'20" E., 615.5 feet N. 85°43'40" E., 551.1 feet N. 70°55'20" E., 478.0 feet N. 57°58'00" E., 281.7 feet N. 48°46'20" E., 208.0 feet N. 46°01'20" E., successively, from beginning of curve;

N. 45°39'30" E., 443.2 feet, parallel to, and 100.0 feet from, the centerline of the Panama Railroad (Quebrancha cut-off) right-of-way, to monument No. 27, which is an 8 inch square concrete post;

Along a curve to the right, parallel to, and 100.0 feet from, the centerline of the Panama Railroad (Quebrancha cut-off) right-of-way, through monuments 27-A, 27-B, and 27-C, all of which are 8 inch square concrete posts, to monument No. 28, which is an 8 inch square concrete post (the chord distances and bearings between monuments are 140.8 feet N. 45°51'40" E., 504.4 feet N. 49°30'30" E., 422.3 feet N. 56°56'40" E., 116.6 feet N. 59°38'00" E., successively, from beginning of curve);

N. 59°49'00" E., 1047.8 feet, parallel to, and 100.0 feet from, the centerline of the Panama Railroad (Quebrancha cut-off) right-of-way, through monuments 28-A and 28-B, both of which are 8 inch square concrete posts, to monument No. 29, which is an 8 inch square concrete post, the distances being 209.6 feet, 749.8 feet and 88.4 feet, successively, from beginning of course;

Along a curve to the right, parallel to, and 100.0 feet from, the centerline of the Panama Railroad (Quebrancha cut-off) right-of-way, through monuments 29-A, 29-B, 29-C and 29-D, all of which are 8 inch square concrete posts, to monument No. 30, which is an 8 inch square concrete post (the chord distances and bearings between monuments are 666.2 feet N. 63°15'20" E., 105.3 feet N. 71°31'40" E., 528.8 feet N. 80°33'40" E., 594.8 feet S. 85°37'20" E., 80.3 feet S. 81°38'30" E., successively, from beginning of curve);

S. 81°31'40" E., 1981.1 feet, parallel to, and 100.0 feet from, the centerline of the Panama Railroad (Quebrancha cut-off) right-of-way, through monuments 30-A, 30-B, 30-C and 30-D, all of which are 8 inch square concrete posts, to monument No. 31, which is an iron rod in concrete, the distances being 602.8 feet, 516.2 feet, 413.2 feet, 352.3 feet and 96.6 feet, successively, from beginning of course;

On a curve to the left, parallel to, and 100.0 feet from, the centerline of the Panama Railroad (Quebrancha cut-off) right-of-way, to monument No. 32, which is an 8 inch square concrete post (the chord length and bearing between monuments 31 and 32 is 1,524.1 feet S. 85°19'20" E.);

S. 88°20'30" E., 951.2 feet parallel to, and 100.0 feet from, the center line of the Panama Railroad (main line) right-of-way, to monument No. 33, which is an 8 inch square concrete post, located 100.0 feet northerly from the centerline of the Panama Railroad (main line) right-of-way, and 120 feet more or less, easterly of Track Span Tower 10-20, the geodetic position of which monument referred to the Canal Zone triangulation system is 9°17' N. plus 1,019.9 feet and longitude 79°52' W., plus 4,627.9 feet from Greenwich;

S. 88°20'30" E., 29 feet more or less, to an unmarked point on the continuous 87 foot-contour of the west shore of the Quebrada Ancha Arm of Gatun Lake;

In a general northerly direction along the 87 foot contour along the shore line of Gatun Lake, as it meanders through an unmarked point "L", which is the southwest corner of the Gatun Lake Military Reservation, to an unmarked point, which is S. 89°57'00" E., 7 feet, more or less, from the above mentioned monument No. 13; (The boundary from unmarked point "L" to last mentioned unmarked point is coincident with the Gatun Lake Military Reservation boundary);

N. 89°57'00" W., 7 feet more or less, to monument No. 13, the point of beginning.

Parcel Number II, as described, contains an area of 1,210 acres, more or less.

PARCEL No. III

Beginning at monument No. 36, which is an 8 inch square concrete post, located 6 feet more or less, from the water's edge of the East bank of the Panama Canal, the geographic position of which monument, referred to the Canal Zone triangulation system, is in latitude 9°17' N., plus 1,501.2 feet and in longitude 79°55' W., plus 2,251.6 feet from Greenwich.

Thence from said initial point by metes and bounds:

S. 75°17'30" E., 201.1 feet through monument No. 36-A, which is a 2 inch galvanized iron pipe, to monument No. 36-B, which is an iron rod in concrete, the distances being 20.0 feet and 181.1 feet, successively, from beginning of course;

S. 75°27'30" E., 604.2 feet, to monument No. 37, which is an 8 inch square concrete post, located 50.0 feet westerly of the centerline of Jadwin Road;

N. 07°39'00" W., 831.3 feet parallel to, and 50.0 feet westerly of the centerline of Jadwin Road, to monument No. 38, which is an 8 inch square concrete post;

N. 80°26'10" E., 365.3 feet, to monument No. 38-A, which is an iron rod in concrete;

N. 80°24'10" E., 195.6 feet, to monument No. 39, which is a 2 inch galvanized iron pipe, located 75.0 feet westerly of the Panama Railroad (main line) right-of-way;

Along a curve to the right, parallel to, and 75.0 feet from, the centerline of the Panama Railroad right-of-way, to monument No. 40, which is a 2 inch galvanized iron pipe, the chord distance and bearing between monuments 39 and 40 is 434.0 feet N. 27°04'50" E.;

N. 07°48'00" W., 1730.3 feet, through monuments 40-A and 40-B, which are 2 inch galvanized iron pipes, to monument No. 34, which is an 8 inch square concrete post, the distances being 688.4 feet, 836.7 feet and 205.2 feet, successively, from beginning of course;

N. 85°59'20" W., 793.5 feet, through monuments 34-A, 34-B, and 2, all of which are 2 inch galvanized iron pipes, to monument No. 35, which is a 2 inch galvanized iron pipe, located 13 feet, more or less, from the water's edge of the East bank of the Panama Canal, the geographic position of which monument is in latitude 9°17' N., plus 4372.5 feet, and in longitude 79°55' W., plus 1857.8 feet from Greenwich;

N. 85°59'20" W., 13 feet, more or less, to an unmarked point on the water's edge of the East Bank of the Panama Canal;

Southerly along the water's edge of the East Bank of the Panama Canal, to an unmarked point, which is N. 75°17'30" W.,