TITLE 43—PUBLIC LANDS: INTERIOR

Chapter I—Bureau of Land Management, Department of the Interior

Appendix—Public Land Orders

[Public Land Order 930]

CALIFORNIA

PARTIALLY REVOKING EXECUTIVE ORDER NO. 4203 OF APRIL 14, 1925

By virtue of the authority vested in the President by section 1 of the act of June 25, 1910 (36 Stat. 847; 43 U. S. C. 141), and pursuant to Executive Order No. 10355 of May 26, 1952, it is ordered as follows:

Executive Order No. 4203 of April 14, 1925, temporarily withdrawing certain public lands in California and Nevada in aid of classification is hereby revoked so far as it affects the following-described land in California:

MOUNT DIABLO MERIDIAN

T. 2 N., R. 16 E.
Sec. 16, W½NE¼SW¼ and SE¼NE¼ SW¼.

The areas described aggregate 30 acres.

The lands are not suitable for cultivation. It is proposed to offer them at public sale. It is unlikely that they will be classified for any other disposition but any application that is filed will be considered on its merits.

This order shall not become effective to change the status of the described lands until 10:00 a. m. on the 35th day after the date of this order. At that time the said lands shall become subject to application, petition, location and selection under the applicable public land laws, subject to valid existing rights, the provisions of existing withdrawals, the requirements of applicable laws, and the 91-day preference right filing period for veterans and others entitled to preference under the act of September 27, 1944 (58 Stat. 747; 43 U. S. C. 279–284) as amended.

Information showing the periods during which and the conditions under which veterans and others may file applications for these lands may be obtained on request from the Manager, Land Office, Sacramento, California.

ORME LEWIS,
Assistant Secretary of the Interior.

NOVEMBER 27, 1953.

[F. R. Doc. 53-10095; Filed, Dec. 2, 1953; 8:47 a. m.]

TITLE 14—CIVIL AVIATION

Chapter II—Civil Aeronautics Administration, Department of Commerce

[Amdt. 49]

PART 609—STANDARD INSTRUMENT APPROACH PROCEDURES

ALTERATIONS

The standard instrument approach procedure alterations appearing hereinafter, which have been published in the Flight Information Manual, are adopted to become effective when indicated in order to promote safety of the flying public. Compliance with the notice, procedures, and effective date provisions of section 4 of the Administrative Procedure Act would be impracticable and contrary to the public interest, and therefore is not required.

Part 609 is amended as follows:

1. The low frequency range procedures prescribed in § 609.6 are amended to read in part:

NOTE: Bearings, headings, courses are magnetic. Distances are in statute miles. Elevations and altitudes are in feet MSL. Ceilings are in feet above airport elevation.

LOW FREQUENCY RANGE PROCEDURES

When an LFR instrument approach is conducted at the below named airport(s), it shall be in accordance with the following instrument approach procedure(s), unless an approach is conducted in accordance with a different procedure authorized by the Administrator for such airport(s). Initial approaches shall be made over specified routes. Minimum altitude(s) shall correspond with those established for en route operation in the particular area or as set forth below:

City and State; airport name, elevation; class of facility; frequency; identification; procedure No.	Initial approach to facility			Procedure turn: ( ) side of final approach course (outbound and inbound); altitudes; limiting distances	Minimum altitude over facility on final approach course (ft.)	Course and distance facility to airport	Ceiling and visibility minimums			If visual contact not established at authorized landing minimums after passing facility within distance specified below, or if landing not accomplished; remarks
	From—	Course and distance	Minimum altitude (ft.)				Condition	Type aircraft: 75 m. p. h. or less	Type aircraft: More than 75 m. p. h.	
ABILENE, TEX. Abilene Municipal Airport, 1,757' SBRAZ–DTV 379 kc, ABI Procedure No. 1	Phantom Hill FM (Final)	----------	2,520	W side N course: 360 outbound. 180 inbound. 3,000' within 25 miles.	2,520	180—2.3	T–dn C–dn A–dn	300–1.0 500–1.0 800–2.0	NA NA NA	Within 2.3 miles, climb to 3,800' on S course* within 10 miles, or as directed by ATC. *CAUTION: 2,754' msl radio tower, 11 miles S airport. NOTE: Minima for twin-engine and smaller aircraft only.
ACOMITA, N. MEX.	(NO ASSOCIATED AIRPORT)									
ADVANCE, MO.	(NO ASSOCIATED AIRPORT)									
AKRON, OHIO Akron Airport, 1,051' SBMRLZ–DTV 362 kc, AKR Procedure No. 1	Tallmadge FM	----------	2,400	S side SW course: 225 outbound. 045 inbound. 2,300' within 10 miles. 2,400' within 25 miles.	1,800	66—0.3	T–dn C–d C–n A–dn	400–1.0 600–1.0 600–1.5 800–2.0	400–1.0 700–1.5 700–1.5 800–2.0	Within 0.3 miles, climb to 2,500' on NE course, or as directed by ATC.
ALBANY, GA. Albany Airport, 196' SBMRAZ–DTV 254 kc, ABY Procedure No. 1	----------	----------	----------	N side E course: 090 outbound. 270 inbound. 1,400' within 25 miles.	1,200	270—4.2	T–dn C–dn S–dn 27 A–dn	300–1.0 500–1.0 500–1.0 800–2.0	300–1.0 500–1.5 500–1.0 800–2.0	Within 4.2 miles, climb to 1,600' on W course within 25 miles. CAUTION: 575' msl tower, 1.5 miles WNW of LFR. NOTE: Deviation authorized in landing minimum obstruction clearance criteria.

LOW FREQUENCY RANGE PROCEDURES—Continued

No. 235—2

City and State; airport name, elevation; class of facility; frequency; identification; procedure No.	Initial approach to facility: From—	Initial approach to facility: Course and distance	Initial approach to facility: Minimum altitude (ft.)	Procedure turn: ( ) side of final approach course (outbound and inbound); altitudes; limiting distances	Minimum altitude over facility on final approach course (ft.)	Course and distance facility to airport	Ceiling and visibility minimums: Condition	Ceiling and visibility minimums: Type aircraft: 75 m. p. h. or less	Ceiling and visibility minimums: Type aircraft: More than 75 m. p. h.	If visual contact not established at authorized landing minimums after passing facility within distance specified below, or if landing not accomplished; remarks
ALBANY, N. Y. Albany Airport, 288' SBRAZ-DTV 263 kc, ALB Procedure No. 1	Saratoga Springs FM		1,600	W side N course: 082 outbound. 208 inbound. 1,600' within 10 miles. 1,800' within 20 miles. 2,000' within 25 miles.	1,100	195—2.8	T-dn C-dn S-dn 19 A-dn	300–1.0 500–1.0 500–1.0 800–2.0	300–1.0 600–1.5 500–1.0 800–2.0	Within 2.8 miles, climb to 1,000' on S course, turn right, continue climb and proceed out W course climbing to 3,000', or when directed by ATC, climb to 5,000' on S course. SHUTTLE: N course within 15 miles to 1,800'. NOTE: Deviation from standard criteria authorized for straight-in minimums and in obstruction clearance NW of airport.
	Round Lake FM (final)		1,100							
	Grafton FM		3,000							
	Coxsackie FM		2,200							
	Delmar FM		1,700							
	Schenectady FM		1,800							
Procedure No. 2	Saratoga Springs FM		2,200	E side S course: 195 outbound. 015 inbound. 2,200' within 25 miles.	1,700 (Over Delmar FM)	015 (From Delmar FM)	T-dn C-dn S-dn 1 A-dn	300–1.0 500–1.0 500–1.0 800–2.0	300–1.0 600–1.5 500–1.0 800–2.0	Within 5.4 miles after passing Delmar FM, climb to 3,000' on N course within 25 miles, or when directed by ATC, climb to 3,000' on W course within 25 miles. SHUTTLE: N course to 1,800' within 15 miles. NOTE: Deviation from standard criteria authorized in distance for final approach from Coxsackie FM.
	Grafton FM		3,000							
	Coxsackie FM (final)		1,700							
	Schenectady FM		1,800							
Schenectady County Airport	(Make let-down to Albany Airport. Fly VFR from Albany Airport to Schenectady County Airport.)									
Troy Airport	(Make let-down to Albany Airport. Fly VFR from Albany Airport to Troy Airport.)									
ALBUQUERQUE, N. MEX. Kirtland AFB, 5,330' SBRAZ-DTV 230 kc, ABQ Procedure No. 1	Alameda Rbn*		6,500	W side course: 175 outbound. 355 inbound. 7,000'*, within 25 miles.	6,000*	355—3.0	T-dn C-dn S-dn 35 A-dn	300–1.0 500–1.0 500–1.0 800–2.0	300–1.0 500–1.5 500–1.0 800–2.0	Within 3.0 miles, climb to 8,000'* on N course, or as directed by ATC. *CAUTION: Terrain exceeding 8,000' in E quadrants of range. All turns to be made on W side of course. NOTE: Ceiling and visibility minimums apply to civil aircraft only.
	Peralta FM (final)		6,000							
ALEXANDRIA, LA. Alexandria AFB, 88' SBMRAZ-DTV 251 kc, AEX Procedure No. 1				E side WE course: 113 outbound. 293 inbound. 1,500' within 25 miles.	900	311—5.7	T-dn C-dn S-d 32 A-dn	300–1.0 500–1.0 500–1.0 800–2.0	300–1.0 500–1.5 500–1.0 800–2.0	Within 5.7 miles, climb to 1,500' on NW course.
ALICE, TEX. Alice Airport, 178' SBRAZ-DTV 224 kc, ALI Procedure No. 1				S side W course: 252 outbound. 072 inbound. 1,400' within 25 miles.	1,000	072—3.6	T-dn C-dn S-d S-n 8 A-dn	300–1.0 500–1.0 500–1.5 NA 800–2.0	300–1.0 500–1.5 500–1.5 NA 800–2.0	Within 3.6 miles turn left, climb to 1,700' on N course, or alternate procedure (when directed by ATC), climb to 1,500' on E course.
ALLENTOWN, PA. Allentown-Bethlehem-Easton Airport, 392' SBMRAZ-DTV 320 kc, ABL Procedure No. 1	Slantington FM		3,000	E side NE course: 059 outbound. 239 inbound. 2,600' within 15 miles. 2,700' within 25 miles.	1,500	191—2.7	T-dn C-d C-n A-dn	300–1.0 600–1.0 600–1.5 800–2.0	300–1.0 600–1.5 600–2.0 800–2.0	Within 2.7 miles, climb to 2,500' on SW course within 15 miles. CAUTION: 1,600' terrain on N side NE course. NOTE: (1) Standard obstruction clearance not provided in altitude over range on final approach; do not descend below procedure turn altitude until inbound on NE course. (2) Nonstandard procedure turn to avoid obstructions to W.
ALMA, GA. Alma Airport, 200' SBRAZ-DTV 242 kc, AMG Procedure No. 1				W side NW course: 319 outbound. 139 inbound. 1,300' within 25 miles.	800	144—2.2	T-dn C-d C-n S-d S-n None A-dn	300–1.0 500–1.0 500–2.0 500–1.0 500–2.0 800–2.0	300–1.0 500–1.5 500–2.0 500–1.0 500–2.0 800–2.0	Within 2.2 miles, climb to 1,500' on right side SE course.