

Milestone 2 Planning Artifact

As-built sitemap, navigation structure, interface wireframes, and design concept

This artifact documents the completed information architecture for the fictional Oracle Red Labs ITS122P project. Protected areas require the role shown; the browser pages and API share one Express origin.

Sitemap

PUBLIC: Home -> Methodology / Services / Who We Serve / Vault / Inquiry / Login / Register

CLIENT: Login or Register -> Engagement Request -> Dashboard -> Engagement Details

ADMIN: Login -> Admin Console -> Services / Resources / Engagements / Inquiries

Navigation rules

Rule	Behavior
Authentication	Protected pages redirect signed-out visitors to login with an allow-listed local next destination.
Role	Clients reach the dashboard; administrators reach the console. Cross-role access redirects safely.
Ownership	Engagement details are selected by reference and constrained to the authenticated client in SQL.
Public continuity	Normal links and browser history remain usable; the site is not a single-page application.

Major page wireframes

Home

Header / primary message and artwork / service teasers / method and audience / inquiry / academic disclaimer

Services + Vault

Page context / API loading state / catalogue or searchable resource grid / empty and error states

Register + Login

Identity fields / validation / live server status / role-based destination

Engagement

Three-step progress / scope and targets / schedule / signed PDF and billing / committed receipt

Client

Summary cards / owned records / detail, history, and eligible cancellation

Administrator

Keyboard tabs / service and resource forms / engagement and invoice controls / inquiry queue

Design concept

The application keeps the existing near-black technical environment and disciplined red signal color defined in DESIGN.md. Public pages explain the fictional concept; client and administrator pages reuse the same tokens in task-focused layouts. Red is reserved for primary actions, state, and risk emphasis.

Interaction and accessibility notes

Every asynchronous region has loading, empty, success, and error copy. Forms keep entered values after a failed request. Controls are labeled, status changes are announced, administrator tabs follow the keyboard tabs pattern, mobile tables become stacked records, and reduced-motion preferences are respected.

Source documents: docs/milestone-2/sitemap.md and docs/milestone-2/wireframes.md