

Cdac Admission System

```
D4_96296_Sangram> show databases;
```

Database
cdac_add_sys
classwork
hr
information_schema
joins
performance_schema
sales
spj

```
8 rows in set (0.01 sec)
```

```
D4_96296_Sangram> use cdac_add_sys;
```

```
      created_at TIMESTAMP at line 5
D4_96296_Sangram> CREATE TABLE Candidate (
->   candidate_id INT AUTO_INCREMENT PRIMARY KEY,
->   name VARCHAR(100) NOT NULL,
->   email VARCHAR(100) UNIQUE,
->   candidate_rank INT NOT NULL,
->   category VARCHAR(20) DEFAULT 'GEN',
->   created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP
-> );
Query OK, 0 rows affected (1.66 sec)
```

```
D4_96296_Sangram> CREATE TABLE Course (
->   course_id INT AUTO_INCREMENT PRIMARY KEY,
->   course_name VARCHAR(100) UNIQUE NOT NULL,
->   total_seats INT CHECK (total_seats > 0)
-> );
Query OK, 0 rows affected (0.72 sec)
```

```
ERROR 1824 (HY000): Failed to open the referenced table
```

```
D4_96296_Sangram> CREATE TABLE Center (
->   center_id INT AUTO_INCREMENT PRIMARY KEY,
->   center_name VARCHAR(100) UNIQUE NOT NULL,
->   location VARCHAR(100)
-> );
Query OK, 0 rows affected (0.52 sec)
```

```

D4_96296_Sangram> CREATE TABLE Center_Course (
->   cc_id INT AUTO_INCREMENT PRIMARY KEY,
->   center_id INT,
->   course_id INT,
->   seats_available INT,
->   FOREIGN KEY (center_id) REFERENCES Center(center_id),
->   FOREIGN KEY (course_id) REFERENCES Course(course_id),
->   UNIQUE(center_id, course_id)
-> );
Query OK, 0 rows affected (0.51 sec)

```

```

D4_96296_Sangram> show tables;

```

```

+-----+
| Tables_in_cdac_add_sys |
+-----+
| candidate               |
| center                  |
| center_course           |
| course                  |
+-----+

```

```

4 rows in set (0.05 sec)

```

```

D4_96296_Sangram> CREATE TABLE Preferences (
->   candidate_id INT,
->   preference_no INT,
->   cc_id INT,
->   PRIMARY KEY (candidate_id, preference_no),
->   FOREIGN KEY (candidate_id) REFERENCES Candidate(candidate_id),
->   FOREIGN KEY (cc_id) REFERENCES Center_Course(cc_id)
-> );

```

```

Query OK, 0 rows affected (0.68 sec)

```

```

Query OK, 0 rows affected (0.68 sec)

```

```

D4_96296_Sangram> CREATE TABLE Allocation (
->   allocation_id INT AUTO_INCREMENT PRIMARY KEY,
->   candidate_id INT,
->   cc_id INT,
->   round_no INT,
->   status VARCHAR(20) DEFAULT 'ALLOCATED',
->   FOREIGN KEY (candidate_id) REFERENCES Candidate(candidate_id),
->   FOREIGN KEY (cc_id) REFERENCES Center_Course(cc_id)
-> );

```

```

Query OK, 0 rows affected (0.45 sec)

```

```

D4_96296_Sangram> );

```

```

('DBDA', 60) at line 1
D4_96296_Sangram> INSERT INTO Course (course_name, total_seats)VALUES('DAC', 240),('DBDA', 60),('ESD', 120),('MC', 120);
Query OK, 4 rows affected (0.63 sec)
Records: 4 Duplicates: 0 Warnings: 0

D4_96296_Sangram> INSERT INTO Center (center_name, location)VALUES ('Sunbeam Pune', 'Pune'),('Sunbeam Karad', 'Karad'),('ACTS Pune', 'Pune'),('IACSD Pune', 'Pune');
Query OK, 4 rows affected (0.14 sec)
Records: 4 Duplicates: 0 Warnings: 0

D4_96296_Sangram> INSERT INTO Center_Course (center_id, course_id, seats_available)VALUES(1, 1, 240),(1, 2, 60),(1, 3, 120),(1, 4, 120);
Query OK, 4 rows affected (0.13 sec)
Records: 4 Duplicates: 0 Warnings: 0

D4_96296_Sangram> INSERT INTO Center_Course (center_id, course_id, seats_available)VALUES(2, 1, 240),(2, 2, 60),(2, 3, 120),(2, 4, 120);
Query OK, 4 rows affected (0.09 sec)
Records: 4 Duplicates: 0 Warnings: 0

D4_96296_Sangram> INSERT INTO Center_Course (center_id, course_id, seats_available)VALUES(3, 1, 240),(3, 2, 60),(3, 3, 120),(3, 4, 120);
Query OK, 4 rows affected (0.07 sec)
Records: 4 Duplicates: 0 Warnings: 0

D4_96296_Sangram> INSERT INTO Center_Course (center_id, course_id, seats_available)VALUES(4, 1, 240),(4, 2, 60),(4, 3, 120),(4, 4, 120);
Query OK, 4 rows affected (0.15 sec)
Records: 4 Duplicates: 0 Warnings: 0

D4_96296_Sangram>

```

```

D4_96296_Sangram> INSERT INTO Candidate (name, email,candidate_rank)VALUES ('Sangram Khedkar', 'sangramkhedkar25@gmail.com', 54),('Moeen Shaikh', 'maoenshaikh34@gmail.com', 50);
Query OK, 2 rows affected (0.07 sec)
Records: 2 Duplicates: 0 Warnings: 0

D4_96296_Sangram> INSERT INTO Preferences (candidate_id, preference_no, cc_id)VALUES(2, 1, 1),(2, 2, 5),(2, 3, 9);
Query OK, 3 rows affected (0.10 sec)
Records: 3 Duplicates: 0 Warnings: 0

D4_96296_Sangram> INSERT INTO Preferences (candidate_id, preference_no, cc_id)VALUES(1, 1, 1),(1, 2, 2),(1, 3, 6);
Query OK, 3 rows affected (0.10 sec)
Records: 3 Duplicates: 0 Warnings: 0

D4_96296_Sangram>

```

```

04_96296_Sangram> CREATE PROCEDURE Round2_Allocation()
-> BEGIN
->     DECLARE done INT DEFAULT 0;
->     DECLARE c_id INT;
->
->     DECLARE cur CURSOR FOR
->         SELECT candidate_id FROM Candidate;
->
->     DECLARE CONTINUE HANDLER FOR NOT FOUND SET done = 1;
->
->     OPEN cur;
->
->     loop2: LOOP
->         FETCH cur INTO c_id;
->         IF done THEN
->             LEAVE loop2;
->         END IF;
->
->         INSERT INTO Allocation(candidate_id, cc_id, round_no)
->         SELECT p.candidate_id, p.cc_id, 2
->         FROM Preferences p
->         JOIN Center_Course cc ON p.cc_id = cc.cc_id
->         WHERE p.candidate_id = c_id
->             AND cc.seats_available > 0
->         ORDER BY p.preference_no
->         LIMIT 1;
->
->         UPDATE Center_Course
->         SET seats_available = seats_available - 1
->         WHERE cc_id = (
->             SELECT cc_id FROM Allocation
->             WHERE candidate_id = c_id AND round_no = 2
->         );
->     END LOOP;
->
->     CLOSE cur;
-> END$$

```

Query OK, 0 rows affected (0.50 sec)