

1)

```
mysql> SELECT pname,color FROM P
-> WHERE city="london";
```

pname	color
Nut	Red
Screw	Red
Cog	Red

```
3 rows in set (0.00 sec)
```

2)

```
mysql> SELECT * FROM S
-> WHERE CITY='LONDON';
```

SID	SNAME	STATUS	CITY
s1	Smith	20	London
s4	Clark	20	London

```
2 rows in set (0.00 sec)
```

3)

```
mysql> SELECT * FROM S
-> WHERE CITY IN('PARIS','ATHENS');
```

SID	SNAME	STATUS	CITY
s2	Jones	10	Paris
s3	Blake	30	Paris
s5	Adams	30	Athens

```
3 rows in set (0.00 sec)
```

4)

```
mysql> SELECT * FROM J WHERE CITY='ATHENS';
```

J#	Jname	city
J3	Reader	Athens
J4	Console	Athens

```
2 rows in set (0.00 sec)
```

5)

```
mysql> SELECT PNAME FROM P WHERE WEIGHT BETWEEN 12 AND 14;
```

PNAME
Nut
Screw
Cam

```
3 rows in set (0.01 sec)
```

6)

```
mysql> SELECT * FROM S
-> WHERE STATUS >= 20;
```

SID	SNAME	STATUS	CITY
s1	Smith	20	London
s3	Blake	30	Paris
s4	Clark	20	London
s5	Adams	30	Athens

4 rows in set (0.00 sec)

7)

```
mysql> SELECT * FROM S
-> WHERE CITY != 'LONDON';
```

SID	SNAME	STATUS	CITY
s2	Jones	10	Paris
s3	Blake	30	Paris
s5	Adams	30	Athens

3 rows in set (0.00 sec)

8)

```
mysql> SELECT DISTINCT CITY FROM S;
```

CITY
London
Paris
Athens

3 rows in set (0.00 sec)

9)

```
mysql> SELECT * FROM S
-> ORDER BY CITY DESC;
```

SID	SNAME	STATUS	CITY
s2	Jones	10	Paris
s3	Blake	30	Paris
s1	Smith	20	London
s4	Clark	20	London
s5	Adams	30	Athens

5 rows in set (0.00 sec)

10)

```
mysql> SELECT * FROM P
-> ORDER BY CITY,PNAME;
```

P#	Pname	Color	Weight	city
p6	Cog	Red	19	London
p1	Nut	Red	12	London
p4	Screw	Red	14	London
p2	Bolt	Green	17	Paris
p5	Cam	Blue	12	Paris
p3	Screw	Blue	17	Rome

6 rows in set (0.00 sec)

11)

```
mysql> SELECT * FROM S
-> WHERE STATUS BETWEEN 10 AND 20;
```

SID	SNAME	STATUS	CITY
s1	Smith	20	London
s2	Jones	10	Paris
s4	Clark	20	London

3 rows in set (0.00 sec)

12)

```
mysql> SELECT PNAME,WEIGHT
-> FROM P
-> WHERE WEIGHT NOT BETWEEN 10 AND 15;
```

PNAME	WEIGHT
Bolt	17
Screw	17
Cog	19

3 rows in set (0.00 sec)