

1)

```
D4_99207_OM>select * from orders where cnum = (select cnum from
customers where cname = 'cisneros');
+-----+-----+-----+-----+-----+
| onum | amt      | odate      | cnum | snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69    | 1990-10-03 | 2008 | 1007 |
| 3006 | 1098.16  | 1990-10-03 | 2008 | 1007 |
+-----+-----+-----+-----+-----+
2 rows in set (0.07 sec)
```

2)

```
D4_99207_OM>select * from salespeople where city!=all(select city from customers where customers.snum=salespeople.snum);
+-----+-----+-----+-----+
| snum | sname    | city      | comm |
+-----+-----+-----+-----+
| 1004 | Motika   | London    | 0.11 |
| 1007 | Rifkin   | Barcelona | 0.15 |
| 1003 | Axelrod  | New York  | 0.10 |
+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

3)

```
D4_99207_OM>select * from orders where snum IN(select snum from
salespeople where sname='motika');
+-----+-----+-----+-----+-----+
| onum | amt      | odate      | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10  | 1990-10-03 | 2007 | 1004 |
+-----+-----+-----+-----+-----+
1 row in set (0.04 sec)
```

4)

```
D4_99207_OM>select * from orders where snum IN(select snum from customers where city='london');
+-----+-----+-----+-----+-----+
| onum | amt      | odate      | cnum | snum |
+-----+-----+-----+-----+-----+
| 3003 | 767.19   | 1990-10-03 | 2001 | 1001 |
| 3008 | 4723.00  | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88  | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

5)

```
D4_99207_OM>select sname,snum from salespeople where snum IN(select snum from customers
-> group by snum
-> having count(cnum)>1);
+-----+-----+
| sname | snum |
+-----+-----+
| Peel  | 1001 |
| Serres | 1002 |
+-----+-----+
2 rows in set (0.03 sec)
```

6)

```
D4_99207_OM>select * from customers where rating > ANY(select rating from customers where city='rome');
```

cnum	cname	city	rating	snum
2002	Giovanni	Rome	200	1003
2003	Liu	San Jose	200	1002
2004	Grass	Berlin	300	1002
2008	Cisneros	San Jose	300	1007

4 rows in set (0.03 sec)

7)

```
D4_99207_OM>select * from orders where amt > ANY(select amt from orders where odate='1990-10-04');
```

onum	amt	odate	cnum	snum
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002
3011	9891.88	1990-10-04	2006	1001

8 rows in set (0.02 sec)

8)

```
D4_99207_OM>select * from customers where rating > ALL(select rating from customers where city='london');
```

cnum	cname	city	rating	snum
2002	Giovanni	Rome	200	1003
2003	Liu	San Jose	200	1002
2004	Grass	Berlin	300	1002
2008	Cisneros	San Jose	300	1007

4 rows in set (0.03 sec)