

1)

```
sunbeam>SELECT o.onum , c.cname
-> FROM customers c INNER JOIN orders o
-> ON c.cnum=o.cnum;
+-----+-----+
| onum | cname |
+-----+-----+
| 3001 | Cisneros |
| 3003 | Hoffman |
| 3002 | Pereira |
| 3005 | Liu |
| 3006 | Cisneros |
| 3009 | Giovanni |
| 3007 | Grass |
| 3008 | Clemens |
| 3010 | Grass |
| 3011 | Clemens |
+-----+-----+
10 rows in set (0.00 sec)
```

2)

```
root>SELECT o.onum,s.sname,c.cname
-> FROM orders o INNER JOIN customers c
-> ON o.cnum=c.cnum
-> INNER JOIN salespeople s
-> ON o.snum = s.snum;
+-----+-----+-----+
| onum | sname | cname |
+-----+-----+-----+
| 3003 | Peel | Hoffman |
| 3009 | Axelrod | Giovanni |
| 3005 | Serres | Liu |
| 3010 | Serres | Grass |
| 3007 | Serres | Grass |
| 3011 | Peel | Clemens |
| 3008 | Peel | Clemens |
| 3006 | Rifkin | Cisneros |
| 3001 | Rifkin | Cisneros |
| 3002 | Motika | Pereira |
+-----+-----+-----+
10 rows in set (0.00 sec)
```

3)

```
sunbeam>SELECT c.cname , s.sname , s.comm
-> FROM customers c INNER JOIN salespeople s
-> ON c.snum=s.snum
-> where s.comm > 0.12;
+-----+-----+-----+
| cname | sname | comm |
+-----+-----+-----+
| Liu | Serres | 0.13 |
| Grass | Serres | 0.13 |
| Cisneros | Rifkin | 0.15 |
+-----+-----+-----+
3 rows in set (0.01 sec)
```

4)

```
D4_99207_OM>select o.onum,s.comm, s.comm*o.amt
-> from orders o INNER JOIN salespeople S
-> ON o.snum=s.snum
-> INNER JOIN customers c
-> ON o.cnum = c.cnum
-> where c.rating > 100;
```

onum	comm	s.comm*o.amt
3010	0.13	40.2935
3007	0.13	9.8475
3005	0.13	670.8585
3006	0.15	164.7240
3001	0.15	2.8035
3009	0.10	171.3230

6 rows in set (0.00 sec)

5)

```
D4_99207_OM>select s1.sname,s2.sname
-> from salespeople s1 INNER JOIN salespeople s2
-> ON s1.city=s2.city
-> where s1.sname != s2.sname AND s1.snum > s2.snum;
```

sname	sname
Motika	Peel

1 row in set (0.00 sec)

2nd part

1)

```
root> SELECT a.sname , SUM(b.qty)
-> FROM s a INNER JOIN sp b
-> ON a.`s#` = b.`s#`
-> GROUP BY a.sname;
```

sname	SUM(b.qty)
Smith	900
Jones	3200
Blake	700
Clark	600
Adams	3100

5 rows in set (0.01 sec)

2)

```

root>SELECT a.pname , SUM(b.qty) "Quantity sold"
-> FROM p a INNER JOIN sp b
-> ON a.`p#` = b.`p#`
-> GROUP BY a.pname;

```

pname	Quantity sold
Nut	1000
Screw	4800
Cam	1100
Cog	1300
Bolt	300

5 rows in set (0.00 sec)

3)

```

root>SELECT a.jname , SUM(b.qty) "Quantity sold"
-> FROM j a INNER JOIN sp b
-> ON a.`j#` = b.`j#`
-> GROUP BY a.jname;

```

jname	Quantity sold
Sorter	800
Console	3300
Punch	1200
Reader	500
Collector	1100
Terminal	400
Adams	1200

7 rows in set (0.00 sec)

4)

```

root>SELECT a.sname,b.pname,c.jname,d.qty
-> FROM s a INNER JOIN sp d
-> ON a.`S#`=d.`S#`
-> INNER JOIN p b
-> ON b.`p#`=d.`p#`
-> INNER JOIN j c
-> ON c.`j#`=d.`j#`
-> ORDER BY a.sname desc;

```

sname	pname	jname	qty
Smith	Nut	Sorter	200
Smith	Nut	Console	700
Jones	Screw	Sorter	400
Jones	Cam	Punch	100
Jones	Screw	Punch	200
Jones	Screw	Reader	200
Jones	Screw	Console	500
Jones	Screw	Collector	600
Jones	Screw	Terminal	400
Jones	Screw	Adams	800
Clark	Cog	Reader	300
Clark	Cog	Adams	300
Blake	Screw	Sorter	200
Blake	Screw	Punch	500
Adams	Cog	Punch	200
Adams	Bolt	Punch	200
Adams	Cog	Console	500
Adams	Cam	Console	400
Adams	Screw	Console	800
Adams	Screw	Console	200
Adams	Bolt	Console	100
Adams	Nut	Console	100
Adams	Cam	Collector	500
Adams	Cam	Adams	100

24 rows in set (0.00 sec)

5)

```
D4_99207_OM>SELECT distinct s.sname from s INNER JOIN sp ON s.`s#`=sp.`s#` INNER JOIN j on sp.`j#` = j.`j#`  
-> where s.city=j.city;  
+-----+  
| sname |  
+-----+  
| Jones |  
| Blake |  
| Clark |  
| Adams |  
+-----+  
4 rows in set (0.00 sec)
```

6)

```
root>SELECT a.pname,SUM(b.qty)  
-> FROM p a INNER JOIN sp b  
-> ON a.`p#`=b.`p#`  
-> WHERE color='RED'  
-> GROUP BY a.pname;  
+-----+-----+  
| pname | SUM(b.qty) |  
+-----+-----+  
| Nut   | 1000       |  
| Screw | 1300       |  
| Cog   | 1300       |  
+-----+-----+  
3 rows in set (0.02 sec)
```

7)

```
root>SELECT a.sname,SUM(b.qty)  
-> FROM s a INNER JOIN sp b  
-> ON a.`s#`=b.`s#`  
-> WHERE status=20  
-> GROUP BY a.sname;  
+-----+-----+  
| sname | SUM(b.qty) |  
+-----+-----+  
| Smith | 900        |  
| Clark | 600        |  
+-----+-----+  
2 rows in set (0.00 sec)
```

8)

```

root>SELECT a.pname,SUM(b.qty)
-> FROM p a INNER JOIN sp b
-> ON a.`p#`=b.`p#`
-> WHERE weight>14
-> GROUP BY a.pname;
+-----+-----+
| pname | SUM(b.qty) |
+-----+-----+
| Screw |          3500 |
| Cog   |          1300 |
| Bolt  |           300 |
+-----+-----+
3 rows in set (0.00 sec)

```

9)

```

D4_99207_OM>select j1.jname,j1.city, sum(s1.qty) FROM j j1 INNER JOIN sp s1
-> ON j1.`j#`=s1.`j#`
-> Group by j1.jname,j1.city
-> HAVING sum(s1.qty)>500;
+-----+-----+-----+
| jname   | city   | sum(s1.qty) |
+-----+-----+-----+
| Sorter  | Paris  |          800 |
| Console | Athens |         3300 |
| Punch   | Rome   |         1200 |
| Collector | London |         1100 |
| Tape    | London |         1200 |
+-----+-----+-----+
5 rows in set (0.03 sec)

```

10)

```

root>SELECT a.pname,SUM(b.qty)
-> FROM p a INNER JOIN sp b
-> ON a.`p#`=b.`p#`
-> WHERE a.weight<15
-> GROUP BY a.pname;
+-----+-----+
| pname | SUM(b.qty) |
+-----+-----+
| Nut   |          1000 |
| Cam   |          1100 |
| Screw |          1300 |
+-----+-----+
3 rows in set (0.00 sec)

```

11)

```
D4_99207_OM>select s1.sname,s1.status FROM s s1 INNER JOIN s s2
-> ON s1.status=s2.status
-> where s2.sname='clark'
-> AND s1.sname != 'clark';
```

sname	status
Smith	20

1 row in set (0.00 sec)

12)

```
D4_99207_OM>select DISTINCT p1.pname,p1.weight from p p1 INNER JOIN p p2
-> ON p1.weight>p2.weight
-> where p2.color='red';
```

pname	weight
Bolt	17
Screw	17
Screw	14
Cog	19

4 rows in set (0.00 sec)

13)

```
D4_99207_OM>select j1.jname,j1.city from j j1 INNER JOIN j j2
-> ON j1.city=j2.city
-> where j2.jname='tape' and j1.jname != 'tape';
```

jname	city
Collector	London

1 row in set (0.00 sec)

14)

```
D4_99207_OM>select p1.pname,p1.weight from p p1 INNER JOIN p p2
-> ON p1.weight<p2.weight
-> where p2.color='green';
```

pname	weight
Nut	12
Screw	14
Cam	12

3 rows in set (0.02 sec)

15)

```
D4_99207_OM>select s1.sname,MAX(s2.qty) FROM s s1 INNER JOIN sp s2
-> ON s1.`s#`=s2.`s#`
-> GROUP BY s1.sname
-> ORDER BY MAX(s2.qty) desc
-> LIMIT 1 ;
```

sname	MAX(s2.qty)
Adams	800

1 row in set (0.03 sec)

16)

```
D4_99207_OM>select s1.sname,SUM(s2.qty) FROM s s1 INNER JOIN sp s2
-> ON s1.`s#`=s2.`s#`
-> GROUP BY s1.sname
-> ORDER BY SUM(s2.qty) desc
-> LIMIT 1 ;
```

sname	SUM(s2.qty)
Jones	3200

1 row in set (0.00 sec)