

ASSIGNMENT 8

Name: Buddhabhushan Sirsat

Roll no.: 99421

1. SELECT * FROM orders WHERE cnum = (SELECT cnum FROM customers WHERE cname='Cisneros');

onum	amt	odate	cnum	snum
3001	18.69	1990-10-03	2008	1007
3006	1098.16	1990-10-03	2008	1007

ASSIGNMENT 8

2. SELECT snum, sname, city FROM salespeople S WHERE city <>
ALL (SELECT C.city FROM customers C WHERE C.snum = S.snum
);

snum	sname	city
1004	Motika	London
1007	Rifkin	Barcelona
1003	Axelrod	New York

ASSIGNMENT 8

3. SELECT * FROM orders WHERE snum = (SELECT snum FROM salespeople WHERE sname='Motika');

onum	amt	odate	cnum	snum
3002	1900.10	1990-10-03	2007	1004

ASSIGNMENT 8

4. `SELECT * FROM orders`
`WHERE snum IN (SELECT snum FROM customers WHERE city =`
`'London');`

onum	amt	odate	cnum	snum
3003	767.19	1990-10-03	2001	1001
3008	4723.00	1990-10-04	2006	1001
3011	9891.88	1990-10-04	2006	1001

ASSIGNMENT 8

5. SELECT sname, snum FROM salespeople WHERE snum IN (
SELECT snum FROM customers GROUP BY snum HAVING
COUNT(cnum) > 1);

sname	snum
Peel	1001
Serres	1002

ASSIGNMENT 8

6. SELECT * FROM customers C1 WHERE C1.RATING >
ANY(SELECT C2.RATING FROM customers C2 WHERE C2.city =
'Rome');

cnum	cname	city	rating	snum
2002	Giovanni	Rome	200	1003
2003	Liu	San Jose	200	1002
2004	Grass	Berlin	300	1002
2008	Cisneros	San Jose	300	1007

ASSIGNMENT 8

7. SELECT * FROM orders WHERE amt > ANY (SELECT amt FROM orders WHERE odate = '1990-10-04');

onum	amt	odate	cnum	snum
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002
3011	9891.88	1990-10-04	2006	1001

ASSIGNMENT 8

8. SELECT * FROM customers C1 WHERE C1.RATING >
ALL(SELECT C2.RATING FROM customers C2 WHERE C2.city =
'London');

cnum	cname	city	rating	snum
2002	Giovanni	Rome	200	1003
2003	Liu	San Jose	200	1002
2004	Grass	Berlin	300	1002
2008	Cisneros	San Jose	300	1007