

Assignment 4

1. Display the PNAME and COLOR from the P table for the CITY="London".

```
mysql> SELECT pname,color FROM p
      -> WHERE city='London';
+-----+-----+
| pname | color |
+-----+-----+
| Nut   | Red   |
| Screw| Red   |
| Cog   | Red   |
+-----+-----+
3 rows in set (0.00 sec)
```

2. Display all the Suppliers from London.

```
mysql> SELECT * FROM s
      -> WHERE city='London';
+-----+-----+-----+-----+
| s#    | Sname | status | CITY    |
+-----+-----+-----+-----+
| S1    | Smith | 20     | London  |
| S4    | Clark | 20     | London  |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

3. Display all the Suppliers from Paris or Athens.

```
mysql> SELECT * FROM s
      -> WHERE city IN('Paris','Athens');
+-----+-----+-----+-----+
| s#    | Sname | status | CITY    |
+-----+-----+-----+-----+
| S2    | Jones | 10     | Paris   |
| S3    | Blake | 30     | Paris   |
| S5    | Adams | 30     | Athens  |
+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

4. Display all the Jobs in Athens.

```
mysql> SELECT * FROM j
      -> WHERE city='Athens';
+-----+-----+-----+
| J# | Jname   | city   |
+-----+-----+-----+
| J3 | Reader  | Athens |
| J4 | Console | Athens |
+-----+-----+-----+
2 rows in set (0.00 sec)
```

5. Display all the Part names with the weight between 12 and 14 (inclusive of both).

```
mysql> SELECT Pname FROM p
      -> WHERE weight BETWEEN 12 AND 14;
+-----+
| Pname |
+-----+
| Nut   |
| Screw|
| Cam   |
+-----+
3 rows in set (0.00 sec)
```

6. Display all the Suppliers with a Status greater than or equal to 20.

```
mysql> SELECT * FROM s
      -> WHERE status >=20;
+-----+-----+-----+-----+
| s#   | Sname | status | CITY   |
+-----+-----+-----+-----+
| S1   | Smith | 20     | London |
| S3   | Blake | 30     | Paris  |
| S4   | Clark | 20     | London |
| S5   | Adams | 30     | Athens |
+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

7. 7. Display all the Suppliers except the Suppliers from London.

```
mysql> SELECT * FROM s
-> WHERE city!='London';
```

s#	Sname	status	CITY
S2	Jones	10	Paris
S3	Blake	30	Paris
S5	Adams	30	Athens

```
3 rows in set (0.00 sec)
```

8. Display only the Cities from where the Suppliers come from.

```
mysql> SELECT DISTINCT city FROM s;
```

city
London
Paris
Athens

```
3 rows in set (0.00 sec)
```

9. Display the Supplier table in the descending order of CITY.

```
mysql> SELECT * FROM s
-> ORDER BY city DESC;
```

s#	Sname	status	CITY
S2	Jones	10	Paris
S3	Blake	30	Paris
S1	Smith	20	London
S4	Clark	20	London
S5	Adams	30	Athens

```
5 rows in set (0.00 sec)
```

10. Display the Part Table in the ascending order of CITY and within the city in the ascending order of Part names.

```
mysql> SELECT * FROM p
-> ORDER BY city ASC, pname ASC;
```

P#	Pname	color	weight	city
P6	Cog	Red	19	London
P1	Nut	Red	12	London
P4	Screw	Red	14	London
P2	Bolt	Green	17	Paris
P5	Cam	Blue	12	Paris
P3	Screw	Blue	17	Rome

```
6 rows in set (0.00 sec)
```

11. Display all the Suppliers with a status between 10 and 20.

```
mysql> SELECT * FROM s
-> WHERE status BETWEEN 10 AND 20;
```

s#	Sname	status	CITY
S1	Smith	20	London
S2	Jones	10	Paris
S4	Clark	20	London

```
3 rows in set (0.00 sec)
```

12. Display all the Parts and their Weight, which are not in the range of 10 and 15.

```
mysql> SELECT pname, weight
-> FROM p
-> WHERE weight NOT BETWEEN 10 AND 15;
```

pname	weight
Bolt	17
Screw	17
Cog	19

```
3 rows in set (0.00 sec)
```