



# **Cross-organizational distributed systems and Clouds**

## Exercise 2: Monitoring and Vertical Scaling

Christopher B. Hauser

Institute of Information Resource Management

2018-05-03

## **Exercise 2: Monitoring and Vertical Scaling**

Welcome to exercise 2. This time we will have the following lessons:

1. Monitoring with InfluxData
2. Vertical Scaling

### **Lessons learned**

- How to set up monitoring with InfluxData
- Benchmark Mediawiki application with artificial workload
- Learn about vertical scaling and its impact

## Lesson 1: Monitoring with InfluxData

### Research: InfluxData TICK stack

First we need a new Instance/VM, which will host the monitoring data and provide a web-based dashboard to access it. The monitoring solution we will use is the TICK stack of InfluxData. While Telegraf will run on the VM with Mediawiki installed, we need another VM for InfluxDB and Chronograf.

Become familiar with InfluxData: <https://www.influxdata.com/products/open-source/>

### Question: Parts and responsibilities of the TICK stack

Please describe the components of the TICK stack and their purpose. Which of these components are needed for a minimum TICK setup?

### Task: Install the monitoring data sink

We will now install the InfluxDB and Chronograf in a new VM, which will be the data sink for several Telegraf monitoring adaptors. This guide follows the official installation guide:

<https://docs.influxdata.com/influxdb/v1.2/introduction/installation/>

Create a new security group on OpenStack (go to "Network" and "Security Groups"):

- Name: monitoring
- Create, and go to "manage rules":
  - Add Rules for TCP ingres ports 8888, 8086, 8088

Create a new instance on OpenStack:

- Name: monitoring
- Source: Create new Volume set to "No", then select Ubuntu Server 16.04 (ubuntu-1604)
- Flavor: select "medium" (4 cores, 4GB memory, 10GB disk)
- Select both the default and the monitoring security groups
- Validate that your ssh key is selected

Then launch the instance, and attach a public floating ip. Log in via SSH to the new vm with username "ubuntu" and the public IP you got assigned. In the new vm, install InfluxDB and Chronograf:

```
curl -sL https://repos.influxdata.com/influxdb.key | sudo apt-key add -  
source /etc/lsb-release
```

```
echo "deb https://repos.influxdata.com/${DISTRIB_ID,,} ${DISTRIB_CODENAME} stable"  
    | sudo tee /etc/apt/sources.list.d/influxdb.list  
sudo apt-get update && sudo apt-get install influxdb  
sudo systemctl start influxdb  
wget https://dl.influxdata.com/chronograf/releases/chronograf_1.3.0_amd64.deb  
sudo dpkg -i chronograf_1.3.0_amd64.deb
```

In your monitoring VM you should have two services influxdb and chronograf running now. Validate that both are running, using the `systemctl` command.

Access the chronograf dashboard via your webbrowser, pointing to your public IP of the monitoring vm and port 8888 (<http://134.60.64.YZ:8888>). Tell Chronograf where InfluxDB is located:

- Connection String: `http://localhost:8086`
- Name: InfluxDB
- Username and Password empty!
- Telegraf database: `telegraf`
- Check the "Make this the default source" box
- Click "add source" button.

You will then see a empty list of hosts. Let's install the Telegraf on the Mediawiki page, to have some data to display :-)

### Question: What ports are used by influxdb?

Now that you have InfluxDB and Chronograf running, what ports are used by InfluxDB? You can get this information from your monitoring VM or from the documentation.

Hint: In the monitoring VM run `sudo netstat -tulpen` to get all ports that are open. Find the InfluxDB application.

### Task: Add monitoring to mediawiki

Next, connect via SSH to the VM hosting your mediawiki. Let's install Telegraf, which will collect monitoring statistics and send it to the monitoring VM.

```
curl -sL https://repos.influxdata.com/influxdb.key | sudo apt-key add -  
source /etc/lsb-release  
echo "deb https://repos.influxdata.com/${DISTRIB_ID,,} ${DISTRIB_CODENAME} stable"  
    | sudo tee /etc/apt/sources.list.d/influxdb.list  
sudo apt-get update && sudo apt-get install telegraf  
sudo service telegraf start
```

We need to configure telegraf to point to your monitoring vm. Open as root (with sudo) e.g. with vim the file `/etc/telegraf/telegraf.conf`. In the `[[outputs.influxdb]]` section change the `urls` field from `urls = ["http://localhost:8086"]` to point to the IP address of your monitoring vm.

Restart telegraf with `service telegraf restart` and check the Chronograf dashboard. You should see monitoring data from host "main-server" now. You will see the basic system metrics of this vm. Let's add monitoring data from apache and mariadb next. Re-open the file `/etc/telegraf/telegraf.conf` and uncomment the following lines:

```
...
[[inputs.apache]]
    urls = ["http://localhost/server-status?auto"]
...
[[inputs.mysql]]
    servers = ["root:PASSWORD_FOR_DATABASE@tcp(127.0.0.1:3306)/"]
...
```

Now restart again telegraf, to apply your changes to the configuration. After some seconds, check the chronograf dashboard again. You have apache2 and mysql monitoring data now as well.

## Lesson 2: Vertical Scaling

### Task: Stressing the Wiki

Now that we have a monitoring and our mediawiki running, it is time to put some load on mediawiki.

1. Run a stressing application from your computer (client) that queries the wiki. For this purpose you can use the apache benchmarking tool. After installing it (<https://httpd.apache.org/docs/2.4/programs/ab.html>), run two separate load tests; one without and one with concurrency. WARNING: before running the test, make sure you are pointing it to YOUR wiki installation.
  1. `ab -n 5000 http://134.60.xy.yz/wiki/index.php/Main_Page/`
  2. `ab -c 10 -n 5000 http://134.60.xy.yz/wiki/index.php/Main_Page/`
2. Explain what consequences the permanent querying has for your application. In particular, identify the (e.g. CPU, memory and network) load caused for your server via the Chronograf dashboard.
3. How many request/per second can your server handle in both test cases (output of ab)? How many requests on the apache and the database are shown in the Chronograf dashboard?
4. What do you think is the bottleneck the current setup? The network? The apache webserver? The database? Use the Chronograf dashboard to find possible bottlenecks.

### Task: Vertical Scaling

Try to scale your application vertically, by adding more virtual hardware resources.

Before we create a new instance with more CPU and Memory, we should back up our work, by creating a new snapshot, e.g. named "mediawiki-snapshot-2" of your main\_server. Remove the first snapshot from exercise 1, since it has no monitoring installed.

After the snapshot finished, delete your main\_server instance with your mediawiki application, and launch a new instance. In the **source tab**, select in "Select Boot Source" the option "Instance Snapshot", and then pick **your snapshot**. Make sure to select "No" in "Create New Volume". Select **flavor medium**. Reassign the previously used floating IP to your new instance.

Next, validate that mediawiki and the monitoring data are still working properly.

Please note: the host attached to your floating IP has now changed. When connecting via ssh, the host key verification will fail. You first have to remove the cached host key, which identified your old instance.

### **Question: Vertical Scaling**

Repeat the steps for stressing the mediawiki. Compare the results of both benchmarks (without concurrency, with concurrency).

What differences can you see / not see? Can you explain them?