1) Create a view that shows all of the customers who have the highest ratings.

```
d5_96305_sanchit> select * from v1;
+------+----------+----------+--------+------+
| cnum | cname    | city     | rating | snum |
+------+----------+----------+--------+------+
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
+------+----------+----------+--------+------+
2 rows in set (0.082 sec)

d5_96305_sanchit>
```

2) Create a view that shows the number of salespeople in each city.

```
d5_96305_sanchit> create view salespeople_in_city as
    -> select city, count(snum)
    -> from salespeople
    -> group by city;
Query OK, 0 rows affected (0.288 sec)

d5_96305_sanchit> select * from salespeople_in_city;
+----------+-------------+
| city     | count(snum) |
+----------+-------------+
| London   |           2 |
| San Jose |           1 |
| Barcelona |           1 |
| New York |           1 |
+----------+-------------+
4 rows in set (0.101 sec)

d5_96305_sanchit>
```

3) Create a view that shows the average and total orders for each salesperson after his or her name. Assume all names are unique.

```
d5_96305_sanchit> create view order_summary as
    -> select s.sname,round((select avg(total_orders) from(select s.sname,  count(o.onum) as total_orders
    -> from salespeople s join orders o on s.snum = o.snum
    -> group by s.sname) p),2) as average_orders, count(o.onum) as total_orders
    -> from salespeople s join orders o on s.snum = o.snum
    -> group by s.sname;
Query OK, 0 rows affected (0.214 sec)

d5_96305_sanchit> select * from order_summary;
+---------+----------------+--------------+
| sname   | average_orders | total_orders |
+---------+----------------+--------------+
| Rifkin  |           2.00 |            2 |
| Peel    |           2.00 |            3 |
| Motika  |           2.00 |            1 |
| Serres  |           2.00 |            3 |
| Axelrod |           2.00 |            1 |
+---------+----------------+--------------+
5 rows in set (0.168 sec)

d5_96305_sanchit>
```

4) Create a view that shows each salesperson with multiple customers.

```
d5_96305_sanchit> create view customer as
    -> select s.snum,s.sname, c.cnum,c.cname
    -> from salespeople s join customers c on s.snum  = s.snum
    -> order by s.snum;
Query OK, 0 rows affected (0.260 sec)

d5_96305_sanchit> select * from customer;
+------+---------+------+----------+
| snum | sname   | cnum | cname    |
+------+---------+------+----------+
| 1001 | Peel    | 2007 | Pereira  |
| 1001 | Peel    | 2008 | Cisneros |
| 1001 | Peel    | 2001 | Hoffman  |
| 1001 | Peel    | 2003 | Liu      |
| 1001 | Peel    | 2006 | Clemens  |
| 1001 | Peel    | 2002 | Giovanni |
```

5)

1) Create View Dailyorders as Select Distinct cnum, snum, onum, odate from Orders;

```
d5_96305_sanchit> insert into dailyorders values(1010,'tej',3030,'1990-10-27');
ERROR 1471 (HY000): The target table dailyorders of the INSERT is not insertable-into
```

2) Create View Custotals as Select cname, Sum (amt) Sum_Amt from Orders, Customers where Orders.cnum=Customers.cnum Group by cname;

```
d5_96305_sanchit> insert into custotals values('tej',1000);
ERROR 1471 (HY000): The target table custotals of the INSERT is not insertable
```

3) Create view Thirdorders as Select * from Dailyorders where odate=’1990-10-03’;

```
d5_96305_sanchit> insert into thirdorders values(2003,1001,3003,'1990-10-06');
ERROR 1471 (HY000): The target table thirdorders of the INSERT is not insertable-into
d5_96305_sanchit>
```

4) Create view Nullcities as Select snum, sname, city from Salespeople where city is NULL OR sname BETWEEN ‘A’ and ‘MZ’;

```
d5_96305_sanchit> select * from nullcities;
+------+---------+----------+
| snum | sname   | city     |
+------+---------+----------+
| 1004 | Motika  | London   |
| 1003 | Axelrod | New York |
+------+---------+----------+
2 rows in set (0.013 sec)

d5_96305_sanchit> update nullcities set sname ='tej' where city = 'London';
Query OK, 1 row affected (0.244 sec)
Rows matched: 1  Changed: 1  Warnings: 0

d5_96305_sanchit>
```

6. Create a view of the Salespeople table called Commissions. This view will include only the snum and comm fields. Through this view, someone could enter or change commissions, but only to values between .10 and .20.

```
d5_96305_sanchit> select * from commission;
+------+------+
| snum | comm |
+------+------+
| 1001 | 0.12 |
| 1002 | 0.13 |
| 1004 | 0.11 |
| 1007 | 0.15 |
| 1003 | 0.10 |
+------+------+
5 rows in set (0.164 sec)

d5_96305_sanchit> update commission set comm = 0.14 where snum = 1002;
Query OK, 1 row affected (0.214 sec)
Rows matched: 1  Changed: 1  Warnings: 0

d5_96305_sanchit> insert into commission values(1008,0.19);
Query OK, 1 row affected (0.227 sec)

d5_96305_sanchit>
```