ASSIGNMENT NO: 7

Solved below queries, using “sales” database.

1. Write a query that lists each order number followed by the name of the customer who made the order.

SELECT o.onum,c.cname

FROM customers c INNER JOIN orders o

ON c.cnum = o.cnum;

```
[d5_96525_Deven@sales]>SELECT o.onum,c.cname
    -> FROM customers c INNER JOIN orders o
    -> ON c.cnum = o.cnum;
+------+----------+
| onum | cname    |
+------+----------+
| 3001 | Cisneros |
| 3003 | Hoffman  |
| 3002 | Pereira  |
| 3005 | Liu      |
| 3006 | Cisneros |
| 3009 | Giovanni |
| 3007 | Grass    |
| 3008 | Clemens  |
| 3010 | Grass    |
| 3011 | Clemens  |
+------+----------+
10 rows in set (0.041 sec)
```

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

SELECT o.onum,c.cname,s.sname

FROM customers c INNER JOIN orders o

ON c.cnum = o.cnum

INNER JOIN salespeople s

ON o.snum = s.snum;

```
ERROR 1146 (42S02): Table 'sales.salesperson' doesn't exist
[d5_96525_Deven@sales]>SELECT o.onum,c.cname,s.sname
    -> FROM customers c INNER JOIN orders o
    -> ON c.cnum = o.cnum
    -> INNER JOIN salespeople s
    -> ON o.snum = s.snum;
+------+----------+---------+
| onum | cname    | sname   |
+------+----------+---------+
| 3003 | Hoffman  | Peel    |
| 3009 | Giovanni | Axelrod |
| 3005 | Liu      | Serres  |
| 3010 | Grass    | Serres  |
| 3007 | Grass    | Serres  |
| 3011 | Clemens  | Peel    |
| 3008 | Clemens  | Peel    |
| 3006 | Cisneros | Rifkin  |
| 3001 | Cisneros | Rifkin  |
| 3002 | Pereira  | Motika  |
+------+----------+---------+
10 rows in set (0.124 sec)
```

3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

SELECT c.cname,s.sname,s.comm

FROM customers c INNER JOIN salespeople s

ON c.snum = s.snum

WHERE s.comm>0.12;

```
[d5_96525_Deven@sales]>SELECT c.cname,s.sname,s.comm
    -> FROM customers c INNER JOIN salespeople s
    -> ON c.snum = s.snum
    -> WHERE s.comm>0.12;
+----------+--------+------+
| cname    | sname  | comm |
+----------+--------+------+
| Liu      | Serres | 0.13 |
| Grass    | Serres | 0.13 |
| Cisneros | Rifkin | 0.15 |
+----------+--------+------+
3 rows in set (0.147 sec)
```

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

SELECT o.onum,s.comm, (o.amt * s.comm)

FROM salespeople s

INNER JOIN orders o ON s.snum = o.snum

INNER JOIN customers c ON o.cnum = c.cnum

WHERE c.rating > 100;

```
[d5_96525_Deven@sales]>SELECT o.onum,s.comm, (o.amt * s.comm)
    -> FROM salespeople s
    -> INNER JOIN orders o ON s.snum = o.snum
    -> INNER JOIN customers c ON o.cnum = c.cnum
    -> WHERE c.rating > 100;
+------+------+------------------+
| onum | comm | (o.amt * s.comm) |
+------+------+------------------+
| 3010 | 0.13 |          40.2935 |
| 3007 | 0.13 |           9.8475 |
| 3005 | 0.13 |         670.8585 |
| 3006 | 0.15 |         164.7240 |
| 3001 | 0.15 |           2.8035 |
| 3009 | 0.10 |         171.3230 |
+------+------+------------------+
6 rows in set (0.024 sec)
```

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed .

SELECT t1.sname,t2.sname,t1.city

FROM salespeople t1 INNER JOIN salespeople t2

ON t1.city=t2.city

WHERE t1.city=t2.city

AND t1.sname>t2.sname;

```
[d5_96525_Deven@sales]>SELECT t1.sname,t2.sname,t1.city
    -> FROM salespeople t1 INNER JOIN salespeople t2
    -> ON t1.city=t2.city
    -> WHERE t1.city=t2.city
    -> AND t1.sname>t2.sname;
+-------+--------+--------+
| sname | sname  | city   |
+-------+--------+--------+
| Peel  | Motika | London |
+-------+--------+--------+
1 row in set (0.139 sec)

[d5_96525_Deven@sales]>
```