ASSIGNMENT 2

1. Write a query that produces all rows from the Customers table for which the salesperson's number is 1001.

```
[d5_96525_Deven@sales]>select * from customers where snum = "1001";
+------+---------+--------+--------+------+
| cnum | cname   | city   | rating | snum |
+------+---------+--------+--------+------+
| 2001 | Hoffman | London |    100 | 1001 |
| 2006 | Clemens | London |    100 | 1001 |
+------+---------+--------+--------+------+
2 rows in set (0.138 sec)

[d5_96525_Deven@sales]>
```

2. Write a select command that produces the rating followed by the name of each customer in San Jose.

```
[d5_96525_Deven@sales]>select rating,cname,city from customers where city = "San Jose";
+--------+----------+----------+
| rating | cname    | city     |
+--------+----------+----------+
|    200 | Liu      | San Jose |
|    300 | Cisneros | San Jose |
+--------+----------+----------+
2 rows in set (0.009 sec)
```

3. Write a query that will produce the snum values of all salespeople from the Orders table (with the duplicate values suppressed).

```
[d5_96525_Deven@sales]>select distinct snum from orders;
+------+
| snum |
+------+
| 1007 |
| 1001 |
| 1004 |
| 1002 |
| 1003 |
+------+
5 rows in set (0.149 sec)
```

4. Write a query that will display all the orders for amount more than Rs. 1,000.

```
[d5_96525_Deven@sales]>select * from orders where amt>1000;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
6 rows in set (0.135 sec)
```

5. Write a query that will give you the names and cities of all salespeople in London with a commission above 0.10.

```
[d5_96525_Deven@sales]>select sname,city from salespeople where comm>0.10;
+--------+-----------+
| sname  | city      |
+--------+-----------+
| Peel   | London    |
| Serres | San Jose  |
| Motika | London    |
| Rifkin | Barcelona |
+--------+-----------+
4 rows in set (0.008 sec)
```

6. Write an SQL query that returns all customers who have a rating greater than 100, along with the customers located in Rome regardless of their rating.

```
[d5_96525_Deven@sales]>select * from customers where rating>100;
+------+----------+----------+--------+------+
| cnum | cname    | city     | rating | snum |
+------+----------+----------+--------+------+
| 2002 | Giovanni | Rome     |    200 | 1003 |
| 2003 | Liu      | San Jose |    200 | 1002 |
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
+------+----------+----------+--------+------+
4 rows in set (0.131 sec)
```

7. What will be the output from the following query? Select * from Orders where (amt < 1000 OR NOT (odate = '1990-10- 03' AND cnum > 2003));

```
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 |  767.19 | 1990-10-03 | 2001 | 1001 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 |   75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 |  309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
```

8. What will be the output of the following query? Select * from Orders where NOT (odate = '1990-10-03' OR snum >1006) AND amt >= 1500;

```
[d5_96525_Deven@sales]>Select * from Orders where NOT (odate = '1990-10-03' OR snum >1006) AND amt >= 1500;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
3 rows in set (0.009 sec)
```

9. What is a simpler way to write this query? Select snum, sname, city, comm from Salespeople Where (comm >= .12 AND comm <= .14);
   SELECT *
   FROM salespeople
   WHERE comm BETWEEN 0.12 AND 0.14;
10. Write a query that selects all orders except those with amount less than 100.
   SELECT *
   FROM orders
   WHERE amt<100;