1. Create a new database named **CDAC** and connect to it.

```
test> use CDAC
switched to db CDAC
```

2. Display the list of collections in the **CDAC** database.

```
CDAC> show collections

CDAC>
```

3. Create a collection named **LIBRARY**.

```
CDAC> db.createCollection("LIBRARY")
{ ok: 1 }
CDAC>
```

4. Insert a document into **LIBRARY** with: title: *MongoDB programming*, author: *Amit*, likes: 100

```
CDAC> db.LIBRARY.insertOne({
| title: "MongoDB programming",
| author: "Amit",
| likes: 100
| })
{
  acknowledged: true,
  insertedId: ObjectId('69ba9502e125d0e0da11402a')
}
CDAC>
```

5. Display the inserted document and note the `_id` field.

```
CDAC> db.LIBRARY.find()
[
  {
    _id: ObjectId('69ba9502e125d0e0da11402a'),
    title: 'MongoDB programming',
    author: 'Amit',
    likes: 100
  }
]
```

6. Insert another document into **LIBRARY** with: title: *MySQL programming*, authors: [Jack, Jill], likes: 200

```
CDAC> db.LIBRARY.insertOne({
| title: "MySQL programming",
| authors: ["Jack","Jill"],
| likes: 200
| })
{
  acknowledged: true,
  insertedId: ObjectId('69ba955be125d0e0da11402b')
}
CDAC>
```

7. Display all documents in the **LIBRARY** collection.

```
CDAC> db.LIBRARY.find()
[
  {
    _id: ObjectId('69ba9502e125d0e0da11402a'),
    title: 'MongoDB programming',
    author: 'Amit',
    likes: 100
  },
  {
    _id: ObjectId('69ba955be125d0e0da11402b'),
    title: 'MySQL programming',
    authors: [ 'Jack', 'Jill' ],
    likes: 200
  }
]
CDAC>
```

8. Display only the first inserted document.

```
CDAC> db.LIBRARY.find({author:"Amit"})
[
  {
    _id: ObjectId('69ba9502e125d0e0da11402a'),
    title: 'MongoDB programming',
    author: 'Amit',
    likes: 100
  }
]
CDAC>
```

9. Display documents using the `pretty()` method.

```
CDAC> db.LIBRARY.find().pretty()
[
  {
    _id: ObjectId('69ba9502e125d0e0da11402a'),
    title: 'MongoDB programming',
    author: 'Amit',
    likes: 100
  },
  {
    _id: ObjectId('69ba955be125d0e0da11402b'),
    title: 'MySQL programming',
    authors: [ 'Jack', 'Jill' ],
    likes: 200
  }
]
CDAC>
```

10. Update the document where author = *Amit* to *Amit Sharma*.

```
CDAC> db.LIBRARY.deleteMany({likes:100})
{ acknowledged: true, deletedCount: 1 }
CDAC> db.LIBRARY.updateOne(
| {author:"Amit"},
| {$set:{author:"Amit Sharma"}}
| )
{
  acknowledged: true,
  insertedId: null,
  matchedCount: 0,
  modifiedCount: 0,
  upsertedCount: 0
}
CDAC>
```

11. Delete all documents with likes = 100.

```
CDAC> db.LIBRARY.deleteMany({likes:100})
{ acknowledged: true, deletedCount: 1 }
CDAC>
```

12. Drop the **LIBRARY** collection.

```
CDAC> db.LIBRARY.drop()
true
CDAC>
```

13. Drop the **CDAC** database.

```
CDAC> db.dropDatabase()
{ ok: 1, dropped: 'CDAC' }
CDAC>
```