

5A Schottky Barrier Rectifiers

PRODUCT SUMMARY

Voltage ratings available from 20 Volts to 60 Volts


FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Low power loss, high efficiency
- For use in low voltage high frequency inverters, free wheeling, and polarity protection applications
- Guardring for overvoltage protection

MECHANICAL DATA

- Case: JEDEC DO-201AD molded plastic body
- Terminals: matte-Sn plated axial leads, solderable per MIL-STD-750, Method 2026
- High temperature soldering guaranteed:
250°C for 10 seconds with 0.375" (9.5mm) lead length, 5lbs (2.3kg) tension
- Polarity: color band denotes cathode end
- Mounting position: Any
- Weight: 0.041 ounce, 1.15 grams

DO-201AD



Dimensions in inches and (millimeters)

 **Pb-free; RoHS-compliant**

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Rating at 25°C ambient temperature unless otherwise specified.
- Single phase, half wave, 60 Hz, resistive or inductive load.
- For capacitive load, derate current by 20%







Parameter	Symbols	SB520	SB530	SB540	SB550	SB560	Units
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	50	60	Volts
Maximum RMS voltage	V _{RMS}	14	21	28	35	42	Volts
Maximum DC blocking voltage	V _{DC}	20	30	40	50	60	Volts
Maximum average forward rectified current 0.375" (9.5mm) lead length (See Fig.1)	I _{F(AV)}	5.0					Amps
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC Method) at rated T _L	I _{FSM}	150.0					Amps
Max. instantaneous forward voltage at 5.0A (Note 1)	V _F	0.55			0.67		Volts
Maximum instantaneous reverse current at rated DC blocking voltage (Note 1) @T _A = 25°C @T _A =100°C	I _R	0.5					mA
		50		25			
Typical thermal resistance (Note 2)	R _{θJA} R _{θJL}	25 8					°C/W
Operating junction temperature range	T _j	-55 to +125			-55 to +150		°C
Storage temperature range	T _{STG}	-55 to +150					°C

Notes: 1. Pulse test: 300us pulse width, 1% duty cycle

2. Thermal resistance junction to lead vertical P.C.B. mounted, 0.375" (9.5mm) lead length

RATINGS AND CHARACTERISTIC CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)



Information furnished by Silicon Standard Corporation is believed to be accurate and reliable. However, Silicon Standard Corporation makes no guarantee or warranty, expressed or implied, as to the reliability, accuracy, timeliness or completeness of such information and assumes no responsibility for its use, or for infringement of any patent or other intellectual property rights of third parties that may result from its use. Silicon Standard reserves the right to make changes as it deems necessary to any products described herein for any reason, including without limitation enhancement in reliability, functionality or design. No license is granted, whether expressly or by implication, in relation to the use of any products described herein or to the use of any information provided herein, under any patent or other intellectual property rights of Silicon Standard Corporation or any third parties.