Verifier-Aligned Cover Complexity for CPWL Neural Network Verification

Anonymous Author(s)
Affiliation
Address
email

Abstract

Proof-producing verification is governed by the local proof objects that a trusted kernel can independently re-check, not by the search trace of a particular solver. For continuous piecewise-linear (CPWL) neural networks, however, complexity is still usually described through linear-region counts, branch-and-bound nodes, or mixed-integer encodings. We introduce *Verifier-Aligned Cover Complexity* (VAC), the minimum number of verifier-visible local certified cells needed to prove either exact semantics or a threshold property over a compact domain. For CPWL expression graphs built from unary affine post-composition, addition, scalar gates, and finite-max modules (equivalently, arbitrary affine nodes after normalization), we prove a guard-certified exactification theorem: a static compilation into guard-affine fragments yields finitely many comparison hyperplanes, and any split tree aligned with them turns every nonempty leaf into an accepted exact affine cell. Hence exact-side VAC is finite. We then show that, after fixing a verifier-facing language, cell-complete proof languages realize VAC up to constant factors, and linear encodings preserve that scale up to constant factors as well. We also derive threshold lower bounds via incompatibility graphs, and prove that the explicit-dictionary decision problems EXACT-VAC-DICT and THRESH-VAC-DICT are NP-complete while the corresponding optimization problems are hard to approximate within $(1-\varepsilon)\ln N$. Thus VAC isolates the language-relative semantic cover quantity underlying proof-producing CPWL verification, distinct from search traces, arrangement counts, and syntax-specific encodings.

1 Introduction

Proof-producing verification is constrained by what a small trusted kernel can independently re-check. For CPWL neural networks, however, complexity is still usually measured by solver- or geometry-centric surrogates such as branch-and-bound nodes, SMT/MIP encodings, or linear-region counts [4, 24, 17, 30, 2, 23, 26]. These quantities matter algorithmically, but they are not the objects that the verifier finally accepts.

Our starting question is therefore proof-theoretic: *what is the local proof unit actually consumed by a proof-producing verifier?* In our setting it is a *local certified cell*: a verifier-facing cell together with a finite payload proving either exact affine semantics on that cell or a local threshold fact. Such cells need not coincide with geometric arrangement regions. One verifier-admissible cell may merge several regions when one certificate suffices, while one geometric region may need further splitting to satisfy the local proof language.

We formalize this viewpoint by *Verifier-Aligned Cover Complexity* (VAC), the minimum number of verifier-visible local certified cells needed for an accepted global proof. VAC is semantic rather than algorithmic, and language-relative because the trusted interface determines which cells and

Submitted to 40th Conference on Neural Information Processing Systems (NeurIPS 2026). Do not distribute.

payloads are admissible. For the CPWL expression graphs considered here—built from unary affine post-composition, addition, scalar gates, and finite-max modules over nonempty compact domains, with arbitrary affine fan-in normalized into that basis—we prove a guard-certified exactification theorem: a static guard compilation exposes finitely many comparison hyperplanes, and once a split tree is aligned with them, every nonempty leaf carries an accepted exact affine payload. This yields finite exact certified covers for the whole class.

VAC sits strictly between arrangement geometry and concrete proof syntax. Arrangement count is only a restricted exact-side degeneration, because verifier-admissible cells may refine, merge, or overlap geometric pieces. Conversely, concrete proof syntax is not the primary comparison layer either: once a verifier-facing language is fixed, and once a proof language realizes local certified cells with bounded overhead, minimum proof size differs from VAC only by that realization overhead, in the same spirit as the separation between semantic proof content and proof-system syntax in proof complexity [5].

Contributions. We make four contributions: (i) a finite exactification theorem for the CPWL class above; (ii) a three-layer proof-complexity decomposition separating the language-relative semantic cover quantity VAC from its syntactic realization cost SCC and its bit-level encoding cost DL; (iii) a verifier-aligned upper/lower-bound package, with exact-side upper bounds from exactification and threshold-side lower bounds from incompatibility graphs; and (iv) NP-completeness of the explicit-dictionary decision problems together with logarithmic inapproximability of the associated optimization problems.

The scope is intentionally narrow. We study CPWL expression graphs over nonempty compact domains; VAC is language-relative by design; and the hardness theorem concerns the explicit-dictionary selection layer, not unrestricted continuous certificate languages. We do not claim language invariance across different verifier-facing interfaces, and we do not claim that every pipeline-generated finite candidate family inherits the dictionary hardness theorem without additional representability assumptions. Section 2 fixes the minimal verifier interface, Section 3 proves guard-certified exactification, Section 4 relates VAC to proof size and encoding, Section 5 gives upper and lower bounds, and Section 6 proves explicit-dictionary selection-layer hardness. Appendix A gives the fuller trusted-task semantics, while Appendices C–G contain the deferred proofs and auxiliary formalizations.

Claim map. The paper makes four logically distinct types of claims. First, a structural theorem: guard-certified exactification yields finite accepted exact covers for the CPWL class studied here. Second, a realization theorem: after fixing a verifier-facing language, cell-complete proof languages and linear encodings realize the same semantic cover scale up to fixed overhead. Third, a semantic lower-bound template: incompatibility graphs yield threshold-side lower bounds in the fixed language. Fourth, a combinatorial hardness theorem: the unrestricted explicit-dictionary selection problem is NP-complete and logarithmically hard to approximate. No claim is made here that VAC is invariant across different verifier-facing languages, nor that every pipeline-generated finite candidate family inherits the dictionary hardness theorem without additional representability assumptions.

2 Verifier-Aligned Certified Covers and Main Results

Appendix A develops the fuller task semantics. Here we keep only the interface needed later. Fix a nonempty compact domain $D \subseteq \mathbb{R}^n$ and a target function $g : D \to \mathbb{R}$. Individual verifier-visible cells $C(\gamma)$ may still be empty; such cells are discharged by FEAS, and whenever an affine infimum over an empty cell appears we use the convention $\inf_{x \in \varnothing} a(x) = +\infty$. A *verifier-aligned cell language* $\mathfrak{L}$ consists of finite descriptions γ with verifier-facing set description $\mathfrak{D}(\gamma)$ and semantic cell

$$C(\gamma) := [\![\mathfrak{D}(\gamma)]\!] \subseteq D.$$

Trusted kernel. The kernel exposes only four primitives: FEAS, which either finds $x \in [\![\mathfrak{D}]\!]$ or proves emptiness; AFFOPT, which certifies $\inf_{x \in [\![\mathfrak{D}]\!]}(w^\top x + b)$ for an affine tag; EVAL, which returns a certified value $g(x)$ at a queried point; and CHECK, which deterministically validates finite symbolic payloads such as containments, local equalities or threshold claims, and finite cover proofs. Search traces and branching heuristics are never trusted.

Certified cells and covers. For threshold $t \in \mathbb{R}$, an *exact certified cell* is $(\gamma, a, \pi^{=})$, where a is affine and the accepted payload proves $g(x) = a(x)$ for all $x \in C(\gamma)$; a *threshold certified cell* is $(\gamma, \pi^{\geq})$, where the accepted payload proves $g(x) \geq t$ on $C(\gamma)$. Finite families of such cells become exact or threshold certified covers once CHECK accepts a global cover payload for

$$D \subseteq \bigcup_i C(\gamma_i).$$

The carrier is the same on both sides; only the local statement changes.

VAC.

$$\mathrm{VAC}^{=}_{\mathfrak{L}}(g; D) := \min\{\, |\mathcal{C}^{=}| : \ \mathcal{C}^{=} \text{ is an exact certified cover of } (g, D)\,\},$$
$$\mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) := \min\{\, |\mathcal{C}^{\geq}| : \ \mathcal{C}^{\geq} \text{ is a threshold certified cover of } (g, D, t)\,\},$$

with value $+\infty$ if no finite accepted cover exists. VAC counts verifier-visible local proof units, not runtime, search depth, or arrangement regions.

Proposition (basic soundness contract). Accepted exact cells state correct affine equalities on their cells, and accepted threshold cells state correct local threshold claims. Consequently, if $\mathcal{C}^{=} = \{(\gamma_i, a_i, \pi_i^{=})\}_{i=1}^{N}$ is an exact certified cover, then

$$\inf_{x \in D} g(x) = \min_{1 \leq i \leq N} \ \inf_{x \in C(\gamma_i)} a_i(x),$$

with the convention $\inf_{x \in \varnothing} a_i(x) = +\infty$; and if $\mathcal{C}^{\geq}$ is a threshold certified cover, then $g(x) \geq t$ for all $x \in D$.

Main theorem package. The rest of the paper proves four facts.

1. **Finite exactification for CPWL graphs.** Section 3 constructs a guard language $\mathfrak{L}_{\mathrm{grd}}$ for allowed CPWL expression graphs and proves $\mathrm{VAC}^{=}_{\mathfrak{L}_{\mathrm{grd}}}(g; D) < \infty$ by compiling the network into finitely many guard-affine fragments and aligning a split tree with the resulting comparison hyperplanes.
2. **VAC, proof languages, and encoding overhead.** Section 4 shows that any c-cell-complete proof language $\mathcal{P}$ over $\mathfrak{L}$ satisfies
$$\mathrm{VAC}^{\star}_{\mathfrak{L}} \leq \mathrm{SCC}^{\star}_{\mathcal{P}} \leq c\,\mathrm{VAC}^{\star}_{\mathfrak{L}}, \qquad \star \in \{=, \geq\},$$
and under linear encodings $\mathrm{DL}^{\star}_{\mathcal{P}}$ is linearly equivalent to $\mathrm{SCC}^{\star}_{\mathcal{P}}$; see Appendix E.
3. **Verifier-aligned bounds.** Section 5 gives exact-side upper bounds from accepted exact covers and threshold-side lower bounds
$$\mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) \geq \chi(G_t^{\mathrm{inc}}(X))$$
from incompatibility graphs. When $\inf_D g \geq t$, exact certified covers also transfer to threshold certified covers of no larger size.
4. **Selection-layer hardness.** Section 6 proves NP-completeness for the decision problems EXACT-VAC-DICT and THRESH-VAC-DICT, together with $(1 - \varepsilon) \ln N$ hardness for the corresponding dictionary-restricted optimization problems; Appendix G gives the full reductions.

This section is only the paper's API: it fixes the verifier-facing objects that later sections construct, count, upper-bound, lower-bound, and prove hard to minimize.

3 Guard-Certified Exactification and Finite Exact Covers for CPWL Networks

We consider finite DAG expression graphs whose scalar nodes are built from four modules: unary affine post-composition nodes, addition nodes, scalar gates such as ReLU/LeakyReLU/PReLU/Abs, and finite-max nodes. Any finite-input affine map is first normalized into unary affine post-compositions plus additions, so this choice of primitives is without loss of generality for the structural arguments below. Vector outputs are handled coordinatewise. Let u_g be the output node and write $g(x) = [\![u_g]\!](x)$ on nonempty compact D.

Guard language. The exact-side language $\mathfrak{L}_{\mathrm{grd}}$ uses finite sets of affine comparison literals $h(x) \le 0$ and $h(x) \ge 0$. A guard set S denotes

$$D_S := D \cap \bigcap_{\lambda \in S} \lambda.$$

For a scalar node u, a *certified guard-affine fragment* is a triple (S, a, Π), where a is affine and Π is accepted as a proof that $[\![u]\!](x) = a(x)$ for all $x \in D_S$. A finite family $\mathcal{F}_u = \{(S_r, a_r, \Pi_r)\}$ is *certified faithful* if the cells D_{S_r} cover D and each payload proves the corresponding local affine equality.

Static compilation. Compilation proceeds by topological induction using only four finite rules: affine propagation, common-refinement addition, gate branching via an affine winner comparison, and finite-max with explicit winner comparisons. Each rule combines already accepted child payloads with finitely many affine guards, so faithfulness is preserved.

Theorem (static guard-certified compilation). Every scalar node u in an allowed CPWL expression graph admits a finite certified faithful family $\mathcal{F}_u$. Applied to the output node, this yields a finite family $\mathcal{F}_g$ and therefore a finite comparison-hyperplane set $\mathcal{H}^\star$ produced by compilation, whose leafwise comparison information suffices to freeze the relevant gate branches and max comparisons. Input coordinates and constants give trivial one-fragment families, and the four rules preserve certified faithfulness inductively. Appendix C gives the full rule-by-rule proof.

Aligned leaves. A split tree recursively branches on literals from $\mathcal{H}^\star$; each leaf v carries a path guard set $S(v)$ and domain $D_v := D_{S(v)}$. The tree is *aligned* with $\mathcal{H}^\star$ if, for every leaf and every $h \in \mathcal{H}^\star$, CHECK accepts at least one side claim $D_v \subseteq \{h \le 0\}$ or $D_v \subseteq \{h \ge 0\}$. Alignment freezes every gate branch choice and max-winner comparison leafwise.

Lemma (aligned nonempty leaves are exact). If T is aligned with $\mathcal{H}^\star$ and $D_v \neq \varnothing$, then some fragment $(S, a, \Pi) \in \mathcal{F}_g$ is valid on all of D_v; restricting Π along the accepted containment $D_v \subseteq D_S$ yields an exact certified cell $(S(v), a_v, \pi_v^{=})$ with $g(x) = a_v(x)$ for all $x \in D_v$. Thus every nonempty aligned leaf is an atomic exact cell in $\mathfrak{L}_{\mathrm{grd}}$. The proof is an aligned-leaf induction that shows the leaf signature fixes every dynamic choice in the compilation; see Appendix D.

Global cover payload. A finite split tree also carries a canonical cover payload: every internal node is covered by its two closed-halfspace children, and infeasible leaves can be removed once FEAS proves emptiness. Hence exactification needs only a finite fully aligned tree and the accepted local payloads attached to its live leaves.

Theorem (guard-certified exactification). For the output of any allowed CPWL expression graph over compact D, there exists a finite split tree $T^\star$ aligned with $\mathcal{H}^\star$ such that every nonempty leaf yields an exact certified cell and the live leaves, together with the split-tree cover payload, form an accepted finite exact certified cover of g in $\mathfrak{L}_{\mathrm{grd}}$. Consequently,

$$\mathrm{VAC}^{=}_{\mathfrak{L}_{\mathrm{grd}}}(g; D) < +\infty.$$

The theorem is structural, not optimal: $|\,\mathrm{Live}(T^\star)|$ is one verifier-accepted upper bound, not necessarily the minimum.

4 VAC, Proof Languages, and Realization Overhead

Exactification gives finite accepted covers; the next question is what quantity those covers measure. The key distinction is between semantic cover complexity, concrete proof syntax, and bit-level encoding.

Fix a verifier-facing language $\mathfrak{L}$. A *proof language* $\mathcal{P}$ over $\mathfrak{L}$ consists of finite proof objects whose leaves denote certified cells from $\mathfrak{L}$ and whose global payload certifies that the leaves jointly form the required cover. This includes flat leaf tables, split trees, and more structured proof objects with the same verifier-visible leaf semantics.

Syntactic and bit-level measures. The minimum leaf count of an accepted proof object defines syntactic certificate complexity:

$$\mathrm{SCC}^{=}_{\mathcal{P}}(g; D) := \min\{\, |\,\mathrm{Leaves}(P)| : \; P \in \mathcal{P} \text{ is an accepted exact proof of } (g, D)\,\},$$

$$\mathrm{SCC}^{\geq}_{\mathcal{P}}(g; D, t) := \min\{\, |\,\mathrm{Leaves}(P)| : \; P \in \mathcal{P} \text{ is an accepted threshold proof of } (g, D, t)\,\}.$$

Fixing a binary encoding analogously gives $\mathrm{DL}^{=}_{\mathcal{P}}$ and $\mathrm{DL}^{\geq}_{\mathcal{P}}$. The canonical flat leaf-table language $\mathcal{P}_{\mathrm{tab}}(\mathfrak{L})$ realizes VAC exactly, because a semantic certified cover is already such a table plus one cover payload.

Cell-complete languages. A proof language is c-cell-complete if every accepted proof object extracts to a certified cover with no more cells than leaves, and every certified cover of size N compiles into an accepted proof object with at most cN leaves. The exact and threshold sides are defined separately but identically.

Theorem (VAC/SCC equivalence under cell completeness). If $\mathcal{P}$ is exact-side or threshold-side c-cell-complete over $\mathfrak{L}$, then for $\star \in \{=, \geq\}$,

$$\mathrm{VAC}^{\star}_{\mathfrak{L}} \leq \mathrm{SCC}^{\star}_{\mathcal{P}} \leq c\,\mathrm{VAC}^{\star}_{\mathfrak{L}}.$$

The left inequality extracts a semantic cover from any accepted proof object; the right inequality compiles an optimal semantic cover back into the chosen syntax with at most c times as many leaves. Under the linear-encoding assumptions formalized in Appendix E, $\mathrm{DL}^{\star}_{\mathcal{P}}$ is likewise linearly equivalent to $\mathrm{SCC}^{\star}_{\mathcal{P}}$. The point is therefore not cross-language invariance, but a clean separation of layers: after fixing $\mathfrak{L}$, VAC measures the semantic cover quantity, SCC measures syntactic realization cost, and DL measures encoding cost.

Arrangement count as a restricted degeneration. Arrangement geometry reappears only under extra exact-side assumptions. If the maximal connected exact-affine regions $U_1, \ldots, U_M$ of g are each realizable as one connected exact certified cell of $\mathfrak{L}$, and each region contains a point not lying in any other region, then the minimum number of connected exact certified cells is exactly M. The upper bound comes from one cell per region; the lower bound uses the region-exclusive witness points, which no connected exact cell can cover across two different maximal regions. Outside this narrow regime arrangement count is not, in general, the semantic cover quantity: a verifier-admissible cell may refine or merge geometric pieces, and threshold proofs need not recover exact affine regions at all. Appendix E expands the proof-language formalization and encoding details.

5 Upper and Lower Bounds for Verifier-Aligned Covers

This section is the quantitative payoff of the previous two sections. Section 3 produced verifier-accepted finite exact covers for the CPWL class studied here, and Section 4 showed that, after fixing the verifier-facing language $\mathfrak{L}$, the paper's quantitative statements are most naturally formulated at the semantic cover layer and then transferred to cell-complete proof-language realizations up to their fixed realization constants. We now package those ingredients into the first quantitative results at the VAC layer. The upper-bound side comes from accepted exact covers produced by guard-certified exactification; the lower-bound side comes from a clean incompatibility graph on threshold witness points. The corresponding SCC and DL statements then follow from Section 4 and Appendix E up to those fixed constants.

5.1 Exact-Side Upper Bounds from Finite Exactification

Fix an allowed CPWL expression graph over nonempty compact domain D, let g be its output, and let

$$\mathcal{H}^{\star}$$

be the finite comparison-hyperplane family produced in Section 3. If T is any split tree aligned with $\mathcal{H}^{\star}$, write

$$\mathrm{Live}(T) := \{v \in \mathrm{Leaves}(T) : D_v \neq \varnothing\}.$$

By the exactification theorem, each $v \in \mathrm{Live}(T)$ carries an exact certified cell

$$\big(S(v), a_v, \pi^{=}_{v}\big)$$

in the guard language $\mathfrak{L}_{\mathrm{grd}}$, and Section 3 also provides the finite global cover payload certifying that the live leaves cover D.

Theorem (Exact-side upper bound from finite exactification). Let T be any split tree aligned with $\mathcal{H}^\star$. Then the family

$$\left\{ \left(S(v), a_v, \pi_v^{=} \right) : v \in \mathrm{Live}(T) \right\}$$

together with the split-tree cover payload is an exact certified cover of D. Consequently,

$$\mathrm{VAC}^{=}_{\mathfrak{L}_{\mathrm{grd}}}(g; D) \leq |\,\mathrm{Live}(T)|.$$

In particular,

$$\mathrm{VAC}^{=}_{\mathfrak{L}_{\mathrm{grd}}}(g; D) < +\infty.$$

Proof sketch. Section 3 proves three facts simultaneously: every aligned nonempty leaf is an accepted exact certified cell; every aligned empty leaf is discharged by infeasibility; and the split tree itself carries a finite global cover payload. Therefore the live leaves are not merely a semantic partition into exact pieces; they already form an accepted exact certified cover in the sense of Section 2. VAC is the minimum size of such a cover, so it cannot exceed the number of live leaves.

The point of the theorem is structural finiteness, not optimality. The right-hand side counts one accepted exactification cover, not arrangement regions of the underlying function geometry. A smaller verifier-accepted cover may still exist because exact certified cells need not coincide one-to-one with connected exact-affine regions.

5.2 Exact-to-Threshold Transfer

The exact-side theorem gives finite accepted exact covers unconditionally for the CPWL class considered here. The threshold side is different: a finite threshold certified cover can exist only when the threshold claim itself is true. The transfer from exact proofs to threshold proofs is therefore conditional on the truth of the threshold statement.

Proposition (Exact-to-threshold transfer). Fix any verifier-facing cell language $\mathfrak{L}$ and threshold $t \in \mathbb{R}$. If

$$\inf_{x \in D} g(x) \geq t,$$

then every exact certified cover of (g, D) with N cells induces a threshold certified cover of (g, D, t) with the same N cell descriptions. Consequently,

$$\mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) \leq \mathrm{VAC}^{=}_{\mathfrak{L}}(g; D).$$

Proof sketch. Take one exact certified cell

$$(\gamma, a, \pi^{=}).$$

Because

$$g(x) = a(x) \qquad \forall x \in C(\gamma),$$

and because the global assumption gives $\inf_D g \geq t$, we have

$$\inf_{x \in C(\gamma)} a(x) = \inf_{x \in C(\gamma)} g(x) \geq t.$$

Calling AFFOPT on the verifier-facing description $\mathfrak{D}(\gamma)$ and the affine tag a yields a finite certificate of this local affine infimum; no optimizer witness is needed. Concatenating that local optimization certificate with the already accepted exact payload gives a finite threshold payload on the same cell description γ. Repeating this cell by cell converts any exact certified cover into a threshold certified cover without changing its cardinality.

Corollary (Threshold-side finiteness is conditional). For every verifier-facing language $\mathfrak{L}$,

$$\inf_{x\in D} g(x) < t \quad \Longrightarrow \quad \mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) = +\infty.$$

For the CPWL guard language,

$$\inf_{x\in D} g(x) \geq t \quad \Longrightarrow \quad \mathrm{VAC}^{\geq}_{\mathfrak{L}_{\mathrm{grd}}}(g; D, t) \leq \mathrm{VAC}^{=}_{\mathfrak{L}_{\mathrm{grd}}}(g; D) \leq |\,\mathrm{Live}(T)|$$

for every split tree T aligned with $\mathcal{H}^{\star}$.

Reason. If a finite threshold certified cover existed while $\inf_D g < t$, then the soundness contract from Section 2 would force $g(x) \geq t$ for all $x \in D$, a contradiction. When the threshold claim is true, the proposition applies to the exactification cover from the previous subsection.

Thus exactification always yields exact-side finiteness, whereas threshold-side finiteness is a semantic consequence of truth. This is precisely why threshold VAC is not just "exact VAC with inequalities": it measures a different proof task.

5.3 Threshold Lower Bounds via Incompatibility Graphs

Upper bounds show that verifier-aligned covers exist. To prove that they sometimes must be large, we move to a clean threshold-side lower-bound template. The question is purely semantic: which witness points can one accepted local threshold cell certify simultaneously?

Fix a verifier-facing language $\mathfrak{L}$ and threshold t.

Definition (Threshold incompatibility graph). Let

$$X = \{x_1, \ldots, x_m\} \subseteq D$$

be a finite witness set. Two points $x_i, x_j \in X$ are *threshold-compatible* if there exists a threshold certified cell

$$(\gamma, \pi^{\geq})$$

such that

$$x_i, x_j \in C(\gamma).$$

If no such threshold certified cell exists, they are *threshold-incompatible*. The corresponding incompatibility graph is the graph

$$G^{\mathrm{inc}}_t(X)$$

on vertex set X with edge relation

$$\{x_i, x_j\} \in E\big(G^{\mathrm{inc}}_t(X)\big) \iff x_i \text{ and } x_j \text{ are threshold-incompatible.}$$

This graph is language-relative and verifier-aligned: it depends only on which pairs of points can be handled together by one accepted local threshold certificate.

Observation. Every threshold certified cell induces an independent set in $G^{\mathrm{inc}}_t(X)$. Indeed, if two vertices contained in the same accepted threshold cell were adjacent, then by definition they would be threshold-incompatible, which is impossible.

Theorem (Chromatic-number lower bound). For every finite witness set $X \subseteq D$,

$$\mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) \geq \chi\big(G^{\mathrm{inc}}_t(X)\big),$$

where χ denotes chromatic number.

Proof sketch. Take any threshold certified cover

$$\mathcal{C}^{\geq} = \{(\gamma_i, \pi_i^{\geq})\}_{i=1}^{N}.$$

Each cell contributes an independent vertex set

$$I_i := X \cap C(\gamma_i)$$

of the incompatibility graph. Because the cells cover D, the sets $I_1, \ldots, I_N$ cover every vertex of X. Hence the graph is covered by N independent sets. The minimum number of independent sets needed to cover the vertices of a finite graph is exactly its chromatic number, so every threshold certified cover must have size at least $\chi(G^{\mathrm{inc}}_t(X))$. Minimizing over all covers gives the claim.

Two corollaries are especially convenient.

Corollary (Clique lower bound). For every finite witness set $X \subseteq D$,

$$\mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) \geq \omega\big(G^{\mathrm{inc}}_t(X)\big),$$

where ω is the clique number.

Corollary (Pairwise incompatibility). If there exist points $x_1, \ldots, x_m \in D$ that are pairwise threshold-incompatible, then

$$\mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) \geq m.$$

These lower bounds are as verifier-aligned as the upper bounds from exactification. They do not count search nodes, branch-and-bound iterations, or linear regions. They record only which witness points one accepted local threshold certificate can or cannot handle together. In that sense they are genuine proof-complexity lower bounds at the fixed semantic cover layer.

Taken together, Sections 3, 4, and the present section give the core quantitative picture of the paper: exactification supplies accepted finite exact covers, threshold incompatibility supplies language-relative lower bounds, and VAC is the fixed-language semantic cover quantity that both sides meet on. Section 6 will then ask the complementary algorithmic question: once an explicit finite pool of candidate verifier-visible cells has been exposed, how hard is it to find the smallest accepted subcover?

6 Selection-Layer Complexity for Explicit Dictionaries

The previous sections identify the fixed-language semantic cover quantity. We now isolate the remaining algorithmic question at the explicit-dictionary selection layer: once a finite family of verifier-visible candidate cells has already been exposed, how hard is it to choose the smallest accepted subcover? Full reductions are in Appendix G.

Dictionary-restricted problems. Work over an explicit finite rational point domain $U = \{u_1, \ldots, u_N\} \subseteq \mathbb{Q}^n$ with explicit values $g(u_i) \in \mathbb{Q}$. An exact dictionary entry is (A_j, a_j) with $A_j \subseteq U$ and affine a_j; it is valid when $g(u) = a_j(u)$ for all $u \in A_j$. EXACT-VAC-DICT asks whether at most k valid entries from a dictionary $\mathcal{D}_=$ cover U, and $\mathrm{OPT}_=(U, \mathcal{D}_=)$ denotes the minimum size of such a cover. For rational threshold t, THRESH-VAC-DICT is defined analogously using valid threshold entries $A_j \subseteq U$ satisfying $g(u) \geq t$ for all $u \in A_j$, with optimum $\mathrm{OPT}_{\geq}(U, \mathcal{D}_{\geq}, t)$.

These problems isolate only the *selection layer*: no continuous search or candidate generation remains; all residual difficulty is combinatorial.

Theorem (NP-completeness of explicit-dictionary VAC selection). The decision problems EXACT-VAC-DICT and THRESH-VAC-DICT are NP-complete. Membership in NP is immediate because a proposed subcover can be checked by finite inspection. For NP-hardness, reduce from SET COVER: encode each universe element as a rational point, set $g \equiv 0$, and use one dictionary entry per set, with affine tag $a_j \equiv 0$ on the exact side and threshold $t = 0$ on the threshold side. Valid subcovers of the dictionary are then exactly set covers, and the optimum value is preserved.

Corollary (Logarithmic inapproximability of explicit-dictionary VAC minimization). For every fixed $\varepsilon \in (0, 1)$, unless $\mathrm{P} = \mathrm{NP}$, neither corresponding optimization problem $\mathrm{OPT}_=(U, \mathcal{D}_=)$ nor $\mathrm{OPT}_{\geq}(U, \mathcal{D}_{\geq}, t)$ admits a polynomial-time approximation within factor $(1 - \varepsilon) \ln N$. The classical logarithmic barrier for SET COVER transfers directly through the optimum-preserving reduction.

The conclusion is deliberately scoped. Appendix G proves hardness for the unrestricted explicit-dictionary selection problem. A concrete proof pipeline inherits this hardness only if the class of candidate families it can expose is rich enough to realize hard set-cover instances, formalized in Theorem G.15. Absent such a representability assumption, no generic hardness transfer follows from the present reduction alone. Candidate generation and cover selection are therefore distinct sources of difficulty.

6.1 Conclusion and Scope

This paper resolves one specific proof-complexity question for proof-producing CPWL verification. For the CPWL expression graphs studied here, it proves finite guard-certified exactification and

therefore finite exact certified covers. After fixing a verifier-facing language, it separates the semantic cover quantity VAC from its syntactic realizations and encodings, and shows that explicit-dictionary cover minimization already contains a genuine combinatorial hardness source.

At the same time, the scope is intentionally limited. The structural theorem is proved for CPWL expression graphs over nonempty compact domains; VAC is language-relative by design; and the hardness theorem is unconditional only for unrestricted explicit dictionaries, with transfer to concrete pipelines requiring additional representability assumptions on the exposed candidate-family class.

The resulting picture is therefore layered rather than absolute: arrangement count, proof syntax, and bit-level encoding are not the semantic cover quantity itself. Once the verifier-facing language is fixed, VAC is the semantic cover quantity being realized, while SCC and DL record realization and encoding overhead

7 Experimental Results

We evaluate the saved v3 artifact on 126 exact-side instances together with matching canonical true-threshold tasks, false controls, curated threshold-stage subsets, selection-stage subsets, and realization measurements. Gold Tiny is the only exhaustive suite in the current artifact, so outside it we do not claim ground-truth VAC values: on the exact side we report accepted exactification upper bounds $U_{\mathrm{eq}}^{\mathrm{align}}$ and exposed exact optima, while on the threshold side we report transfer upper bounds $U_{\geq}^{\mathrm{transfer}}$, exposed optima over the bounded threshold language implemented by the pipeline, and certified exposed lower bounds. Detailed plots and per-family breakdowns are deferred to Appendix I.

The exact-side results support the finite exactification story. All 126 instances complete, and $U_{\mathrm{eq}}^{\mathrm{align}}$ grows with the number of compiled comparison hyperplanes H while staying far below the crude 2^H envelope (Appendix I, Fig. I.2). The median accepted exact upper bounds are 32.5, 34.0, and 33.0 on Family A, Family B, and ThresholdStress, compared with 2.0 on the exhaustive Gold Tiny suite. Exact compression is usually tight: the median ratio $U_{\mathrm{eq}}^{\mathrm{align}}/\mathrm{OPT}_{\mathrm{eq}}^{\mathrm{exposed}}$ is $1.0\times$ on Family A, Family B, Gold Tiny, and ThresholdStress. The main exception is SelectionStress, whose median compression factor is $12.5\times$, confirming that candidate exposure and semantic optimum can separate substantially even when the constructive exactification bound remains moderate.

Threshold-side behavior matches the theory but is not captured by a single monotone slogan. On all 126 false controls the artifact finds no finite accepted threshold cover, while on all 126 canonical true-threshold tasks the transfer upper bound dominates the exposed threshold optimum. On the curated threshold subset, enlarging the exposed threshold language from D_{transfer} to $+D_{\mathrm{drop}}$ reduces the median exposed optimum from 38.0 to 19.5, with the median exposed lower bound staying at 16.0. In most benchmark families the exposed threshold optimum is smaller than the exposed exact optimum, but this is not universal: the only 12 instances with $\mathrm{OPT}_{\geq}^{\mathrm{exposed}} > \mathrm{OPT}_{=}^{\mathrm{exposed}}$ all come from SelectionStress. We therefore state threshold results in the language-relative form used throughout the artifact rather than as a blanket claim that threshold covers are always easier.

The selection and realization experiments complete the picture. On the curated explicit-candidate subset, the selection dictionary grows from a median of 40.5 candidates at D_{leaf} to 586.0 at $+D_{\mathrm{drop}}$, while the median exposed exact optimum collapses from 40.5 to 3.0; this is direct evidence of selection-layer compression after candidate exposure. On the realization side, compact/core proof size is almost perfectly linear in proof-cell count (Pearson correlation 0.995, fitted slope ≈ 206 bytes per cell), whereas archive bundles are much larger and strongly family-dependent, with median archive-to-core ratios ranging from $5.1\times$ on Gold Tiny to $251.7\times$ on SelectionStress. Core checking remains sub-millisecond on the saved bundle, and exactification generation stays below 5.8 seconds on every shipped instance. Overall, the experiments support three empirical claims: exactification yields observable finite covers at moderate constructive cost, threshold and selection exposure can materially change the optimum before any hardness statement is invoked, and compact/core realizations—not full archives—are the correct object to compare at the SCC/DL-facing layer.

References

[1] Rudy Bunel, Ilker Turkaslan, Philip H. S. Torr, Pushmeet Kohli, and M. Pawan Kumar. A unified view of piecewise linear neural network verification. In *Advances in Neural Information Processing Systems*, 2018.

[2] Rudy Bunel, Ilker Turkaslan, Philip H. S. Torr, Pushmeet Kohli, and M. Pawan Kumar. Branch and bound for piecewise linear neural network verification. *Journal of Machine Learning Research*, 21(42):1–39, 2020.

[3] Hong-Ming Chiu, Hao Chen, Huan Zhang, and Richard Y. Zhang. Sdp-crown: Efficient bound propagation for neural network verification with tightness of semidefinite programming. In *International Conference on Machine Learning (ICML)*, 2025.

[4] Edmund M. Clarke, Orna Grumberg, and Doron A. Peled. *Model Checking*. MIT Press, 1999.

[5] Stephen A. Cook and Robert A. Reckhow. The relative efficiency of propositional proof systems. *Journal of Symbolic Logic*, 44(1):36–50, 1979.

[6] Lucas C. Cordeiro, Matthew L. Daggitt, Julien Girard-Satabin, Omri Isac, Taylor T. Johnson, Guy Katz, Ekaterina Komendantskaya, Augustin Lemesle, Edoardo Manino, Artjoms Sinkarovs, and Haoze Wu. Neural network verification is a programming language challenge. In *Programming Languages and Systems (ESOP)*, Lecture Notes in Computer Science, pages 206–235. Springer, 2025.

[7] Remi Desmartin, Omri Isac, Grant Passmore, Ekaterina Komendantskaya, Kathrin Stark, and Guy Katz. A certified proof checker for deep neural network verification in imandra. In *16th International Conference on Interactive Theorem Proving (ITP 2025)*, volume 352 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 1:1–1:21. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2025.

[8] Irit Dinur and David Steurer. Analytical approach to parallel repetition. In *Proceedings of the 46th Annual ACM Symposium on Theory of Computing*, pages 624–633, 2014.

[9] Hai Duong, ThanhVu Nguyen, and Matthew B. Dwyer. Generating and checking dnn verification proofs. In *Advances in Neural Information Processing Systems*, 2025. NeurIPS 2025 poster.

[10] Hai Duong, David Shriver, ThanhVu Nguyen, and Matthew B. Dwyer. Compositional neural network verification via assume-guarantee reasoning. In *Advances in Neural Information Processing Systems*, 2025. NeurIPS 2025 spotlight.

[11] Ruediger Ehlers. Formal verification of piece-wise linear feed-forward neural networks. In *Automated Technology for Verification and Analysis (ATVA)*, volume 10482 of *Lecture Notes in Computer Science*, pages 269–286. Springer, 2017.

[12] Uriel Feige. A threshold of $\ln n$ for approximating set cover. *Journal of the ACM*, 45(4): 634–652, 1998.

[13] Claudio Ferrari, Mark Niklas M"uller, Nikola Jovanovic, and Martin Vechev. Complete verification via multi-neuron relaxation guided branch-and-bound. In *International Conference on Learning Representations (ICLR)*, 2022.

[14] Marc Fischer, Christian Sprecher, Dimitar I. Dimitrov, Gagandeep Singh, and Martin Vechev. Shared certificates for neural network verification. In *Computer Aided Verification (CAV)*, pages 127–148. Springer, 2022.

[15] Timon Gehr, Matthew Mirman, Dana Drachsler-Cohen, Petar Tsankov, Swarat Chaudhuri, and Martin Vechev. AI2: Safety and robustness certification of neural networks with abstract interpretation. In *2018 IEEE Symposium on Security and Privacy (SP)*. IEEE, 2018.

[16] Omri Isac, Clark W. Barrett, Min Zhang, and Guy Katz. Neural network verification with proof production. In *Formal Methods in Computer-Aided Design (FMCAD)*, pages 38–48, 2022.

[17] Guy Katz, Clark Barrett, David L. Dill, Kyle Julian, and Mykel J. Kochenderfer. Reluplex: An efficient SMT solver for verifying deep neural networks. In *Computer Aided Verification*, volume 10426 of *Lecture Notes in Computer Science*, pages 97–117. Springer, 2017.

[18] Guy Katz, Derek A. Huang, Duligur Ibeling, Kyle Julian, Christopher Lazarus, Rachel Lim, Parth Shah, Shantanu Thakoor, Haoze Wu, Aleksandar Zeljic, David L. Dill, Mykel J. Kochenderfer, and Clark W. Barrett. The marabou framework for verification and analysis of deep neural networks. In *Computer Aided Verification (CAV)*, volume 11561 of *Lecture Notes in Computer Science*, pages 443–452. Springer, 2019.

[19] Changliu Liu, Tomer Arnon, Christopher Lazarus, Christopher Strong, Clark Barrett, and Mykel J. Kochenderfer. Algorithms for verifying deep neural networks. *Foundations and Trends in Optimization*, 4(3–4):244–404, 2021.

[20] Jiaxiang Liu, Yunhan Xing, Xiaomu Shi, Fu Song, Zhiwu Xu, and Zhong Ming. Abstraction and refinement: Towards scalable and exact verification of neural networks. *ACM Transactions on Software Engineering and Methodology*, 33(5):129:1–129:35, 2024.

[21] Diego Manzanas Lopez, Sung Woo Choi, Hoang-Dung Tran, and Taylor T. Johnson. Nnv 2.0: The neural network verification tool. In *Computer Aided Verification (CAV)*, volume 13965 of *Lecture Notes in Computer Science*, pages 397–412. Springer, 2023.

[22] Edoardo Manino, Iury Bessa, and Lucas C. Cordeiro. Towards global neural network abstractions with locally-exact reconstruction. *Neural Networks*, 165:344–357, 2023.

[23] Guido Montufar, Razvan Pascanu, Kyunghyun Cho, and Yoshua Bengio. On the number of linear regions of deep neural networks. In *Advances in Neural Information Processing Systems 27*, 2014.

[24] George C. Necula. Proof-carrying code. In *Proceedings of the 24th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, pages 106–119, 1997.

[25] Maithra Raghu, Ben Poole, Jon Kleinberg, Surya Ganguli, and Jascha Sohl-Dickstein. On the expressive power of deep neural networks. In *International Conference on Machine Learning (ICML)*, 2017.

[26] Thiago Serra, Christian Tjandraatmadja, and Srikumar Ramalingam. Bounding and counting linear regions of deep neural networks. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 4558–4566, 2018.

[27] Zhouxing Shi, Qirui Jin, Zico Kolter, Suman Jana, Cho-Jui Hsieh, and Huan Zhang. Neural network verification with branch-and-bound for general nonlinearities. In *Tools and Algorithms for the Construction and Analysis of Systems (TACAS)*, pages 315–335. Springer, 2025.

[28] David Shriver, Sebastian G. Elbaum, and Matthew B. Dwyer. Dnnv: A framework for deep neural network verification. In *Computer Aided Verification (CAV)*, volume 12759 of *Lecture Notes in Computer Science*, pages 137–150. Springer, 2021.

[29] Gagandeep Singh, Timon Gehr, Markus Püschel, and Martin Vechev. An abstract domain for certifying neural networks. *Proceedings of the ACM on Programming Languages*, 3(POPL): 41:1–41:30, 2019.

[30] Vincent Tjeng, Kai Yuanqing Xiao, and Russ Tedrake. Evaluating robustness of neural networks with mixed integer programming. In *International Conference on Learning Representations*, 2019.

[31] Shiqi Wang, Kexin Pei, Justin Whitehouse, Junfeng Yang, and Suman Jana. Formal security analysis of neural networks using symbolic intervals. In *27th USENIX Security Symposium (USENIX Security 18)*, pages 1599–1614. USENIX Association, 2018.

[32] Shiqi Wang, Huan Zhang, Kaidi Xu, Xue Lin, Suman Jana, Cho-Jui Hsieh, and J. Zico Kolter. Beta-CROWN: Efficient bound propagation with per-neuron split constraints for neural network robustness verification. In *Advances in Neural Information Processing Systems*, pages 29909–29921, 2021.

[33] Kaidi Xu, Huan Zhang, Shiqi Wang, Yihan Wang, Suman Jana, Xue Lin, and Cho-Jui Hsieh. Fast and complete: Enabling complete neural network verification with rapid and massively parallel incomplete verifiers. In *International Conference on Learning Representations (ICLR)*, 2021.

[34] Huan Zhang, Tsui-Wei Weng, Pin-Yu Chen, Cho-Jui Hsieh, and Luca Daniel. Efficient neural network robustness certification with general activation functions. In *Advances in Neural Information Processing Systems*, 2018.

[35] Huan Zhang, Shiqi Wang, Kaidi Xu, Linyi Li, Bo Li, Suman Jana, Cho-Jui Hsieh, and J. Zico Kolter. General cutting planes for bound-propagation-based neural network verification. In *Advances in Neural Information Processing Systems*, 2022.

A Trusted Task Semantics and Snapshot Soundness

Section 2 deliberately keeps only the smallest semantic interface needed by the main theorem flow: the trusted kernel, local certified cells, certified covers, and the statements proved later for the CPWL class. This appendix restores the fuller task-level substrate that sits underneath that compressed presentation. Its purpose is not to introduce new structural results. Its role is to make precise what a partially completed verifier-visible proof state already means externally.

At this level, the paper is about five objects:

1. a minimal trusted interface, consisting only of the primitives the verifier may invoke directly;
2. leaf-level evidence objects, namely infeasibility certificates, affine lower-bound certificates, exact leaf certificates, and point witnesses;
3. *snapshots*, which package a finite leaf cover together with all currently accepted evidence and therefore certify a global interval;
4. *anytime refinement*, which explains why adding accepted evidence or refining leaves can only strengthen that certified interval; and
5. the *finite exactification boundary*, which characterizes when a finite accepted snapshot already collapses to the true global optimum.

This appendix is purely task-semantic. It does not assume a specific network architecture, search strategy, branch-and-bound trace, or proof language. Section 3 later shows that for the CPWL class studied in the paper, the finite exactification condition is in fact achieved.

A.1 Global Tasks, Leaf Covers, and the Trusted Interface

Fix a nonempty compact input domain

$$D \subseteq \mathbb{R}^n$$

and a target function

$$g : D \to \mathbb{R}.$$

At the task layer there are two equivalent views.

Threshold tasks. Given a threshold $t \in \mathbb{R}$, define the global threshold statement

$$\Phi_t(g, D) : \qquad \forall x \in D,\ g(x) \geq t.$$

Equivalently,

$$\Phi_t(g, D) \iff \inf_{x \in D} g(x) \geq t.$$

Optimization tasks. Instead of asking about only one threshold, we may ask for a verifier-certified interval

$$[L, U] \qquad \text{such that} \qquad L \leq \inf_{x \in D} g(x) \leq U.$$

Whenever the infimum is attained, the same statements may be read with $\min_{x \in D} g(x)$ in place of $\inf_{x \in D} g(x)$. This is the case in the paper's main compact CPWL settings.

The trusted primitives. The verifier trusts only the following four primitives.

FEAS. Given a verifier-facing set description $\mathfrak{D}$, the primitive either returns a witness

$$x \in [\![\mathfrak{D}]\!]$$

or an infeasibility certificate proving

$$[\![\mathfrak{D}]\!] = \varnothing.$$

AFFOPT. Given a verifier-facing set description $\mathfrak{D}$ and an affine function

$$a(x) = w^\top x + b,$$

this primitive certifies the exact value

$$L = \inf_{x \in [\![\mathfrak{D}]\!]} a(x),$$

with the convention

$$\inf_{x \in \varnothing} a(x) = +\infty.$$

When $[\![\mathfrak{D}]\!]$ is nonempty and compact, the primitive may also return an optimizer

$$x^\star \in [\![\mathfrak{D}]\!], \qquad L = a(x^\star).$$

EVAL. Given a point $x \in D$, the primitive returns $g(x)$ together with a certificate anchoring that value to the true semantics of the target.

CHECK. This is a deterministic checker for finite symbolic payloads. It validates containments, finite covers, local lower bounds, local equalities, local threshold claims, and finite derivation chains assembled from the other trusted primitives. It does *not* search for new certificates and it does *not* act as a semantic oracle for arbitrary quantified statements.

The interface is intentionally minimal. Search policies, branching heuristics, candidate generators, and runtime traces are not trusted. Only finite evidence reducible to FEAS, AFFOPT, EVAL, and CHECK contributes to the verifier-visible semantics.

Leaf descriptions and leaf covers. All local evidence is attached to *leaves*. A leaf description is written ℓ and carries a verifier-facing set description $\mathfrak{D}_\ell$. Its semantic domain is

$$D_\ell := [\![\mathfrak{D}_\ell]\!].$$

A finite family

$$\mathcal{L} = \{\ell_1, \dots, \ell_N\}$$

is a *leaf cover* of D if the verifier accepts a finite cover payload proving

$$D \subseteq \bigcup_{\ell \in \mathcal{L}} D_\ell, \qquad D_\ell \subseteq D \quad \text{for all } \ell \in \mathcal{L}.$$

Leaves may overlap.

Refinement of leaf covers. Given two leaf covers $\mathcal{L}$ and $\mathcal{L}'$, we say that $\mathcal{L}'$ *refines* $\mathcal{L}$, written

$$\mathcal{L}' \succeq \mathcal{L},$$

if there is a parent map

$$p : \mathcal{L}' \to \mathcal{L}$$

and accepted containments and cover statements such that every new leaf lies inside its parent,

$$D_{\ell'} \subseteq D_{p(\ell')},$$

and every old leaf is covered by its children,

$$D_\ell \subseteq \bigcup_{\ell' : p(\ell') = \ell} D_{\ell'}.$$

This is the task-level notion of splitting one verified region into subregions.

A.2 Leaf Certificates and Point Witnesses

The task layer uses four kinds of local evidence.

Infeasible leaves. An infeasibility certificate is written

$$\mathrm{Infeas}(\ell; \pi_\ell^{\mathrm{infeas}}),$$

and is accepted exactly when FEAS proves

$$D_\ell = \varnothing.$$

Its soundness is immediate. Infeasibility is also downward closed: if $D_{\ell'} \subseteq D_\ell$ and $D_\ell = \varnothing$, then $D_{\ell'} = \varnothing$ as well.

Affine lower-bound leaves. A lower-bound certificate is written

$$\mathrm{LB}(\ell; a_\ell, L_\ell, \pi_\ell^{\mathrm{dom}}, \pi_\ell^{\mathrm{opt}}),$$

where $a_\ell(x) = w_\ell^\top x + b_\ell$ is affine, π_ℓ^{dom} is accepted as a proof of

$$a_\ell(x) \le g(x) \qquad \forall x \in D_\ell,$$

and π_ℓ^{opt} is accepted as a proof of

$$L_\ell = \inf_{x \in D_\ell} a_\ell(x).$$

Consequently,

$$g(x) \ge a_\ell(x) \ge L_\ell \qquad \forall x \in D_\ell,$$

so every accepted lower-bound certificate yields a sound leafwise lower bound on the target.

Lower-bound certificates are reusable under refinement. If $D_{\ell'} \subseteq D_\ell$, then the same affine tag a_ℓ remains valid on the child leaf, and re-running AFFOPT on $D_{\ell'}$ yields

$$L_{\ell \to \ell'} := \inf_{x \in D_{\ell'}} a_\ell(x), \qquad L_{\ell \to \ell'} \ge L_\ell.$$

Thus refinement never weakens an accepted affine lower bound.

Exact leaves. An exact certificate is written

$$\mathrm{Exact}(\ell; a_\ell, \mu_\ell, x_\ell^\star, \pi_\ell^{\mathrm{eq}}, \pi_\ell^{\mathrm{opt}}),$$

where the checker accepts

$$g(x) = a_\ell(x) \qquad \forall x \in D_\ell,$$

and AFFOPT certifies that

$$x_\ell^\star \in D_\ell, \qquad \mu_\ell = a_\ell(x_\ell^\star) = \inf_{x \in D_\ell} a_\ell(x).$$

Hence

$$\mu_\ell = \inf_{x \in D_\ell} g(x), \qquad g(x_\ell^\star) = \mu_\ell.$$

Exact certificates also descend under refinement: on a nonempty child leaf the equality payload restricts, and the same affine tag is re-optimized there; on an empty child, FEAS instead discharges the child by infeasibility.

Point witnesses. A point witness is written

$$\mathrm{Pt}(x, v, \pi^{\mathrm{eval}}),$$

where $x \in D$ and EVAL certifies

$$v = g(x).$$

Every accepted point witness immediately yields a global upper bound

$$\inf_{y \in D} g(y) \le g(x) = v.$$

This is the only route by which a semantic upper bound enters the trusted substrate.

These four objects—infeasible leaves, affine lower-bound leaves, exact leaves, and point witnesses—form the complete task-layer alphabet from which snapshot intervals and three-valued outputs are built.

A.3 Snapshots and Certified Interval Semantics

A verifier run usually exposes only a finite amount of already accepted evidence at any given time. The external meaning of that evidence is captured by a *snapshot*.

Evidence stores. Let $\mathcal{L}$ be a leaf cover. An evidence store over $\mathcal{L}$ consists of

1. a leaf-evidence map
$$\mathsf{E} : \mathcal{L} \to \{\text{finite sets of accepted leaf certificates}\},$$
where each $\mathsf{E}(\ell)$ may contain accepted Infeas, LB, or Exact certificates; and
2. a finite set of point witnesses
$$\mathsf{W} = \{\mathrm{Pt}(x_i, v_i, \pi_i^{\mathrm{eval}})\}_{i=1}^{M}.$$

The store is *locally consistent* if no leaf simultaneously carries an accepted infeasibility certificate and an accepted optimization certificate. Multiple lower-bound or exact certificates on the same leaf are allowed.

Snapshots. A snapshot is a triple
$$\mathsf{Snap} = (\mathcal{L}, \mathsf{E}, \mathsf{W}),$$
where $\mathcal{L}$ is a leaf cover and $(\mathcal{L}, \mathsf{E}, \mathsf{W})$ is a locally consistent evidence store.

Given a snapshot, define the pool of numeric lower-bound values attached to a leaf by
$$\mathsf{B}_{\mathsf{E}}(\ell) := \{L : \mathrm{LB}(\ell; \cdots, L, \cdots) \in \mathsf{E}(\ell)\} \cup \{\mu : \mathrm{Exact}(\ell; \cdots, \mu, \cdots) \in \mathsf{E}(\ell)\}.$$

Every exact certificate therefore contributes its exact leaf value to the same lower-bound pool as ordinary affine lower bounds.

The leaf contribution is defined by
$$\mathrm{lb}_{\mathsf{E}}(\ell) := \begin{cases} +\infty, & \text{if } \mathsf{E}(\ell) \text{ contains an accepted infeasibility certificate,} \\ \sup \mathsf{B}_{\mathsf{E}}(\ell), & \text{if } \mathsf{B}_{\mathsf{E}}(\ell) \neq \varnothing, \\ -\infty, & \text{if } \mathsf{B}_{\mathsf{E}}(\ell) = \varnothing. \end{cases} \tag{1}$$

The global lower and upper bounds certified by the snapshot are
$$\mathrm{LB}(\mathsf{Snap}) := \min_{\ell \in \mathcal{L}} \mathrm{lb}_{\mathsf{E}}(\ell), \tag{2}$$
$$\mathrm{UB}(\mathsf{Snap}) := \begin{cases} \min\{v : \mathrm{Pt}(x, v, \pi^{\mathrm{eval}}) \in \mathsf{W}\}, & \mathsf{W} \neq \varnothing, \\ +\infty, & \mathsf{W} = \varnothing. \end{cases} \tag{3}$$

The conventions $+\infty$ and $-\infty$ are what make the semantics anytime: even when no witness has yet been found, or no local lower-bound payload has yet been accepted on a leaf, the snapshot still has a well-defined certified interval.

Proposition (snapshot interval soundness). If all evidence carried by a snapshot $\mathsf{Snap} = (\mathcal{L}, \mathsf{E}, \mathsf{W})$ is accepted by the trusted primitives, then
$$\mathrm{LB}(\mathsf{Snap}) \leq \inf_{x \in D} g(x) \leq \mathrm{UB}(\mathsf{Snap}). \tag{4}$$

Proof. Fix any $x \in D$. Because $\mathcal{L}$ is a leaf cover of D, there exists some leaf $\ell \in \mathcal{L}$ with $x \in D_\ell$.

If $\mathsf{E}(\ell)$ contained an accepted infeasibility certificate, then $D_\ell = \varnothing$, contradicting $x \in D_\ell$. Therefore either $\mathrm{lb}_{\mathsf{E}}(\ell) = -\infty$, in which case there is nothing to prove, or $\mathsf{B}_{\mathsf{E}}(\ell)$ is nonempty and every value in it is a valid lower bound on $g(x)$:

- if $b = L \in \mathsf{B}_{\mathsf{E}}(\ell)$ comes from a lower-bound certificate, then $g(x) \geq L$ by local dominance plus affine optimization;

- if $b = \mu \in \mathsf{B_E}(\ell)$ comes from an exact certificate, then $g(x) \geq \mu$ because exactness implies $\mu = \inf_{y \in D_\ell} g(y)$.

Hence

$$g(x) \geq \sup \mathsf{B_E}(\ell) = \mathrm{lb}_{\mathsf{E}}(\ell) \geq \mathrm{LB}(\mathsf{Snap}).$$

Since $x \in D$ was arbitrary, the left inequality of (4) follows.

For the right inequality, if $\mathsf{W} = \varnothing$ then $\mathrm{UB}(\mathsf{Snap}) = +\infty$ and there is nothing to prove. Otherwise choose a point witness of minimum value in W:

$$\mathrm{Pt}(x^\times, v^\times, \pi^{\mathrm{eval}}) \in \mathsf{W}, \qquad v^\times = \mathrm{UB}(\mathsf{Snap}).$$

By soundness of EVAL,

$$\inf_{x \in D} g(x) \leq g(x^\times) = v^\times = \mathrm{UB}(\mathsf{Snap}).$$

This proves (4). □

Thus every accepted snapshot is already a certificate-carrying interval for the global optimization task. The three-valued threshold semantics is just a derived view of that interval.

A.4 Runtime States, Obligations, and Anytime Refinement

Snapshots are external objects. Internally, a run may also carry unfinished obligations that have not yet been discharged.

Obligations and runtime states. An obligation is a pair

$$\omega = (\ell, \tau),$$

where ℓ is a leaf and the task type τ is one of

$$\mathrm{INFEAS}, \qquad \mathrm{LB}, \qquad \mathrm{SPLIT}, \qquad \mathrm{WIT}.$$

The intended meanings are:

- INFEAS: try to prove that the leaf is empty;
- LB: try to produce a certified affine lower bound on the leaf;
- SPLIT: refine the leaf into subleaves; and
- WIT: search for a point witness that may decrease the global upper bound.

A runtime state is a quadruple

$$\Sigma = (\mathcal{L}, \mathsf{E}, \mathsf{W}, \mathsf{Q}),$$

where $(\mathcal{L}, \mathsf{E}, \mathsf{W})$ is a snapshot and Q is a finite obligation queue. The external projection is simply

$$\mathsf{Snap}(\Sigma) := (\mathcal{L}, \mathsf{E}, \mathsf{W}).$$

The queue is not part of the trusted semantics. It only records how the run may continue.

A common *need-driven* policy is to prioritize obligations on leaves that currently determine the global lower bound, leaves that still carry no lower-bound payload, leaves chosen for witness search, or leaves whose present local language cannot be strengthened without further splitting. The exact queue discipline is irrelevant to the verifier; only the accepted snapshot after each step matters externally.

Basic state transitions. At the task level, a state may evolve through the following three updates.

1. **Add a point witness.** Insert a newly accepted point witness into W.
2. **Add leaf evidence.** Insert a newly accepted infeasibility, lower-bound, or exact certificate into $\mathsf{E}(\ell)$ for some leaf ℓ.
3. **Refine a leaf.** Replace one leaf ℓ by a finite family of child leaves $\mathrm{Ch}(\ell)$ together with accepted containments

$$D_{\ell'} \subseteq D_\ell \qquad (\ell' \in \mathrm{Ch}(\ell))$$

and an accepted cover statement

$$D_\ell \subseteq \bigcup_{\ell' \in \mathrm{Ch}(\ell)} D_{\ell'}.$$

The third update is the only subtle one, because accepted parent evidence must remain valid after refinement. The correct rule is *descendant-closure replacement*: a refinement does not discard a parent conclusion and restart from scratch. Instead it pushes every accepted parent certificate to the child family in a verifier-checkable way.

- An accepted infeasibility certificate on the parent induces accepted infeasibility certificates on all children.
- An accepted affine lower-bound certificate on the parent is reused on each child by restricting the same affine tag and re-optimizing it over the child domain.
- An accepted exact certificate on the parent restricts to each nonempty child; one then re-optimizes the same affine tag over that child. Any child proved empty is instead discharged by FEAS.

This closure rule is what makes refinement monotone at the snapshot level.

Monotone expansion. Let

$$\Sigma = (\mathcal{L}, \mathsf{E}, \mathsf{W}, \mathsf{Q}), \qquad \Sigma' = (\mathcal{L}', \mathsf{E}', \mathsf{W}', \mathsf{Q}').$$

We say that Σ' is a *monotone expansion* of Σ, written

$$\Sigma' \succeq \Sigma,$$

if all of the following hold:

1. $\mathcal{L}'$ refines $\mathcal{L}$;
2. $\mathsf{W} \subseteq \mathsf{W}'$;
3. on every unchanged leaf, old accepted certificates are preserved;
4. on every refined leaf, every accepted parent certificate has been pushed to the child family by descendant-closure replacement, possibly together with stronger new child certificates; and
5. no accepted evidence is deleted except through this explicit descent to children.

Proposition (anytime monotonicity). If $\Sigma' \succeq \Sigma$, then

$$\mathrm{LB}(\mathsf{Snap}(\Sigma')) \geq \mathrm{LB}(\mathsf{Snap}(\Sigma)), \tag{5}$$

$$\mathrm{UB}(\mathsf{Snap}(\Sigma')) \leq \mathrm{UB}(\mathsf{Snap}(\Sigma)). \tag{6}$$

Proof. The upper-bound inequality is immediate because $\mathsf{W} \subseteq \mathsf{W}'$ and the upper bound is the minimum value over accepted point witnesses.

For the lower bound, consider any old leaf $\ell \in \mathcal{L}$.

- If ℓ survives unchanged, then its accepted lower-bound pool can only grow, so its leaf contribution cannot decrease.
- If ℓ is refined into children $\mathrm{Ch}(\ell)$, then every child inherits every accepted parent conclusion in a sound way. Parent infeasibility yields child infeasibility; a parent lower-bound certificate yields a child lower-bound certificate with numeric value at least as large; and a parent exact certificate yields either child exactness or child infeasibility. Therefore every child contribution is at least as strong as the former parent contribution.

Hence replacing an old leaf by its refined child family cannot decrease the minimum leaf contribution over the cover. This proves (5). Together with the upper-bound argument, we obtain (6). □

This is the precise sense in which the task-layer semantics is *anytime*: every monotone refinement step narrows or preserves the certified interval, never widens it.

Corollary (monotone stability of decisive outputs). Under monotone expansion, an accepted **COUNTEREX** output stays **COUNTEREX**, and an accepted **PROVED** output stays **PROVED**. Only **UNKNOWN** may change, and it may change only to a stronger conclusion.

Proof. If a state already contains a point witness with value below the threshold, that witness remains present in every monotone expansion, so the counterexample persists. If a state already proves the threshold statement, then by soundness the statement is true; a later accepted counterexample witness cannot appear without contradiction, while the lower bound can only increase by the anytime monotonicity inequality (5). □

A.5 Three-Valued Semantics and Finite Exactification

The interval semantics induces a three-valued threshold semantics.

Three-valued rule. Given a threshold $t \in \mathbb{R}$ and a snapshot Snap, output

- **COUNTEREX** if some accepted point witness in W has value $v < t$;
- **PROVED** if no such counterexample witness exists and
$$\mathrm{LB}(\mathsf{Snap}) \geq t;$$
- **UNKNOWN** otherwise, together with the certified interval
$$[\mathrm{LB}(\mathsf{Snap}), \mathrm{UB}(\mathsf{Snap})].$$

The priority is
$$\mathrm{COUNTEREX} \succ \mathrm{PROVED} \succ \mathrm{UNKNOWN}.$$

Proposition (three-valued soundness). If all evidence carried by a snapshot is accepted, then:

1. **COUNTEREX** implies
$$\inf_{x \in D} g(x) < t;$$
2. **PROVED** implies
$$\inf_{x \in D} g(x) \geq t;$$
3. **UNKNOWN** returns a certified interval containing $\inf_D g$.

Proof. If the output is **COUNTEREX**, there exists an accepted point witness with value $v < t$, so by soundness of EVAL
$$\inf_{x \in D} g(x) \leq v < t.$$
If the output is **PROVED**, then by definition $\mathrm{LB}(\mathsf{Snap}) \geq t$, and Proposition (4) gives
$$\inf_{x \in D} g(x) \geq \mathrm{LB}(\mathsf{Snap}) \geq t.$$
The **UNKNOWN** case is exactly the interval soundness statement (4). □

Finite exactification. A finite snapshot
$$\mathsf{Snap}^\star = (\mathcal{L}^\star, \mathsf{E}^\star, \mathsf{W}^\star)$$
is a *finite exactification* of (g, D) if all of the following hold:

1. $\mathcal{L}^\star$ is a finite leaf cover of D;
2. every leaf in $\mathcal{L}^\star$ is either discharged by an accepted infeasibility certificate or carries an accepted exact certificate; and
3. whenever a leaf carries an exact certificate with optimizer $x_\ell^\star$ and value μ_ℓ, the point witness
$$\mathrm{Pt}(x_\ell^\star, \mu_\ell, \pi_\ell^{\mathrm{eval}})$$
is present in $\mathsf{W}^\star$.

This is a purely task-level notion. It says exactly what finite external evidence is sufficient for the certified interval to collapse to the true optimum.

Theorem (finite exactification collapse). If $\mathsf{Snap}^\star$ is a finite exactification of (g, D), then

$$\mathrm{LB}(\mathsf{Snap}^\star) = \mathrm{UB}(\mathsf{Snap}^\star) = \inf_{x \in D} g(x). \tag{7}$$

If the infimum is attained, then both sides are equal to $\min_{x \in D} g(x)$.

Proof. Let $\mathcal{L}^\star_{\mathrm{live}}$ denote the leaves carrying exact certificates. For every such leaf,

$$\mu_\ell = \inf_{x \in D_\ell} g(x)$$

by exactness. Moreover, any other accepted lower-bound value on the same leaf is at most μ_ℓ, because it is itself a valid lower bound on g over D_ℓ. Therefore the leaf contribution on every live leaf is exactly μ_ℓ, while infeasible leaves contribute $+\infty$. Hence

$$\mathrm{LB}(\mathsf{Snap}^\star) = \min_{\ell \in \mathcal{L}^\star_{\mathrm{live}}} \mu_\ell.$$

Since the live leaves cover all feasible points of D, the right-hand side is exactly $\inf_{x \in D} g(x)$.

On the other hand, every live leaf contributes its optimizer witness to $\mathsf{W}^\star$, so

$$\mathrm{UB}(\mathsf{Snap}^\star) \le \min_{\ell \in \mathcal{L}^\star_{\mathrm{live}}} \mu_\ell = \inf_{x \in D} g(x).$$

Combined with the general interval soundness statement (4), this proves (7). □

As a direct corollary, once a run reaches a finite exactification, the threshold task becomes binary and exact: for every threshold t, the output is **PROVED** iff $\inf_D g \ge t$ and **COUNTEREX** iff $\inf_D g < t$. This theorem is purely semantic. Section 3 later supplies the structural reason why such finite exactification exists for the CPWL class treated in the paper.

B Formal Definitions of Certified Cells, Covers, and Payload Syntax

Section 2 intentionally keeps the main text at the interface level. It names the trusted kernel, exact and threshold certified cells, exact and threshold certified covers, and the complexity quantities built from them, but it suppresses most of the formal backend. This appendix restores that backend. Its purpose is not to add new structural theorems. Its purpose is to make fully explicit what an *accepted cover* is as a finite verifier-visible object.

The key point is simple. An accepted cover is not just a semantic statement of the form

$$D \subseteq \bigcup_{i=1}^{N} C(\gamma_i).$$

It is a finite tuple consisting of:

1. a finite table of verifier-facing cell descriptions;
2. a finite local payload attached to each listed cell; and
3. one finite global cover payload that derives the cover statement from accepted containment, local-cover, or miss-set emptiness facts.

This appendix fixes those finite objects abstractly. Later parts of the paper then instantiate them in concrete ways:

- Section 3 and Appendix D realize exact cells by aligned guard leaves and realize global cover payloads by split-tree cover derivations;
- Section 5 and the continuous-side arguments use the same backend with threshold payloads and finite miss-set cover certificates;
- Appendix E then interprets these same accepted covers inside proof languages and description-length notions.

B.1 Verifier-Facing Cell Descriptions and Local Conclusions

Fix a verifier-facing cell language $\mathfrak{L}$. Every description

$$\gamma \in \mathfrak{L}$$

is a finite object equipped with a verifier-facing set description

$$\mathfrak{D}(\gamma)$$

and a semantic cell

$$C(\gamma) := [\![\mathfrak{D}(\gamma)]\!] \subseteq D.$$

We also introduce one distinguished root description

$$\top_D,$$

with

$$\mathfrak{D}(\top_D) := \mathfrak{D}_D, \qquad C(\top_D) = D.$$

This is only a bookkeeping device for global cover derivations.

At the local level, the verifier ever only accepts one of two conclusion types.

Exact local conclusion. Given $\gamma \in \mathfrak{L}$ and an affine function

$$a(x) = w^\top x + b,$$

the corresponding exact local statement is

$$\mathrm{Eq}(\gamma, a): \qquad \forall x \in C(\gamma),\ g(x) = a(x).$$

Threshold local conclusion. Given $\gamma \in \mathfrak{L}$ and a threshold $t \in \mathbb{R}$, the corresponding threshold local statement is

$$\mathrm{Thr}(\gamma, t): \qquad \forall x \in C(\gamma),\ g(x) \geq t.$$

A *local payload* is any finite verifier-visible object from which CHECK, possibly together with explicit invocations of the other trusted primitives, can deterministically validate one of these two statements. We do *not* fix a bit-level encoding here. The only requirements are:

1. finiteness;
2. verifier-checkability through the trusted kernel;
3. explicit attachment to one named cell description γ.

This formulation is deliberately broad. It covers both direct payloads, such as one explicit leaf-equality certificate, and composite payloads, such as a lower-bound proof plus an affine optimization certificate plus a scalar threshold check.

B.2 Local Payload Schemata

The main text writes local payloads only as $\pi^=$ and $\pi^\geq$. Here we make their finite structure explicit.

Exact local payload schema. A finite exact local payload over (γ, a) is a triple

$$\pi^= = (\Pi^{\mathrm{cell}}, \Pi^{\mathrm{stmt}}, \Pi^{\mathrm{aux}}),$$

where:

1. Π^{cell} is a finite cell block identifying γ and any finite subdescriptions or local side data referenced by the proof;
2. Π^{stmt} is a finite derivation block that the verifier accepts as a proof of
$$\mathrm{Eq}(\gamma, a);$$
3. Π^{aux} is an optional finite auxiliary block, carrying additional verifier-visible data not needed merely to accept the local equality itself, for example optimizer witnesses, side certificates, child-payload references, or normalization metadata.

An *accepted exact certified cell* is then a triple

$$\mathfrak{c} = (\gamma, a, \pi^=)$$

for which the verifier accepts Π^{stmt} as a proof of $\mathrm{Eq}(\gamma, a)$. As in the main text, its semantic domain is written

$$|\mathfrak{c}| := C(\gamma).$$

Threshold local payload schema. A finite threshold local payload over (γ, t) is a triple

$$\pi^{\geq} = (\Pi^{\mathrm{cell}}, \Pi^{\mathrm{stmt}}, \Pi^{\mathrm{aux}}),$$

where:

1. Π^{cell} again identifies the local cell description and any finite subdescriptions referenced by the proof;
2. Π^{stmt} is a finite derivation block accepted by the verifier as a proof of
$$\mathrm{Thr}(\gamma, t);$$
3. Π^{aux} is an optional finite auxiliary block, for example a local affine under-estimator, a center evaluation witness, an optimizer certificate, or any other finite subpayload used compositionally by the threshold proof.

An *accepted threshold certified cell* is a pair

$$\mathfrak{c} = (\gamma, \pi^{\geq})$$

for which the verifier accepts Π^{stmt} as a proof of $\mathrm{Thr}(\gamma, t)$. Again,

$$|\mathfrak{c}| := C(\gamma).$$

Proposition (local soundness contract). If the verifier accepts an exact certified cell $(\gamma, a, \pi^{=})$, then

$$g(x) = a(x) \qquad \forall x \in C(\gamma).$$

If it accepts a threshold certified cell $(\gamma, \pi^{\geq})$, then

$$g(x) \geq t \qquad \forall x \in C(\gamma).$$

Proof. This is exactly what the accepted local derivation blocks certify. □

Optimization consequence of an exact local payload. Suppose $(\gamma, a, \pi^{=})$ is an accepted exact certified cell and AFFOPT accepts a finite optimizer block proving

$$\mu = \inf_{x \in C(\gamma)} a(x).$$

Then

$$\mu = \inf_{x \in C(\gamma)} g(x).$$

If $C(\gamma)$ is nonempty and compact, the infimum is attained and equals the local minimum of g on that cell.

Proof. By local soundness, $g = a$ on $C(\gamma)$. Therefore the two infima coincide on the same set. □

Derived threshold payload from an exact cell. The threshold schema is intentionally broad enough to contain exact-to-threshold transformations as one special case. Concretely, if the verifier accepts an exact certified cell $(\gamma, a, \pi^{=})$ and also accepts a finite affine-optimization payload proving

$$\inf_{x \in C(\gamma)} a(x) \geq t,$$

then the finite combined payload

$$\mathrm{LiftThr}(\pi^{=}, \pi^{\mathrm{opt}})$$

is an accepted threshold payload for the same cell γ.

Proof. The checker combines the accepted equality statement

$$g(x) = a(x) \qquad \forall x \in C(\gamma)$$

with the accepted affine lower bound

$$a(x) \geq t \qquad \forall x \in C(\gamma),$$

which is itself implied by the optimizer statement. Hence it accepts

$$g(x) \geq t \qquad \forall x \in C(\gamma).$$

□

This is the abstract form of the exact-to-threshold transfer used later in Section 5.

B.3 Cover Sequents and the Global Cover-Payload Grammar

To turn local certified cells into a cover, the verifier needs a finite object proving that the listed cells jointly cover D. We formalize this with *cover sequents*.

Cover sequents. Let η be any verifier-facing description whose semantic set is $C(\eta) \subseteq D$, and let Γ be a finite set of descriptions. The sequent

$$\eta \rightsquigarrow \Gamma$$

means the semantic inclusion

$$C(\eta) \subseteq \bigcup_{\gamma \in \Gamma} C(\gamma).$$

A *global cover payload* for a target family $\Gamma_* = \{\gamma_1, \ldots, \gamma_N\}$ is a finite derivation of the root sequent

$$\top_D \rightsquigarrow \Gamma_*.$$

The grammar is built from finite atomic cover steps plus finite composition rules. We use the following atomic forms.

(i) Containment atom. If the verifier accepts a finite containment proof

$$\rho_{\eta \subseteq \eta'}$$

of

$$C(\eta) \subseteq C(\eta'),$$

then we may form the one-step cover sequent

$$\eta \rightsquigarrow \{\eta'\}.$$

(ii) Direct local-cover atom. If the verifier accepts a finite payload

$$\rho_{\eta \triangleleft \Gamma}$$

proving the local cover statement

$$C(\eta) \subseteq \bigcup_{\gamma \in \Gamma} C(\gamma),$$

then we may form the sequent

$$\eta \rightsquigarrow \Gamma.$$

This is the abstract backend for split-tree two-child cover steps, local partition steps, or any other direct finite cover claim supported by the language.

(iii) Miss-set emptiness atom. Suppose the language admits a finite verifier-facing descriptor

$$\mathfrak{D}^{\mathrm{miss}}_{\eta;\Gamma}$$

whose semantic set is exactly

$$[\![\mathfrak{D}^{\mathrm{miss}}_{\eta;\Gamma}]\!] = C(\eta) \setminus \bigcup_{\gamma \in \Gamma} C(\gamma).$$

If FEAS accepts a finite infeasibility certificate proving this miss-set empty, then we may again form the sequent

$$\eta \rightsquigarrow \Gamma.$$

This is the abstract form used later for Boolean miss-set cover certificates such as the finite ball-cover payloads in the continuous-side arguments.

These atoms are then combined by two explicit grammar rules.

(iv) Composition rule. Suppose we have already derived

$$\eta \rightsquigarrow \{\eta_1, \ldots, \eta_m\}$$

and, for each $1 \leq j \leq m$, also derived

$$\eta_j \rightsquigarrow \Gamma_j.$$

Then we may derive

$$\eta \rightsquigarrow \bigcup_{j=1}^{m} \Gamma_j.$$

Semantically, this is just substitution of child covers into a parent cover.

(v) Empty-target elimination. If FEAS accepts a finite certificate proving

$$C(\eta_0) = \varnothing,$$

and we have already derived

$$\eta \rightsquigarrow \Gamma \cup \{\eta_0\},$$

then we may derive

$$\eta \rightsquigarrow \Gamma.$$

Thus empty cells may be dropped from target covers without changing the semantic union.

Definition (global cover-payload grammar). A *global cover payload* is any finite derivation tree whose nodes are cover sequents and whose leaves are atomic containments, direct local-cover atoms, or miss-set emptiness atoms, and whose internal steps use only the two rules above. A target family

$$\Gamma_* = \{\gamma_1, \ldots, \gamma_N\}$$

is said to be *accepted as a global cover* when such a derivation concludes

$$\top_D \rightsquigarrow \Gamma_*.$$

This formulation makes the finiteness completely explicit. An accepted global cover is not an infinite semantic claim. It is a finite derivation tree built from finitely many local cover atoms, finitely many containment atoms, finitely many miss-set emptiness certificates, and finitely many composition steps.

Proposition (soundness of cover derivations). Every accepted derivation of a cover sequent

$$\eta \rightsquigarrow \Gamma$$

is semantically sound, i.e.

$$C(\eta) \subseteq \bigcup_{\gamma \in \Gamma} C(\gamma).$$

Proof. Proceed by induction on the derivation tree. For atomic containments and direct local-cover atoms, soundness is exactly the content of the accepted finite payloads. For miss-set atoms, emptiness of

$$C(\eta) \setminus \bigcup_{\gamma \in \Gamma} C(\gamma)$$

immediately yields the desired cover inclusion. For a composition step, if

$$C(\eta) \subseteq \bigcup_{j=1}^{m} C(\eta_j) \quad \text{and} \quad C(\eta_j) \subseteq \bigcup_{\gamma \in \Gamma_j} C(\gamma) \ \ (1 \leq j \leq m),$$

then

$$C(\eta) \subseteq \bigcup_{j=1}^{m} \bigcup_{\gamma \in \Gamma_j} C(\gamma) = \bigcup_{\gamma \in \cup_j \Gamma_j} C(\gamma).$$

For empty-target elimination, replacing

$$\Gamma \cup \{\eta_0\}$$

by

$$\Gamma$$

does not change the union because $C(\eta_0) = \varnothing$. $\square$

B.4 Accepted Certified Covers as Finite Objects

With the local schemata and the global cover grammar fixed, an accepted certified cover is now an explicit finite object.

Definition (accepted exact certified cover object). An accepted exact certified cover object is a pair

$$\mathfrak{C}^{=} = \Big(\{(\gamma_i, a_i, \pi_i^{=})\}_{i=1}^{N},\ \pi^{\mathrm{cov}}\Big),$$

where:

1. each $(\gamma_i, a_i, \pi_i^{=})$ is an accepted exact certified cell;
2. π^{cov} is a finite global cover payload deriving

$$\top_D \rightsquigarrow \{\gamma_1, \ldots, \gamma_N\}.$$

Its size is the number N of listed local cells.

Definition (accepted threshold certified cover object). An accepted threshold certified cover object is a pair

$$\mathfrak{C}^{\geq} = \Big(\{(\gamma_i, \pi_i^{\geq})\}_{i=1}^{N},\ \pi^{\mathrm{cov}}\Big),$$

where:

1. each $(\gamma_i, \pi_i^{\geq})$ is an accepted threshold certified cell;
2. π^{cov} is a finite global cover payload deriving

$$\top_D \rightsquigarrow \{\gamma_1, \ldots, \gamma_N\}.$$

Again, its size is the number of listed local cells.

Thus every accepted cover is concretely a finite cell table, a finite local-payload table, and one finite global derivation tree. This is the formal backend of the shorter cover definitions given in Section 2.

Remark on empty cells. By the empty-target elimination rule, empty listed cells can always be removed once FEAS has discharged them as empty. Therefore minimum-size covers may always be taken over nonempty cells alone. The convention

$$\inf_{x \in \varnothing} a(x) = +\infty$$

used elsewhere in the paper is compatible with this simplification.

B.5 Global Soundness Contract for Accepted Covers

We can now restate the cover-level soundness contract in fully formal form.

Proposition (threshold-cover soundness). Let

$$\mathfrak{C}^{\geq} = \Big(\{(\gamma_i, \pi_i^{\geq})\}_{i=1}^{N},\ \pi^{\mathrm{cov}}\Big)$$

be an accepted threshold certified cover object for the threshold t. Then

$$g(x) \geq t \qquad \forall x \in D.$$

Proof. By soundness of the global cover derivation,

$$D \subseteq \bigcup_{i=1}^{N} C(\gamma_i).$$

Hence every $x \in D$ lies in some $C(\gamma_i)$. By local threshold soundness on that cell,

$$g(x) \geq t.$$

Since x was arbitrary, the claim follows. □

Proposition (exact-cover soundness). Let

$$\mathfrak{C}^{=} = \Big(\{(\gamma_i, a_i, \pi_i^{=})\}_{i=1}^{N},\ \pi^{\mathrm{cov}}\Big)$$

be an accepted exact certified cover object. Then

$$\inf_{x\in D} g(x) = \inf_{x\in\cup_i C(\gamma_i)} g(x) = \min_{1\le i\le N} \inf_{x\in C(\gamma_i)} a_i(x),$$

with the convention that empty cells contribute $+\infty$.

Proof. The accepted global cover payload implies

$$D \subseteq \bigcup_{i=1}^{N} C(\gamma_i).$$

Because every $C(\gamma_i)$ lies inside D, the union on the right is a subset of D, so in fact

$$\inf_{x\in D} g(x) = \inf_{x\in\cup_i C(\gamma_i)} g(x).$$

Now on each cell $C(\gamma_i)$, local exact soundness gives

$$g(x) = a_i(x) \qquad \forall x \in C(\gamma_i),$$

so

$$\inf_{x\in C(\gamma_i)} g(x) = \inf_{x\in C(\gamma_i)} a_i(x).$$

Since the union is finite,

$$\inf_{x\in\cup_i C(\gamma_i)} g(x) = \min_{1\le i\le N} \inf_{x\in C(\gamma_i)} g(x) = \min_{1\le i\le N} \inf_{x\in C(\gamma_i)} a_i(x).$$

This is the desired identity. □

Corollary (exact-cover optimization by local affine optimization). Suppose in addition that for each i, AFFOPT accepts a finite optimizer block proving

$$\mu_i = \inf_{x\in C(\gamma_i)} a_i(x).$$

Then

$$\inf_{x\in D} g(x) = \min_{1\le i\le N} \mu_i.$$

If every listed cell is nonempty and compact, then each infimum is attained and the same formula holds with local minima and global minimum in place of infima.

Proof. Combine the previous proposition with the accepted affine optimizer statements. □

B.6 Concrete Instantiations Used in the Paper

It is useful to close by recording how the abstract syntax above is instantiated in the paper's two main semantic branches.

Guard-exact exact cells. In Section 3, the language is

$$\mathfrak{L}_{\mathrm{grd}},$$

where a description γ is a finite guard set S and

$$C(\gamma) = D_S.$$

There the local exact payload $\pi^{=}$ is the restricted fragment-equality payload produced by the static CPWL compilation. The global cover payload is the split-tree derivation assembled from finitely many two-child cover atoms and finitely many empty-leaf eliminations. Appendix D gives this construction in full detail.

Threshold-side instantiations. On the threshold side, the paper only needs the abstract schema fixed above: a local threshold payload is any finite verifier-visible object proving

$$\forall x \in C(\gamma),\ g(x) \geq t.$$

Depending on the language, such a payload may be direct, or it may itself be composite—for example, a local affine lower-bound block plus an affine optimizer certificate plus a scalar threshold check. Whenever the corresponding language admits a finite miss-set descriptor, the global cover payload can be realized through the miss-set emptiness atom of the cover grammar defined above.

Why this appendix matters for exactification. The structural exactification theorem in Section 3 proves more than leafwise semantic exactness. To conclude that the live leaves form an *accepted exact certified cover* in the sense of Section 2, one still needs exactly the backend fixed here:

1. a finite local exact payload attached to each leaf; and
2. a finite derivation of the root cover sequent

$$\top_D \rightsquigarrow \{\text{live leaves}\}.$$

That is why Appendix D includes an explicit global cover-payload construction lemma rather than stopping at semantic coverage alone.

In short, this appendix turns the main text's interface-level terms—certified cell, certified cover, accepted cover payload—into precise finite verifier-facing objects. The later structural, complexity, and hardness results are then statements about these explicit objects rather than about an informal semantic cover notion.

C Local Rules A/R/G/M and Static Guard Compilation

Section 3 states the structural compilation theorem used by the exactification argument. This appendix supplies the local rule-level proofs. Its role is deliberately narrow. We do *not* yet prove aligned-leaf exactness, global split-tree cover assembly, or finite exactification of the whole network; those belong to Appendix D. The present appendix proves only that the static compilation manipulates finite verifier-visible objects and that each local rule preserves certified faithfulness.

The basic formal backend for certified cells and payloads was fixed in Appendix B. Here we specialize it to the exact side of the guard language. Throughout the appendix:

- $D \subseteq \mathbb{R}^n$ is nonempty compact;
- u denotes a scalar node in an allowed CPWL expression graph;
- $[[u]] : D \to \mathbb{R}$ denotes the true scalar semantics of that node;
- the guard language is generated by affine comparison literals.

Allowed CPWL expression graphs are assumed to be already normalized so that the affine primitives are exactly unary affine post-composition and addition. Any finite-input affine map can be decomposed into this basis by introducing finitely many scalar multiples and additions, so the compilation rules below lose no generality.

For every affine function

$$h(x) = w^\top x + b,$$

we write the associated closed-halfspace literals as

$$h \leq 0 \qquad \text{and} \qquad h \geq 0.$$

A finite set of such literals is a *guard set* S, with semantic cell

$$D_S := D \cap \bigcap_{\lambda \in S} \lambda.$$

When S and T are guard sets, their common refinement cell is simply

$$D_{S \cup T} = D_S \cap D_T.$$

A *certified guard-affine fragment* for a scalar node u is a triple

$$(S, a, \Pi),$$

where S is a guard set, $a(x) = w^\top x + b$ is affine, and Π is a finite payload accepted by the verifier as a proof of

$$[[u]](x) = a(x) \qquad \forall x \in D_S.$$

A finite family

$$\mathcal{F}_u = \{(S_r, a_r, \Pi_r)\}_{r=1}^{R_u}$$

is *certified faithful* for u if:

1. the cells $\{D_{S_r}\}_{r=1}^{R_u}$ cover D; and
2. every payload Π_r is accepted as a proof of
$$[[u]](x) = a_r(x) \qquad \forall x \in D_{S_r}.$$

Thus every compiled fragment is already an accepted local exact statement in the sense of Section 2; what later appendices add is leaf alignment and a global cover payload.

C.1 Preliminaries: Restriction and Common Refinement

The rule proofs repeatedly use two elementary closure principles.

Restriction of accepted exact payloads. Suppose the verifier accepts a finite payload proving

$$[[u]](x) = a(x) \qquad \forall x \in D_S,$$

and also accepts a finite containment proof

$$D_{S'} \subseteq D_S.$$

Then the same equality is valid on the smaller cell $D_{S'}$. We therefore obtain a derived finite payload, denoted

$$\mathrm{Restr}(S' \subseteq S; \Pi),$$

that the verifier accepts as a proof of

$$[[u]](x) = a(x) \qquad \forall x \in D_{S'}.$$

This is exactly the downward-closure rule for accepted exact payloads already implicit in Appendix B.

Common refinement of certified faithful families. If

$$\mathcal{F}_1 = \{(S_i, a_i, \Pi_i)\}_{i=1}^{R_1} \qquad \text{and} \qquad \mathcal{F}_2 = \{(T_j, b_j, \Theta_j)\}_{j=1}^{R_2}$$

both cover D, then the refined family of cells

$$\{D_{S_i \cup T_j}\}_{1 \le i \le R_1,\ 1 \le j \le R_2}$$

also covers D. Indeed, for every $x \in D$ there exist indices i, j with $x \in D_{S_i}$ and $x \in D_{T_j}$, hence

$$x \in D_{S_i \cup T_j} = D_{S_i} \cap D_{T_j}.$$

We use this observation in Rules R and M.

C.2 Rule A: Affine Propagation

Assume a scalar node y is obtained from a scalar node ϕ by affine post-composition:

$$y(x) = \alpha\phi(x) + \beta.$$

Suppose

$$\mathcal{F}_\phi = \{(S_r, a_r, \Pi_r)\}_{r=1}^{R}$$

is certified faithful for ϕ. Rule A outputs the family

$$\mathcal{F}_y := \{(S_r, \alpha a_r + \beta, \Pi_r^{\mathrm{A}})\}_{r=1}^{R},$$

where each new payload Π_r^{A} is the finite verifier-visible record consisting of:

1. the already accepted child payload Π_r;
2. the affine coefficients α, β;
3. the declaration that the new node is obtained from the child node by affine propagation.

The checker only needs to confirm that the guard set has not changed and that the new affine tag is exactly the symbolic transformation of the old one.

Theorem C.1 (Rule A). Rule A preserves certified faithfulness.

Proof. Coverage is immediate, since the output family uses exactly the same guard cells D_{S_r} as the input family.

Fix one input fragment (S_r, a_r, Π_r) and one point $x \in D_{S_r}$. Because Π_r is accepted, the verifier has already established

$$[[\phi]](x) = a_r(x).$$

Therefore

$$[[y]](x) = \alpha[[\phi]](x) + \beta = \alpha a_r(x) + \beta.$$

So the proposed output tag is semantically correct on D_{S_r}.

It remains to justify verifier acceptance. The payload Π_r^{A} is finite and introduces no new semantic search object: it only points to an already accepted equality payload, records the affine post-composition coefficients, and asks the checker to validate a one-step symbolic transformation. Hence the verifier accepts

$$[[y]](x) = \alpha a_r(x) + \beta \qquad \forall x \in D_{S_r}.$$

Thus every output fragment is locally exact, and the family remains certified faithful. □

C.3 Rule R: Addition on a Common Refinement

Assume

$$y(x) = \phi_1(x) + \phi_2(x),$$

and suppose

$$\mathcal{F}_1 = \{(S_i, a_i, \Pi_i)\}_{i=1}^{R_1}, \qquad \mathcal{F}_2 = \{(T_j, b_j, \Theta_j)\}_{j=1}^{R_2}$$

are certified faithful for ϕ_1 and ϕ_2, respectively. Rule R outputs the common-refinement family

$$\mathcal{F}_y := \big\{(S_i \cup T_j,\ a_i + b_j,\ \Pi_{ij}^{\mathrm{R}}) : 1 \le i \le R_1,\ 1 \le j \le R_2\big\},$$

where Π_{ij}^{R} is the finite payload recording:

1. the already accepted child payloads Π_i and Θ_j;
2. the new guard set $S_i \cup T_j$;
3. the symbolic identity that the new affine tag is the sum $a_i + b_j$.

Theorem C.2 (Rule R). Rule R preserves certified faithfulness.

Proof. Coverage follows from common refinement: because the two input families both cover D, the refined cells $D_{S_i \cup T_j}$ cover D as (i, j) ranges over all pairs.

Now fix an output fragment

$$(S_i \cup T_j,\ a_i + b_j,\ \Pi_{ij}^{\mathrm{R}})$$

and a point $x \in D_{S_i \cup T_j}$. Since

$$D_{S_i \cup T_j} \subseteq D_{S_i} \cap D_{T_j},$$

the already accepted child payloads imply

$$[[\phi_1]](x) = a_i(x), \qquad [[\phi_2]](x) = b_j(x).$$

Therefore

$$[[y]](x) = [[\phi_1]](x) + [[\phi_2]](x) = a_i(x) + b_j(x).$$

So the proposed affine tag is semantically exact on the refined cell.

Verifier acceptance is again finite and local. The checker only has to confirm that the child payloads are already accepted, that the new cell is the common-refinement cell $D_{S_i \cup T_j}$, and that the announced affine tag is the symbolic sum of the two child tags. Hence it accepts the local exact statement on $D_{S_i \cup T_j}$. The output family is therefore certified faithful. □

C.4 Rule G: Gating by an Affine Winner Comparison

Let $y = \sigma(\phi)$, where σ is one of the scalar gates used in Section 3:

$$\mathrm{ReLU}(z) = \max\{z, 0\}, \qquad \mathrm{Leaky}_\alpha(z) = \max\{z, \alpha z\}, \qquad \mathrm{Abs}(z) = \max\{z, -z\}.$$

We also allow PReLU with a fixed compile-time parameter α, handled exactly like the Leaky case. The standard Leaky/PReLU regime is $0 \le \alpha \le 1$, but the rule below is correct for every fixed compile-time $\alpha \in \mathbb{R}$.

For a fixed gate type σ, define the two affine branch templates

$$b_1^\sigma(z) := z, \qquad b_2^\sigma(z) := \begin{cases} 0, & \text{for ReLU,} \\ \alpha z, & \text{for Leaky/PReLU,} \\ -z, & \text{for Abs,} \end{cases}$$

and their affine winner comparison

$$d_\sigma(z) := b_1^\sigma(z) - b_2^\sigma(z).$$

Thus

$$\sigma(z) = \max\{b_1^\sigma(z), b_2^\sigma(z)\},$$

and the active affine branch is decided by the sign of $d_\sigma(z)$.

For an input fragment (S, a, Π), write

$$a(x) = w^\top x + b,$$

and abbreviate the corresponding affine branch tags by

$$b_1(a) := b_1^\sigma \circ a, \qquad b_2(a) := b_2^\sigma \circ a, \qquad d(a) := d_\sigma \circ a = b_1(a) - b_2(a).$$

Rule G now branches on the actual winner comparison $d(a)$:

1. If $d(a)$ is nonconstant, the rule outputs the two fragments

$$(S \cup \{d(a) \ge 0\},\ b_1(a),\ \Pi^{\mathrm{G},1}), \qquad (S \cup \{d(a) \le 0\},\ b_2(a),\ \Pi^{\mathrm{G},2}).$$

2. If $d(a)$ is a nonnegative constant, the first branch wins everywhere on D_S, so the rule outputs the single fragment

$$(S,\ b_1(a),\ \Pi^{\mathrm{G},\mathrm{const}+}).$$

3. If $d(a)$ is a negative constant, the second branch wins everywhere on D_S, so the rule outputs the single fragment

$$(S,\ b_2(a),\ \Pi^{\mathrm{G},\mathrm{const}-}).$$

In the degenerate case $d(a) \equiv 0$, the two affine branches coincide identically, so either constant-branch output is acceptable.

All Rule G payloads are finite. Each records:

1. the accepted child payload Π;
2. the optional new winner literal when $d(a)$ is nonconstant;
3. a branch tag recording which affine branch $b_1(a)$ or $b_2(a)$ is claimed to win on the current cell; and
4. the finite symbolic formula for the chosen affine branch and its comparison $d(a)$.

The checker only has to verify that the announced branch formulas match the gate type and that the literal being added is exactly the affine comparison deciding between those two branches.

Theorem C.3 (Rule G). Rule G preserves certified faithfulness.

Proof. Fix one input fragment (S, a, Π). Because Π is accepted,

$$[[\phi]](x) = a(x) \qquad \forall x \in D_S. \tag{C.1}$$

We prove coverage and local exactness case by case.

Nonconstant-comparison case. Assume $d(a)$ is nonconstant. Since the two closed halfspaces $\{d(a) \le 0\}$ and $\{d(a) \ge 0\}$ cover all of $\mathbb{R}^n$, we have

$$D_S \subseteq D_{S\cup\{d(a)\le 0\}} \ \cup \ D_{S\cup\{d(a)\ge 0\}}.$$

Thus replacing the input fragment by the two output fragments preserves coverage.

Take any point $x \in D_{S\cup\{d(a)\ge 0\}}$. Then $x \in D_S$ and $d(a)(x) \ge 0$, so

$$b_1(a)(x) \ge b_2(a)(x).$$

Using (C.1),

$$[[y]](x) = \sigma([[\phi]](x)) = \sigma(a(x)) = \max\{b_1(a)(x), b_2(a)(x)\} = b_1(a)(x).$$

Hence the first output fragment is semantically exact on its cell.

Similarly, for any point $x \in D_{S\cup\{d(a)\le 0\}}$, the inequality $d(a)(x) \le 0$ implies

$$b_2(a)(x) \ge b_1(a)(x),$$

so again by (C.1),

$$[[y]](x) = \sigma(a(x)) = \max\{b_1(a)(x), b_2(a)(x)\} = b_2(a)(x).$$

Thus the second output fragment is semantically exact on its cell.

The overlap of the two child cells is contained in

$$\{x : d(a)(x) = 0\}.$$

On that overlap the two branch tags agree because

$$b_1(a)(x) - b_2(a)(x) = d(a)(x) = 0.$$

Therefore boundary points cause no consistency problem: if both branch literals hold, both local affine equalities certify the same semantic value.

Constant-comparison case. Assume now that $d(a)$ is constant. If $d(a) \ge 0$, then $b_1(a)(x) \ge b_2(a)(x)$ for every $x \in D_S$, so

$$[[y]](x) = \sigma(a(x)) = b_1(a)(x) \qquad \forall x \in D_S.$$

Hence the single output fragment $(S, b_1(a), \Pi^{\mathrm{G,const+}})$ is locally exact and coverage is unchanged. If instead $d(a) < 0$, the same argument gives

$$[[y]](x) = b_2(a)(x) \qquad \forall x \in D_S,$$

so the single output fragment $(S, b_2(a), \Pi^{\mathrm{G,const-}})$ is locally exact. When $d(a) \equiv 0$, the two affine branches coincide identically and either single-fragment output is valid.

In all cases every output fragment is locally exact, all payloads remain finite, and the union of the output cells covers the union of the input cells. Thus Rule G preserves certified faithfulness. □

C.5 Rule M: Finite Max with Explicit Winner Constraints

Assume

$$y(x) = \max_{1\le i\le k} \phi_i(x),$$

and for each child ϕ_i suppose we have a certified faithful family

$$\mathcal{F}_i = \{(S_{i,r}, a_{i,r}, \Pi_{i,r})\}_{r=1}^{R_i}.$$

For every index tuple

$$\mathbf{r} = (r_1, \ldots, r_k),$$

define the common-refinement guard set

$$S_{\mathbf{r}} := \bigcup_{i=1}^{k} S_{i,r_i}$$

and abbreviate the corresponding child affine tags by

$$a_i := a_{i,r_i} \qquad (1 \le i \le k).$$

Thus on the cell $D_{S_{\mathbf{r}}}$, every child node is already represented by an accepted affine tag.

Now fix a candidate winner index $p \in \{1, \dots, k\}$. For every competitor $q \neq p$, define the affine comparison

$$d_{pq}(x) := a_p(x) - a_q(x).$$

Rule M treats each competitor as follows.

1. If d_{pq} is a negative constant, then p can never dominate q on this common refinement, so the candidate p is discarded.
2. If d_{pq} is a nonnegative constant, then no new literal is needed; the comparison is globally valid on the refinement cell.
3. If d_{pq} is nonconstant, the rule adds the winner literal

$$d_{pq} \ge 0.$$

Let $S(\mathcal{C}_{p,\mathbf{r}})$ denote the finite set of all nonconstant winner literals added for the surviving candidate p on the tuple $\mathbf{r}$. If p is not discarded, Rule M outputs the fragment

$$\big(S_{\mathbf{r}} \cup S(\mathcal{C}_{p,\mathbf{r}}),\ a_p,\ \Pi^{\mathrm{M}}_{p,\mathbf{r}}\big).$$

The payload $\Pi^{\mathrm{M}}_{p,\mathbf{r}}$ is finite and contains:

1. the tuple of already accepted child payloads $\Pi_{1,r_1}, \dots, \Pi_{k,r_k}$;
2. the chosen winner index p;
3. for each competitor $q \neq p$, either the explicit constant comparison $d_{pq} \ge 0$ or the newly added literal $d_{pq} \ge 0$;
4. the declaration that the output affine tag is the winner tag a_p.

Theorem C.4 (Rule M). Rule M preserves certified faithfulness.

Proof. We must prove both coverage and local exactness.

Coverage. Fix any point $x \in D$. Because each child family $\mathcal{F}_i$ is certified faithful, for every i there exists some r_i such that

$$x \in D_{S_{i,r_i}}.$$

Hence for the tuple $\mathbf{r} = (r_1, \dots, r_k)$ we have

$$x \in D_{S_{\mathbf{r}}}.$$

On this refinement cell, each child semantics is represented by the corresponding affine tag:

$$[[\phi_i]](x) = a_i(x) \qquad (1 \le i \le k).$$

Now choose any winner index

$$p^\star \in \operatorname*{arg\,max}_{1 \le i \le k} a_i(x).$$

For every competitor $q \neq p^\star$, the comparison

$$a_{p^\star}(x) - a_q(x) \ge 0$$

holds. Therefore:

- if $d_{p^\star q}$ is a constant, it cannot be negative, otherwise $p^\star$ would fail to dominate q at x;

- if $d_{p^\star q}$ is nonconstant, then x satisfies the corresponding winner literal $d_{p^\star q} \geq 0$.

Thus x belongs to the surviving winner fragment for $p^\star$:

$$x \in D_{S_{\mathbf{r}} \cup S(\mathcal{C}_{p^\star,\mathbf{r}})}.$$

So the Rule M output family still covers D.

Local exactness. Fix one surviving output fragment

$$\big(S_{\mathbf{r}} \cup S(\mathcal{C}_{p,\mathbf{r}}),\ a_p,\ \Pi^{\mathrm{M}}_{p,\mathbf{r}}\big)$$

and a point

$$x \in D_{S_{\mathbf{r}} \cup S(\mathcal{C}_{p,\mathbf{r}})}.$$

Since $x \in D_{S_{\mathbf{r}}}$, the child payloads give

$$[[\phi_i]](x) = a_i(x) \qquad (1 \leq i \leq k).$$

Moreover, for every competitor $q \neq p$, either:

- d_{pq} is a nonnegative constant, hence $a_p(x) \geq a_q(x)$ automatically; or
- the literal $d_{pq} \geq 0$ is part of the guard set, hence again $a_p(x) \geq a_q(x)$ on the current cell.

Therefore $a_p(x)$ dominates all competitors and

$$[[y]](x) = \max_{1 \leq i \leq k} [[\phi_i]](x) = \max_{1 \leq i \leq k} a_i(x) = a_p(x).$$

So the proposed winner tag is semantically exact on its output cell.

The remaining issue is overlap consistency. Different winner fragments may overlap only where several affine competitors tie. But on every such overlap, all active winner tags take the same value, since they are equal at the overlap point by the relevant winner inequalities in both directions. Thus local exactness is compatible across overlapping winner cells.

Finally, verifier acceptance is finite. The payload $\Pi^{\mathrm{M}}_{p,\mathbf{r}}$ only points to already accepted child payloads, records a finite tuple of affine comparisons, and asks the checker to verify that each required winner condition is either a stored nonnegative constant fact or a literal explicitly added to the guard set. Hence the checker accepts the announced exact equality on the output cell. Therefore Rule M preserves certified faithfulness. □

C.6 Topological Induction over the Expression Graph

We now combine the four local closure rules into the global static compilation theorem for allowed CPWL expression graphs.

Base fragments. Input coordinates and scalar constants give immediate one-fragment certified faithful families:

$$\mathcal{F}_{x_p} = \{(\varnothing,\ x \mapsto x_p,\ \Pi^{\mathrm{ax}}_{x_p})\}, \qquad \mathcal{F}_c = \{(\varnothing,\ x \mapsto c,\ \Pi^{\mathrm{ax}}_{c})\}.$$

Here $\Pi^{\mathrm{ax}}_{x_p}$ and Π^{ax}_{c} are the trivial finite atomic payloads accepted by the verifier for the corresponding identities on all of D.

Theorem C.5 (topological-induction static compilation theorem). For every scalar node u in an allowed CPWL expression graph, there exists a finite certified faithful family

$$\mathcal{F}_u = \{(S_r, a_r, \Pi_r)\}_{r=1}^{R_u}$$

of guard-affine fragments such that each Π_r is accepted as a proof of

$$[[u]](x) = a_r(x) \qquad \forall x \in D_{S_r},$$

and the cells $\{D_{S_r}\}_{r=1}^{R_u}$ cover D.

Proof. Order the nodes of the finite expression graph topologically.

Base case. For input coordinates and constants, the base fragment families above are already certified faithful.

Inductive step. Assume certified faithful families have been constructed for all predecessors of the current node u. There are only four possible module types:

1. if u is obtained by affine post-composition from one predecessor, apply Rule A and invoke Theorem C.1;
2. if u is an addition node, apply Rule R and invoke Theorem C.2;
3. if u is a scalar gate, apply Rule G and invoke Theorem C.3;
4. if u is a finite-max node, apply Rule M and invoke Theorem C.4.

In each case, the resulting output family is again certified faithful. Therefore the induction proceeds through the whole DAG and yields a certified faithful family for every scalar node, in particular for the output node u_g. □

Corollary C.6 (finiteness of compilation hyperplanes). For every scalar node u, the certified faithful family $\mathcal{F}_u$ introduces only finitely many affine comparison hyperplanes. In particular, the output-node family $\mathcal{F}_g$ determines a finite comparison-hyperplane set

$$\mathcal{H}^\star.$$

Proof. The base fragments introduce none. Rule A introduces no new hyperplanes. Rule R only takes common refinements of already finite guard sets. Rule G introduces at most one new gate-comparison hyperplane per input fragment, and Rule M introduces only finitely many pairwise winner-comparison hyperplanes because each max node has finitely many children and each child family is finite. Induction over the finite expression graph therefore yields only finitely many hyperplanes overall. □

This completes the purely local part of the CPWL theorem package. We now know that static compilation produces only finitely many verifier-visible guard-affine fragments, each already carrying an accepted exact local payload. Appendix D uses the finite hyperplane set $\mathcal{H}^\star$ to build aligned split trees, restricts these compiled fragments to nonempty leaves, and assembles the resulting exact leaves into a finite accepted exact certified cover.

D Aligned Trees, Global Cover Payload, and Finite Exactification

This appendix closes the exactification argument from Section 3. Appendix C already proved the local structural part: every scalar node in an allowed CPWL expression graph admits a finite certified-faithful compilation into guard-affine fragments. What remains is the global closure step. We must show that once a split tree freezes, leafwise, the side of every relevant comparison hyperplane, then:

1. some compiled fragment is compatible with every nonempty aligned leaf;
2. that compatible fragment restricts to an accepted exact certified cell on the leaf;
3. the split tree itself yields a finite global cover payload in the precise cover grammar of Appendix B;
4. after removing empty leaves, the remaining exact leaves form an accepted finite exact certified cover.

The third point is the formal closure that the main text needs most. It upgrades "semantic exactification" to "accepted exact certified cover" and is therefore the strict backend of both Section 3 and the exact-side upper bound in Section 5.

Throughout the appendix we fix the output node u_g of the expression graph, write

$$g(x) := [[u_g]](x),$$

and let

$$\mathcal{F}_g = \{(S_r, a_r, \Pi_r)\}_{r=1}^{R_g}$$

be the compiled certified-faithful family for the output node supplied by Appendix C. We also write

$$\mathcal{H}^\star$$

for the finite set of affine comparison hyperplanes introduced during that compilation.

D.1 Split Trees, Leaf Descriptions, and Alignment

A split tree recursively refines the domain by affine comparison literals from the guard language.

Definition D.1 (split-tree semantics). Let T be a finite rooted binary tree. Every node v carries a guard set $S(v)$ such that:

1. the root r has
$$S(r) = \varnothing;$$
2. if an internal node v splits on a hyperplane
$$h_v(x) = 0,$$
then its two children, denoted v^- and v^+, have guard sets
$$S(v^-) = S(v) \cup \{h_v \le 0\}, \qquad S(v^+) = S(v) \cup \{h_v \ge 0\}.$$

For every node v, let

$$\eta_v := S(v)$$

viewed as a verifier-facing description in the guard language. Its semantic domain is

$$C(\eta_v) = D_{S(v)}.$$

For leaves we abbreviate

$$D_v := C(\eta_v) = D_{S(v)}.$$

When $v = r$, we identify η_r with the root description $\top_D$ from Appendix B, since both describe the full domain D.

Proposition D.2 (leaf coverage). For every split tree T,

$$D \subseteq \bigcup_{v \in \mathrm{Leaves}(T)} D_v.$$

Proof. At the root we have $D_{S(r)} = D$. If a node with guard set $S(v)$ is split on $h_v = 0$, then the two closed halfspaces cover the ambient space, so

$$D_{S(v)} \subseteq D_{S(v)\cup\{h_v \le 0\}} \ \cup \ D_{S(v)\cup\{h_v \ge 0\}}.$$

Iterating this finite cover step down the tree yields the stated leaf coverage. □

The exactification condition is not merely that a leaf contains points on one side of a hyperplane. It is that the whole leaf domain has a verifier-visible side relation to every comparison hyperplane that matters to the compiled fragments.

Definition D.3 (leaf-side signatures and aligned leaves). Let

$$\mathcal{H} = \{h_1, \dots, h_M\}$$

be a finite family of affine hyperplanes. For a leaf v and a hyperplane $h_m \in \mathcal{H}$, define

$$\Sigma_v(h_m) \subseteq \{\le, \ge\}$$

by declaring:

1. $\le \in \Sigma_v(h_m)$ iff the verifier accepts a finite side certificate proving
$$D_v \subseteq \{h_m \le 0\};$$
2. $\ge \in \Sigma_v(h_m)$ iff the verifier accepts a finite side certificate proving
$$D_v \subseteq \{h_m \ge 0\}.$$

If both signs belong to $\Sigma_v(h_m)$, then necessarily

$$D_v \subseteq \{h_m = 0\}.$$

We say that v is *aligned with* $\mathcal{H}$ if

$$\Sigma_v(h_m) \ne \varnothing \qquad \forall h_m \in \mathcal{H}.$$

A split tree is *aligned with* $\mathcal{H}$ if every leaf is aligned with $\mathcal{H}$.

Definition D.4 (compatible literals and compatible fragments). Fix a leaf v aligned with $\mathcal{H}^\star$.

1. A literal λ induced by a hyperplane $h \in \mathcal{H}^\star$ is *compatible with* v if its sign belongs to $\Sigma_v(h)$.
2. A compiled fragment (S, a, Π) is *compatible with* v if every literal in S is compatible with v.

When (S, a, Π) is compatible with v, the accepted side certificates for the literals in S bundle into a finite containment proof, denoted

$$\rho_{v \subseteq S},$$

with verifier-accepted conclusion

$$D_v \subseteq D_S. \tag{D.1}$$

Thus the aligned-leaf problem is reduced to a single combinatorial statement: every nonempty aligned leaf must admit at least one compatible compiled fragment.

D.2 Alignment Selects a Compatible Compiled Fragment

For every scalar node u in the expression graph, write

$$\mathcal{F}_u = \{(S_r, a_r, \Pi_r)\}_{r=1}^{R_u}$$

for the certified-faithful family produced by Appendix C, and write $\mathcal{H}_u$ for the finite set of comparison hyperplanes introduced in that compilation. By construction,

$$\mathcal{H}^\star = \mathcal{H}_{u_g}.$$

Lemma D.5 (aligned-fragment lemma). Let u be any scalar node in the allowed CPWL expression graph. If v is a nonempty leaf aligned with $\mathcal{H}_u$, then some fragment in $\mathcal{F}_u$ is compatible with v.

Proof. We argue by induction over the topological compilation of u.

Atomic nodes. If u is an input coordinate or a constant, then $\mathcal{F}_u$ consists of a single fragment with empty guard set. The empty guard set is compatible with every leaf.

Rule A: affine propagation. Suppose

$$u(x) = \alpha\phi(x) + \beta.$$

Rule A introduces no new literals, so

$$\mathcal{H}_u = \mathcal{H}_\phi.$$

By the induction hypothesis, some child fragment $(S, a, \Pi) \in \mathcal{F}_\phi$ is compatible with v. Rule A outputs the fragment

$$(S, \alpha a + \beta, \Pi^{\mathrm{A}})$$

on the same guard set S, which is therefore also compatible with v.

Rule R: addition. Suppose

$$u(x) = \phi_1(x) + \phi_2(x).$$

Rule R introduces no new comparison hyperplanes, so

$$\mathcal{H}_u = \mathcal{H}_{\phi_1} \cup \mathcal{H}_{\phi_2}.$$

Because v is aligned with $\mathcal{H}_u$, it is aligned with both child hyperplane families. By induction there exist compatible child fragments

$$(S_i, a_i, \Pi_i) \in \mathcal{F}_{\phi_1}, \qquad (T_j, b_j, \Theta_j) \in \mathcal{F}_{\phi_2}.$$

Every literal in $S_i \cup T_j$ is therefore compatible with v, so the common-refinement output fragment

$$(S_i \cup T_j,\ a_i + b_j,\ \Pi^{\mathrm{R}}_{ij})$$

is compatible with v.

Rule G: scalar gating. Suppose

$$u = \sigma(\phi)$$

for one of the scalar gates allowed in Section 3. By induction there exists a compatible child fragment

$$(S, a, \Pi) \in \mathcal{F}_\phi.$$

Let $b_1(a)$, $b_2(a)$, and $d(a) = b_1(a) - b_2(a)$ be the two affine branch tags and the affine winner comparison used by Rule G in Appendix C. If $d(a)$ is constant, Rule G outputs a single fragment on the unchanged guard set S, which remains compatible with v.

Assume now that $d(a)$ is nonconstant. Then the comparison hyperplane

$$d(a)(x) = 0$$

belongs to $\mathcal{H}_u$. Since v is aligned with $\mathcal{H}_u$, the verifier accepts at least one of

$$D_v \subseteq \{d(a) \le 0\}, \qquad D_v \subseteq \{d(a) \ge 0\}.$$

If the second holds, then the first Rule G branch fragment

$$(S \cup \{d(a) \ge 0\},\ b_1(a),\ \Pi^{\mathrm{G},1})$$

is compatible with v. If the first holds, then the second Rule G branch fragment

$$(S \cup \{d(a) \le 0\},\ b_2(a),\ \Pi^{\mathrm{G},2})$$

is compatible with v. If both hold, then $D_v \subseteq \{d(a) = 0\}$ and the two affine branch tags agree on the whole leaf, so either branch fragment may be chosen. Thus some Rule G output fragment is compatible with v.

Rule M: finite max. Suppose

$$u(x) = \max_{1 \le i \le k} \phi_i(x).$$

For each child ϕ_i, the induction hypothesis yields a fragment

$$(S_{i,r_i}, a_i, \Pi_i) \in \mathcal{F}_{\phi_i}$$

compatible with v. Hence the common-refinement guard set

$$S_{\mathbf{r}} := \bigcup_{i=1}^{k} S_{i,r_i}$$

is compatible with v.

We now choose a compatible winner. For every pair (i, j), define the affine difference

$$d_{ij}(x) := a_i(x) - a_j(x).$$

If d_{ij} is constant, then its sign is globally fixed. If d_{ij} is nonconstant, then the hyperplane $d_{ij} = 0$ belongs to $\mathcal{H}_u$, so alignment of v forces at least one of

$$D_v \subseteq \{d_{ij} \le 0\}, \qquad D_v \subseteq \{d_{ij} \ge 0\}$$

to be verifier-accepted. Thus every pairwise comparison between the affine competitors is fixed on the whole leaf.

Define a preorder on $\{1, \ldots, k\}$ by

$$i \preceq_v j \iff D_v \subseteq \{a_i \le a_j\}.$$

Because every pairwise comparison is fixed leafwise, this is a total preorder on a finite set. Let p be any maximal element. For a total preorder, maximality implies

$$q \preceq_v p \qquad \forall q \in \{1, \ldots, k\},$$

since otherwise totality would force $p \prec_v q$, contradicting maximality.

We claim that the Rule M candidate p survives and is compatible with v.

- If for some $q \neq p$ the comparison d_{pq} were a negative constant, then $a_p < a_q$ everywhere, so $q \not\preceq_v p$, contradicting the displayed property.
- If d_{pq} is a nonnegative constant, Rule M adds no new winner literal, so compatibility is automatic.
- If d_{pq} is nonconstant, the displayed property gives
$$D_v \subseteq \{a_q \leq a_p\} = \{d_{pq} \geq 0\},$$
so the required winner literal $d_{pq} \geq 0$ is compatible with v.

Therefore every winner constraint required for candidate p is accepted on the whole leaf. The output fragment
$$\big(S_{\mathbf{r}} \cup S(\mathcal{C}_{p,\mathbf{r}}),\ a_p,\ \Pi^{\mathrm{M}}_{p,\mathbf{r}}\big)$$
is compatible with v.

This completes the induction. Every nonempty leaf aligned with $\mathcal{H}_u$ admits at least one compatible fragment in $\mathcal{F}_u$. □

The content of the lemma is exactly the structural claim used in the main text: alignment does not invent a new affine model. It selects one of the finitely many already certified compiled fragments whose guard conditions are valid on the whole leaf.

D.3 Exact Leaves and Their Local Optimization

Once a compatible fragment has been selected on a nonempty aligned leaf, exactification follows by restriction.

Theorem D.6 (exact leaf theorem). Let T be a split tree aligned with $\mathcal{H}^\star$, and let $v \in \mathrm{Leaves}(T)$ satisfy $D_v \neq \varnothing$. Then there exist an affine function a_v and a verifier-accepted exact payload
$$\pi_v^{=}$$
such that
$$g(x) = a_v(x) \qquad \forall x \in D_v. \tag{D.2}$$
Equivalently, every nonempty aligned leaf is an exact certified cell in the guard language.

Proof. Apply Lemma D.5 to the output node u_g. Since v is aligned with $\mathcal{H}^\star = \mathcal{H}_{u_g}$ and nonempty, some compiled output fragment
$$(S, a, \Pi) \in \mathcal{F}_g$$
is compatible with v. By Definition D.4, the verifier accepts a finite containment proof
$$\rho_{v \subseteq S} : D_v \subseteq D_S.$$
Appendix C already established the restriction rule for accepted exact payloads. Therefore the fragment payload Π, which is accepted as a proof of
$$g(x) = a(x) \qquad \forall x \in D_S,$$
may be restricted along the accepted containment. Define
$$a_v := a, \qquad \pi_v^{=} := \mathrm{Restr}(D_v \subseteq D_S; \Pi).$$
Then the verifier accepts
$$g(x) = a_v(x) \qquad \forall x \in D_v,$$
which is exactly the required exact leaf statement. □

Corollary D.7 (exact leaf optimization). Under the assumptions of Theorem D.6, AFFOPT applied to a_v over the verifier-facing leaf description η_v returns a certificate of
$$\mu_v := \inf_{x \in D_v} a_v(x).$$
Because D_v is nonempty and compact, this infimum is attained at some point $x_v^\star \in D_v$, and the verifier can therefore accept the full exact leaf certificate
$$\mathrm{Exact}(v; a_v, \mu_v, x_v^\star, \pi_v^{=}, \pi_v^{\mathrm{opt}}).$$
Moreover,
$$\mu_v = \inf_{x \in D_v} g(x) = \min_{x \in D_v} g(x). \tag{D.3}$$

Proof. The equality payload from Theorem D.6 gives

$$g = a_v \qquad \text{on } D_v.$$

Since a_v is affine and D_v is nonempty compact, AFFOPT returns an attained optimum of a_v on D_v. Combining the optimizer payload with the exact leaf payload yields the displayed equality for the true function g. □

Thus any aligned split tree can be turned into an exact leaf table after empty leaves have been discharged by infeasibility. What remains is to turn that leaf table into an *accepted cover* in the formal sense of Appendix B.

D.4 Explicit Global Cover Payload from a Split Tree

The exact leaves already provide the local exact cells. To obtain an accepted exact certified cover object, we still need a finite global cover derivation. Appendix B fixed the relevant grammar: cover sequents, direct local-cover atoms, composition, and empty-target elimination. We now instantiate that grammar for split trees.

For a node v of T, write

$$\mathrm{Leaves}(v)$$

for the descendant leaves of the subtree rooted at v, and define the target family

$$\Gamma_v := \{\eta_w : \ w \in \mathrm{Leaves}(v)\}.$$

Definition D.8 (split-local cover atom). Let v be an internal node split on $h_v = 0$, with children v^- and v^+. The associated *split-local cover payload* is the finite object

$$\rho_v^{\mathrm{split}}$$

that CHECK accepts as a proof of the direct local-cover sequent

$$\eta_v \rightsquigarrow \{\eta_{v^-}, \eta_{v^+}\}. \tag{D.4}$$

Concretely, ρ_v^{split} records the parent guard set $S(v)$, the split hyperplane h_v, and the two child guard sets

$$S(v^-) = S(v) \cup \{h_v \le 0\}, \qquad S(v^+) = S(v) \cup \{h_v \ge 0\}.$$

The verifier checks only finite syntax:

1. the child descriptions are exactly the parent description extended by the two closed-halfspace literals;
2. the corresponding semantic claim is

$$D_{S(v)} \subseteq D_{S(v^-)} \cup D_{S(v^+)},$$

which holds because the two closed halfspaces $\{h_v \le 0\}$ and $\{h_v \ge 0\}$ cover the ambient space.

Thus ρ_v^{split} is a valid direct local-cover atom in the grammar of Appendix B.

Lemma D.9 (global cover payload from a split tree). Let T be any finite split tree.

1. For every node v of T, there exists a finite cover derivation

$$\Pi_v^{\mathrm{cov}}$$

concluding the sequent

$$\eta_v \rightsquigarrow \Gamma_v. \tag{D.5}$$

In particular, for the root r one obtains a finite global cover payload

$$\Pi_T^{\mathrm{cov}}$$

concluding

$$\top_D \rightsquigarrow \Gamma_r = \{\eta_v : \ v \in \mathrm{Leaves}(T)\}. \tag{D.6}$$

2. If a subset $E \subseteq \mathrm{Leaves}(T)$ is certified empty by FEAS, then repeated empty-target elimination yields another finite cover derivation

$$\Pi^{\mathrm{cov}}_{T,\mathrm{live}}$$

concluding

$$\top_D \rightsquigarrow \{\eta_v : \ v \in \mathrm{Leaves}(T) \setminus E\}. \tag{D.7}$$

Hence any split tree, together with finite infeasibility certificates for its empty leaves, canonically yields a finite accepted global cover payload over its live leaves.

Proof. For the first statement we argue by induction on the subtree rooted at v.

Base case: v is a leaf. Then $\Gamma_v = \{\eta_v\}$. The verifier accepts the reflexive containment proof

$$\rho^{\mathrm{id}}_v : C(\eta_v) \subseteq C(\eta_v),$$

so by the containment atom of Appendix B we obtain the sequent

$$\eta_v \rightsquigarrow \{\eta_v\}.$$

This is the required derivation Π^{cov}_v.

Induction step: v is internal. Let v^- and v^+ denote its two children. By Definition D.8, the verifier accepts the split-local cover atom

$$\eta_v \rightsquigarrow \{\eta_{v^-}, \eta_{v^+}\}.$$

By the induction hypothesis, there exist finite derivations

$$\Pi^{\mathrm{cov}}_{v^-} : \eta_{v^-} \rightsquigarrow \Gamma_{v^-}, \qquad \Pi^{\mathrm{cov}}_{v^+} : \eta_{v^+} \rightsquigarrow \Gamma_{v^+}.$$

Applying the composition rule from Appendix B yields a finite derivation

$$\Pi^{\mathrm{cov}}_v : \eta_v \rightsquigarrow \Gamma_{v^-} \cup \Gamma_{v^+}.$$

But

$$\Gamma_{v^-} \cup \Gamma_{v^+} = \Gamma_v,$$

so this proves (D.5).

Applying the construction to the root r gives (D.6), since $\eta_r = \top_D$.

For the second statement, let E be the set of leaves whose descriptions are certified empty. Starting from the derivation (D.6), apply the empty-target elimination rule once for each $v \in E$. Because the target family is finite, only finitely many elimination steps are needed. Each step removes one empty target description without changing the semantic union. The resulting derivation is exactly (D.7). □

This is the missing formal closure step: split trees do not merely induce a semantic leaf cover. They induce a finite *accepted* global cover derivation in the grammar already fixed in Appendix B.

D.5 Finite Fully Aligned Trees and Accepted Finite Exactification

We now prove that the alignment hypothesis itself can always be realized finitely because the comparison family $\mathcal{H}^\star$ is finite.

Theorem D.10 (finite fully aligned tree exists). Let

$$\mathcal{H}^\star = \{h_1, \ldots, h_M\}$$

be the finite comparison-hyperplane family extracted from the static compilation of the output node. Then there exists a finite split tree $T^\star$ aligned with $\mathcal{H}^\star$.

Proof. Start from the root leaf with empty guard set. Process the hyperplanes in $\mathcal{H}^\star$ one by one. At stage m, split every current leaf on the two literals

$$h_m \le 0, \qquad h_m \ge 0.$$

After M rounds this yields a finite binary split tree $T^\star$.

Every final leaf contains, in its path guard set, one explicit side literal for each hyperplane h_m. Therefore for every leaf v and every m the verifier certainly accepts at least one of

$$D_v \subseteq \{h_m \le 0\}, \qquad D_v \subseteq \{h_m \ge 0\}.$$

Thus every leaf is aligned with every hyperplane in $\mathcal{H}^\star$, so $T^\star$ is aligned with $\mathcal{H}^\star$. □

The finiteness of exactification now follows by combining the aligned-fragment lemma, the exact leaf theorem, and the explicit split-tree cover derivation.

Theorem D.11 (finite exactification theorem). Let g be the output of an allowed CPWL expression graph over nonempty compact domain D, and let $\mathcal{H}^\star$ be the finite comparison-hyperplane family extracted from static compilation. If T is any split tree aligned with $\mathcal{H}^\star$, then its live leaves

$$\mathrm{Live}(T) := \{v \in \mathrm{Leaves}(T) : D_v \neq \varnothing\}$$

carry an accepted exact certified cover object

$$\mathbf{C}_T^{=} := \Big(\{(\eta_v, a_v, \pi_v^{=})\}_{v \in \mathrm{Live}(T)}, \Pi^{\mathrm{cov}}_{T,\mathrm{live}}\Big)$$

in the guard language. Consequently,

$$\mathrm{VAC}^{=}_{\mathfrak{L}_{\mathrm{grd}}}(g; D) \le |\,\mathrm{Live}(T)|. \tag{D.8}$$

In particular, since a finite aligned tree exists by Theorem D.10,

$$\mathrm{VAC}^{=}_{\mathfrak{L}_{\mathrm{grd}}}(g; D) < +\infty. \tag{D.9}$$

Proof. For each live leaf $v \in \mathrm{Live}(T)$, Theorem D.6 supplies an affine function a_v and an accepted exact payload $\pi_v^{=}$ proving

$$g(x) = a_v(x) \qquad \forall x \in D_v = C(\eta_v).$$

Thus each live leaf defines an accepted exact certified cell

$$(\eta_v, a_v, \pi_v^{=}).$$

For each empty leaf $v \notin \mathrm{Live}(T)$, FEAS provides a finite infeasibility certificate for $C(\eta_v) = D_v = \varnothing$. Lemma D.9 then yields a finite global cover payload

$$\Pi^{\mathrm{cov}}_{T,\mathrm{live}}$$

concluding

$$\top_D \rightsquigarrow \{\eta_v :\ v \in \mathrm{Live}(T)\}.$$

By the definitions in Appendix B, the pair of this global payload with the listed live-leaf exact cells is an accepted exact certified cover object. Its size is exactly $|\,\mathrm{Live}(T)|$, so by minimality of VAC we obtain (D.8).

Taking $T = T^\star$ from Theorem D.10 yields a finite accepted exact certified cover, which proves (D.9). □

Corollary D.12 (exact leaf table and global optimum). Let T be any split tree aligned with $\mathcal{H}^\star$. For each live leaf v, let

$$\mu_v := \inf_{x \in D_v} a_v(x).$$

Because $D \neq \varnothing$ and Proposition D.2 shows that the leaves of T cover D, the live-leaf set $\mathrm{Live}(T)$ is nonempty. Then

$$\inf_{x \in D} g(x) = \min_{v \in \mathrm{Live}(T)} \mu_v. \tag{D.10}$$

If $T = T^\star$ is the finite aligned tree from Theorem D.10, then the right-hand side is finite and attained leafwise.

Proof. By Theorem D.11, the live leaves form an accepted exact certified cover of D. Since $D \neq \varnothing$, at least one live leaf must remain after empty-leaf elimination. The basic soundness contract from Section 2 therefore reduces the global infimum of g to the minimum of the local affine infima over the listed exact cells. Those local affine infima are precisely the μ_v. □

Corollary D.13 (naive leaf-count bound). If $|\mathcal{H}^\star| = M$, then the tree $T^\star$ from Theorem D.10 may be chosen with depth at most M and therefore with at most

$$2^M$$

leaves. Hence the construction proves finiteness, not optimality.

Proof. The tree construction splits once on each of the M hyperplanes, so its depth is at most M. A binary tree of depth M has at most 2^M leaves. Theorem D.11 shows only that this explicit aligned tree yields one accepted exact certified cover. VAC may still be strictly smaller because different live leaves can later be merged, omitted, or replaced by a smaller verifier-accepted exact cover. □

This appendix is therefore the exact formal bridge from local CPWL compilation to accepted exact certified covers. Appendix C proved that the network admits finitely many verifier-accepted guard-affine fragments. The present appendix proved that full alignment with their finite comparison geometry turns those fragments into exact leaves, and that the split tree itself contributes the finite global cover payload required by the cover grammar. That is the closure used in the main text whenever exactification is invoked as an accepted cover theorem rather than merely as a semantic decomposition.

E Proof Languages, SCC/DL, and Arrangement Degeneration

This appendix expands Section 4. The main text uses a three-layer picture: after fixing a verifier-facing language, VAC measures the semantic cover quantity; a concrete proof language realizes that quantity with some leaf overhead, measured by SCC; and a binary encoding adds a further description-length layer, measured by DL. The purpose of this appendix is to formalize that separation and the assumptions under which the three layers are linearly comparable.

There are four tasks.

1. We formalize proof languages as finite verifier-visible objects whose leaves denote accepted certified cells and whose global payload proves a cover statement in the grammar of Appendix B.
2. We define leaf-realizing and c-cell-complete proof languages and prove the exact-side and threshold-side equivalence between VAC and minimum leaf count.
3. We isolate the linear-encoding hypothesis under which description length is linearly equivalent to syntactic certificate complexity.
4. We record the full restricted exact-side statement under which arrangement count reappears as a degeneration of verifier-aligned cover complexity.

Throughout, we fix a verifier-facing cell language $\mathfrak{L}$ in the sense of Section 2. Thus every

$$\gamma \in \mathfrak{L}$$

comes with a verifier-facing set description $\mathfrak{D}(\gamma)$ and semantic cell

$$C(\gamma) := [\![\mathfrak{D}(\gamma)]\!] \subseteq D.$$

Exact certified cells, threshold certified cells, and accepted cover payloads are understood exactly as formalized in Appendix B.

E.1 Proof Languages and the Canonical Flat Leaf-Table Syntax

A proof language is a syntactic realization layer. It does not change what the verifier-visible local proof unit is; it only changes how a finite family of such local units is packaged into one accepted proof object.

Definition (proof language over $\mathfrak{L}$). A proof language $\mathcal{P}$ over $\mathfrak{L}$ is a class of finite objects P such that every object is equipped with:

1. a finite leaf set
$$\mathrm{Leaves}(P),$$
2. a leaf-semantics map sending each leaf $\lambda \in \mathrm{Leaves}(P)$ to one certified cell over $\mathfrak{L}$, and
3. a finite global payload that the verifier can deterministically re-check as a proof that the leaf cells jointly form the required cover.

The same syntax may be used on two different semantic sides.

- On the *exact side*, every leaf denotes an exact certified cell
$$\mathfrak{c}_\lambda = (\gamma_\lambda, a_\lambda, \pi_\lambda^{=}).$$
- On the *threshold side*, every leaf denotes a threshold certified cell
$$\mathfrak{c}_\lambda = (\gamma_\lambda, \pi_\lambda^{\geq}).$$

The proof object may carry additional syntax—for example tree structure, node tags, sharing metadata, or explicit cover-witness tables—but all such extra structure is realization overhead rather than new semantic proof content.

Definition (accepted proof objects). An object $P \in \mathcal{P}$ is an *accepted exact proof object* for (g, D) if:

1. every leaf of P is interpreted as an exact certified cell over $\mathfrak{L}$;
2. the verifier accepts every leaf-level exact payload; and
3. the verifier accepts the global payload as a proof of
$$D \subseteq \bigcup_{\lambda \in \mathrm{Leaves}(P)} |\mathfrak{c}_\lambda|.$$

Similarly, P is an *accepted threshold proof object* for (g, D, t) if each leaf is interpreted as a threshold certified cell and the verifier accepts the corresponding threshold-side cover statement.

Whenever P is accepted, its leaves already determine a finite semantic certified cover. We write
$$\mathrm{Cells}^{=}(P) := \{\mathfrak{c}_\lambda : \lambda \in \mathrm{Leaves}(P)\}$$
for the exact-side extracted family, and analogously
$$\mathrm{Cells}^{\geq}(P) := \{\mathfrak{c}_\lambda : \lambda \in \mathrm{Leaves}(P)\}$$
for the threshold side.

Definition (flat leaf-table language). For every verifier-facing language $\mathfrak{L}$, define the flat leaf-table language
$$\mathcal{P}_{\mathrm{tab}}(\mathfrak{L})$$
as follows.

- An exact-side object is a pair
$$P^{=} = \big(\{(\gamma_i, a_i, \pi_i^{=})\}_{i=1}^{N},\ \Pi^{\mathrm{cov}}\big),$$
where each listed entry is an exact certified cell and Π^{cov} is an accepted global cover payload for the listed family.
- A threshold-side object is defined analogously as
$$P^{\geq} = \big(\{(\gamma_i, \pi_i^{\geq})\}_{i=1}^{N},\ \Pi^{\mathrm{cov}}\big).$$

Its leaves are literally the listed table entries themselves. No hidden normalization layer is inserted.

Proposition E.1 (the flat leaf-table syntax realizes VAC exactly). For every verifier-facing language $\mathfrak{L}$,

$$\mathrm{SCC}^{=}_{\mathcal{P}_{\mathrm{tab}}(\mathfrak{L})}(g; D) = \mathrm{VAC}^{=}_{\mathfrak{L}}(g; D),$$
$$\mathrm{SCC}^{\geq}_{\mathcal{P}_{\mathrm{tab}}(\mathfrak{L})}(g; D, t) = \mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t).$$

Proof. We prove the exact-side identity; the threshold side is identical.

Every exact certified cover

$$\mathcal{C}^{=} = \{(\gamma_i, a_i, \pi_i^{=})\}_{i=1}^{N}$$

together with its accepted global cover payload is already, by inspection, an accepted object of $\mathcal{P}_{\mathrm{tab}}(\mathfrak{L})$ with exactly N leaves. Therefore

$$\mathrm{SCC}^{=}_{\mathcal{P}_{\mathrm{tab}}(\mathfrak{L})}(g; D) \leq \mathrm{VAC}^{=}_{\mathfrak{L}}(g; D).$$

Conversely, every accepted object of $\mathcal{P}_{\mathrm{tab}}(\mathfrak{L})$ explicitly stores a finite family of exact certified cells together with an accepted global cover payload, so it is itself exactly an exact certified cover. Hence its leaf count cannot be smaller than the minimum semantic cover size, giving

$$\mathrm{VAC}^{=}_{\mathfrak{L}}(g; D) \leq \mathrm{SCC}^{=}_{\mathcal{P}_{\mathrm{tab}}(\mathfrak{L})}(g; D).$$

Combining the two inequalities proves the exact-side claim. □

Proposition E.1 is conceptually important: for a fixed verifier-facing language, VAC is not merely analogous to proof size. It is already minimum proof size in the canonical zero-overhead syntax.

E.2 Leaf-Realizing and Cell-Complete Proof Languages

Section 4 defines VAC semantically. To compare VAC with any more structured syntax, we need only one interface notion: the syntax must realize semantic certified covers with at most constant-factor leaf overhead.

Definition (syntactic certificate complexity). For a proof language $\mathcal{P}$ over $\mathfrak{L}$, define

$$\mathrm{SCC}^{=}_{\mathcal{P}}(g; D) := \min\left\{ |\,\mathrm{Leaves}(P)| : \begin{array}{l} P \in \mathcal{P} \text{ is an accepted exact proof object} \\ \text{for } (g, D) \end{array} \right\},$$

and

$$\mathrm{SCC}^{\geq}_{\mathcal{P}}(g; D, t) := \min\left\{ |\,\mathrm{Leaves}(P)| : \begin{array}{l} P \in \mathcal{P} \text{ is an accepted threshold proof object} \\ \text{for } (g, D, t) \end{array} \right\}.$$

If no accepted proof object exists on the relevant side, the corresponding SCC value is defined to be $+\infty$.

Definition (leaf-realizing proof language). A proof language $\mathcal{P}$ is *leaf-realizing* for $\mathfrak{L}$ on a given side if every leaf of every accepted proof object on that side denotes one certified cell from $\mathfrak{L}$.

Definition (c-cell-complete proof language). Fix $c \geq 1$. We say that $\mathcal{P}$ is *c-cell-complete* for $\mathfrak{L}$ on a given side if:

1. *semantic extraction*: every accepted proof object P on that side extracts to a certified cover of size at most $|\,\mathrm{Leaves}(P)|$;
2. *syntactic realization*: every certified cover of size N on that side compiles into an accepted proof object $P \in \mathcal{P}$ with
$$|\,\mathrm{Leaves}(P)| \leq cN.$$

The constant c may depend on the fixed proof syntax and its compilation discipline, but not on the concrete instance (g, D, t).

Theorem E.2 (exact-side VAC–SCC equivalence). If $\mathcal{P}$ is exact-side c-cell-complete for $\mathfrak{L}$, then

$$\mathrm{VAC}^{=}_{\mathfrak{L}}(g; D) \leq \mathrm{SCC}^{=}_{\mathcal{P}}(g; D) \leq c\,\mathrm{VAC}^{=}_{\mathfrak{L}}(g; D).$$

Proof. For the left inequality, let P be any accepted exact proof object. By semantic extraction, the extracted family $\mathrm{Cells}^{=}(P)$ is an exact certified cover of size at most $|\,\mathrm{Leaves}(P)|$. Hence

$$\mathrm{VAC}^{=}_{\mathfrak{L}}(g; D) \le |\,\mathrm{Leaves}(P)|.$$

Taking the minimum over all accepted exact proof objects yields

$$\mathrm{VAC}^{=}_{\mathfrak{L}}(g; D) \le \mathrm{SCC}^{=}_{\mathcal{P}}(g; D).$$

For the right inequality, if

$$\mathrm{VAC}^{=}_{\mathfrak{L}}(g; D) = +\infty,$$

there is nothing to prove. Otherwise choose an optimal exact certified cover

$$\mathcal{C}^{=}$$

of size

$$|\mathcal{C}^{=}| = \mathrm{VAC}^{=}_{\mathfrak{L}}(g; D).$$

By syntactic realization, this cover compiles into an accepted proof object $P_{\mathcal{C}} \in \mathcal{P}$ such that

$$|\,\mathrm{Leaves}(P_{\mathcal{C}})| \le c\,|\mathcal{C}^{=}| = c\,\mathrm{VAC}^{=}_{\mathfrak{L}}(g; D).$$

Minimizing over accepted exact proof objects gives

$$\mathrm{SCC}^{=}_{\mathcal{P}}(g; D) \le c\,\mathrm{VAC}^{=}_{\mathfrak{L}}(g; D).$$

This proves the exact-side equivalence. □

Theorem E.3 (threshold-side VAC–SCC equivalence). If $\mathcal{P}$ is threshold-side c-cell-complete for $\mathfrak{L}$, then

$$\mathrm{VAC}^{\ge}_{\mathfrak{L}}(g; D, t) \le \mathrm{SCC}^{\ge}_{\mathcal{P}}(g; D, t) \le c\,\mathrm{VAC}^{\ge}_{\mathfrak{L}}(g; D, t).$$

Proof. The argument is identical to that of Theorem E.2 after replacing "exact certified cover" everywhere by "threshold certified cover." □

Corollary E.4 (cell-complete syntaxes realize VAC without overhead beyond the realization constant). If $\mathcal{P}$ is cell-complete on a given side, meaning $c = 1$, then on that side

$$\mathrm{SCC}_{\mathcal{P}} = \mathrm{VAC}_{\mathfrak{L}}.$$

More generally, a c-cell-complete syntax changes minimum proof size only by the realization constant c.

Thus, after fixing $\mathfrak{L}$, VAC is the semantic cover quantity, while SCC is the minimum leaf count in one chosen cell-complete realization of that quantity.

Remark E.4A (Language relativity is essential). All comparisons in this appendix are made after fixing the verifier-facing language $\mathfrak{L}$. Changing $\mathfrak{L}$ can change which cells and local payloads are admissible, and therefore can change VAC itself. Theorems E.2–E.6 are not invariance claims across different verifier interfaces; they are realization and encoding comparisons relative to one fixed semantic layer.

E.3 Description Length and Linear Encoding Equivalence

Leaf count is the correct semantic size measure for the theorem map. Bit-length is one level lower still, because it depends on a concrete serialization of the chosen proof syntax.

Definition (description length). Fix a binary encoding scheme for the proof language $\mathcal{P}$. For every proof object $P \in \mathcal{P}$, let

$$|P|_{\mathrm{bit}}$$

denote the length of its encoding. Define

$$\mathrm{DL}^{=}_{\mathcal{P}}(g; D) := \min\Big\{\, |P|_{\mathrm{bit}} : P \in \mathcal{P} \text{ is an accepted exact proof object for } (g, D) \Big\},$$

and

$$\mathrm{DL}^{\ge}_{\mathcal{P}}(g; D, t) := \min\Big\{\, |P|_{\mathrm{bit}} : P \in \mathcal{P} \text{ is an accepted threshold proof object for } (g, D, t) \Big\}.$$

If no accepted proof object exists on the relevant side, the corresponding description length is defined to be $+\infty$.

Definition (linear encoding property). We say that the chosen binary encoding of $\mathcal{P}$ is *linear* if there exist constants

$$0 < b_- \le b_+, \qquad b_0 \ge 0,$$

depending only on the fixed syntax and fixed serialization scheme, such that every accepted proof object P satisfies

$$b_- \,|\,\mathrm{Leaves}(P)| - b_0 \le |P|_{\mathrm{bit}} \le b_+ \,|\,\mathrm{Leaves}(P)| + b_0. \tag{8}$$

This hypothesis isolates exactly the regime in which bit-length and leaf count stay on the same scale: bounded global headers, bounded per-leaf control overhead, and no superlinear duplication or compression effect as a function of the number of leaves.

Theorem E.5 (exact-side SCC–DL linear equivalence). Assume the encoding of $\mathcal{P}$ is linear in the sense of (8). Then the following are equivalent:

1. there exists an accepted exact proof object for (g, D);
2. $\mathrm{SCC}^{=}_{\mathcal{P}}(g; D) < +\infty$;
3. $\mathrm{DL}^{=}_{\mathcal{P}}(g; D) < +\infty$.

Moreover, whenever these quantities are finite,

$$b_- \,\mathrm{SCC}^{=}_{\mathcal{P}}(g; D) - b_0 \le \mathrm{DL}^{=}_{\mathcal{P}}(g; D) \le b_+ \,\mathrm{SCC}^{=}_{\mathcal{P}}(g; D) + b_0.$$

Proof. The equivalence of the three finiteness statements is immediate from the definitions: an accepted exact proof object exists if and only if the feasible set over which $\mathrm{SCC}^{=}_{\mathcal{P}}(g; D)$ is minimized is nonempty, and this is exactly the same feasible set over which $\mathrm{DL}^{=}_{\mathcal{P}}(g; D)$ is minimized.

Assume now that accepted exact proof objects exist. Let P_* be one whose leaf count is minimum. Then

$$|\,\mathrm{Leaves}(P_*)| = \mathrm{SCC}^{=}_{\mathcal{P}}(g; D).$$

Applying the upper bound in (8) gives

$$|P_*|_{\mathrm{bit}} \le b_+ \,|\,\mathrm{Leaves}(P_*)| + b_0 = b_+ \,\mathrm{SCC}^{=}_{\mathcal{P}}(g; D) + b_0.$$

Since $\mathrm{DL}^{=}_{\mathcal{P}}(g; D)$ is the minimum bit-length over all accepted exact proof objects,

$$\mathrm{DL}^{=}_{\mathcal{P}}(g; D) \le b_+ \,\mathrm{SCC}^{=}_{\mathcal{P}}(g; D) + b_0.$$

For the lower bound, let Q_* be an accepted exact proof object of minimum bit-length. Then

$$|Q_*|_{\mathrm{bit}} = \mathrm{DL}^{=}_{\mathcal{P}}(g; D).$$

Applying the lower bound in (8) yields

$$\mathrm{DL}^{=}_{\mathcal{P}}(g; D) = |Q_*|_{\mathrm{bit}} \ge b_- \,|\,\mathrm{Leaves}(Q_*)| - b_0.$$

Because Q_* is just one accepted exact proof object, its leaf count is at least the minimum accepted leaf count, namely

$$|\,\mathrm{Leaves}(Q_*)| \ge \mathrm{SCC}^{=}_{\mathcal{P}}(g; D).$$

Therefore

$$\mathrm{DL}^{=}_{\mathcal{P}}(g; D) \ge b_- \,\mathrm{SCC}^{=}_{\mathcal{P}}(g; D) - b_0.$$

Combining the two inequalities proves the exact-side statement. □

Theorem E.6 (threshold-side SCC–DL linear equivalence). Under the same linear encoding hypothesis, the following are equivalent:

1. there exists an accepted threshold proof object for (g, D, t);
2. $\mathrm{SCC}^{\ge}_{\mathcal{P}}(g; D, t) < +\infty$;
3. $\mathrm{DL}^{\ge}_{\mathcal{P}}(g; D, t) < +\infty$.

Whenever these quantities are finite,

$$b_- \,\mathrm{SCC}^{\ge}_{\mathcal{P}}(g; D, t) - b_0 \le \mathrm{DL}^{\ge}_{\mathcal{P}}(g; D, t) \le b_+ \,\mathrm{SCC}^{\ge}_{\mathcal{P}}(g; D, t) + b_0.$$

Proof. The proof is identical to that of Theorem E.5 after replacing accepted exact proof objects by accepted threshold proof objects throughout. □

Corollary E.7 (VAC, SCC, and DL lie on one linear scale under the appendix hypotheses). If $\mathcal{P}$ is c-cell-complete for $\mathfrak{L}$ on a given side and its encoding is linear, then on that side VAC, SCC, and DL are linearly comparable. Concretely:

- on the exact side,

$$b_- \, \mathrm{VAC}^{=}_{\mathfrak{L}}(g; D) - b_0 \le \mathrm{DL}^{=}_{\mathcal{P}}(g; D) \le b_+ c \, \mathrm{VAC}^{=}_{\mathfrak{L}}(g; D) + b_0;$$

- on the threshold side,

$$b_- \, \mathrm{VAC}^{\ge}_{\mathfrak{L}}(g; D, t) - b_0 \le \mathrm{DL}^{\ge}_{\mathcal{P}}(g; D, t) \le b_+ c \, \mathrm{VAC}^{\ge}_{\mathfrak{L}}(g; D, t) + b_0.$$

Proof. Combine Theorems E.2–E.3 with Theorems E.5–E.6. □

This appendix therefore formalizes the three-layer interpretation used in the main text, all relative to a fixed verifier-facing language $\mathfrak{L}$:

- VAC is *semantic cover complexity*;
- SCC is *syntactic realization complexity*;
- DL is *bit-level description complexity*.

VAC is independent of the chosen syntax once $\mathfrak{L}$ is fixed, while SCC and DL additionally depend on the realization and encoding choices.

E.4 Arrangement Count as a Restricted Exact-Side Degeneration

Arrangement count is sometimes treated as if it were the natural complexity measure for CPWL verification. In this paper it is not. It reappears only in a narrow exact-side regime in which function geometry and verifier language geometry align almost perfectly.

The relevant language is the guard language of Section 3. A guard-realizable exact certified cell is an exact certified cell of the form

$$\mathfrak{c} = (S, a, \pi^{=}), \qquad |\mathfrak{c}| = D_S,$$

where S is a guard set and the verifier accepts

$$g(x) = a(x) \qquad \forall x \in D_S.$$

We say that such a cell is *connected* if D_S is connected.

Definition (maximal connected exact-affine region). A set $U \subseteq D$ is an *exact-affine connected region* if:

1. U is nonempty and connected;
2. there exists an affine function a_U such that

$$g(x) = a_U(x) \qquad \forall x \in U.$$

It is *maximal* if it is inclusion-maximal among connected exact-affine subsets of D.

Suppose the maximal connected exact-affine regions of g on D are

$$U_1, \ldots, U_M.$$

This number is the connected arrangement count relevant to the present discussion.

Proposition E.8 (arrangement degeneration under connected realizability and witness separation). Assume that:

1. for each maximal connected exact-affine region U_j, there exists one connected guard-realizable exact certified cell
$$\mathfrak{c}_j = (S_j, a_j, \pi_j^{=})$$
whose semantic domain is exactly
$$|\mathfrak{c}_j| = U_j;$$
2. for each j, there exists a witness point
$$x_j \in U_j \setminus \bigcup_{i \neq j} U_i.$$

Then the minimum number of connected guard-realizable exact certified cells needed to cover D is exactly M.

Proof. The realizability assumption immediately gives an exact connected cover with one certified cell per maximal region, so the minimum is at most M.

For the reverse inequality, let
$$\mathfrak{c} = (S, a, \pi^{=})$$
be any connected guard-realizable exact certified cell. By local soundness,
$$g(x) = a(x) \qquad \forall x \in D_S,$$
and by connectedness D_S is a connected exact-affine subset of D. Therefore, by maximality of the regions $U_1, \ldots, U_M$, there exists some index r such that
$$D_S \subseteq U_r.$$
In particular, one connected exact certified cell cannot simultaneously contain witness points from two different maximal regions. Indeed, if both x_j and $x_{j'}$ belonged to D_S, then both would belong to the same maximal region U_r, contradicting the witness-separation property unless $j = j' = r$.

Hence each connected exact certified cell can cover at most one of the witness points $x_1, \ldots, x_M$. Any connected exact certified cover of D must therefore use at least M cells. Combining this with the upper bound proves that the minimum is exactly M. □

Why this is only a degeneration. Proposition E.8 also explains why arrangement count is not, in general, the semantic cover quantity studied in the paper.

1. A geometric exact-affine piece may fail to be realizable as one verifier-admissible exact cell.
2. If disconnected cells are allowed, several disjoint exact-affine pieces carrying the same affine label may be merged by one exact certified cell.
3. Threshold proofs require only local threshold validity, not exact affine recovery, so threshold-side complexity is naturally measured by threshold certified covers rather than exact-affine regions.

Thus arrangement count is a legitimate exact-side boundary case only under additional connected-realizability and witness-separation assumptions. Outside that restricted regime, the relevant fixed-language semantic cover quantity remains verifier-aligned cover complexity itself.

F Additional Proofs for Upper and Lower Bounds

This appendix expands Section 5. The main text states the quantitative theorem package in its cleanest form. Here we record the full semantic proofs behind that package.

There are four ingredients.

1. We show that the aligned exactification cover built in Appendix D is already an *accepted* exact certified cover, so it immediately yields an exact-side upper bound.

2. We prove the exact-to-threshold transfer formally by converting each nonempty exact certified cell into a threshold certified cell using one additional affine-optimization payload.
3. We give the complete incompatibility-graph lower-bound argument: every threshold cell induces an independent set, independent-set coverings are the same as graph colorings, and therefore threshold VAC is bounded below by the chromatic number.
4. We isolate the technical boundary cases, especially the two-sided statement that false threshold claims force
$$\mathrm{VAC}^{\geq} = +\infty,$$
while true threshold claims yield finite threshold covers only in languages that are expressive enough to admit them.

Throughout, $\mathfrak{L}$ denotes an arbitrary verifier-facing cell language in the sense of Section 2, and $\mathfrak{L}_{\mathrm{grd}}$ denotes the guard language specialized in Section 3. All exact and threshold certified cells, all accepted global cover payloads, and all soundness contracts are understood in the formal sense of Appendix B.

F.1 Exact-Side Upper Bounds from Accepted Exactification Covers

We begin with the exact side. By Appendix D, aligned split trees yield not only semantic exact leaves but also a finite global cover derivation in the accepted cover grammar.

Fix an allowed CPWL expression graph over nonempty compact domain D, let g be its output, and let
$$\mathcal{H}^{\star}$$
be the finite comparison-hyperplane family extracted by the static compilation in Appendix C. If T is any split tree aligned with $\mathcal{H}^{\star}$, write
$$\mathrm{Live}(T) := \{v \in \mathrm{Leaves}(T) : D_v \neq \varnothing\}.$$

Proposition F.1 (aligned exactification yields an accepted exact cover). Let T be any split tree aligned with $\mathcal{H}^{\star}$. Then the family
$$\mathcal{C}_T^{=} := \left\{ \left(S(v), a_v, \pi_v^{=}\right) : v \in \mathrm{Live}(T) \right\}$$
together with the split-tree global payload from Appendix D is an accepted exact certified cover of D in the guard language $\mathfrak{L}_{\mathrm{grd}}$.

Proof. Appendix D proves exactly the three ingredients required by the cover definition from Appendix B.

1. By Theorem D.6 and Corollary D.7, every nonempty aligned leaf v carries an accepted exact certified cell
$$\left(S(v), a_v, \pi_v^{=}\right)$$
in the guard language.
2. By Lemma D.9, the split tree itself contributes a finite global cover payload proving that all leaf domains together cover D.
3. By the empty-leaf elimination step in Theorem D.11, empty leaves may be removed from the target family without changing the accepted cover statement.

After deleting the empty leaves, the remaining listed cells are precisely the live leaves, and the same accepted global cover derivation witnesses
$$D \subseteq \bigcup_{v \in \mathrm{Live}(T)} D_{S(v)}.$$
By the formal definitions in Appendix B, this is exactly an accepted exact certified cover. □

Corollary F.2 (exact-side upper bound from aligned exactification). For every split tree T aligned with $\mathcal{H}^\star$,

$$\mathrm{VAC}^{=}_{\mathfrak{L}_{\mathrm{grd}}}(g; D) \le |\operatorname{Live}(T)|.$$

In particular,

$$\mathrm{VAC}^{=}_{\mathfrak{L}_{\mathrm{grd}}}(g; D) < +\infty.$$

Proof. Proposition F.1 gives one accepted exact certified cover with exactly $|\operatorname{Live}(T)|$ listed cells. VAC is the minimum size of an accepted exact certified cover, so it cannot exceed the size of this particular one. Finiteness follows because Appendix D also proves the existence of a finite fully aligned split tree. □

Corollary F.3 (naive exact-side count bound). If $M := |\mathcal{H}^\star|$, then there exists an aligned split tree $T^\star$ such that

$$\mathrm{VAC}^{=}_{\mathfrak{L}_{\mathrm{grd}}}(g; D) \le |\operatorname{Live}(T^\star)| \le 2^M.$$

Proof. Appendix D, Corollary D.13, constructs a fully aligned split tree whose total number of leaves is at most 2^M. Every live leaf is one of those leaves, so

$$|\operatorname{Live}(T^\star)| \le 2^M.$$

Combining this with Corollary F.2 yields the claim. □

The point of Corollaries F.2–F.3 is structural existence, not optimality. The aligned exactification tree supplies *one* accepted exact cover. VAC measures the smallest accepted exact cover, which may be strictly smaller if several exact leaves can be merged into one verifier-accepted exact cell.

F.2 Exact-to-Threshold Transfer in Full Detail

We now formalize the transfer from exact certified covers to threshold certified covers.

Lemma F.4 (local threshold conversion from a nonempty exact cell). Let

$$\mathfrak{c} = (\gamma, a, \pi^{=})$$

be an accepted exact certified cell in a verifier-facing language $\mathfrak{L}$, and assume that $C(\gamma)$ is nonempty. If

$$\inf_{x \in C(\gamma)} g(x) \ge t,$$

then there exists a finite threshold payload $\pi^{\ge}_{\gamma,t}$ such that

$$(\gamma, \pi^{\ge}_{\gamma,t})$$

is an accepted threshold certified cell for threshold t.

Proof. Because $\mathfrak{c}$ is an accepted exact certified cell, the verifier accepts the local equality statement

$$g(x) = a(x) \qquad \forall x \in C(\gamma).$$

By the trusted-interface contract from Appendix A, AFFOPT can be invoked on the verifier-facing description $\mathfrak{D}(\gamma)$ and the affine function a. It returns a finite certificate proving the exact affine infimum

$$\mu_\gamma := \inf_{x \in C(\gamma)} a(x).$$

The hypothesis

$$\inf_{x \in C(\gamma)} g(x) \ge t$$

and the accepted exact equality imply

$$\mu_\gamma = \inf_{x \in C(\gamma)} a(x) = \inf_{x \in C(\gamma)} g(x) \ge t.$$

Therefore the concatenation of:

1. the already accepted exact local payload $\pi^{=}$,
2. the new affine-optimization certificate for μ_γ, and
3. the finite scalar check $\mu_\gamma \geq t$

forms a finite threshold payload proving

$$g(x) \geq t \qquad \forall x \in C(\gamma).$$

This is precisely an accepted threshold certified cell. No optimizer witness or attainment claim is needed for this conversion. □

Proposition F.5 (exact-to-threshold transfer). Fix any verifier-facing language $\mathfrak{L}$ and threshold $t \in \mathbb{R}$. Assume

$$\inf_{x \in D} g(x) \geq t.$$

If

$$\mathcal{C}^{=} = \{(\gamma_i, a_i, \pi_i^{=})\}_{i=1}^{N}$$

is an accepted exact certified cover of (g, D), then there exists an accepted threshold certified cover of (g, D, t) with at most N cells. Consequently,

$$\mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) \leq \mathrm{VAC}^{=}_{\mathfrak{L}}(g; D).$$

Proof. Appendix B shows that empty listed cells may be removed from an accepted cover without changing the cover statement. Hence we may first discard every exact cell with empty semantic domain and obtain an accepted exact certified cover

$$\widetilde{\mathcal{C}}^{=} = \{(\gamma_i, a_i, \pi_i^{=})\}_{i=1}^{N'}$$

with $N' \leq N$ and all $C(\gamma_i)$ nonempty.

Now fix one cell of $\widetilde{\mathcal{C}}^{=}$. Since

$$C(\gamma_i) \subseteq D$$

and the global hypothesis gives

$$\inf_{x \in D} g(x) \geq t,$$

we also have

$$\inf_{x \in C(\gamma_i)} g(x) \geq t.$$

Lemma F.4 therefore converts each nonempty exact cell

$$(\gamma_i, a_i, \pi_i^{=})$$

into an accepted threshold certified cell

$$(\gamma_i, \pi_{i,t}^{\geq}).$$

The global cover payload is unchanged, because the semantic cell descriptions γ_i themselves are unchanged. This conversion uses only the local exact equalities, the cellwise infimum certificates returned by AFFOPT, and the scalar checks $\mu_{\gamma_i} \geq t$; it does not require compactness or optimizer attainment. Thus the converted family

$$\widetilde{\mathcal{C}}^{\geq} := \{(\gamma_i, \pi_{i,t}^{\geq})\}_{i=1}^{N'}$$

forms an accepted threshold certified cover of size $N' \leq N$. Minimizing over exact certified covers gives the VAC inequality. □

Corollary F.6 (guard-language threshold finiteness under a true threshold claim). Let g be the output of an allowed CPWL expression graph over nonempty compact domain D, and let T be any split tree aligned with $\mathcal{H}^\star$. If

$$\inf_{x \in D} g(x) \geq t,$$

then

$$\mathrm{VAC}^{\geq}_{\mathfrak{L}_{\mathrm{grd}}}(g; D, t) \leq \mathrm{VAC}^{=}_{\mathfrak{L}_{\mathrm{grd}}}(g; D) \leq |\,\mathrm{Live}(T)|.$$

Proof. The second inequality is Corollary F.2. The first is Proposition F.5 applied to the exact certified cover supplied by Proposition F.1. □

F.3 Incompatibility-Graph Lower Bounds

We now turn to the lower-bound side. Fix again a verifier-facing language $\mathfrak{L}$ and threshold t. For a finite witness set

$$X = \{x_1, \dots, x_m\} \subseteq D,$$

let

$$G_t^{\mathrm{inc}}(X)$$

be the threshold incompatibility graph defined in Section 5.

Lemma F.7 (every threshold cell induces an independent set). Let

$$(\gamma, \pi^{\geq})$$

be any accepted threshold certified cell. Then the vertex subset

$$X \cap C(\gamma)$$

is an independent set of $G_t^{\mathrm{inc}}(X)$.

Proof. Suppose two vertices $x_i, x_j \in X \cap C(\gamma)$ were adjacent in $G_t^{\mathrm{inc}}(X)$. By definition of the incompatibility graph, this would mean that x_i and x_j are threshold-incompatible: no single accepted threshold certified cell can contain them both. But the cell $(\gamma, \pi^{\geq})$ does contain them both, since both belong to $C(\gamma)$. This contradiction shows that no adjacent pair can occur inside $X \cap C(\gamma)$, so that subset is independent. □

Lemma F.8 (independent-set cover number equals chromatic number). For every finite graph $G = (V, E)$, the minimum number of independent sets whose union covers V equals $\chi(G)$.

Proof. Any proper coloring of G with k colors partitions V into k color classes, and each color class is an independent set. Therefore the minimum number of independent sets needed to cover V is at most $\chi(G)$.

Conversely, suppose

$$V \subseteq I_1 \cup \cdots \cup I_k$$

where each I_j is an independent set. Assign to each vertex $v \in V$ the smallest index j such that $v \in I_j$. If two adjacent vertices received the same color j, then both would lie in the independent set I_j, which is impossible. Hence this assignment is a proper k-coloring of G, so

$$\chi(G) \leq k.$$

Taking the minimum over all independent-set covers gives equality. □

Theorem F.9 (chromatic-number lower bound). For every finite witness set $X \subseteq D$,

$$\mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) \geq \chi\big(G_t^{\mathrm{inc}}(X)\big).$$

Proof. Take any accepted threshold certified cover

$$\mathcal{C}^{\geq} = \{(\gamma_i, \pi_i^{\geq})\}_{i=1}^{N}.$$

For each listed cell define

$$I_i := X \cap C(\gamma_i).$$

By Lemma F.7, every I_i is an independent set of $G_t^{\mathrm{inc}}(X)$. Because the cover is global,

$$D \subseteq \bigcup_{i=1}^{N} C(\gamma_i),$$

so in particular every vertex of X belongs to at least one I_i. Thus

$$X \subseteq \bigcup_{i=1}^{N} I_i,$$

meaning that the vertex set of the incompatibility graph is covered by N independent sets. By Lemma F.8, this implies

$$N \geq \chi\big(G_t^{\mathrm{inc}}(X)\big).$$

Since the argument applies to every accepted threshold certified cover, the minimum cover size satisfies the same inequality. □

Corollary F.10 (clique lower bound). For every finite witness set $X \subseteq D$,

$$\mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) \geq \omega\big(G_t^{\mathrm{inc}}(X)\big),$$

where ω denotes clique number.

Proof. Every finite graph satisfies

$$\chi(G) \geq \omega(G).$$

Applying this to Theorem F.9 gives the claim. □

Corollary F.11 (pairwise incompatibility). If there exist points $x_1, \ldots, x_m \in D$ that are pairwise threshold-incompatible, then

$$\mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) \geq m.$$

Proof. The corresponding incompatibility graph contains a clique on those m vertices, so Corollary F.10 applies. □

F.4 Technical Boundary Cases and When Threshold VAC Is Infinite

The upper- and lower-bound theorems above sit on a simple but important semantic boundary. Exact-side finiteness is a structural theorem for the CPWL class considered here. Threshold-side finiteness is not structural in the same unconditional sense: it is constrained first by the truth of the threshold claim and then by the expressive power of the chosen verifier-facing language.

Proposition F.12 (false threshold claims force infinite threshold VAC). If

$$\inf_{x \in D} g(x) < t,$$

then for every verifier-facing language $\mathfrak{L}$,

$$\mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) = +\infty.$$

Proof. Assume for contradiction that there exists a finite accepted threshold certified cover

$$\mathcal{C}^{\geq} = \{(\gamma_i, \pi_i^{\geq})\}_{i=1}^{N}.$$

By local threshold soundness, every accepted listed cell satisfies

$$g(x) \geq t \qquad \forall x \in C(\gamma_i).$$

Because the cover is global,

$$D \subseteq \bigcup_{i=1}^{N} C(\gamma_i),$$

it follows that

$$g(x) \geq t \qquad \forall x \in D.$$

Hence

$$\inf_{x \in D} g(x) \geq t,$$

contradicting the hypothesis. Therefore no finite threshold certified cover exists, and by definition threshold VAC is $+\infty$. □

Remark F.13 (truth of the threshold claim alone does not force finiteness in an arbitrary language). The converse to Proposition F.12 is false in general. Even if

$$\inf_{x \in D} g(x) \geq t,$$

a very weak verifier-facing language may simply fail to admit any finite threshold certified cover. Thus the correct statement is not

$$\inf_{D} g \geq t \iff \mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) < +\infty$$

for every $\mathfrak{L}$. Rather:

- the implication
$$\mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) < +\infty \Longrightarrow \inf_{D} g \geq t$$
always holds by Proposition F.12;
- the reverse implication requires an additional representability statement for the chosen language.

For the CPWL guard language studied in this paper, that representability statement is supplied by guard-certified exactification together with exact-to-threshold transfer.

Remark F.14 (witness-set lower bounds are finite shadows of a possibly infinite cover problem). For every finite witness set X, the chromatic lower bound of Theorem F.9 is finite because $G_t^{\mathrm{inc}}(X)$ is a finite graph. When Proposition F.12 applies, these finite graph bounds remain true but become only finite shadows of the full semantic obstruction:

$$\chi\big(G_t^{\mathrm{inc}}(X)\big) \leq \mathrm{VAC}^{\geq}_{\mathfrak{L}}(g; D, t) = +\infty.$$

This is why incompatibility graphs are best understood as verifier-aligned lower-bound templates, not as complete characterizations of threshold VAC.

Remark F.15 (cell-complete proof languages inherit the same quantitative bounds). Appendix E proves that, on either side, every c-cell-complete proof language realizes VAC up to the fixed realization constant c. Therefore every upper bound and lower bound in this appendix immediately transfers to minimum proof size in any such language, with only the syntax-dependent constant-factor change already isolated in Appendix E.

This completes the full proof package behind Section 5. The exact side is finite because aligned exactification already produces accepted exact covers; the threshold side can be obtained from the exact side when the threshold claim is true; and lower bounds arise from the purely semantic fact that one accepted threshold cell can certify only an independent set of witness points in the incompatibility graph.

G Hardness Reductions, Approximation Barrier, and Boundary Cases

This appendix expands Section 6. The main text isolates a deliberately narrow algorithmic question: once a finite pool of verifier-visible candidate cells has *already* been exposed, how hard is it to choose a smallest accepted subcover? The answer is that unrestricted explicit-dictionary selection already contains the full combinatorial hardness of SET COVER. Here we give the full reductions, record optimum preservation on both the exact and threshold sides, transfer the classical logarithmic approximation barrier, and make the boundary cases explicit.

The scope is intentionally precise. We do *not* claim here that unrestricted semantic VAC over an arbitrary continuous verifier language is itself presented as an NP-complete decision problem. Instead, we isolate the more robust statement that the finite-dictionary decision problems are already NP-complete, and that the corresponding optimization problems are already hard, even when every local validity condition can be re-checked by direct pointwise inspection.

Throughout, all numerical inputs are rational and encoded in binary. In particular, the point domain

$$U = \{u_1, \ldots, u_N\} \subseteq \mathbb{Q}^n$$

and the value table

$$\{g(u_i)\}_{i=1}^{N} \subseteq \mathbb{Q}$$

are explicit parts of the input. We write

$$\mathrm{OPT}_{\mathrm{SC}}(\mathcal{U}, \mathcal{S})$$

for the optimum of a set-cover instance with universe $\mathcal{U}$ and family $\mathcal{S}$.

G.1 Finite-Dictionary Problems and Explicit Verification

We first restate the two dictionary-restricted decision problems together with their associated optimization problems in fully explicit form.

Exact-side dictionary problem. An instance of EXACT-VAC-DICT consists of:

1. a finite rational point set
$$U = \{u_1, \ldots, u_N\} \subseteq \mathbb{Q}^n;$$
2. an explicit value table $\{g(u_i)\}_{i=1}^{N}$;
3. a finite dictionary
$$\mathcal{D}_= = \{\eta_1, \ldots, \eta_m\}, \qquad \eta_j = (A_j, a_j),$$
where $A_j \subseteq U$ is explicitly listed and a_j is an affine function with rational coefficients;
4. a budget $k \in \mathbb{N}$.

A dictionary entry $\eta_j = (A_j, a_j)$ is *valid* if

$$g(u) = a_j(u) \qquad \forall u \in A_j.$$

The decision problem asks whether there exists an index set

$$J \subseteq \{1, \ldots, m\}, \qquad |J| \le k,$$

such that every selected entry is valid and

$$U \subseteq \bigcup_{j \in J} A_j.$$

The associated optimization problem minimizes the number of selected valid entries and is denoted

$$\mathrm{OPT}_=(U, \mathcal{D}_=).$$

Threshold-side dictionary problem. An instance of THRESH-VAC-DICT consists of the same finite rational point set U, the same explicit value table, a rational threshold t, a finite dictionary

$$\mathcal{D}_\ge = \{A_1, \ldots, A_m\}, \qquad A_j \subseteq U,$$

and a budget $k \in \mathbb{N}$. A dictionary entry A_j is *valid* if

$$g(u) \ge t \qquad \forall u \in A_j.$$

The decision problem asks whether there exists

$$J \subseteq \{1, \ldots, m\}, \qquad |J| \le k,$$

such that every selected entry is valid and

$$U \subseteq \bigcup_{j \in J} A_j.$$

Its optimization value is written

$$\mathrm{OPT}_\ge(U, \mathcal{D}_\ge, t).$$

These two problems are the cleanest dictionary-restricted versions of verifier-aligned cover selection. All candidate local proof units are already explicit. The remaining tasks are the decision question of whether a budget-k accepted subcover exists and the associated optimization question of choosing a smallest accepted subcover.

Proposition G.1 (Both dictionary problems belong to NP). EXACT-VAC-DICT and THRESH-VAC-DICT are both in NP.

Proof. For EXACT-VAC-DICT, a witness is the chosen index set

$$J \subseteq \{1, \ldots, m\}.$$

The verifier checks in polynomial time that $|J| \leq k$, that for every selected entry $\eta_j = (A_j, a_j)$ and every $u \in A_j$ one has

$$g(u) = a_j(u),$$

and that the selected subsets cover all of U. Since the point set, the value table, and the affine coefficients are explicit rational data, every arithmetic comparison is polynomial-time in the total input length.

For THRESH-VAC-DICT, the same witness format works. The verifier checks $|J| \leq k$, checks for every selected subset A_j and every $u \in A_j$ that

$$g(u) \geq t,$$

and then checks that the selected subsets cover all of U. This is again polynomial-time. Hence both problems lie in NP. □

G.2 Optimum-Preserving Reduction to EXACT-VAC-DICT

Fix an arbitrary SET COVER instance

$$(\mathcal{U}, \mathcal{S}, k), \qquad \mathcal{U} = \{e_1, \ldots, e_N\}, \qquad \mathcal{S} = \{S_1, \ldots, S_m\}.$$

We construct an instance of EXACT-VAC-DICT in polynomial time as follows.

1. Set the ambient dimension to $n = 1$.
2. Encode each universe element e_i by the rational point

   $$u_i := i \in \mathbb{Q}.$$

   Thus

   $$U := \{u_1, \ldots, u_N\} \subseteq \mathbb{Q}.$$
3. Define the target values by the constant table

   $$g(u_i) := 0 \qquad (1 \leq i \leq N).$$
4. For every set $S_j \in \mathcal{S}$, create one exact dictionary entry

   $$\eta_j = (A_j, a_j), \qquad A_j := \{u_i : e_i \in S_j\}, \qquad a_j(x) := 0.$$
5. Keep the same budget k.

Call the resulting exact-side instance

$$I_=(U, g, \mathcal{D}_=, k).$$

Lemma G.2 (All constructed exact entries are valid). Every dictionary entry $\eta_j = (A_j, a_j)$ in $I_=$ is valid.

Proof. For every $u \in A_j$ we have, by construction,

$$g(u) = 0 = a_j(u).$$

Thus each entry satisfies the exact-side validity condition. □

Lemma G.3 (YES/NO equivalence for the exact-side reduction). The original set-cover instance $(\mathcal{U}, \mathcal{S}, k)$ is a YES instance if and only if the constructed exact-side instance $I_=$ is a YES instance.

Proof. Assume first that $(\mathcal{U}, \mathcal{S}, k)$ is a YES instance. Then some index set

$$J \subseteq \{1, \ldots, m\}, \qquad |J| \leq k,$$

satisfies

$$\mathcal{U} \subseteq \bigcup_{j \in J} S_j.$$

By Lemma G.2 all selected exact entries are valid. To show exact-side coverage, take any encoded point $u_i \in U$. Since the corresponding element e_i lies in some selected set S_j, the point u_i lies in the corresponding subset A_j. Hence

$$U \subseteq \bigcup_{j \in J} A_j,$$

so $I_=$ is a YES instance.

Conversely, suppose $I_=$ is a YES instance. Then some index set

$$J \subseteq \{1, \ldots, m\}, \qquad |J| \leq k,$$

selects valid entries and satisfies

$$U \subseteq \bigcup_{j \in J} A_j.$$

Take any universe element $e_i \in \mathcal{U}$. Its encoded point u_i belongs to U, so coverage implies that $u_i \in A_j$ for some selected $j \in J$. By the definition of A_j, this is equivalent to $e_i \in S_j$. Hence every universe element is covered by the selected sets, so $(\mathcal{U}, \mathcal{S}, k)$ is also a YES instance. □

Lemma G.4 (Optimum preservation on the exact side). For the reduction above,

$$\mathrm{OPT}_=(U, \mathcal{D}_=) = \mathrm{OPT}_{\mathrm{SC}}(\mathcal{U}, \mathcal{S}).$$

Proof. The reduction preserves the chosen index set exactly: selecting the subfamily $\{S_j : j \in J\}$ in the set-cover instance corresponds to selecting the exact dictionary entries indexed by the same J, and vice versa. Lemma G.3 shows that cover feasibility is preserved in both directions, and the cardinality of the selected family is unchanged. Therefore the optimal values are equal. □

G.3 Optimum-Preserving Reduction to THRESH-VAC-DICT

We now use the same set-cover instance

$$(\mathcal{U}, \mathcal{S}, k), \qquad \mathcal{U} = \{e_1, \ldots, e_N\}, \qquad \mathcal{S} = \{S_1, \ldots, S_m\},$$

and build a threshold-side dictionary instance.

1. Reuse the rational point encoding
$$U = \{u_1, \ldots, u_N\} \subseteq \mathbb{Q}, \qquad u_i := i.$$
2. Reuse the constant value table
$$g(u_i) := 0 \qquad (1 \leq i \leq N).$$
3. Fix the threshold
$$t := 0.$$
4. For each set $S_j \in \mathcal{S}$, create one threshold dictionary entry
$$A_j := \{u_i : e_i \in S_j\}.$$
5. Keep the same budget k.

Call the resulting threshold-side instance

$$I_\geq = (U, g, t, \mathcal{D}_\geq, k).$$

Lemma G.5 (All constructed threshold entries are valid). Every threshold dictionary entry A_j in $I_\geq$ is valid.

Proof. For every $u \in A_j$ we have, by construction,

$$g(u) = 0 \geq 0 = t.$$

Hence each threshold entry is valid. □

Lemma G.6 (YES/NO equivalence for the threshold-side reduction). The original set-cover instance $(\mathcal{U}, \mathcal{S}, k)$ is a YES instance if and only if the constructed threshold-side instance $I_{\geq}$ is a YES instance.

Proof. If the selected sets indexed by J cover $\mathcal{U}$, then the corresponding subsets A_j cover U by the same point-encoding argument as in Lemma G.3, and all selected threshold entries are valid by Lemma G.5. Hence $I_{\geq}$ is a YES instance.

Conversely, if the selected threshold entries indexed by J cover U, then for every encoded point u_i there exists some selected A_j containing it. By construction this means $e_i \in S_j$, so the corresponding selected sets cover all of $\mathcal{U}$. Thus the original set-cover instance is a YES instance. □

Lemma G.7 (Optimum preservation on the threshold side). For the reduction above,

$$\mathrm{OPT}_{\geq}(U, \mathcal{D}_{\geq}, 0) = \mathrm{OPT}_{\mathrm{SC}}(\mathcal{U}, \mathcal{S}).$$

Proof. Exactly as on the exact side, the reduction preserves the chosen index set and its size. Lemma G.6 gives feasibility preservation in both directions. Hence the optimum values agree. □

G.4 NP-Completeness and Approximation Barrier

The full decision theorem from Section 6 is now immediate.

Theorem G.8 (NP-completeness of explicit-dictionary selection). The decision problems EXACT-VAC-DICT and THRESH-VAC-DICT are NP-complete.

Proof. By Proposition G.1, both problems lie in NP. Lemma G.3 gives a polynomial-time reduction from SET COVER to EXACT-VAC-DICT, and Lemma G.6 gives a polynomial-time reduction from SET COVER to THRESH-VAC-DICT. Hence both dictionary-restricted decision problems are NP-hard. Combining NP-hardness with Proposition G.1 yields NP-completeness. □

The structure of the reduction matters. The target function is constant, the threshold is constant, and every local dictionary entry is automatically valid. Therefore the hardness does *not* come from local symbolic verification. It comes entirely from the combinatorics of selecting a smallest accepted subcover.

Lemma G.9 (Approximation-preserving transfer). Let $\rho : \mathbb{N} \to [1, \infty)$ be any function.

1. If there exists a polynomial-time $\rho(N)$-approximation algorithm for EXACT-VAC-DICT, then there exists a polynomial-time $\rho(N)$-approximation algorithm for SET COVER.
2. If there exists a polynomial-time $\rho(N)$-approximation algorithm for THRESH-VAC-DICT, then there exists a polynomial-time $\rho(N)$-approximation algorithm for SET COVER.

Here N denotes the size of the universe of the original set-cover instance, equivalently the size of the encoded point domain U.

Proof. We prove the exact-side statement; the threshold-side proof is identical.

Assume there is a polynomial-time algorithm $\mathcal{A}_{=}$ that, on every exact dictionary instance with $|U| = N$, returns a valid subcover of size at most

$$\rho(N)\ \mathrm{OPT}_{=}(U, \mathcal{D}_{=}).$$

Given a set-cover instance $(\mathcal{U}, \mathcal{S})$ with $|\mathcal{U}| = N$, form the exact-side dictionary instance $I_{=}$ by the reduction above and run $\mathcal{A}_{=}$ on it. Let J be the returned index set. Mapping J back to the set family

$$\{S_j : j \in J\} \subseteq \mathcal{S}$$

produces a set cover of $\mathcal{U}$ by Lemma G.3. Moreover,

$$|J| \le \rho(N)\ \mathrm{OPT}_{=}(U, \mathcal{D}_{=}) = \rho(N)\ \mathrm{OPT}_{\mathrm{SC}}(\mathcal{U}, \mathcal{S}),$$

where the equality is Lemma G.4. Hence we obtain a polynomial-time $\rho(N)$-approximation for SET COVER. The threshold-side statement follows from the same argument using Lemma G.7. □

Corollary G.10 (Logarithmic approximation barrier for explicit-dictionary minimization). For every fixed $\varepsilon \in (0, 1)$, unless $\mathrm{P} = \mathrm{NP}$, there is no polynomial-time algorithm that approximates either

$$\mathrm{OPT}_{=}(U, \mathcal{D}_{=}) \qquad \text{or} \qquad \mathrm{OPT}_{\ge}(U, \mathcal{D}_{\ge}, t)$$

within factor

$$(1 - \varepsilon) \ln N, \qquad N := |U|.$$

Proof. The classical logarithmic approximation barrier for SET COVER goes back to Feige [12], and the fixed-ε hardness form used in Section 6 is given by Dinur and Steurer [8]. If either associated dictionary-restricted optimization problem admitted a polynomial-time $(1 - \varepsilon) \ln N$ approximation, Lemma G.9 would transfer the same guarantee to SET COVER, contradicting those lower bounds. □

This is the natural approximation scale for classical cover minimization within the unrestricted explicit-dictionary model. Thus the selection layer is not a benign post-processing step after candidate generation; even after candidate cells are explicit, it already inherits the standard logarithmic barrier of set-family optimization.

G.5 Boundary Cases and Scope Clarifications

We close by recording exactly what the appendix establishes and what it does not.

Proposition G.11 (Threshold-side hardness already holds on the true-claim subclass). Restrict THRESH-VAC-DICT to instances satisfying

$$\inf_{u \in U} g(u) \ge t.$$

The restricted decision and optimization problems remain NP-hard, and the optimum-preserving reduction above still applies.

Proof. In every reduced threshold instance $I_{\ge}$ we set

$$g \equiv 0 \qquad \text{on } U, \qquad t = 0.$$

Hence

$$\inf_{u \in U} g(u) = 0 = t.$$

So the reduction lands entirely inside the subclass where the global threshold claim is true. Lemmas G.6–G.7 therefore already prove NP-hardness and optimum preservation on that restricted subclass. □

This clarifies an important boundary case. On the threshold side, false claims automatically force semantic threshold VAC to be $+\infty$ by Proposition F.12 of Appendix F. The hardness result here is not exploiting that trivial obstruction; it survives on the much smaller subclass where the threshold claim itself is globally true.

Proposition G.12 (Trivial conventions and redundant entries). For both dictionary problems:

1. if $U = \varnothing$, then the optimum value is 0;
2. deleting an invalid dictionary entry does not change the optimum value;
3. deleting an empty dictionary entry does not increase the optimum value;
4. deleting a duplicate copy of an already-present valid entry does not increase the optimum value.

Proof. If $U = \varnothing$, the empty subfamily already covers the domain, so the optimum is 0. An invalid entry can never appear in a feasible solution by definition, hence deleting it does not change feasibility or the optimum. An empty entry covers no points, so deleting it cannot remove any feasible cover. A duplicate valid entry contributes the same subset as an existing one, so retaining one copy is always as good as retaining both. □

Thus the NP-hardness statement is not an artifact of pathological dictionary encodings. It persists after the obvious syntactic cleanup operations.

(i) The hardness is dictionary-restricted. The input already contains the full finite candidate pool. No claim is made here about the unrestricted decision complexity of semantic VAC over arbitrary infinite continuous languages.

(ii) The hardness is purely combinatorial. In the constructed instances, local validity is trivial:

$$g \equiv 0, \qquad a_j \equiv 0, \qquad t = 0.$$

Hence the obstruction comes entirely from selecting a smallest accepted subcover, not from generating cells or proving local soundness.

(iii) What the reduction proves unconditionally. The reduction proves hardness for the unrestricted explicit-dictionary selection problem: the input already contains the full finite candidate family, and the only remaining task is to choose a smallest accepted subcover.

Definition G.13 (Pipeline-exposed dictionary class). Fix a family Π of proof-producing mechanisms. For each verification instance I, let $\mathcal{D}_\Pi(I)$ denote the finite dictionary of verifier-visible candidate cells exposed by Π before any cover-minimization step. The exposed dictionary class of Π is

$$\mathfrak{C}_\Pi := \{\mathcal{D}_\Pi(I) : I \in \mathcal{I}_\Pi\},$$

where $\mathcal{I}_\Pi$ is the instance family on which Π is defined.

Definition G.14 (Set-cover-rich exposed family class). We say that Π is *set-cover-rich* if there is a polynomial-time mapping from every set-cover instance $(\mathcal{U}, \mathcal{S}, k)$ to a verification instance I such that feasible accepted subcovers of $\mathcal{D}_\Pi(I)$ correspond to set covers of $(\mathcal{U}, \mathcal{S})$. If the correspondence preserves optimum cardinality, we say that the realization is *optimum-preserving*.

Theorem G.15 (Conditional transfer to concrete pipelines). Let Π be a proof-producing mechanism whose exposed dictionary class is set-cover-rich. Then the induced selection problem over dictionaries in $\mathfrak{C}_\Pi$ is NP-hard. If the realizing map is optimum-preserving, then the logarithmic inapproximability barrier of Corollary G.10 transfers as well.

Proof sketch. Compose the classical set-cover reduction used above with the realizing map into $\mathfrak{C}_\Pi$. By hypothesis, feasible accepted subcovers correspond to set covers, and in the optimum-preserving case the optimum values coincide. NP-hardness and logarithmic inapproximability therefore transfer directly. □

Remark G.16 (Why the richness hypothesis cannot be dropped). Without a representability hypothesis, no generic transfer from unrestricted explicit dictionaries to arbitrary pipeline-generated candidate pools is valid. A concrete pipeline may expose only a highly structured class of candidate families, and within such classes minimum-cover problems can be substantially easier than general set cover. The present appendix therefore proves unconditional hardness only for unrestricted explicit dictionaries. Characterizing which pipeline-generated family classes are set-cover-rich, and which admit polynomial-time minimization, is a natural open problem beyond the scope of the present paper.

(iv) Relation to the proof-language layer. Section 4 shows that, once a concrete syntax realizes semantic covers with only constant-factor leaf overhead, minimum leaf count tracks the corresponding semantic selection problem up to that fixed realization factor. Combined with the results above, this identifies a genuine combinatorial complexity source at the explicit-dictionary selection layer.

Transfer to any particular proof pipeline, however, requires that the exposed candidate-family class satisfy an additional representability hypothesis such as Theorem G.15.

In that precise sense, Section 6 is about *selection-layer hardness*, and this appendix supplies the full reductions behind that claim.

H Related Work

This appendix expands the positioning sketched in Section 1. The organizing principle is the layer used for comparison. Much of the neural-network verification literature is naturally solver-centered, geometry-centered, or proof-format-centered. Our paper instead studies a proof-centered semantic cover layer, defined only after fixing a verifier-facing language: one counts verifier-visible local certified cells together with an accepted global cover, and then compares proof languages by the overhead with which they realize that layer. The point of this appendix is therefore not simply to list neighboring topics, but to make explicit where the present work sits relative to them.

H.1 Field Positioning and Solver-Centered Verification

Broad surveys and taxonomies usually organize neural-network verification by solver family or algorithmic workflow. Representative references include the survey of Liu et al. [19], the unified CPWL-verification view of Bunel et al. [1], and the more recent programming-languages positioning of Cordeiro et al. [6]. These works are important context for the present paper because they clarify the dominant categories in the field: SMT, mixed-integer optimization, branch-and-bound, relaxation, propagation, and reachability. Our paper agrees that these distinctions matter algorithmically, but asks a different question: once a proof-producing pipeline is in place, what is the semantic size of the proof object that the trusted verifier must actually consume?

That question is deliberately orthogonal to the main complete-verification lines. Classical SMT-style and phase-search methods for CPWL networks include Reluplex and the work of Ehlers [17, 11]. Mixed-integer formulations provide another exact route, represented by Tjeng et al. [30]. Branch-and-bound and relaxation-guided complete verification have since become a major line of development, with representative systems and analyses in [2, 33, 13, 32, 35, 27, 3]. These works typically measure difficulty through runtime, branching quality, relaxation strength, node counts, or encoding size. By contrast, our VAC formalism abstracts away from the internal search trace and counts verifier-accepted local cells instead.

A similar contrast applies to propagation, abstract-interpretation, and reachability-based verification. Symbolic interval analysis, abstract interpretation, abstract domains, linear bound propagation, and reachable-set tools all produce certified information, but the natural performance proxies in those literatures remain bound tightness, propagation cost, refinement behavior, or set representation size rather than the semantic size of the final proof object [31, 15, 29, 34, 21]. Framework papers such as Marabou and DNNV are also highly relevant because they make tool-chain decomposition explicit: they separate network representation, property language, solver backend, and proof or checking infrastructure [18, 28]. Our paper can be read as pushing that decomposition one step further by asking what the trusted backend ought to count.

In this sense, the present work is not a competing solver architecture. Sections 2 through 5 aim to define a quantity that can sit above many solver families. Different verifiers may expose different candidate cells, different proof languages, or different local payload schemas, but the semantic question remains the same: how many verifier-visible local units are needed before the global statement can be accepted?

H.2 Proof Production, Proof Checking, and Certificate Reuse

The closest line in spirit is proof-producing neural verification. Isac et al. [16] show how a verifier can emit independently checkable proof artifacts rather than only final verdicts. Fischer et al. [14] study how certificates can be shared across related verification instances. More recent work studies certified proof checking inside theorem-proving environments [7], cross-tool proof formats and proof checkers [9], and compositional assume-guarantee reasoning for neural verification [10].

Our contribution is complementary to this literature. Those works ask how to produce, represent, exchange, certify, or reuse proofs. We ask what the semantic size of a proof should be once one looks only at verifier-accepted local units. This is why Section 4 separates VAC from proof syntax: within a fixed verifier-facing language, VAC is the semantic cover quantity; SCC is the size of a particular cell-complete proof-language realization; and DL is its encoding length. Put differently, proof production and proof checking make verifier-visible proof objects possible; our paper studies the complexity of those objects after the verifier interface has been fixed.

This distinction also explains why the current paper is language-relative without being syntax-first. APTP-style or theorem-prover-style proof formats are important realizations, but the present paper does not argue that one such format is fundamental. Instead, after fixing the verifier-facing language, it treats the accepted local cell as the semantic proof unit and compares proof languages by how efficiently they realize covers of such units. That is exactly the role played by the cell-complete realization theorems in Section 4.

H.3 CPWL Geometry, Linear Regions, and Exact Abstraction

A second nearby literature studies the geometry and expressive power of piecewise-linear networks through linear regions and related decompositions [23, 25, 26]. These papers are indispensable background because they explain why CPWL models admit finite hyperplane structure at all. However, they do not by themselves define proof complexity. A verifier-admissible exact cell may be coarser than a geometric region, finer than a geometric region, or overlapping in ways that arrangement cells do not capture. On the threshold side, a proof may not need to reconstruct the full arrangement at all. This is why Section 4 treats arrangement count only as a restricted exact-side degeneration under connectedness and language-realizability assumptions, rather than as the semantic cover quantity of the theory.

More closely related are works on abstraction with locally exact structure or exact refinement. Manino et al. [22] study global abstractions with locally exact reconstruction, and Liu et al. [20] develop abstraction-refinement schemes aimed at scalable exact verification. These works are adjacent to our guard-certified exactification results because they also take seriously the idea that local exact structure can be the right bridge between continuous semantics and verifiable reasoning. The difference is in the role played by that local structure. In our paper, exactification is not introduced as another heuristic verification strategy; it is a structural theorem for the CPWL expression graphs under study. Section 3 uses it to prove the existence of finite accepted exact certified covers, and Section 5 then turns that existence result into exact-side upper bounds for a verifier-aligned proof-complexity quantity.

The same distinction matters for candidate generation versus cover complexity. Abstraction and refinement papers often have to solve both problems simultaneously: how to generate good local candidates, and how to reason over them. Our dictionary-hardness results in Section 6 intentionally isolate only the explicit-dictionary selection layer. Once a finite candidate pool of verifier-visible cells has already been exposed as an unrestricted explicit dictionary, selecting a smallest accepted subcover is set-cover hard; transfer of that hardness to any particular pipeline-generated family requires additional representability assumptions.

H.4 Classical Lineage: Proof Complexity, Trusted Checking, and PL Views of Verification

The broader theoretical lineage comes from proof complexity, model checking, and small trusted kernels. Cook and Reckhow's classical separation between semantic proof content and the overhead of a concrete proof system is the clearest ancestor of our VAC/SCC/DL split [5]. Model checking provides the paradigm of local facts plus global composition under a small trusted checker [4]. Proof-carrying code makes the same architectural point in a different domain: trust the small checker and the carried proof, not the whole analyzer that found it [24]. The recent PL-oriented positioning of neural-network verification in [6] is especially close in spirit to our own framing.

The present paper imports these ideas into CPWL neural verification in a concrete way. Section 2 fixes a deliberately small verifier interface. Section 3 shows that CPWL expression graphs admit verifier-accepted local exact cells after guard-certified exactification. Section 4 then separates language-relative semantic cover complexity from the size of any specific proof language, and Sections 5 and 6 study quantitative bounds and minimization hardness for that semantic quantity. In

that sense, the paper is neither proposing a new solver proxy nor rebranding arrangement count. It is proposing a proof-centered complexity language for what a trusted verifier must actually accept.

Taken together, these literatures explain both the motivation and the limits of our claims. We build on solver-centered verification, proof-producing infrastructures, CPWL geometry, and classical proof-complexity ideas. But the central thesis of the paper is that none of solver trace length, region count, or a particular proof syntax is the fixed-language semantic cover quantity. After fixing the verifier-facing interface, the relevant comparison object is the verifier-visible local certified cell and the accepted cover built from such cells.

I Experimental Results

This appendix collects the full experimental evidence that complements the main-text summary. The reporting principle matches the theory developed in Sections 3–6: we emphasize verifier-facing cover quantities rather than solver-trace proxies. Outside the Gold Tiny exhaustive suite, the experiments do not claim ground-truth VAC values. Instead, on the exact side we report accepted exactification upper bounds $U_{\mathrm{eq}}^{\mathrm{align}}$ together with dictionary-restricted optima over the exposed exact candidate language; on the threshold side we report transfer upper bounds $U_{\geq}^{\mathrm{transfer}}$, dictionary-restricted optima over the bounded exposed threshold language implemented in the v3 pipeline, and exposed lower bounds. Realization metrics are split into compact/core payloads and full archive bundles.

The saved v3 paper bundle covers 126 exact-side instances, 126 canonical true-threshold rows, 126 false-control rows, 102 threshold-stage rows on a curated threshold subset, 120 selection-stage rows on a curated selection subset, and 126 realization measurements. Across the false-control rows, no finite accepted threshold cover appears. The figures below are generated directly from the saved bundle and are intended to make the experiment section load-bearing while keeping the main text compact.

I.1 Gold Tiny Calibration and Scope

Gold Tiny is the only suite in the current artifact for which true $\mathrm{VAC}^{=}$ and true $\mathrm{VAC}^{\geq}$ are computed exhaustively. It therefore plays a calibration role rather than a scaling role. Figure I.1 should be read first. On the exact side, five of the six tiny cases collapse to the same value across arrangement count, true guard-language $\mathrm{VAC}^{=}$, exposed exact optimum, and accepted exactification upper bound. The lone intended exception is the maxout example, where arrangement count, true exact VAC, and accepted exactification upper bound separate. This is precisely the type of gap the paper's semantic viewpoint predicts: arrangement geometry, semantic cover size, and constructive exactification upper bounds need not coincide.

The threshold panel is equally important for scope. In the Gold Tiny exhaustive rows, the true guard-language threshold VAC is 1 on every canonical true task, but the exposed threshold optimum can still be strictly larger because the bounded exposed threshold language implemented by the artifact is not the same object as the full guard language. Thus the Gold Tiny suite calibrates both halves of the experimental story: exact-side upper bounds are genuine verifier-facing upper bounds, while threshold-side exposed metrics remain language-relative by design.



Figure I.1: Gold Tiny exhaustive calibration. Panel (a) compares arrangement count, true exact VAC in the guard language, the exposed exact optimum, and the accepted exactification upper bound. Five of the six tiny cases coincide on the exact side; the maxout case exhibits the intended separation *arrangement count* $<$ *true exact VAC* $<$ *exactification upper bound*. Panel (b) compares true guard-language threshold VAC, the exposed lower bound, the exposed threshold optimum, and the transfer upper bound on canonical true-threshold tasks. This panel should be read as a language-calibration plot: exposed threshold quantities need not equal the true guard-language threshold VAC even on the tiny exhaustive suite.



Figure I.2: Exactification scaling across the full benchmark suite. Each point is one saved exact-side row. The dashed curve is the crude 2^H envelope. Accepted exact upper bounds grow with H, but remain far below the envelope on the shipped paper-facing bundle.

I.2 Exact-Side Exactification and Compression

Figure I.2 summarizes the constructive exactification upper bounds across the full benchmark suite. The accepted exact upper bound $U_{\mathrm{eq}}^{\mathrm{align}}$ grows with the number $H = |\mathcal{H}^\star|$ of compiled comparison hyperplanes, but on the saved bundle it stays well below the crude 2^H envelope. This is the main empirical counterpart of the finite exactification theorem: the theorem only guarantees a finite aligned split-tree upper bound, while the artifact shows that the realized upper bounds are much smaller than the coarsest combinatorial envelope on the benchmark families shipped here.

Figure I.3 complements the scaling view with a compression view. The compression factor is

$$\frac{U_{\mathrm{eq}}^{\mathrm{align}}}{\mathrm{OPT}_{\mathrm{eq}}^{\mathrm{exposed}}}.$$

For Family A, Family B, and ThresholdStress, the median compression factor is $1.0\times$, meaning that the accepted exactification upper bound closely tracks the exposed exact optimum. Gold Tiny is also mostly at $1.0\times$, with the small maxout example producing the one visible exact-side gap. By contrast, SelectionStress is deliberately designed to enlarge the exposed candidate language while keeping the final semantic exact cover small, and the resulting median compression factor is $12.5\times$ with substantially larger outliers. This is the cleanest experimental manifestation of the paper's exact-side "candidate exposure versus semantic optimum" distinction.



Figure I.3: Exact-side compression factor by family. The plotted quantity is $U_{\mathrm{eq}}^{\mathrm{align}}/\mathrm{OPT}_{\mathrm{eq}}^{\mathrm{exposed}}$. Family A, Family B, and ThresholdStress stay concentrated at $1.0\times$, while SelectionStress exhibits large exposed-language compression. Gold Tiny is almost entirely at $1.0\times$, with the maxout example providing the intended small deviation.



Figure I.4: Transfer upper bound versus exposed threshold optimum on canonical true-threshold tasks. All points lie below the diagonal, as required by the exact-to-threshold transfer upper bound.

I.3 Threshold-Side Upper Bounds, Exposure, and Diagnostics

The threshold side is organized around one canonical true-threshold task per instance together with one false control. The false controls are clean in the saved bundle: none of the 126 false-control rows admits a finite accepted threshold cover. On the positive side, Figure I.4 plots the transfer upper bound against the exposed threshold optimum for the canonical true tasks. Every point lies below the diagonal, exactly as expected from the transfer theorem: an accepted exact cover transfers to a threshold cover of no larger size.

The threshold story is more subtle than a blanket "threshold is easier" slogan. Figure I.6 is included specifically to make that subtlety explicit. On Family A, Family B, Gold Tiny, and ThresholdStress, the exposed threshold optimum is typically below the exposed exact optimum. However, SelectionStress is intentionally a counterexample family: it targets exact-side cancellation/compression and therefore can have a much smaller exposed exact optimum while still requiring a larger threshold-side exposed cover in the bounded threshold language implemented by the artifact. The threshold section of the paper should therefore be written in the language-relative form used throughout the repository notes, not as a claim of universal threshold dominance.

Figure I.5 then isolates the threshold-stage exposure mechanism on the curated threshold subset. The conservative v3 default sets the parent-backtracking depth to zero, so the D_{transfer} and $+D_{\text{parent}}$ stages are intentionally dormant controls. The visible gain arrives at the $+D_{\text{drop}}$ stage: the median dictionary size increases from 38.0 to 254.5, while the median exposed threshold optimum decreases from 38.0 to 19.5. The median exposed lower bound stays at 16.0, so the final stage is not merely adding vacuous candidates; it is exposing a strictly better cover language while remaining close to the certified lower-bound floor.



Figure I.5: Threshold-stage ablation on the curated threshold subset. Under the conservative v3 default, parent backtracking is disabled, so D_{transfer} and $+D_{\text{parent}}$ coincide. The $+D_{\text{drop}}$ stage enlarges the exposed threshold dictionary and reduces the median exposed optimum from 38.0 to 19.5 while the median exposed lower bound remains at 16.0.



Figure I.6: Threshold-versus-exact diagnostic on the canonical true-threshold rows. Most benchmark families lie below the diagonal, while SelectionStress intentionally lies above it. Thus threshold exposed optima are not universally smaller than exact exposed optima; the comparison depends on the exposed candidate language and on the benchmark family.



Figure I.7: Selection-stage ablation on the curated explicit-candidate subset. Candidate exposure grows from D_{leaf} to $+D_{\text{drop}}$, while the median exposed exact optimum collapses from 40.5 to 3.0. This is a stress-family demonstration of selection-layer compression after candidate exposure, not a blanket claim about every benchmark family.

I.4 Selection-Layer Exposure on Explicit Candidate Families

The exact-side selection experiment is intentionally separated from the exactification scaling experiment. Its job is not to estimate unrestricted semantic hardness for every benchmark family. Its job is to show what happens after the pipeline has already exposed an explicit finite candidate family and the remaining problem is to select a smallest accepted subcover inside that family.

Figure I.7 shows the stagewise behavior on the curated selection subset. The median dictionary size grows from 40.5 at D_{leaf} to 145.0 at $D_{\text{leaf}} + D_{\text{frag}}$, then to 224.0 at $+D_{\text{parent}}$, and finally to 586.0 at $+D_{\text{drop}}$. At the same time, the median exposed exact optimum stays at 40.5 through the first two stages and then collapses to 3.0 at the parent/drop stages. The qualitative lesson is that exposing more candidates can make the selection layer dramatically more informative before any theorem-level hardness statement is invoked.

The repository's SelectionStress family is deliberately targeted to make this phenomenon visible. Accordingly, Figure I.7 should be interpreted as an explicit-dictionary stress demonstration rather than as a blanket empirical statement that selection is the dominant difficulty on every family. That scoped interpretation matches the theoretical hardness discussion in Section 6 and Appendix G.



Figure I.8: Realization-side payload metrics. Panel (a) shows near-linear scaling between proof-cell count and compact/core binary payload size. Panel (b) shows that archive bundles are much larger than compact/core payloads, especially on SelectionStress; archive size therefore should not be conflated with semantic proof payload size.

I.5 Realization-Side Payload, Checking Cost, and Runtime

The realization figures separate the semantic proof payload from full engineering archives. This distinction is essential for interpreting the SCC/DL-facing part of the artifact. Figure I.8 shows that compact/core binary payload size is almost perfectly linear in proof-cell count, while archive bundles are much larger and vary strongly by family. On the saved bundle, the fitted core-byte slope is approximately 206 bytes per proof cell, and the Pearson correlation between proof-cell count and compact/core binary size is about 0.995. By contrast, the median archive-to-core ratio is only about $5.1\times$ on Gold Tiny but rises to roughly $21.6\times$ on Family A, $15.6\times$ on Family B, $18.5\times$ on ThresholdStress, and $251.7\times$ on SelectionStress. The archive should therefore be read as engineering overhead, not as a direct measure of semantic proof payload size.

Figure I.9 shows the same near-linear behavior for checker runtime on compact/core payloads. The saved bundle stays below one millisecond for the core binary checker, with the largest observed values remaining around 0.6 ms. Finally, Figure I.10 reports exactification generation time as a function of H. The paper-facing bundle is not designed as a maximal stress benchmark, yet it is still useful to record that the constructive exactification pass remains within a few seconds on all shipped instances. In the saved run, the largest generation times stay below approximately 6 seconds.

Taken together, these figures support the main text's final empirical message: exactification yields observable finite exact covers with moderate constructive cost; threshold-side and selection-side exposure change the optimum before any hardness statement is applied; and compact/core proof realizations are the right object to compare at the realization layer, while full archive bundles should be reported separately.



Figure I.9: Compact/core checker time versus proof-cell count. Core checking remains sub-millisecond on the saved bundle and is close to linear in proof-cell count.



Figure I.10: Exactification generation time versus $H = |\mathcal{H}^\star|$. The constructive exactification pass grows with problem size but remains within a few seconds on the saved paper-facing bundle.