

# PSA: Markov Sick-Sicker model in R

The DARTH workgroup

Developed by the Decision Analysis in R for Technologies in Health (DARTH) workgroup:

Fernando Alarid-Escudero, PhD (1)

Eva A. Enns, MS, PhD (2)

M.G. Myriam Hunink, MD, PhD (3,4)

Hawre J. Jalal, MD, PhD (5)

Eline M. Krijkamp, MSc (3)

Petros Pechlivanoglou, PhD (6,7)

Alan Yang, MSc (7)

In collaboration of:

1. Division of Public Administration, Center for Research and Teaching in Economics (CIDE), Aguascalientes, Mexico
2. University of Minnesota School of Public Health, Minneapolis, MN, USA
3. Erasmus MC, Rotterdam, The Netherlands
4. Harvard T.H. Chan School of Public Health, Boston, USA
5. University of Pittsburgh Graduate School of Public Health, Pittsburgh, PA, USA
6. University of Toronto, Toronto ON, Canada
7. The Hospital for Sick Children, Toronto ON, Canada

Please cite our publications when using this code:

- Jalal H, Pechlivanoglou P, Krijkamp E, Alarid-Escudero F, Enns E, Hunink MG. An Overview of R in Health Decision Sciences. *Med Decis Making*. 2017; 37(3): 735-746. <https://journals.sagepub.com/doi/abs/10.1177/0272989X16686559>
- Krijkamp EM, Alarid-Escudero F, Enns EA, Jalal HJ, Hunink MGM, Pechlivanoglou P. Microsimulation modeling for health decision sciences using R: A tutorial. *Med Decis Making*. 2018;38(3):400–22. <https://journals.sagepub.com/doi/abs/10.1177/0272989X18754513>
- Krijkamp EM, Alarid-Escudero F, Enns E, Pechlivanoglou P, Hunink MM, Jalal H. A Multidimensional Array Representation of State-Transition Model Dynamics. *Med Decis Making*. 2020 Online first. <https://doi.org/10.1177/0272989X19893973>
- Alarid-Escudero, F., Krijkamp, E. M., Enns, E. A., Hunink, M. G. M., Pechlivanoglou, P., & Jalal, H. (2020). Cohort state-transition models in R: From conceptualization to implementation. *arXiv:2001.07824v1*, 1–31. <http://arxiv.org/abs/2001.07824>
- Alarid-Escudero, F., Enns, E. A., Kuntz, K. M., Michaud, T. L., & Jalal, H. (2019). “Time Traveling Is Just Too Dangerous” But Some Methods Are Worth Revisiting: The Advantages of Expected Loss Curves Over Cost-Effectiveness Acceptability Curves and Frontier. *Value in Health*, 22(5), 611–618. <https://doi.org/10.1016/j.jval.2019.02.008>

Copyright 2017, THE HOSPITAL FOR SICK CHILDREN AND THE COLLABORATING INSTITUTIONS. All rights reserved in Canada, the United States and worldwide. Copyright, trademarks, trade names and any

and all associated intellectual property are exclusively owned by THE HOSPITAL FOR Sick CHILDREN and the collaborating institutions. These materials may be used, reproduced, modified, distributed and adapted with proper attribution.

```
rm(list = ls())      # clear memory (removes all the variables from the workspace)
```

## 01 Load packages

```
if (!require('pacman')) {
  install.packages('pacman')
}
library(pacman) # use this package to conveniently install other packages
# load (install if required) packages from CRAN
p_load("here", "dplyr", "devtools", "scales", "ellipse", "ggplot2", "lazyeval",
       "igraph", "truncnorm", "ggraph", "reshape2", "knitr", "stringr", "reshape2")
# load (install if required) packages from GitHub
# install_github("DARTH-git/dampack", force = TRUE) Uncomment if there is a newer version
# install_github("DARTH-git/dectree", force = TRUE) Uncomment if there is a newer version
# install_github("annaheath/EVSI", force = TRUE) #Uncomment if there is a newer version
p_load_gh("DARTH-git/dampack", "DARTH-git/dectree")
p_load_gh("annaheath/EVSI")
```

## 02 Load functions

```
source("Functions.R")
```

## 03 Input model parameters

```
# Strategy names
v_names_str <- c("No Treatment", "Treatment")

# Number of strategies
n_str <- length(v_names_str)

# Markov model parameters
age      <- 25                # age at baseline
max_age  <- 55                # maximum age of follow up
n_t      <- max_age - age     # time horizon, number of cycles
v_n      <- c("H", "S1", "S2", "D") # the 4 states of the model: Healthy (H),
                                   # Sick (S1), Sicker (S2), Dead (D)
n_s      <- length(v_n)      # number of health states

# Transition probabilities (per cycle)
p_HD     <- 0.005             # probability to die when healthy
p_HS1    <- 0.15              # probability to become sick when healthy
p_S1H    <- 0.5               # probability to become healthy when sick
p_S1S2   <- 0.105            # probability to become sicker when sick
hr_S1    <- 3                 # hazard ratio of death in sick vs healthy
hr_S2    <- 10                # hazard ratio of death in sicker vs healthy
r_HD     <- -log(1 - p_HD)    # rate of death in healthy
r_S1D    <- hr_S1 * r_HD      # rate of death in sick
r_S2D    <- hr_S2 * r_HD      # rate of death in sicker
p_S1D    <- 1 - exp(-r_S1D)   # probability to die in sick
p_S2D    <- 1 - exp(-r_S2D)   # probability to die in sicker
```

```

# Cost and utility inputs
c_H    <- 2000  # cost of remaining one cycle in the healthy state
c_S1   <- 4000  # cost of remaining one cycle in the sick state
c_S2   <- 15000 # cost of remaining one cycle in the sicker state
c_trt  <- 12000 # cost of treatment(per cycle)
c_D    <- 0     # cost of being in the death state
u_H    <- 1     # utility when healthy
u_S1   <- 0.75  # utility when sick
u_S2   <- 0.5   # utility when sicker
u_D    <- 0     # utility when dead
u_trt  <- 0.95  # utility when being treated

# Discounting factor
d_r    <- 0.03 # equal discount of costs and QALYs by 3%
# calculate discount weights for costs for each cycle based on discount rate d_c
v_dwc  <- 1 / (1 + d_r) ^ (0:n_t)
# calculate discount weights for effectiveness for each cycle based on discount rate d_e
v_dwe  <- 1 / (1 + d_r) ^ (0:n_t)

```

## 04 Define and initialize matrices and vectors

### 04.1 Cohort trace

```

# create the markov trace matrix M capturing the proportion of the cohort
# in each state at each cycle
m_M_notrt <- m_M_trt <- matrix(NA,
                                nrow      = n_t + 1, ncol = n_s,
                                dimnames = list(paste("cycle", 0:n_t, sep = " "), v_n))

head(m_M_notrt) # show first 6 rows of the matrix

```

```

##           H S1 S2 D
## cycle 0 NA NA NA NA
## cycle 1 NA NA NA NA
## cycle 2 NA NA NA NA
## cycle 3 NA NA NA NA
## cycle 4 NA NA NA NA
## cycle 5 NA NA NA NA

```

```

# The cohort starts as healthy
m_M_notrt[1, ] <- m_M_trt[1, ] <- c(1, 0, 0, 0) # initiate first cycle of cohort trace

```

### 04.2 Transition probability matrix

```

# create the transition probability matrix for NO treatment (notrt)
m_P_notrt <- matrix(0,
                    nrow = n_s,
                    ncol = n_s,
                    dimnames = list(v_n, v_n)) # name the columns and rows of the matrix

m_P_notrt

```

```

##      H S1 S2 D
## H    0  0  0  0

```

```
## S1 0 0 0 0
## S2 0 0 0 0
## D 0 0 0 0
```

Fill in the transition probability matrix:

```
# from Healthy
m_P_notrt["H", "H"] <- 1 - (p_HS1 + p_HD)
m_P_notrt["H", "S1"] <- p_HS1
m_P_notrt["H", "D"] <- p_HD
# from Sick
m_P_notrt["S1", "H"] <- p_S1H
m_P_notrt["S1", "S1"] <- 1 - (p_S1H + p_S1S2 + p_S1D)
m_P_notrt["S1", "S2"] <- p_S1S2
m_P_notrt["S1", "D"] <- p_S1D
# from Sicker
m_P_notrt["S2", "S2"] <- 1 - p_S2D
m_P_notrt["S2", "D"] <- p_S2D
# from Dead
m_P_notrt["D", "D"] <- 1

# check rows add up to 1
rowSums(m_P_notrt)
```

```
## H S1 S2 D
## 1 1 1 1
```

```
# create transition probability matrix for treatment same as no treatment
m_P_trt <- m_P_notrt
```

## 05 Run Markov model

```
for (t in 1:n_t){ # loop through the number of cycles
  m_M_notrt[t + 1, ] <- t(m_M_notrt[t, ]) %*% m_P_notrt # estimate the Markov trace
  # for the next cycle (t + 1)
  m_M_trt[t + 1, ] <- t(m_M_trt[t, ]) %*% m_P_trt # estimate the Markov trace
  # for the next cycle (t + 1)
} # close the loop

head(m_M_notrt) # show the first 6 lines of the matrix
```

```
##           H           S1           S2           D
## cycle 0 1.0000000 0.0000000 0.0000000 0.0000000
## cycle 1 0.8450000 0.1500000 0.0000000 0.0050000
## cycle 2 0.7890250 0.1837612 0.01575000 0.01146377
## cycle 3 0.7586067 0.1881968 0.03427491 0.01892157
## cycle 4 0.7351211 0.1853199 0.05235988 0.02719916
## cycle 5 0.7138373 0.1807036 0.06925860 0.03620055
```


## 06 Compute and Plot Epidemiological Outcomes

### 06.1 Cohort trace

```

# create a plot of the data
matplot(m_M_notrt, type = 'l',
        ylab = "Probability of state occupancy",
        xlab = "Cycle",
        main = "Cohort Trace")
# add a legend to the graph
legend("topright", v_n, col = 1:n_s, lty = 1:n_s, bty = "n")

```




## 06.2 Overall Survival (OS)

```

# calculate the overall survival (OS) probability for no treatment
v_os_notrt <- 1 - m_M_notrt[, "D"]
# alternative way of calculating the OS probability
v_os_notrt <- rowSums(m_M_notrt[, 1:3])
# create a simple plot showing the OS
plot(0:n_t, v_os_notrt, type = 'l',
     ylim = c(0, 1),
     ylab = "Survival probability",
     xlab = "Cycle",
     main = "Overall Survival")
# add grid
grid(nx = n_t, ny = 10, col = "lightgray", lty = "dotted", lwd = par("lwd"),
     equilogs = TRUE)

```




#### 06.2.1 Life Expectancy (LE)

```
v_le <- sum(v_os_notrt)      # summing probability of OS over time (i.e. life expectancy)
```

#### 06.3 Disease prevalence

```
v_prev <- rowSums(m_M_notrt[, c("S1", "S2")]) / v_os_notrt
plot(v_prev,
     ylim = c(0, 1),
     ylab = "Prevalence",
     xlab = "Cycle",
     main = "Disease prevalence")
```




#### 06.4 Proportion of sick in S1 state

```
v_prop_S1 <- m_M_notrt[, "S1"] / v_prev
plot(0:n_t, v_prop_S1,
     xlab = "Cycle",
     ylab = "Proportion",
     main = "Proportion of sick in S1 state",
     col = "black", type = "l")
```



## Proportion of sick in S1 state



## 07 Compute Cost-Effectiveness Outcomes

```
# Vectors with costs and utilities by treatment
v_u_notrt <- c(u_H, u_S1, u_S2, u_D)
v_u_trt   <- c(u_H, u_trt, u_S2, u_D)

v_c_notrt <- c(c_H, c_S1, c_S2, c_D)
v_c_trt   <- c(c_H, c_S1 + c_trt, c_S2 + c_trt, c_D)
```

### 07.1 Mean Costs and QALYs for Treatment and NO Treatment

```
v_tu_notrt <- m_M_notrt %>% v_u_notrt
v_tu_trt   <- m_M_trt   %>% v_u_trt

v_tc_notrt <- m_M_notrt %>% v_c_notrt
v_tc_trt   <- m_M_trt   %>% v_c_trt
```

### 07.2 Discounted Mean Costs and QALYs

```
tu_d_notrt <- t(v_tu_notrt) %>% v_dwe
tu_d_trt   <- t(v_tu_trt)   %>% v_dwe

tc_d_notrt <- t(v_tc_notrt) %>% v_dwc
tc_d_trt   <- t(v_tc_trt)   %>% v_dwc
```

```

# store them into a vector
v_tc_d      <- c(tc_d_notrt, tc_d_trt)
v_tu_d      <- c(tu_d_notrt, tu_d_trt)

# Dataframe with discounted costs and effectiveness
df_ce       <- data.frame(Strategy = v_names_str,
                          Cost      = v_tc_d,
                          Effect    = v_tu_d)

df_ce

##      Strategy      Cost    Effect
## 1 No Treatment  75976.15 15.83885
## 2   Treatment 141623.03 16.40041

```

### 07.3 Compute ICERs of the Markov model

```

df_cea <- calculate_icers(cost      = df_ce$Cost,
                          effect    = df_ce$Effect,
                          strategies = df_ce$Strategy)

df_cea

##      Strategy      Cost    Effect Inc_Cost Inc_Effect      ICER Status
## 1 No Treatment  75976.15 15.83885      NA      NA      NA      ND
## 2   Treatment 141623.03 16.40041 65646.88  0.5615578 116901.4      ND


```

### 07.4 Plot frontier of the Markov model

```

plot(df_cea, effect_units = "Quality of Life", xlim = c(15.6, 16.6))

```



## 08 Deterministic Sensitivity Analysis

### 08.1 List of input parameters

Create list `l_params_all` with all input probabilities, cost and utilities.

```
l_params_all <- list(
  p_HD = 0.005, # probability to die when healthy
  p_HS1 = 0.15, # probability to become sick when healthy
  p_S1H = 0.5, # probability to become healthy when sick
  p_S1S2 = 0.105, # probability to become sicker when sick
  hr_S1 = 3, # hazard ratio of death in sick vs healthy
  hr_S2 = 10, # hazard ratio of death in sicker vs healthy
  c_H = 2000, # cost of remaining one cycle in the healthy state
  c_S1 = 4000, # cost of remaining one cycle in the sick state
  c_S2 = 15000, # cost of remaining one cycle in the sicker state
  c_trt = 12000, # cost of treatment(per cycle)
  c_D = 0, # cost of being in the death state
  u_H = 1, # utility when healthy
  u_S1 = 0.75, # utility when sick
  u_S2 = 0.5, # utility when sicker
  u_D = 0, # utility when dead
  u_trt = 0.95, # utility when treated
  d_e = 0.03, # discount factor for effectiveness
  d_c = 0.03 # discount factor for costs
)
```

```
# store the parameter names into a vector
v_names_parms <- names(l_params_all)
```

## 08.2 Load Sick-Sicker Markov model function

```
source("Functions_markov_sick-sicker.R")
# Test function
calculate_ce_out(l_params_all)
```

```
##      Strategy      Cost      Effect      NMB
## 1 No Treatment  75976.15  15.83885  1507909
## 2   Treatment 141623.03  16.40041  1498418
```

## 08.3 One-way sensitivity analysis (OWSA)


```
options(scipen = 999) # disabling scientific notation in R
# dataframe containing all parameters, their basecase values, and the min and
# max values of the parameters of interest
df_params_owsa <- data.frame(pars = c("p_S1S2", "c_trt", "u_S1", "u_trt"),
                             min  = c(0.05, 6000, 0.65, 0.80), # min parameter values
                             max  = c(0.155, 18000, 0.85, 0.98) # max parameter values
                             )

owsa_nmb <- run_owsa_det(params_range = df_params_owsa, # dataframe with parameters for owsa
                        params_basecase = l_params_all, # list with all parameters
                        nsamp = 100, # number of parameter values
                        FUN = calculate_ce_out, # function to compute outputs
                        outcomes = c("NMB"), # output to do the OWSA on
                        strategies = v_names_str, # names of the strategies
                        n_wtp = 120000) # extra argument to pass to FUN

## Warning: strategy name 'No Treatment' was converted to 'No.Treatment' for
## compatibility. See ?make.names
```


### 08.3.1 Plot OWSA

```
plot(owsa_nmb, txtsize = 16, n_x_ticks = 5, n_y_ticks = 3,
     facet_scales = "free") +
  theme(legend.position = "bottom",
        axis.text.x = element_text(angle = 45, vjust = 0.5))
```




### 08.3.2 Optimal strategy with OWSA

```
owsa_opt_strat(owsa = owsa_nmb)
```



### 08.3.3 Tornado plot

```
owsa_tornado(owsa = owsa_nmb)
```



## 08.4 Two-way sensitivity analysis (TWSA)

```
# dataframe containing all parameters, their basecase values, and the min and
# max values of the parameters of interest
df_params_twsa <- data.frame(pars = c("c_trt", "u_trt"),
                             min = c(6000, 0.80), # min parameter values
                             max = c(18000, 0.98) # max parameter values
                             )


twsa_nmb <- run_twsa_det(params_range = df_params_twsa, # dataframe with parameters for twsa
                        params_basecase = l_params_all, # list with all parameters
                        nsamp = 40, # number of parameter values
                        FUN = calculate_ce_out, # function to compute outputs
                        outcomes = c("NMB"), # output to do the twsa on
                        strategies = v_names_str, # names of the strategies
                        n_wtp = 120000) # extra argument to pass to FUN
```

### 08.4.1 Plot TWSA

```
plot(twsa_nmb) +
  ggtitle(label = "Two-way sensitivity analysis",
          subtitle = "Net monetary benefit") +
  theme(legend.position = "bottom")
```

## Two-way sensitivity analysis

### Net monetary benefit



## 09 Probabilistic Sensitivity Analysis (PSA)

```
# Function to generate PSA input dataset
generate_psa_params <- function(n_sim = 1000, seed = 071818){
  set.seed(seed) # set a seed to be able to reproduce the same results
  df_psa <- data.frame(
    # Transition probabilities (per cycle)
    p_HS1 = rbeta(n_sim, 30, 170) , # probability to become sick when healthy
    p_S1H = rbeta(n_sim, 60, 60) , # probability to become healthy when sick
    p_S1S2 = rbeta(n_sim, 84, 716) , # probability to become sicker when sick
    p_HD = rbeta(n_sim, 10, 1990), # probability to die when healthy
    hr_S1 = rlnorm(n_sim, log(3), 0.01), # rate ratio of death in S1 vs healthy
    hr_S2 = rlnorm(n_sim, log(10), 0.02), # rate ratio of death in S2 vs healthy

    # State rewards
    # Costs
    c_H = rgamma(n_sim, shape = 100, scale = 20) , # cost of remaining one cycle in state H
    c_S1 = rgamma(n_sim, shape = 177.8, scale = 22.5), # cost of remaining one cycle in state S1
    c_S2 = rgamma(n_sim, shape = 225, scale = 66.7) , # cost of remaining one cycle in state S2
    c_Trt = rgamma(n_sim, shape = 73.5, scale = 163.3), # cost of treatment (per cycle)
    c_D = 0 , # cost of being in the death state

    # Utilities
    u_H = rbeta(n_sim, shape1 = 200, shape2 = 3) , # utility when healthy
    u_S1 = rbeta(n_sim, shape1 = 130, shape2 = 45) , # utility when sick
  )
}
```



```

u_S2 = rbeta(n_sim, shape1 = 230, shape2 = 230), # utility when sicker
u_D = 0 , # utility when dead
u_TrT = rbeta(n_sim, shape1 = 300, shape2 = 15) , # utility when being treated
d_e = 0.03, # discount factor for effectiveness
d_c = 0.03 # discount factor for costs
)
return(df_psa)
}
# Try it
generate_psa_params(10)

```

```

##      p_HS1      p_S1H      p_S1S2      p_HD      hr_S1      hr_S2      c_H
## 1  0.15132349 0.4820445 0.08485456 0.003973762 3.055410 10.148768 1887.449
## 2  0.12522484 0.4392546 0.11683397 0.004813328 3.005252 9.928044 1966.291
## 3  0.15673720 0.5311020 0.11925841 0.004491843 2.982392 10.021998 2101.059
## 4  0.11276858 0.4493088 0.09393848 0.010646056 2.981918 10.167486 1728.664
## 5  0.14292946 0.5825087 0.11628065 0.007045338 3.024975 10.006505 2160.895
## 6  0.20088601 0.4580278 0.10403415 0.004058637 2.971345 10.012715 1969.304
## 7  0.14347796 0.5492245 0.09294048 0.005658464 2.989181 10.001860 1641.192
## 8  0.13149270 0.4899896 0.12838861 0.007354969 2.984080 9.919332 2276.032
## 9  0.15593267 0.5705602 0.09237907 0.004162148 2.988974 10.142331 1717.867
## 10 0.09824029 0.5127637 0.10683148 0.002141140 2.968692 9.749869 2132.549
##      c_S1      c_S2      c_TrT c_D      u_H      u_S1      u_S2 u_D      u_TrT
## 1  4173.600 14607.88 10673.74 0 0.9829120 0.7252701 0.4757751 0 0.9435773
## 2  4188.264 14714.84 13380.61 0 0.9693926 0.7610392 0.4591563 0 0.9501528
## 3  4578.682 16664.54 12522.58 0 0.9910033 0.7076433 0.5032719 0 0.9670124
## 4  3395.922 15669.87 13833.65 0 0.9928844 0.7124119 0.5132492 0 0.9649128
## 5  3878.562 15302.70 13154.65 0 0.9748972 0.7344718 0.4895693 0 0.9325969
## 6  3970.522 15303.55 13914.95 0 0.9832065 0.7169406 0.4628316 0 0.9456881
## 7  3680.588 15378.20 12117.86 0 0.9917677 0.7851270 0.4504530 0 0.9093339
## 8  3781.956 15614.73 12070.99 0 0.9727485 0.7582961 0.4727426 0 0.9390084
## 9  3448.146 15401.50 11760.17 0 0.9836544 0.7648816 0.4851046 0 0.9537789
## 10 4656.666 15198.97 10216.98 0 0.9915345 0.7751203 0.5311969 0 0.9577708
##      d_e d_c
## 1  0.03 0.03
## 2  0.03 0.03
## 3  0.03 0.03
## 4  0.03 0.03
## 5  0.03 0.03
## 6  0.03 0.03
## 7  0.03 0.03
## 8  0.03 0.03
## 9  0.03 0.03
## 10 0.03 0.03

```

```

# Number of simulations
n_sim <- 1000

# Generate PSA input dataset
df_psa_input <- generate_psa_params(n_sim = n_sim)
# First six observations
head(df_psa_input)

```

```


##      p_HS1      p_S1H      p_S1S2      p_HD      hr_S1      hr_S2      c_H

```

```
## 1 0.1513235 0.5617628 0.1033817 0.006269864 2.962948 9.820157 1658.447
## 2 0.1252248 0.4380343 0.1152594 0.005371105 3.014068 10.100813 2050.281
## 3 0.1567372 0.5458102 0.1274505 0.004301015 3.018588 9.825985 2094.425
## 4 0.1127686 0.5106953 0.1015742 0.005319105 2.979709 9.697122 2135.411
## 5 0.1429295 0.5277308 0.1020384 0.004225209 3.025490 10.254387 1665.257
## 6 0.2008860 0.5252364 0.1030676 0.008319206 2.979175 10.366400 2049.794
##      c_S1      c_S2      c_Trt c_D      u_H      u_S1      u_S2 u_D      u_Trt
## 1 4191.109 15165.80 10292.050 0 0.9816602 0.7395884 0.5106656 0 0.9496993
## 2 4133.823 15042.66 10779.006 0 0.9906084 0.7240259 0.4927761 0 0.9731185
## 3 3567.033 15052.49 12811.443 0 0.9834960 0.6910869 0.5024542 0 0.9598494
## 4 3726.226 16084.60 10072.741 0 0.9919197 0.7065183 0.5118351 0 0.9357411
## 5 3654.486 15201.84 14917.228 0 0.9953850 0.6838064 0.5021483 0 0.9635901
## 6 3927.001 17060.57 9581.097 0 0.9813330 0.7766346 0.5035428 0 0.9506926
##      d_e d_c
## 1 0.03 0.03
## 2 0.03 0.03
## 3 0.03 0.03
## 4 0.03 0.03
## 5 0.03 0.03
## 6 0.03 0.03
```

```
# Histogram of parameters
```

```
ggplot(reshape2::melt(df_psa_input, variable.name = "Parameter",
  value.name = "Parameter value"),
  aes(x = `Parameter value`)) +
  facet_wrap(~Parameter, scales = "free") +
  geom_histogram(aes(y = ..density..), alpha = 0.8) +
  scale_x_continuous(breaks = number_ticks(2)) +
  ylab("") +
  theme_bw(base_size = 14) +
  theme(axis.text.y = element_blank(), text = element_text(size=10))
```



```
# Initialize dataframes with PSA output
# Dataframe of costs
df_c <- as.data.frame(matrix(0,
                             nrow = n_sim,
                             ncol = n_str))
colnames(df_c) <- v_names_str
# Dataframe of effectiveness
df_e <- as.data.frame(matrix(0,
                             nrow = n_sim,
                             ncol = n_str))
colnames(df_e) <- v_names_str
```

## 09.1 Conduct probabilistic sensitivity analysis

```
# Run Markov model on each parameter set of PSA input dataset
for(i in 1:n_sim){
  l_psa_input <- update_param_list(l_params_all, df_psa_input[i,])
  df_out_psa <- calculate_ce_out(l_psa_input)
  df_c[i, ] <- df_out_psa$Cost
  df_e[i, ] <- df_out_psa$Effect
  # Display simulation progress
  if(i/(n_sim/10) == round(i/(n_sim/10), 0)) { # display progress every 10%
    cat('\r', paste(i/n_sim * 100, "% done", sep = " "))
  }
}
```

```
## 10 % done 20 % done 30 % done 40 % done 50 % done 60 % done 70 % done 80 % done 90 % done 100 % done
```

## 09.2 Create PSA object for dampack

```
l_psa <- make_psa_obj(cost      = df_c,  
                     effectiveness = df_e,  
                     parameters  = df_psa_input,  
                     strategies  = v_names_str)
```

### 09.2.1 Save PSA objects

```
save(df_psa_input, df_c, df_e, v_names_str, n_str, l_psa,  
     file = "markov_sick-sicker_PSA_dataset.RData")
```

## 09.3 Create probabilistic analysis graphs


```
load(file = "markov_sick-sicker_PSA_dataset.RData")
```

Vector with willingness-to-pay (WTP) thresholds.

```
v_wtp <- seq(0, 200000, by = 10000)
```

### 09.3.1 Cost-Effectiveness Scatter plot

```
plot(l_psa)
```



## 09.4 Conduct CEA with probabilistic output

```
# Compute expected costs and effects for each strategy from the PSA
df_out_ce_psa <- summary(l_psa)

# Calculate incremental cost-effectiveness ratios (ICERs)
df_cea_psa <- calculate_icers(cost      = df_out_ce_psa$meanCost,
                             effect    = df_out_ce_psa$meanEffect,
                             strategies = df_out_ce_psa$Strategy)


df_cea_psa

##      Strategy      Cost      Effect Inc_Cost Inc_Effect      ICER Status
## 1 No.Treatment  77033.8  15.69937      NA      NA      NA      ND
## 2 Treatment  143354.8  16.27791    66321  0.5785414 114634.8      ND

# Save CEA table with ICERs
# As .RData
save(df_cea_psa,
     file = "markov_sick-sicker_probabilistic_CEA_results.RData")
# As .csv
write.csv(df_cea_psa,
          file = "markov_sick-sicker_probabilistic_CEA_results.csv")
```

### 09.4.1 Plot cost-effectiveness frontier

```
plot(df_cea_psa)
```




### 09.4.2 Cost-effectiveness acceptability curves (CEACs) and frontier (CEAF)

```
ceac_obj <- ceac(wtp = v_wtp, psa = l_psa)
# Regions of highest probability of cost-effectiveness for each strategy
summary(ceac_obj)

##   range_min range_max cost_eff_strat
## 1         0  120000   No.Treatment
## 2  120000  200000     Treatment


# CEAC & CEAF plot
plot(ceac_obj)
```



### 09.4.3 Expected Loss Curves (ELCs)


The expected loss is the the quantification of the foregone benefits when choosing a suboptimal strategy given current evidence.

```
elc_obj <- calc_exp_loss(wtp = v_wtp, psa = l_psa)
# ELC plot
plot(elc_obj, log_y = FALSE)
```



#### 09.4.4 Expected value of perfect information (EVPI)

```
evpi <- calc_evpi(wtp = v_wtp, psa = l_psa)
# EVPI plot
plot(evpi, effect_units = "QALY")
```



#### 07.4.5 Expected value of partial perfect information (EVPPI)

```
evppi <- calc_evppi(psa = l_psa,
  wtp = v_wtp,
  params = c("p_S1S2"),
  outcome = c("nmb"),
  type = c("gam", "poly"),
  poly.order = 2,
  k = -1,
  pop = 1
)
# EVPPI plot
dampack::plot.evppi(evppi)
```



