

# SA: Markov Sick-Sicker model in R

The DARTH workgroup

Developed by the Decision Analysis in R for Technologies in Health (DARTH) workgroup:

Fernando Alarid-Escudero, PhD (1)

Eva A. Enns, MS, PhD (2)

M.G. Myriam Hunink, MD, PhD (3,4)

Hawre J. Jalal, MD, PhD (5)

Eline M. Krijkamp, MSc (3)

Petros Pechlivanoglou, PhD (6,7)

Alan Yang, MSc (7)

In collaboration of:

1. Division of Public Administration, Center for Research and Teaching in Economics (CIDE), Aguascalientes, Mexico
2. University of Minnesota School of Public Health, Minneapolis, MN, USA
3. Erasmus MC, Rotterdam, The Netherlands
4. Harvard T.H. Chan School of Public Health, Boston, USA
5. University of Pittsburgh Graduate School of Public Health, Pittsburgh, PA, USA
6. University of Toronto, Toronto ON, Canada
7. The Hospital for Sick Children, Toronto ON, Canada

Please cite our publications when using this code:

- Jalal H, Pechlivanoglou P, Krijkamp E, Alarid-Escudero F, Enns E, Hunink MG. An Overview of R in Health Decision Sciences. *Med Decis Making*. 2017; 37(3): 735-746. <https://journals.sagepub.com/doi/abs/10.1177/0272989X16686559>
- Krijkamp EM, Alarid-Escudero F, Enns EA, Jalal HJ, Hunink MGM, Pechlivanoglou P. Microsimulation modeling for health decision sciences using R: A tutorial. *Med Decis Making*. 2018;38(3):400-22. <https://journals.sagepub.com/doi/abs/10.1177/0272989X18754513>
- Krijkamp EM, Alarid-Escudero F, Enns E, Pechlivanoglou P, Hunink MM, Jalal H. A Multidimensional Array Representation of State-Transition Model Dynamics. *Med Decis Making*. Feb;40(2):242-248. <https://doi.org/10.1177/0272989X19893973>
- Alarid-Escudero, F., Krijkamp, E. M., Enns, E. A., Hunink, M. G. M., Pechlivanoglou, P., & Jalal, H. (2020). Cohort state-transition models in R: From conceptualization to implementation. *ArXiv:2001.07824v1*, 1-31. <http://arxiv.org/abs/2001.07824>

Copyright 2017, THE HOSPITAL FOR SICK CHILDREN AND THE COLLABORATING INSTITUTIONS. All rights reserved in Canada, the United States and worldwide. Copyright, trademarks, trade names and any and all associated intellectual property are exclusively owned by THE HOSPITAL FOR SICK CHILDREN and the collaborating institutions. These materials may be used, reproduced, modified, distributed and adapted with proper attribution.

Change eval to TRUE if you want to knit this document.

```
rm(list = ls())      # clear memory (removes all the variables from the workspace)
```

## 01 Load packages

```
if (!require('pacman')){
  install.packages('pacman')
  library(pacman) # use this package to conveniently install other packages
}
# load (install if required) packages from CRAN
pacman::p_load("dplyr", "devtools", "scales", "ellipse", "ggplot2", "lazyeval",
               "igraph", "truncnorm", "ggraph", "reshape2", "knitr", "stringr",
               "diagram", "dampack")
# load (install if required) packages from GitHub
# install_github("DARTH-git/darthtools", force = TRUE) Uncomment if there is a newer version
p_load_gh("DARTH-git/darthtools")
```

## 02 Load functions

```
# No function needed
```

## 03 Input model parameters

```
# Strategy names
v_names_str <- c("No Treatment", "Treatment")

# Markov model parameters
age      <- 25          # age at baseline
max_age  <- 55          # maximum age of follow up
n_t      <- max_age - age # time horizon, number of cycles
v_names_states <- c("H", "S1", "S2", "D") # the 4 states of the model: Healthy (H), Sick (S1),
                                           # Sicker (S2), Dead (D)

v_init <- c("H" = 1,
           "S1" = 0,
           "S2" = 0,
           "D" = 0)      # initial cohort distribution (everyone allocated to the "healthy"

# Transition probabilities (per cycle)
p_HD      <- 0.005      # probability to die when healthy
p_HS1     <- 0.15       # probability to become sick when healthy, conditional on surviving
p_S1H     <- 0.5        # probability to become healthy when sick, conditional on surviving
p_S1S2    <- 0.105      # probability to become sicker when sick, conditional on surviving
hr_S1     <- 3          # hazard ratio of death in sick vs healthy
hr_S2     <- 10         # hazard ratio of death in sicker vs healthy
r_HD      <- - log(1 - p_HD) # rate of death in healthy
r_S1D     <- hr_S1 * r_HD  # rate of death in sick
r_S2D     <- hr_S2 * r_HD  # rate of death in sicker
p_S1D     <- 1 - exp(-r_S1D) # probability to die in sick
p_S2D     <- 1 - exp(-r_S2D) # probability to die in sicker
```

```

# Cost and utility inputs
c_H <- 2000 # cost of remaining one cycle in the healthy state
c_S1 <- 4000 # cost of remaining one cycle in the sick state
c_S2 <- 15000 # cost of remaining one cycle in the sicker state
c_trt <- 12000 # cost of treatment (per cycle)
c_D <- 0 # cost of being in the death state
u_H <- 1 # utility when healthy
u_S1 <- 0.75 # utility when sick
u_S2 <- 0.5 # utility when sicker
u_D <- 0 # utility when dead
u_trt <- 0.95 # utility when being treated
d_e <- 0.03 # discount rate per cycle for costs by 3%
d_c <- 0.03 # discount rate per cycle for QALYs by 3%

n_str <- length(v_names_str) # Number of strategies
n_states <- length(v_names_states) # number of states

# Discount weights for costs and effects
v_dwc <- 1 / (1 + d_c) ^ (0:n_t)
v_dwe <- 1 / (1 + d_e) ^ (0:n_t)

```

## Create a state-transition diagram of the cohort model

```

m_P_diag <- matrix(0,
                    nrow = n_states, ncol = n_states,
                    dimnames = list(v_names_states, v_names_states))
m_P_diag["H" , "S1"] = ""
m_P_diag["H" , "D" ] = ""
m_P_diag["H" , "H" ] = ""
m_P_diag["S1", "H" ] = ""
m_P_diag["S1", "S2"] = ""
m_P_diag["S1", "D" ] = ""
m_P_diag["S1", "S1"] = ""
m_P_diag["S2", "D" ] = ""
m_P_diag["S2", "S2"] = ""
m_P_diag["D", "D" ] = ""
layout.fig <- c(3, 1)

plotmat(t(m_P_diag), t(layout.fig), self.cex = 0.5, curve = 0, arr.pos = 0.7,
        latex = T, arr.type = "curved", relsize = 0.9, box.prop = 0.8,
        cex = 0.8, box.cex = 0.9, lwd = 1)

```

## 04 Define and initialize matrices and vectors

### 04.1 Cohort trace

```

# create the markov trace matrix M capturing the proportion of the cohort in
# each state at each cycle
m_M_notrt <- m_M_trt <- matrix(NA,
                                nrow = n_t + 1, ncol = n_states,
                                dimnames = list(paste("cycle", 0:n_t, sep = " "),
                                                  v_names_states))

```

```
head(m_M_notrt) # show first 6 rows of the matrix

# The cohort starts as healthy
m_M_notrt[1, ] <- c(1, 0, 0, 0) # initiate first cycle of cohort trace
m_M_trt[1, ] <- c(1, 0, 0, 0) # initiate first cycle of cohort trace
```

## 04.2 Transition probability matrices

```
# create the transition probability matrix for both treatment arms
m_P_notrt <- m_P_trt <- matrix(0,
                                nrow = n_states,
                                ncol = n_states,
                                dimnames = list(v_names_states,
                                                  v_names_states)) # name the columns and rows of the matrix
m_P_notrt
```

Fill in the transition probability matrix:

```
# from Healthy
m_P_notrt["H", "H" ] <- (1 - p_HD) * (1 - p_HS1)
m_P_notrt["H", "S1" ] <- (1 - p_HD) * p_HS1
m_P_notrt["H", "D" ] <- p_HD
# from Sick
m_P_notrt["S1", "H" ] <- (1 - p_S1D) * p_S1H
m_P_notrt["S1", "S1" ] <- (1 - p_S1D) * (1 - (p_S1H + p_S1S2))
m_P_notrt["S1", "S2" ] <- (1 - p_S1D) * p_S1S2
m_P_notrt["S1", "D" ] <- p_S1D
# from Sicker
m_P_notrt["S2", "S2" ] <- 1 - p_S2D
m_P_notrt["S2", "D" ] <- p_S2D
# from Dead
m_P_notrt["D", "D" ] <- 1

# Check that transition probabilities are in [0, 1]
check_transition_probability(m_P_notrt, verbose = TRUE)
# Check that all rows sum to 1
check_sum_of_transition_array(m_P_notrt, n_states = n_states, n_cycles = n_t, verbose = TRUE)

# Overwrite the transition probability matrix for treatment with the no treatment values as they are the same
m_P_trt <- m_P_notrt
```

## 05 Run Markov model

```
for (t in 1:n_t){      # loop through the number of cycles
  m_M_notrt[t + 1, ] <- t(m_M_notrt[t, ]) %*% m_P_notrt # estimate the Markov trace
                                                           # for the next cycle (t + 1)
  m_M_trt[t + 1, ] <- t(m_M_trt[t, ]) %*% m_P_trt      # estimate the Markov trace
                                                           # for the next cycle (t + 1)
} # close the loop

head(m_M_notrt) # show the first 6 lines of the matrix
```

## 06 Compute and Plot Epidemiological Outcomes

### 06.1 Cohort trace

```
# create a plot of the data
matplot(m_M_notrt, type = 'l',
        ylab = "Probability of state occupancy",
        xlab = "Cycle",
        main = "Cohort Trace")
# add a legend to the graph
legend("topright", v_names_states,
       col = 1:n_states, lty = 1:n_states, bty = "n")
```

### 06.2 Overall Survival (OS)

```
# calculate the overall survival (OS) probability for no treatment
v_os_notrt <- 1 - m_M_notrt[, "D"]
# alternative way of calculating the OS probability
v_os_notrt <- rowSums(m_M_notrt[, 1:3])
# create a simple plot showing the OS
plot(0:n_t, v_os_notrt, type = 'l',
     ylim = c(0, 1),
     ylab = "Survival probability",
     xlab = "Cycle",
     main = "Overall Survival")
# add grid
grid(nx = n_t, ny = 10, col = "lightgray", lty = "dotted", lwd = par("lwd"),
     equilogs = TRUE)
```

#### 06.2.1 Life Expectancy (LE)

```
v_le <- sum(v_os_notrt) # summing probability of OS over time (i.e. life expectancy)
```

### 06.3 Disease prevalence

```
v_prev <- rowSums(m_M_notrt[, c("S1", "S2")]) / v_os_notrt
plot(v_prev,
     ylim = c(0, 1),
     ylab = "Prevalence",
     xlab = "Cycle",
     main = "Disease prevalence")
```

### 06.4 Proportion of sick in S1 state

```
v_prop_S1 <- m_M_notrt[, "S1"] / v_prev
plot(0:n_t, v_prop_S1,
     xlab = "Cycle",
     ylab = "Proportion",
     main = "Proportion of sick in S1 state",
     col = "black", type = "l")
```

## 07 Compute Cost-Effectiveness Outcomes

```
# Vectors with costs and utilities by treatment
v_u_notrt <- c(u_H, u_S1, u_S2, u_D)
v_u_trt   <- c(u_H, u_trt, u_S2, u_D)

v_c_notrt <- c(c_H, c_S1, c_S2, c_D)
v_c_trt   <- c(c_H, c_S1 + c_trt, c_S2 + c_trt, c_D)
```

### 07.1 Mean Costs and QALYs for Treatment and NO Treatment

```
v_tu_notrt <- m_M_notrt %>% v_u_notrt
v_tu_trt   <- m_M_trt   %>% v_u_trt

v_tc_notrt <- m_M_notrt %>% v_c_notrt
v_tc_trt   <- m_M_trt   %>% v_c_trt
```

### 07.2 Discounted Mean Costs and QALYs

```
tu_d_notrt <- t(v_tu_notrt) %>% v_dwe
tu_d_trt   <- t(v_tu_trt)   %>% v_dwe

tc_d_notrt <- t(v_tc_notrt) %>% v_dwc
tc_d_trt   <- t(v_tc_trt)   %>% v_dwc

# store them into a vector
v_tc_d <- c(tc_d_notrt, tc_d_trt)
v_tu_d <- c(tu_d_notrt, tu_d_trt)

# data.frame with discounted costs and effectiveness
df_ce <- data.frame(Strategy = v_names_str,
                    Cost      = v_tc_d,
                    Effect     = v_tu_d,
                    )
df_ce
```

### 07.3 Compute ICERs of the Markov model

```
df_cea <- calculate_icers(cost      = df_ce$Cost,
                          effect     = df_ce$Effect,
                          strategies = df_ce$Strategy
                          )
df_cea
```

### 07.4 Plot frontier of the Markov model

```
plot(df_cea, effect_units = "QALYs", xlim = c(15.6, 16.6))
```

## 08 Deterministic Sensitivity Analysis

### 08.1 List of input parameters

Create list `l_params_all` with all input probabilities, cost and utilities.

```
l_params_all <- as.list(data.frame(
  p_HD    = 0.005, # probability to die when healthy
  p_HS1   = 0.15,  # probability to become sick when healthy, conditional on surviving
  p_S1H   = 0.5,   # probability to become healthy when sick, conditional on surviving
  p_S1S2  = 0.105, # probability to become sicker when sick, conditional on surviving
  hr_S1   = 3,     # hazard ratio of death in sick vs healthy
  hr_S2   = 10,    # hazard ratio of death in sicker vs healthy
  c_H     = 2000,  # cost of remaining one cycle in the healthy state
  c_S1    = 4000,  # cost of remaining one cycle in the sick state
  c_S2    = 15000, # cost of remaining one cycle in the sicker state
  c_trt   = 12000, # cost of treatment(per cycle)
  c_D     = 0,     # cost of being in the death state
  u_H     = 1,     # utility when healthy
  u_S1    = 0.75,  # utility when sick
  u_S2    = 0.5,   # utility when sicker
  u_D     = 0,     # utility when dead
  u_trt   = 0.95,  # utility when treated
  d_e     = 0.03,  # discount factor for effectiveness
  d_c     = 0.03   # discount factor for costs
))

# store the parameter names into a vector
v_names_params <- names(l_params_all)
```

### 08.2 Load Sick-Sicker Markov model function

```
source("Functions_markov_sick-sicker_sol.R")
# Test function
calculate_ce_out(l_params_all)
```

### 08.3 One-way sensitivity analysis (OWSA)

```
options(scipen = 999) # disabling scientific notation in R
# data.frame containing all parameters, their base-case values, and the min and
# max values of the parameters of interest
df_params_owsa <- data.frame(pars = c("p_S1S2", "c_trt", "u_S1", "u_trt"),
                             min  = c(0.05, 6000, 0.65, 0.80), # min parameter values
                             max  = c(0.155, 18000, 0.85, 0.98) # max parameter values
                             )

owsa_nmb <- run_owsa_det(params_range = df_params_owsa, # data.frame with parameters for OWSA
                        params_basecase = l_params_all, # list with all parameters
                        nsamp           = 100,          # number of parameter values
                        FUN              = calculate_ce_out, # function to compute outputs
                        outcomes        = c("NMB"),      # output to do the OWSA on
                        strategies      = v_names_str,   # names of the strategies
                        n_wtp           = 120000)        # extra argument to pass to FUN
```

### 08.3.1 Plot OWSA

```
plot(owsa_nmb, txtsize = 10, n_x_ticks = 4,  
     facet_scales = "free") +  
  theme(legend.position = "bottom")
```

### 08.3.2 Optimal strategy with OWSA

```
owsa_opt_strat(owsa = owsa_nmb, txtsize = 10)
```

### 08.3.3 Tornado plot

```
owsa_tornado(owsa = owsa_nmb)
```

## 08.4 Two-way sensitivity analysis (TWSA)

```
# dataframe containing all parameters, their basecase values, and the min and  
# max values of the parameters of interest  
df_params_twsa <- data.frame(pars = c("c_trt", "u_trt"),  
                             min = c(6000, 0.80), # min parameter values  
                             max = c(18000, 0.98) # max parameter values  
                             )  
  
twsa_nmb <- run_twsa_det(params_range = df_params_twsa, # data.frame with parameters for TWSA  
                        params_basecase = l_params_all, # list with all parameters  
                        nsamp = 40, # number of parameter values  
                        FUN = calculate_ce_out, # function to compute outputs  
                        outcomes = c("NMB"), # output to do the TWSA on  
                        strategies = v_names_str, # names of the strategies  
                        n_wtp = 120000) # extra argument to pass to FUN
```

l ## 08.4.1 Plot TWSA

```
plot(twsa_nmb)
```

## 09 Probabilistic Sensitivity Analysis (PSA)

```
# Function to generate PSA input dataset  
gen_psa <- function(n_sim = 1000, seed = 071818){  
  set.seed(seed) # set a seed to be able to reproduce the same results  
  df_psa <- data.frame(  
    # Transition probabilities (per cycle)  
    p_HS1 = rbeta(n_sim, shape1 = 30, shape2 = 170), # probability to become sick when healthy  
    p_S1H = rbeta(n_sim, shape1 = 60, shape2 = 60), # probability to become healthy when sick  
    p_S1S2 = rbeta(n_sim, shape1 = 84, shape2 = 716), # probability to become sicker when sick  
    p_HD = rbeta(n_sim, shape1 = 10, shape2 = 1990), # probability to die when healthy  
    hr_S1 = rlnorm(n_sim, meanlog = log(3), sdlog = 0.01), # rate ratio of death in S1 vs healthy  
    hr_S2 = rlnorm(n_sim, meanlog = log(10), sdlog = 0.02), # rate ratio of death in S2 vs healthy  
  
    # State rewards  
    # Costs  
    c_H = rgamma(n_sim, shape = 100, scale = 20), # cost of remaining one cycle in state H
```



```

c_S1 = rgamma(n_sim, shape = 177.8, scale = 22.5), # cost of remaining one cycle in state S1
c_S2 = rgamma(n_sim, shape = 225, scale = 66.7), # cost of remaining one cycle in state S2
c_Trt = rgamma(n_sim, shape = 73.5, scale = 163.3), # cost of treatment (per cycle)
c_D = 0, # cost of being in the death state

# Utilities
u_H = rbeta(n_sim, shape1 = 200, shape2 = 3), # utility when healthy
u_S1 = rbeta(n_sim, shape1 = 130, shape2 = 45), # utility when sick
u_S2 = rbeta(n_sim, shape1 = 230, shape2 = 230), # utility when sicker
u_D = 0, # utility when dead
u_Trt = rbeta(n_sim, shape1 = 300, shape2 = 15), # utility when being treated
d_e = 0.03, # discount factor for effectiveness
d_c = 0.03 # discount factor for costs
)
return(df_psa)
}
# Try it
gen_psa(10)

# Number of simulations
n_sim <- 1000

# Generate PSA input dataset
df_psa_input <- gen_psa(n_sim = n_sim)
# First six observations
head(df_psa_input)

# Histogram of parameters
ggplot(melt(df_psa_input, variable.name = "Parameter"), aes(x = value)) +
  facet_wrap(~Parameter, scales = "free") +
  geom_histogram(aes(y = ..density..)) +
  scale_x_continuous(breaks = scales::pretty_breaks(n = 3)) +
  theme_bw(base_size = 16) +
  theme(axis.text = element_text(size=6))

# Initialize dataframes with PSA output
# Dataframe of costs
df_c <- as.data.frame(matrix(0,
                             nrow = n_sim,
                             ncol = n_str))
colnames(df_c) <- v_names_str
# Dataframe of effectiveness
df_e <- as.data.frame(matrix(0,
                             nrow = n_sim,
                             ncol = n_str))
colnames(df_e) <- v_names_str

```

## 09.1 Conduct probabilistic sensitivity analysis

```

# Run Markov model on each parameter set of PSA input dataset
for(i in 1:n_sim){
  l_out_temp <- calculate_ce_out(df_psa_input[i, ])
  df_c[i, ] <- l_out_temp$Cost
}

```

```

df_e[i, ] <- l_out_temp$Effect
# Display simulation progress
if(i/(n_sim/10) == round(i/(n_sim/10), 0)) { # display progress every 10%
  cat('\r', paste(i/n_sim * 100, "% done", sep = " "))
}
}

```

## 09.2 Create PSA object for dampack

```

l_psa <- make_psa_obj(cost      = df_c,
                     effectiveness = df_e,
                     parameters  = df_psa_input,
                     strategies  = v_names_str)

```

### 09.2.1 Save PSA objects

```

save(df_psa_input, df_c, df_e, v_names_str, n_str, l_psa,
     file = "markov_sick-sicker_PSA_dataset.RData")

```

## 09.3 Create probabilistic analysis graphs

```

load(file = "markov_sick-sicker_PSA_dataset.RData")

```

Vector with willingness-to-pay (WTP) thresholds.

```

v_wtp <- seq(0, 200000, by = 10000)

```

### 09.3.1 Cost-Effectiveness Scatter plot

```

plot(l_psa)

```

## 09.4 Conduct CEA with probabilistic output

```

# Compute expected costs and effects for each strategy from the PSA
df_out_ce_psa <- summary(l_psa)

# Calculate incremental cost-effectiveness ratios (ICERs)
df_cea_psa <- calculate_icers(cost      = df_out_ce_psa$meanCost,
                             effect    = df_out_ce_psa$meanEffect,
                             strategies = df_out_ce_psa$Strategy)

df_cea_psa

# Save CEA table with ICERs
# As .RData
save(df_cea_psa,
     file = "markov_sick-sicker_probabilistic_CEA_results.RData")
# As .csv
write.csv(df_cea_psa,
          file = "markov_sick-sicker_probabilistic_CEA_results.csv")

```

### 09.4.1 Plot cost-effectiveness frontier

```
plot(df_cea_psa)
```

### 09.4.2 Cost-effectiveness acceptability curves (CEACs) and frontier (CEAF)

```
ceac_obj <- ceac(wtp = v_wtp, psa = l_psa)
# Regions of highest probability of cost-effectiveness for each strategy
summary(ceac_obj)
# CEAC & CEAF plot
plot(ceac_obj)
```

### 09.4.3 Expected Loss Curves (ELCs)

The expected loss is the the quantification of the foregone benefits when choosing a suboptimal strategy given current evidence.

```
elc_obj <- calc_exp_loss(wtp = v_wtp, psa = l_psa)
elc_obj
# ELC plot
plot(elc_obj, log_y = FALSE)
```

### 09.4.4 Expected value of perfect information (EVPI)

```
evpi <- calc_evpi(wtp = v_wtp, psa = l_psa)
# EVPI plot
plot(evpi, effect_units = "QALY")
```