Markov Sick-Sicker model in R

The DARTH workgroup

Developed by the Decision Analysis in R for Technologies in Health (DARTH) workgroup:

Fernando Alarid-Escudero, PhD (1)

Eva A. Enns, MS, PhD (2)

M.G. Myriam Hunink, MD, PhD (3,4)

Hawre J. Jalal, MD, PhD (5)

Eline M. Krijkamp, MSc (3)

Petros Pechlivanoglou, PhD (6,7)

Alan Yang, MSc (7)

In collaboration of:

- 1. Drug Policy Program, Center for Research and Teaching in Economics (CIDE) CONACyT, Aguas-calientes, Mexico
- 2. University of Minnesota School of Public Health, Minneapolis, MN, USA
- 3. Erasmus MC, Rotterdam, The Netherlands
- 4. Harvard T.H. Chan School of Public Health, Boston, USA
- 5. University of Pittsburgh Graduate School of Public Health, Pittsburgh, PA, USA
- 6. University of Toronto, Toronto ON, Canada
- 7. The Hospital for Sick Children, Toronto ON, Canada

Please cite our publications when using this code:

- Jalal H, Pechlivanoglou P, Krijkamp E, Alarid-Escudero F, Enns E, Hunink MG. An Overview of R in Health Decision Sciences. Med Decis Making. 2017; 37(3): 735-746. https://journals.sagepub.com/doi/abs/10.1177/0272989X16686559
- Krijkamp EM, Alarid-Escudero F, Enns EA, Jalal HJ, Hunink MGM, Pechlivanoglou P. Microsimulation modeling for health decision sciences using R: A tutorial. Med Decis Making. 2018;38(3):400–22. https://journals.sagepub.com/doi/abs/10.1177/0272989X18754513
- Krijkamp EM, Alarid-Escudero F, Enns E, Pechlivanoglou P, Hunink MM, Jalal H. A Multidimensional Array Representation of State-Transition Model Dynamics. BioRxiv 670612 2019.https://www.biorxiv.org/content/10.1101/670612v1

Copyright 2017, THE HOSPITAL FOR SICK CHILDREN AND THE COLLABORATING INSTITUTIONS. All rights reserved in Canada, the United States and worldwide. Copyright, trademarks, trade names and any and all associated intellectual property are exclusively owned by THE HOSPITAL FOR Sick CHILDREN and the collaborating institutions. These materials may be used, reproduced, modified, distributed and adapted with proper attribution.

```
rm(list = ls())  # clear memory (removes all the variables from the workspace)
```

01 Load packages

02 Load functions

```
# no functions needed
```

03 Input model parameters

```
# Strategy names
v_names_str <- c("No Treatment", "Treatment")</pre>
# Number of strategies
n_str <- length(v_names_str)</pre>
# Markov model parameters
      <- 25
age
                                   # age at baseline
max_age <- 55
                                   # maximum age of follow up
n_t <- max_age - age
                                  # time horizon, number of cycles
       <- c("H", "S1", "S2", "D") # the 4 states of the model: Healthy (H), Sick (S1),
v n
                                   # Sicker (S2), Dead (D)
n_states <- length(v_n)</pre>
                                   # number of health states
# Transition probabilities (per cycle)
       <- 0.005
                                    # probability to die when healthy
p_HD
        <- 0.15
                                   # probability to become sick when healthy
p_HS1
p_S1H <- 0.5
                                   # probability to become healthy when sick
p_S1S2 <- 0.105
                                   # probability to become sicker when sick
       <- 3
                                   # hazard ratio of death in sick vs healthy
hr_S1
hr S2
       <- 10
                                   # hazard ratio of death in sicker vs healthy
r_HD # <- your turn
                                  # rate of death in healthy
r_S1D # <- your turn
                                     # rate of death in sick
                               # rate of death in sicker
r_S2D # <- your turn
p_S1D # <- your turn
                                  # probability to die in sick
p_S2D  # <- your turn
                                   # probability to die in sicker
# Cost and utility inputs
c_H <- 2000
                                   # cost of remaining one cycle in the healthy state
c_S1 <- 4000
                                   # cost of remaining one cycle in the sick state
c_S2 <- 15000
                                   # cost of remaining one cycle in the sicker state
c_trt <- 12000
                                   # cost of treatment(per cycle)
```

```
c_D <- 0
                                     # cost of being in the death state
         <- 1
                                     # utility when healthy
u_H
        <- 0.75
                                     # utility when sick
u S1
                                     # utility when sicker
        <- 0.5
u S2
       <- 0
                                     # utility when dead
u_D
        <- 0.95
u_trt
                                     # utility when being treated
# Discounting factor
       <- 0.03
                                     # equal discount of costs and QALYs by 3%
d_r
\# calculate discount weights for costs for each cycle based on discount rate d_c
v_dwc <-1 / (1 + d_r) ^ (0:n_t)
 \hbox{\it\# calculate discount weights for effectiveness for each cycle based on discount rate $d\_e$ }
v_dwe <-1 / (1 + d_r) ^ (0:n_t)
```

04 Define and initialize matrices and vectors

04.1 Cohort trace

04.2 Transition probability matrix

Fill in the transition probability matrix:

```
# from Healthy
# from Sick
# from Sicker
# from Dead
# create transition probability matrix for treatment same as no treatment
m_P_trt <- m_P_notrt</pre>
```

05 Run Markov model

your turn

06 Compute and Plot Epidemiological Outcomes

06.1 Cohort trace

your turn

06.2 Overall Survival (OS)

your turn

06.2.1 Life Expectancy (LE)

your turn

06.3 Disease prevalence

your turn

06.4 ratio of sick(S1) vs sicker(S2)

your turn

07 Compute Cost-Effectiveness Outcomes

07.1 Mean Costs and QALYs for Treatment and NO Treatment

your turn

07.2 Discounted Mean Costs and QALYs

your turn

07.3 Compute ICERs of the Markov model

your turn

07.4 Plot frontier of the Markov model

your turn