A Tutorial on Time-Dependent Cohort State-Transition Models in R using a Cost-Effectiveness Analysis Example

Appendix

Fernando Alarid-Escudero, PhD* Eline Krijkamp, MSc[†] Eva A. Enns, PhD[‡] Alan Yang, MSc[§] Myriam G.M. Hunink, PhD[†]¶ Petros Pechlivanoglou, PhD[∥] Hawre Jalal, MD, PhD**

2021-08-30

Cohort tutorial model components

This table contains an overview of the key model components used in the code for the Sick-Sicker example from the DARTH manuscript: "A Tutorial on Time-Dependent Cohort State-Transition Models in R". The first column gives the mathematical notation for some of the model components that are used in the equations in the manuscript. The second column gives a description of the model component with the R name in the third column. The forth gives the data structure, e.g. scalar, list, vector, matrix etc, with the according dimensions of this data structure in the fifth column. The final column indicated the type of data that is stored in the data structure, e.g. numeric (5.2,6.3,7.4), category (A,B,C), integer (5,6,7), logical (TRUE, FALSE).

Element	Description	R name	Data structure	Dimensions	Data type
$\overline{n_t}$	Time horizon	n_t	scalar		numeric
v_s	Names of the health states	v_n	vector	${\tt n_states} \ge 1$	character
n_s	Number of health states	n_states	scalar		numeric
$n_{S_{tunnels}}$	Number of health states with tunnels	n_states_tunn	iels	numeric	
		scalar			

^{*}Division of Public Administration, Center for Research and Teaching in Economics (CIDE), Aguascalientes, AGS, Mexico

[†]Department of Epidemiology and Department of Radiology, Erasmus University Medical Center, Rotterdam, The Netherlands

[‡]Division of Health Policy and Management, University of Minnesota School of Public Health, Minneapolis, MN, USA

[§]The Hospital for Sick Children, Toronto

[¶]Center for Health Decision Sciences, Harvard T.H. Chan School of Public Health, Boston, USA

The Hospital for Sick Children, Toronto and University of Toronto, Toronto, Ontario, Canada

^{**}University of Pittsburgh, Pittsburgh, PA, USA

Element	Description	R name	Data structure	Dimensions	Data type
y_{str}	Names of the strategies	v_names_str	scalar		character
str	Number of strategies	n_str	scalar		character
l_c	Discount rate for costs	d_c	scalar		numeric
$l_{\mathbf{e}}$	Discount rate for effects	d_e	scalar		numeric
	Discount weights for costs	v_dwc	vector	$(n_t x 1) + 1$	numeric
	Discount weights for effects	v_dwe	vector	$(n_t x 1) + 1$	numeric
vcc	Within-cycle correction weights using Simpson's $1/3$ rule	V_WCC	vector	$(\texttt{n_t} \ \texttt{x} \ \texttt{1} \) + \texttt{1}$	numeric
$ge_{_0}$	Age at baseline	n_age_init	scalar		numeric
ge	Maximum age of follow up	n_age_max	scalar		numeric
I_{ad}	Cohort trace for age-dependency	m_M_ad	matrix	$(\mathtt{n_t}+1) \ge \mathtt{n_states}$	numeric
$I_{tunnels}$	Aggregated Cohort trace for state-dependency	m_M_tunnels	matrix	$(n_t + 1) \times n_s$ tates	numeric
n_0	Initial state vector	v_s_init	vector	1 x n_states	numeric
n_t	State vector in cycle t	v_mt	vector	$1 \times n$ _states	numeric
	Transition probabilities				
[H,S1]	From Healthy to Sick conditional on surviving	p_HS1	scalar		numeric
[S1,H]	From Sick to Healthy conditional on surviving	p_S1H	scalar		numeric
[S1,S2]	From Sick to Sicker conditional on surviving	p_S1S2	scalar		numeric
[H,D]	Constant rate of dying when Healthy (all-cause mortality rate)	r_HD	scalar		numeric
$r_{[S1,H]}$	Hazard ratio of death in Sick vs Healthy	hr_S1	scalar		numeric
$r_{[S2,H]}$	Hazard ratio of death in Sicker vs Healthy	hr_S2	scalar		numeric
$r_{[S1,S2]_{trtB}}$	Hazard ratio of becoming Sicker when Sick under treatment B	hr_S1S2_trtB	scalar		numeric
$[S1,S2]_{trtB}$	probability to become Sicker when Sick under treatment B conditional on surviving	p_S1S2_trtB	scalar		numeric
	Age-specific mortality				
[H,D,t]	Age-specific background mortality rates	v_r_{HDage}	vector	$\mathtt{n_t}$	$\operatorname{numeric}$
S1,D,t]	Age-specific mortality rates in the Sick state	v_r_S1Dage	vector	$\mathtt{n_t} \ge 1$	$\operatorname{numeric}$
S2,D,t]	Age-specific mortality rates in the Sicker state	v_r_S2Dage	vector	$\mathtt{n_t} \ge 1$	$\operatorname{numeric}$
H,D,t]	Age-specific mortality risk in the Healthy state	v_p_HDage	vector	$\mathtt{n_t} \ge 1$	numeric
S1,D,t]	Age-specific mortality rates in the Sick state	v_p_S1Dage	vector	$\mathtt{n_t} \ge 1$	numeric
[S2,D,t]	Age-specific mortality rates in the Sicker state	v_p_S2Dage	vector	$\mathtt{n_t} \ge 1$	$\operatorname{numeric}$
[S1,S2,t]	Time-dependent transition probabilities from sick to sicker	v_p_S1S2_tunnels	vector	n_t x 1	numeric

Element	Description	R name	Data structure	Dimensions	Data typ
	Annual costs				
	Healthy individuals	c_H	scalar		numeric
	Sick individuals in Sick	_	scalar		numeric
	Sick individuals in Sicker	c_S1			
	Dead individuals	c_S2 c_D	scalar scalar		numeric numeric
	Additional costs treatment A	_	scalar		
		c_trtA			numeric
	Additional costs treatment B	c_trtB	scalar		numeric
	Utility weights				
	Healthy individuals	u_H	scalar		numeric
	Sick individuals in Sick	u_S1	scalar		numeric
	Sick individuals in Sicker	u_S2	scalar		numeric
	Dead individuals	u_D	scalar		numeric
	Treated with treatment A	u_trtA	scalar		numeric
	Transition weights				
	Utility decrement of healthy individuals when	du_HS1	scalar		numeric
	transitioning to S1	- · · · -			
	Cost of healthy individuals when transitioning	ic_S1	scalar		numeric
	to S1		2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		
	Cost of dying	ic_D	scalar		numeric
	Lists				
	Cohort traces for each strategy	1_m_M	list		numeric
	Transition arrays for each strategy	1_A_A	list		numeric
	number of tunnel states	n_tunnel_size	scalar		numeric
	tunnel names of the Sick state	v_Sick_tunnel	vector	$1 \times n_{\mathtt{states}}$	numeric
	state names including tunnel states	v_n_tunnel	vector	1 x n_states	characte
	number of states including tunnel states	n_states_tunnels	scalar	1 11 11_D 0000D	numeric
	initial state vector for the model with tunnels	v_s_init_tunnels	Scarar		numeric
P	Time-dependent transition probability array	a_P	array	n_states x n_states	numeric
	F-111111111111111111111111111111111111	-	- U	x n_t	
$\mathbf{P}_{tunnels}$	Transition probability array for the model with	a_P_tunnels	array	${ t n_states_tunnels } \ { t x}$	numeric
	tunnels		-	$\mathtt{n}_{\mathtt{states_tunnels}}$ x	
				 n_t	

Element	Description	R name	Data structure	Dimensions	Data type
A	Transition dynamics array	a_A	array	n_s tates x n_s tates x $(n_t + 1)$	numeric
R_u	Transition rewards for effects	a_R_u	array	n_s tates x n_s tates x $(n_t + 1)$	numeric
R_c	Transition rewards for costs	a_R_c	array	$n_states \ x \ n_states \ x \ (n_t + 1)$	numeric
$\mathbf{Y}_{\mathbf{u}}$	Expected effects per states per cycle	a_Y_u	array	$n_states x n_states x (n_t + 1)$	numeric
Y_c	Expected costs per state per cycle	a_Y_c	array	$\begin{array}{l} {\tt n_states} \ x \ {\tt n_states} \\ x \ ({\tt n_t} + 1) \end{array}$	numeric
	Data structures				
	Expected QALYs per cycle under a strategy	v_qaly_str	vector	$1 \times (n_t + 1)$	numeric
	Expected costs per cycle under a strategy	v_cost_str	vector	$1 \times (n_t + 1)$	numeric
	Total expected discounted QALYs for a strategy	$n_tot_qaly_str$	scalar		$\operatorname{numeric}$
	Total expected discounted costs for a strategy	n_tot_cost_str	scalar		$\operatorname{numeric}$
	Summary of the model outcomes	df_cea	data frame		
	Summary of the model outcomes	table_cea	table		
	Input parameters values of the model for the cost-effectiveness analysis	df_psa	data frame		

Table II: Input parameters for probabilistic analysis of the time-dependent 3-state model

Parameter	Distribution	Distribution values	Parameter mean	Parameter standard
				error
Number of simulation	n_sim	1000		
Annual transition probabilities				
- Disease onset (Healthy to	Beta	$\alpha = 30, \beta = 170$	0.15	0.026
Sick)				
- Recovery (Sick to Healthy)	Beta	$\alpha = 60, \beta = 60$	0.5	0.045
- Disease progression (Sick to	Beta	$\alpha = 84, \beta = 716$	0.106	0.011
Sicker) in the age-dependent				
model				
Risks of disease and treatment				

Parameter	Distribution	Distribution values	Parameter mean	Parameter standard error
- Hazard ratio of death in Sick	Lognormal	$log(\mu) = log(3)$, $log(\sigma) = 0.01$	3	0.03
vs Healthy - Hazard ratio of death in Sicker vs Healthy	Lognormal	$log(\mu) = log(10) \ , log(\sigma) = 0.2$	10	0.2
- Hazard ratio of Sick to Sicker under treatment B Annual costs	Lognormal	$log(\mu) = log(0.6)$, $log(\sigma) = 0.2$	0.60	0.013
- Healthy individuals	Gamma	Shape = 100, $Scale = 20$	2000	200
- Sick individuals in Sick	Gamma	Shape = 177.8, Scale = 22.5	4000	300
- Sick individuals in Sicker	Gamma	Shape = 225, $Scale = 66.7$	15000	1000
- Cost of treatment A for individuals in Sick or Sicker	Gamma	Shape = 73.5, Scale = 163.3	12000	1400
- Cost of treatment B for individuals in Sick or Sicker Utility weights	Gamma	Shape=86.2,Scale=150.8	13050	1430
- Healthy individuals	Beta	$\alpha = 200, \beta = 3$	0.985	0.008
- Sick individuals in Sick	Beta	$\alpha = 130, \beta = 45$	0.74	0.033
- Sick individuals in Sicker	Beta	$\alpha=230,\beta=230$	0.5	0.023
- Individuals treated with treatment A Transition rewards	Beta	$\alpha = 300, \beta = 15$	0.95	0.012
- Disutility when transitioning from Healthy to Sick	Beta	$\alpha=11,\beta=1088$	0.01	0.003
- Increase in cost when transitioning from Healthy to Sick	Gamma	$\alpha=25,\beta=40$	1000	195
- Increase in cost when dying	Gamma	$\alpha = 100, \beta = 20$	2000	200