

Class Method



Expressions

Computing with Primitive Types

- For the primitive types `int`, `double`, and `boolean`, Java supports a notation for expressions that appeals to the one that we use in arithmetic and algebra courses.
- For example, we can write
 - `10 * 12.50`
 - `width + height`
 - `Math.PI * radius`



Arithmetic and Relation Operators

Symbol	Parameter types	Result	Example	
+	numeric, numeric	numeric	$x + 2$	addition
-	numeric, numeric	numeric	$x - 2$	subtraction
*	numeric, numeric	numeric	$x * 2$	multiplication
/	numeric, numeric	numeric	$x / 2$	division
%	integer, integer	integer	$x \% y$	modulo

>	numeric, numeric	boolean	$x > 2$	greater than
>=	numeric, numeric	boolean	$x >= 2$	greater or equal
<	numeric, numeric	boolean	$x < 2$	less than
<=	numeric, numeric	boolean	$x <= 2$	less or equal
==	numeric, numeric	boolean	$x == 2$	equal
!=	numeric, numeric	boolean	$x != 2$	not equal



Logic Operators

Symbol	Parameter types	Result	Example	
!	boolean	boolean	!(x < 0)	logical negation
&&	boolean, boolean	boolean	a && b	logical and
	boolean, boolean	boolean	a b	logical or

- Example

(x != 0) && (x < 10) . . . determines whether a is not equal to x (int or double) and x is less than 10



Expressions - Method Calls

- A method is roughly like a function. Like a function, a method **consumes data** and **produces data**.
- However, a METHOD is associated with a class.

Example:

- To compute the length of the string in Java, we use the **Length** method from the **String** class like this:
`"hello world".length()`
- To concatenate "world" to the end of the "hello"
`String str = "hello";`
`str.concat("world");`
- `Math.sqrt(10)` is square of 10



Method Calls

- When the method is called, it always receives at least ***one argument***: **an instance (object) of the class** with which the method is associated;
- Speaks of **INVOKING a method on an instance or object**
- In general, a method call has this shape:
object.methodName(arg1, arg2, ...)



Design Class Method Steps

The design of methods follows the same design recipes

1. Problem analysis and data definitions

- Specify pieces of information the method needs and output information

2. Purpose and contract (method signature)

- The purpose statement is just a comment that describes the method's task in general terms.
- The method signature is a specification of inputs and outputs, or **contract** as we used to call it.



Design Class Method Steps

3. Examples

- the creation of examples that illustrate the purpose statement in a concrete manner

4. Method template

- lists all parts of data available for the computation inside of the body of the method

5. Method definition

- Implement method

6. Tests

- to turn the examples into executable tests



Coffee Seller Example

Take a look at this revised version of our first problem . . . Design a method that ***computes the cost of selling bulk coffee*** at a specialty coffee seller from a receipt that includes the ***kind of coffee***, the ***unit price***, and the ***total amount*** (weight) sold. . .

- Examples

- 1) 100 pounds of Hawaiian Kona at \$15.95/pound
→ \$1,595.00
- 2) 1,000 pounds of Ethiopian coffee at \$8.00/pound
→ \$8,000.00
- 3) 1,700 pounds of Colombian Supreme at \$9.50/pound
→ 16,150.00

1. Problem analysis and data definitions

```
class Coffee {  
    String kind;  
    double price;  
    double weight;  
    Coffee(String kind, double price,  
            double weight) {  
        this.kind = kind;  
        this.price = price;  
        this.weight = weight;  
    }  
}
```

Coffee

- String kind
- double price
- double weight

```
import junit.framework.*;  
public class CoffeeTest extends TestCase {  
    public void testConstructor() {  
        new Coffee("Hawaiian Kona", 15.95, 100);  
        new Coffee("Ethiopian", 8.0, 1000);  
        new Coffee("Colombian Supreme ", 9.5, 1700);  
    }  
}
```

1. Problem analysis and data definitions

- Methods are a part of a class.
- Thus, if the **Coffee** class already had a **cost** method, we could write:
`new Coffee("Kona", 15.95, 100).cost()`
and expect this method call to produce 1595.0.
- The only piece of information the method needs is ***the instance of the class Coffee*** for which we are computing the selling cost.
- It will produce a **double value** that represents the selling **cost**.

Coffee
- String kind - double price - double weight
??? cost(???)

2. Purpose and contract

- First we add a contract, a purpose statement, and a header for *cost* to the *Coffee* class

```
// the bill for a Coffee sale
class Coffee {
    String kind;
    double price; // in dollars per pound
    double weight; // in pounds
    Coffee(String kind, double price, double weight) {
        ...
    }

    // to compute the total cost of this coffee purchase
    // [in dollars]
    double cost() { ... }
}
```

↑

a **purpose** statement

Contract is a **METHOD SIGNATURE**



3. Examples

- `new Coffee("Hawaiian Kona", 15.95, 100).cost()`
// should produce 1595.0
- `new Coffee("Ethiopian", 8.0, 1000).cost()`
// should produce 8000.0
- `new Coffee("Colombian", 9.5, 1700).cost()`
// should produce 16150.0



Primary argument: **this**

- **cost** method is always invoked on some specific **instance** of **Coffee**.
 - The **instance** is the **primary argument** to the method, and it has a standard name, **this**
- We can thus use **this** to refer to the instance of **Coffee** and access to three pieces of data: the **kind**, the **price**, and the **weight** in method body
 - Access field with: **object.field**
 - E.g: **this.kind**, **this.price**, **this.weight**



4. **cost** method template

```
// to compute the total cost of this coffee purchase
// [in cents]
double cost() {
    ...this.kind...
    ...this.price...
    ...this.weight...
}
```



5. `cost` method result

- The two relevant pieces are `this.price` and `this.weight`. If we multiply them, we get the result that we want:

```
// to compute the total cost of this coffee purchase
// [in cents]
double cost() {
    return this.price * this.weight;
}
```




5. Coffee class and method

```
class Coffee {  
    String kind;  
    double price;  
    double weight;  
  
    Coffee(String kind, double price, double weight) {  
        this.kind = kind;  
        this.price = price;  
        this.weight = weight;  
    }  
  
    // to compute the total cost of this coffee purchase  
    // [in dollars]  
    double cost() {  
        return this.price * this.weight;  
    }  
}
```

6. Test **cost** method

```
import junit.framework.TestCase;
public class CoffeeTest extends TestCase {
    public void testConstructor() {
        ...
    }

    public void testCost() {
        assertEquals(
            new Coffee("Hawaiian Kona", 15.95, 100).cost(), 1595.0);
        Coffee c2 = new Coffee("Ethiopian", 8.0, 1000);
        assertEquals(c2.cost(), 8000.0);
        Coffee c3 = new Coffee("Colombian Supreme ", 9.5, 1700);
        assertEquals(c3.cost(), 16150.0);
    }
}
```



Methods consume more data

Design method to such problems:

... The coffee shop owner may wish to find out whether a coffee sale involved a price over a certain amount ...

Coffee
<ul style="list-style-type: none">- String kind- double price- double weight
<code>double cost()</code> <code>??? priceOver(???)</code>



Purpose statement and signature

- This method must consume two arguments:
 - given instance of coffee: **this**
 - a second argument, the **number of dollars** with which it is to compare the ***price*** of the sale's record.

```
// to determine whether this coffee's price is more  
// than amount  
boolean priceOver(double amount) { ... }
```



Examples

- `new Coffee("Hawaiian Kona", 15.95, 100)`
 `.priceOver(12)`
 expected true
- `new Coffee("Ethiopian", 8.00,`
 `1000).priceOver(12)`
 expected false
- `new Coffee("Colombian Supreme ", 9.50,`
 `1700).priceOver(12)`
 expected false



priceOver method template and result

```
// to determine whether this coffee's price is more than amount
boolean priceOver(double amount) {
    ... this.kind
    ... this.price
    ... this.weight
    ... amount
}
```

The only relevant pieces of data in the template are *amount* and *this.price*:

```
// to determine whether this coffee's price is more than amount
boolean priceOver(double amount) {
    return this.price > amount;
}
```

Test **priceOver** method

```
import junit.framework.TestCase;
public class CoffeeTest extends TestCase {
    ...


    public void testPriceOver() {
        assertTrue(new Coffee("Hawaiian Kona", 15.95, 100)
            .priceOver(12));
        Coffee c2 = new Coffee("Ethiopian", 8.00, 1000);
        Coffee c3 = new Coffee("Colombian Supreme ", 9.50, 1700);
        assertFalse(c2.priceOver(12));
        assertFalse(c3.priceOver(12));
    }
}
```



Cartesian Point example

- Suppose we wish to represent the pixels (colored dots) on our computer monitors.
 - A pixel is very much like a Cartesian point. It has an **x coordinate**, which tells us where the pixel is in the horizontal direction, and it has a **y coordinate**, which tells us where the pixel is located in the downwards vertical direction.
 - Given the two numbers, we can locate a pixel on the monitor
- Computes how far some pixel is from the origin
- Computes the distance between 2 pixels

Class diagram, Define Class and Test



```
class CartPt {  
    int x;  
    int y;  
    CartPt(int x, int y) {  
        this.x = x;  
        this.y = y;  
    }  
}
```

```
import junit.framework.*;  
public class CartPtTest extends TestCase {  
    public void testConstrutor() {  
        new CartPt(5, 12);  
        CartPt aCartPt1 = new CartPt(0, 3);  
        CartPt aCartPt2 = new CartPt(3, 4);  
    }  
}
```



Computes

How far some pixel is from the origin

CartPt
int x int y
??? distanceToO(???)



distanceTo0 method signature

inside of CartPt

```
// Computes how far this pixel is from the origin  
double distanceTo0() { ... }
```

- Examples
 - `new CartPt(5, 12).distanceTo0()` should be 13.0
 - `new CartPt(0, 3).distanceTo0()` should be 3.0
 - `new CartPt(4, 7).distanceTo0()` should be 8.062

distanceTo0 method template

```
class CartPt {  
    int x;  
    int y;  
  
    CartPt(int x, int y) {  
        this.x = x;  
        this.y = y;  
    }  
  
    // Computes how far this pixel is from the origin  
    double distanceTo0() {  
        ...this.x...  
        ...this.y...  
    }  
}
```

Add a contract, a purpose statement
METHOD SIGNATURE



distanceTo0 method implementation

```
class CartPt {  
    int x;  
    int y;  
  
    CartPt(int x, int y) {  
        this.x = x;  
        this.y = y;  
    }  
  
    // Computes how far this pixel is from the origin  
    double distanceTo0() {  
        return Math.sqrt(this.x * this.x + this.y * this.y);  
    }  
}
```



Test **distanceTo0** method

```
import junit.framework.*;
public class CartPtTest extends TestCase {
    ...

    public void testDistanceTo0() {
        assertEquals(new CartPt(5, 12).distanceTo0(), 13.0, 0.001);
        CartPt aCartPt1 = new CartPt(0, 3);
        assertEquals(aCartPt1.distanceTo0(), 3.0, 0.001);
        CartPt aCartPt2 = new CartPt(4, 7);
        assertEquals(aCartPt2.distanceTo0(), 8.062, 0.001);
    }
}
```



Computes the distance between 2 pixels

CartPt
int x int y
double distanceToO() ??? distanceTo(???)



distanceTo Method Signature

inside of CartPt

```
// Computes distance from this CartPt to another  
CartPt
```

```
double distanceTo(CartPt that) { ... }
```

- Examples
 - `new CartPt(6, 8).distanceTo(new CartPt(3, 4))`
should be 5.0
 - `new CartPt(0, 3).distanceTo(new CartPt(4, 0))` should be 5.0
 - `new CartPt(1, 2).distanceTo(new CartPt(5, 3))` should be 4.123

distanceTo method template

```
class CartPt {  
    int x;  
    int y;  
    ...  
    // Computes how far this pixel is from the origin  
    double distanceTo0() {  
        return Math.sqrt(this.x * this.x + this.y * this.y);  
    }  
  
    // Computes distance from this CartPt to another CartPt  
    double distanceTo(CartPt that) {  
        ...this.x...this.y...  
        ...that.x...that.y...  
        ...this.distanto0()...that.distanceTo0()...  
    }  
}
```

Add a contract, a purpose statement
METHOD SIGNATURE



distanceTo method implement

```
class CartPt {  
    int x;  
    int y;  
    ...  
    // Computes how far this pixel is from the origin  
    double distanceTo0() {  
        return Math.sqrt(this.x * this.x + this.y * this.y);  
    }  
  
    // Computes distance from this CartPt to another CartPt  
    double distanceTo(CartPt that) {  
        return Math.sqrt((that.x - this.x)*(that.x - this.x)  
            + (that.y - this.y)*(that.y - this.y));  
    }  
}
```



Test **distanceTo** method

```
import junit.framework.*;
public class CartPtTest extends TestCase {
    ...


    public void testDistanceTo() {
        assertEquals(new CartPt(6, 8).distanceTo(
            new CartPt(3, 4)), 5.0, 0.001);

        assertEquals(new CartPt(0, 3).distanceTo(
            new CartPt(4, 0)), 5.0, 0.001);

        CartPt aCartPt1 = new CartPt(1, 2);
        CartPt aCartPt2 = new CartPt(5, 3);
        assertEquals(aCartPt1.distanceTo(aCartPt2), 4.123, 0.001);
    }
}
```



Class diagram - Final






Object Compare



Star example

- Suppose we wish to represent a **star** information which has **first name**, **last name**, **instrument** he uses and his **sales**.
- Design methods:
 - Check whether one star's sales is greater than another star's sales.
 - Check whether one star is same another star.

Class Diagram





Define Class and Constructor

```
class Star {  
    String firstName;  
    String lastName;  
    String instrument;  
    int sales;  
  
    // constructor  
    Star(String firstName, String lastName,  
        String instrument, int sales) {  
        this.firstName = firstName;  
        this.lastName = lastName;  
        this.instrument = instrument;  
        this.sales = sales;  
    }  
}
```




Test **Star** Constructor

```
import junit.framework.*;

class TestStar extends TestCase {
    void testConstructor() {
        new Star("Abba", "John", "vocals", 12200);
        new Star("Elton", "John", "guitar", 20000);
        new Star("Debie", "Gission", "organ", 15000);
    }
}
```



Check whether one star's sales is greater than another star's sales.

Star
String firstName String lastName String instrument int sales
??? biggerSales(???)

biggerSales() Method Signature

inside of **Star** class

```
// check whether this star's sales is greater than  
// another star's sales  
boolean biggerSales(Star other) { ... }
```

- Examples

```
new Star("Elton", "John", "guitar", 20000)  
.biggerSales(new Star("Abba", "John",  
"vocals", 12200)) expected true
```

```
new Star("Abba", "John", "vocals", 12200)  
.biggerSales(new Star("Debie", "Gission",  
"organ", 15000)) expected false
```



biggerSales() method template

```
class Star {
    String firstName;
    String lastName;
    String instrument;
    int sales;
    ...

    // check whether this star's sales is greater than
    // another star's sales
    boolean biggerSales(Star other) {
        ...this.firstName...this.lastName...
        ...this.instrument...this.sales...
        ...other.firstName...other.lastName...
        ...other.instrument...other.sales...
    }
}
```



biggerSales method implement

```
class Star {  
    String firstName;  
    String lastName;  
    String instrument;  
    int sales;  
    ...  
  
    // check whether this star's sales is greater than  
    // another star's sales  
    boolean biggerSales(Star other) {  
        return (this.sales > other.sales);  
    }  
}
```



biggerSales() method test

```
import junit.framework.TestCase;

public class StarTest extends TestCase {
    ...
    public void testBiggerSales () {
        Star aStar1 = new Star("Abba", "John", "vocals", 12200);
        assertTrue(new Star("Elton", "John", "guitar", 20000)
                    .biggerSales(aStar1));
        assertFalse(aStar1.biggerSales(
            new Star("Debie", "Gission", "organ", 15000)));
    }
}
```

Compare equals of 2 objects

- Check whether one star is same another star.

Star
String firstName String lastName String instrument int sales
boolean biggerSales(Star other) ??? same(???)

same() Method Signature

inside of **Star** class

```
// check whether this star is same another star  
boolean same(Star other) { ... }
```

- Examples

```
new Star("Elton", "John", "guitar", 20000)  
.same(new Star("Elton", "John", "guitar",  
20000)) expected true
```

```
new Star("Elton", "John", "guitar", 20000)  
.same(new Star("Debie", "Gission", "organ",  
15000)) expected false
```




same() method template

```
class Star {  
    String firstName;  
    String lastName;  
    String instrument;  
    int sales;  
    ...  
  
    // check whether this star is same another star  
    boolean same(Star other) {  
        ...this.firstName...this.lastName...  
        ...this.instrument...this.sales...  
        ...this.biggerSales(...)  
        ...other.firstName...other.lastName...  
        ...other.instrument...other.sales...  
        ...other.biggerSales(...)  
    }  
}
```



same() method implement

```
class Star {  
    String firstName;  
    String lastName;  
    String instrument;  
    int sales;  
    ...  
  
    // check whether this star is same another star  
    boolean same(Star other) {  
        return (this.firstName.equals(other.firstName)  
            && this.lastName.equals(other.lastName)  
            && this.instrument.equals(other.instrument)  
            && this.sales == other.sales);  
    }  
}
```

same() method test

```
import junit.framework.TestCase;
public class StarTest extends TestCase {
    ...
    public void testSame() {
        assertTrue(new Star("Abba", "John", "vocals", 12200)
            .same(new Star("Abba", "John", "vocals", 12200)));

        Star aStar1 = new Star("Elton", "John", "guitar", 20000);
        assertTrue(aStar1.same(
            new Star("Elton", "John", "guitar", 20000)));

        Star aStar2 = new Star("Debie", "Gission", "organ", 15000);
        Star aStar3 = new Star("Debie", "Gission", "organ", 15000);
        assertFalse(aStar1.same(aStar2));
        assertTrue(aStar2.same(aStar3));
    }
}
```



Other solution: `equals` method

- **A:** Why we do not use JUnit built-in `assertEquals` method?
- **Q:** Can override build-in `equals` method


```
class Star {
    String firstName;
    String lastName;
    String instrument;
    int sales;
    ...
    public boolean equals(Object obj) {
        if (null == obj || !(obj instanceof Star))
            return false;
        else { Star that = (Star) obj;
            return this.firstName.equals(that.firstName)
                && this.lastName.equals(that.lastName)
                && this.instrument.equals(that.instrument)
                && this.sales == that.sales;
        }
    }
}
```

equals method test

```
import junit.framework.TestCase;
public class StarTest extends TestCase {
    ...
    public void testEquals() {
        assertFalse(new Star("Abba", "John", "vocals", 12200)
            .equals(new Star("Abba", "John", "vocals", 20000)));

        assertEquals(new Star("Elton", "John", "guitar", 20000),
            new Star("Elton", "John", "guitar", 20000));

        Star aStar1 = new Star("Debie", "Gission", "organ", 15000);
        Star aStar2 = new Star("Debie", "Gission", "organ", 15000);
        assertEquals(aStar1, aStar2);
    }
}
```



Conditional Computations



Conditional Computation Example

- . . . Develop a method that computes the yearly interest for *certificates of deposit* (CD) for banks. The interest rate for a CD depends on the amount of deposited money. Currently, the bank pays 2% for amounts up to \$5,000, 2.25% for amounts between \$5,000 and \$10,000, and 2.5% for everything beyond that. . . .



Define Class

CD
String owner int amount

```
class CD {  
    String owner;  
    int amount; // cents  
  
    CD(String owner, int amount) {  
        this.owner = owner;  
        this.amount = amount;  
    }  
}
```




interest method signature

CD
String owner int amount
??? interest(???)

```
// computes the yearly interest for this CD  
double interest() { ... }
```



Example

- Translating the intervals from the problem analysis into tests yields three “interior” examples:
 - `new CD("Kathy", 250000).interest()` expect 5000.0
 - `new CD("Matthew", 510000).interest()` expect 11475.0
 - `new CD("Shriram", 1100000).interest()` expect 27500.0



Conditional computation

- To express this kind of conditional computation, Java provides the so-called IF-STATEMENT, which can distinguish two possibilities:

```
if (condition) {  
    statement1  
}
```

```
if (condition) {  
    statement1  
}  
else {  
    statement2  
}
```

```
if (condition1) {  
    statement1  
}  
else {  
    if (condition2) {  
        statement2  
    }  
    else {  
        statement3  
    }  
}
```



interest method template

```
// compute the interest rate for this account
double interest() {
    if (0 <= this.amount && this.amount < 500000) {
        ...this.owner...this.amount...
    }
    else {
        if (500000 <= this.amount && this.amount < 1000000) {
            ...this.owner...this.amount...
        }
        else {
            ...this.owner...this.amount...
        }
    }
}
```



interest() method implement

```
// compute the interest rate for this account
double interest() {
    if (0 <= this.amount && this.amount < 500000) {
        return 0.02 * this.amount;
    }
    else {
        if (500000 <= this.amount && this.amount < 1000000) {
            return 0.0225 * this.amount;
        }
        else {
            return 0.025 * this.amount;
        }
    }
}
```



interest() full implement

```
// compute the interest rate for this account
```

```
double interest() {  
    if (this.amount < 0) {  
        return 0;  
    }  
    else {  
        if (this.amount < 500000) {  
            return 0.02 * this.amount;  
        }  
        else {  
            if (this.amount < 1000000) {  
                return 0.0225 * this.amount;  
            }  
            else {  
                return 0.025 * this.amount;  
            }  
        }  
    }  
}
```



interest() full implement

```
// compute the interest rate for this account
double interest() {
    if (this.amount < 0)
        return 0;
    else
        if (this.amount < 500000)
            return 0.02 * this.amount;
        else
            if (this.amount < 1000000)
                return 0.0225 * this.amount;
            else
                return 0.025 * this.amount;
}
```



interest() different implement

```
// compute the interest rate for this account
double interest() {
    if (this.amount < 0)
        return 0;
    if (this.amount < 500000)
        return 0.02 * this.amount;
    if (this.amount < 1000000)
        return 0.0225 * this.amount;
    return 0.025 * this.amount;
}
```