Decision Analysis in R for Technologies in Health

Appendix A

Microsimulation modeling for health decision sciences using R: A tutorial.

March 2018

Fernando Alarid-Escudero, PhD¹ Eva A. Enns, MS, PhD¹ M.G. Myriam Hunink, MD, PhD^{2,3} Hawre J. Jalal, MD, PhD⁴ Eline M. Krijkamp, MSc² Petros Pechlivanoglou, PhD⁵

Acknowledgements and attribution.

Please cite our papers when using any of the material

Jalal H, et al. An Overview of R in Health Decision Sciences. *Med. Dec. Mak.* 2017; 37(3): 735-746. Krijkamp EM, et al. Microsimulation modeling for health decision sciences using R: A tutorial. Med Decis Making. 2018;38(3):400-22.

In collaboration of:

- ¹ University of Minnesota School of Public Health, Minneapolis, MN, USA
- ² Erasmus MC, Rotterdam, The Netherlands
- ³ Harvard T.H. Chan School of Public Health, Boston, USA
- ⁴ University of Pittsburgh Graduate School of Public Health, Pittsburgh, PA, USA
- ⁵ The Hospital for Sick Children, Toronto and University of Toronto, Toronto ON, Canada

© Copyright 2017, THE HOSPITAL FOR SICK CHILDREN AND THE COLLABORATING INSTITUTIONS. All rights reserved in Canada, the United States and worldwide. Copyright, trademarks, trade names and any and all associated intellectual property are exclusively owned by THE HOSPITAL FOR SICK CHILDREN and the collaborating institutions and may not be used, reproduced, modified, distributed or adapted in any way without written permission.

Appendix A - Microsimulation modeling for health decision sciences using R: A tutorial.

Krijkamp EM, Alarid-Escudero F, Enns EA, Jalal HJ, Hunink MGM, Pechlivanoglou P.

2018

This code forms the basis for the microsimulation model of the article: Krijkamp EM, Alarid-Escudero F, Enns EA, Jalal HJ, Hunink MGM, Pechlivanoglou P. Microsimulation modeling for health decision sciences using R: A tutorial. Med Decis Making. 2018;38(3):400-22.

Please cite the article when using this code.

See GitHub for more information or code updates https://github.com/DARTH-git/Microsimulation-tutorial

To program this tutorial we made use of R: 3.3.0 GUI 1.68 Mavericks build (7202) RStudio: Version 1.0.136 2009-2016 RStudio, Inc.

Code of Appendix A

```
#rm(list = ls()) # remove any variables in R's memory
```

Model input

```
# Model input
n.i <- 100000  # number of simulated individuals
n.t <- 30  # time horizon, 30 cycles
v.n <- c("H","S1","S2","D") # the model states: Healthy (H), Sick (S1), Si
cker (S2), Dead (D)
n.s <- length(v.n)  # the number of health states
v.M_1 <- rep("H", n.i)  # everyone begins in the healthy state
d.c <- d.e <- 0.03  # equal discounting of costs and QALYs by 3%
v.Trt <- c("No Treatment", "Treatment") # store the strategy names</pre>
```

Transition probabilities (per cycle)

```
p.HD
       <- 0.005
                                # probability to die when healthy
                                # probability to become sick when healthy
p.HS1 <- 0.15
                                # probability to become healthy when sick
p.S1H <- 0.5
                                # probability to become sicker when sick
p.S1S2 <- 0.105
                                # rate ratio of death when sick vs healthy
rr.S1 <- 3
rr.S2 <- 10
                                # rate ratio of death when sicker vs healthy
                             # rate of death when healthy
r.HD \leftarrow -\log(1 - p.HD)
r.S1D <- rr.S1 * r.HD
                               # rate of death when sick
r.S2D <- rr.S2 * r.HD
                               # rate of death when sicker
```

```
p.S1D <- 1 - exp(- r.S1D) # probability to die when sick
p.S2D <- 1 - exp(- r.S2D) # probability to die when sicker
```

Cost and utility inputs

```
<- 2000
c.H
                              # cost of remaining one cycle healthy
c.S1
       <- 4000
                              # cost of remaining one cycle sick
c.S2
      <- 15000
                              # cost of remaining one cycle sicker
c.Trt <- 12000
                              # cost of treatment (per cycle)
       <- 1
                              # utility when healthy
u.H
u.S1
       <- 0.75
                              # utility when sick
u.S2 <- 0.5
                              # utility when sicker
u.Trt <- 0.95
                              # utility when sick(er) and being treated
```

Functions

The MicroSim function for the simple microsimulation of the 'Sick-Sicker' model keeps track of what happens to each individual during each cycle.

```
MicroSim <- function(v.M_1, n.i, n.t, v.n, d.c, d.e, TR.out = TRUE, TS.out =
TRUE, Trt = FALSE, seed = 1) {
# Arguments:
 # v.M_1: vector of initial states for individuals
 # n.i:
            number of individuals
          total number of cycles to run the model vector of health state names
 # n.t:
 # v.n:
 # d.c:
           discount rate for costs
 # d.e: discount rate for health outcome (QALYs)
 # TR.out: should the output include a microsimulation trace? (default is T
RUE)
# TS.out: should the output include a matrix of transitions between states
? (default is TRUE)
 # Trt: are the n.i individuals receiving treatment? (scalar with a Bool
ean value, default is FALSE)
            starting seed number for random number generator (default is 1)
 # seed:
# Makes use of:
 # Probs: function for the estimation of transition probabilities
 # Costs: function for the estimation of cost state values
            function for the estimation of state specific health outcomes (Q
 # Effs:
ALYs)
 v.dwc < -1 / (1 + d.c) ^ (0:n.t) # calculate the cost discount weight bas
ed on the discount rate d.c
 v.dwe <- 1 / (1 + d.e) ^ (0:n.t) # calculate the QALY discount weight bas
ed on the discount rate d.e
# create the matrix capturing the state name/costs/health outcomes for all i
ndividuals at each time point
```

```
m.M \leftarrow m.C \leftarrow m.E \leftarrow matrix(nrow = n.i, ncol = n.t + 1,
                                dimnames = list(paste("ind", 1:n.i, sep = " ")
                                                paste("cycle", 0:n.t, sep = "
")))
 m.M[, 1] < - v.M_1
                                        # indicate the initial health state
  for (i in 1:n.i) {
    set.seed(seed + i)
                                        # set the seed for every individual f
or the random number generator
    m.C[i, 1] <- Costs(m.M[i, 1], Trt) # estimate costs per individual for t
he initial health state conditional on treatment
    m.E[i, 1] <- Effs (m.M[i, 1], Trt) # estimate QALYs per individual for t
he initial health state conditional on treatment
    for (t in 1:n.t) {
      v.p <- Probs(m.M[i, t]) # calculate the transition probabilit</pre>
ies at cycle t
      m.M[i, t + 1] <- sample(v.n, prob = v.p, size = 1) # sample the next h
ealth state and store that state in matrix m.M
      m.C[i, t + 1] <- Costs(m.M[i, t + 1], Trt) # estimate costs per indiv</pre>
idual during cycle t + 1 conditional on treatment
      m.E[i, t+1] \leftarrow Effs(m.M[i, t+1], Trt) # estimate QALYs per indiv
idual during cycle t + 1 conditional on treatment
    } # close the loop for the time points
    if(i/100 == round(i/100,0)) { # display the progress of the simu
Lation
      cat('\r', paste(i/n.i * 100, "% done", sep = " "))
  } # close the loop for the individuals
 tc <- m.C %*% v.dwc # total (discounted) cost per individual
  te <- m.E %*% v.dwe
                           # total (discounted) QALYs per individual
 tc_hat <- mean(tc)  # average (discounted) cost
te_hat <- mean(te)  # average (discounted) QALYs</pre>
  if (TS.out == TRUE) { # create a matrix of transitions across states
    TS <- paste(m.M, cbind(m.M[, -1], NA), sep = "->") # transitions from one
state to the other
    TS <- matrix(TS, nrow = n.i)
    rownames(TS) <- paste("Ind", 1:n.i, sep = " ") # name the rows</pre>
    colnames(TS) <- paste("Cycle", 0:n.t, sep = " ") # name the columns</pre>
  } else {
   TS <- NULL
```

```
if (TR.out == TRUE) { # create a trace from the individual trajectories
    TR <- t(apply(m.M, 2, function(x) table(factor(x, levels = v.n, ordered =
TRUE))))
    TR <- TR / n.i
                                                          # create a distribut
ion trace
                                                        # name the rows
    rownames(TR) <- paste("Cycle", 0:n.t, sep = " ")</pre>
    colnames(TR) <- v.n</pre>
                                                         # name the columns
  } else {
   TR <- NULL
  results <- list(m.M = m.M, m.C = m.C, m.E = m.E, tc = tc, te = te, tc_hat =
tc hat, te hat = te hat, TS = TS, TR = TR) # store the results from the simul
ation in a list
  return(results) # return the results
} # end of the MicroSim function
```

Probability function

The Probs function that updates the transition probabilities of every cycle is shown below.

```
Probs <- function(M_it) {</pre>
             health state occupied by individual i at cycle t (character vari
  # M it:
able)
  v.p.it <- rep(NA, n.s)
                            # create vector of state transition probabilitie
S
                             # name the vector
  names(v.p.it) <- v.n</pre>
  # update v.p.it with the appropriate probabilities
  v.p.it[M_it == "H"] <- c(1 - p.HS1 - p.HD, p.HS1, 0, p.HD)
# transition probabilities when healthy
  v.p.it[M it == "S1"] <- c(p.S1H, 1- p.S1H - p.S1S2 - p.S1D, p.S1S2, p.S1D)
# transition probabilities when sick
  v.p.it[M_it == "S2"] \leftarrow c(0, 0, 1 - p.S2D, p.S2D)
# transition probabilities when sicker
  v.p.it[M_it == "D"] <- c(0, 0, 0, 1)
# transition probabilities when dead
  ifelse(sum(v.p.it) == 1, return(v.p.it), print("Probabilities do not sum to
1")) # return the transition probabilities or produce an error
```

Costs function

The Costs function estimates the costs at every cycle.

```
Costs <- function (M_it, Trt = FALSE) {
    # M_it: health state occupied by individual i at cycle t (character variable)</pre>
```

Health outcome function

The Effs function to update the utilities at every cycle.

```
Effs <- function (M it, Trt = FALSE, cl = 1) {</pre>
 # M_it: health state occupied by individual i at cycle t (character variabl
e)
 # Trt: is the individual treated? (default is FALSE)
  # cl: cycle length (default is 1)
  u.it <- 0
                                 # by default the utility for everyone is zer
  u.it[M_it == "H"] <- u.H # update the utility if healthy</pre>
  u.it[M it == "S1"] <- Trt * u.Trt + (1 - Trt) * u.S1 # update the utility
if sick conditional on treatment
  u.it[M_it == "S2"] <- u.S2 # update the utility if sicker</pre>
  QALYs <- u.it * cl
                               # calculate the QALYs during cycle t
  return(QALYs)
                               # return the OALYs
}
```

Run the simulation

```
sim_no_trt <- MicroSim(v.M_1, n.i, n.t, v.n, d.c, d.e, Trt = FALSE) # run fo
r no treatment
sim_trt <- MicroSim(v.M_1, n.i, n.t, v.n, d.c, d.e, Trt = TRUE) # run fo
r treatment</pre>
```

Cost-effectiveness analysis

```
# store the mean costs (and the MCSE) of each strategy in a new variable v.C
(vector costs)
v.C <- c(sim_no_trt$tc_hat, sim_trt$tc_hat)
se.C <- c(sd(sim_no_trt$tc), sd(sim_trt$tc)) / sqrt(n.i)
# store the mean QALYs (and the MCSE) of each strategy in a new variable v.E
(vector health outcomes)
v.E <- c(sim_no_trt$te_hat, sim_trt$te_hat)
se.E <- c(sd(sim_no_trt$te), sd(sim_trt$te)) / sqrt(n.i)</pre>
```

```
delta.C <- v.C[2] - v.C[1]  # calculate incremental costs
delta.E <- v.E[2] - v.E[1]  # calculate incremental QALYs
se.delta.E <- sd(sim_trt$te - sim_no_trt$te) / sqrt(n.i) # Monte Carlo square
d error (MCSE) of incremental costs
se.delta.C <- sd(sim_trt$tc - sim_no_trt$tc) / sqrt(n.i) # Monte Carlo square
d error (MCSE) of incremental QALYs
ICER <- delta.C / delta.E  # calculate the ICER
results <- c(delta.C, delta.E, ICER)  # store the values in a new vari
able</pre>
```

Create full incremental cost-effectiveness analysis table

					Incremental		QALYs			
	Costs	*	QALYs	*	Costs	*	Gained	*	ICER	
No	75996	183	15.823	0.016						
Treatment										
Treatment	141644	343	16.384	0.016	65648	164	0.561	0.001	117087	
* are MCSE values										