

## Ejercicio 1

```
R2 R3 R1 PC1
R1-00042423(config)#exit
R1-00042423#wr
Building configuration...

*Mar 1 00:22:48.663: %SYS-5-CONFIG_I: Configured from console by console[OK]
R1-00042423#show ip interface brief
Interface IP-Address OK? Method Status Protocol
FastEthernet0/0 10.23.0.1 YES manual up
Serial0/0 unassigned YES unset administratively down down
FastEthernet0/1 10.23.0.65 YES manual up
Serial0/1 unassigned YES unset administratively down down
Serial0/2 unassigned YES unset administratively down down
FastEthernet1/0 10.23.0.129 YES manual up
FastEthernet2/0 unassigned YES unset up
FastEthernet2/1 unassigned YES unset up
FastEthernet2/2 unassigned YES unset up
FastEthernet2/3 unassigned YES unset up
FastEthernet2/4 unassigned YES unset up

R1-00042423#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, * - candidate default, U - per-user static route
        o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

    10.0.0.0/8 is variably subnetted, 6 subnets, 4 masks
C       10.23.0.0/26 is directly connected, FastEthernet0/0
C       10.23.0.64/27 is directly connected, FastEthernet0/1
S       10.23.0.112/28 [1/0] via 10.23.0.130
S       10.23.0.96/28 [1/0] via 10.23.0.130
S       10.23.0.132/30 [1/0] via 10.23.0.130
C       10.23.0.128/30 is directly connected, FastEthernet1/0
R1-00042423#
```

```
R2-000424243(config)#exit
R2-000424243#
*Mar 1 00:23:03.303: %SYS-5-CONFIG_I: Configured from console by console
R2-000424243#wr
Building configuration...
[OK]
R2-000424243#
R2-000424243#show ip interface brief
Interface IP-Address OK? Method Status Protocol
FastEthernet0/0 10.23.0.97 YES manual up
Serial0/0 unassigned YES unset administratively down down
FastEthernet0/1 10.23.0.130 YES manual up
Serial0/1 unassigned YES unset administratively down down
Serial0/2 unassigned YES unset administratively down down
FastEthernet1/0 10.23.0.133 YES manual up
FastEthernet2/0 unassigned YES unset up
FastEthernet2/1 unassigned YES unset up
FastEthernet2/2 unassigned YES unset up
FastEthernet2/3 unassigned YES unset up
FastEthernet2/4 unassigned YES unset up

R2-000424243#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, * - candidate default, U - per-user static route
        o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

    10.0.0.0/8 is variably subnetted, 4 subnets, 2 masks
S       10.23.0.112/28 [1/0] via 10.23.0.134
C       10.23.0.96/28 is directly connected, FastEthernet0/0
C       10.23.0.132/30 is directly connected, FastEthernet1/0
C       10.23.0.128/30 is directly connected, FastEthernet0/1
R2-000424243#
```

```
R3-00042423(config)#exit
R3-00042423#wr
Building configuration...

*Mar 1 00:23:19.591: %SYS-5-CONFIG_I: Configured from console by console[OK]
R3-00042423#show ip interface brief
Interface IP-Address OK? Method Status Protocol
FastEthernet0/0 10.23.0.113 YES manual up up
Serial0/0 unassigned YES unset administratively down down
FastEthernet0/1 10.23.0.134 YES manual up up
Serial0/1 unassigned YES unset administratively down down
Serial0/2 unassigned YES unset administratively down down
FastEthernet1/0 unassigned YES unset administratively down down
FastEthernet2/0 unassigned YES unset up down
FastEthernet2/1 unassigned YES unset up down
FastEthernet2/2 unassigned YES unset up down
FastEthernet2/3 unassigned YES unset up down
FastEthernet2/4 unassigned YES unset up down

R3-00042423#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

10.0.0.0/8 is variably subnetted, 6 subnets, 4 masks
S 10.23.0.0/26 [1/0] via 10.23.0.133
S 10.23.0.64/27 [1/0] via 10.23.0.133
C 10.23.0.112/28 is directly connected, FastEthernet0/0
S 10.23.0.96/28 [1/0] via 10.23.0.133
C 10.23.0.132/30 is directly connected, FastEthernet0/1
S 10.23.0.128/30 [1/0] via 10.23.0.133
R3-00042423#
```

```
PC1> trace 10.23.00.114
trace to 10.23.00.114, 8 hops max, press Ctrl+C to stop
 1 10.23.0.1 15.085 ms 15.861 ms 15.473 ms
 2 * * *
 3 * * *
 4 * * *
 5 * * *
 6 * * *
 7 * * *
 8 * * *

PC1>
```

