

# Implementing Connection Load Balancing and TAF

By Ahmed Baraka


# Objectives

In this lecture, you will learn how to perform the following:



- Set up the following configurations:
  - Client-side connect-time load balancing
  - Server-side connect-time load balancing with and without having the Load Balancing Advisory (LBA) enabled
  - Transparent Application Failover (TAF) on client side
  - Basic TAF on server side
  - Preconnect TAF on the client side and on the server side.
- Describe Fast Connection Failover (FCF)
- Describe and enable Fast Application Notification (FAN)

# Load Balancing Options





# Client-Side Connect-Time Load Balancing

- Defined by setting the parameter **LOAD\_BALANCE=ON** in **tnsnames.ora**




```
HRSRV=
(DESCRIPTION =
  (ADDRESS_LIST =
    (LOAD_BALANCE=ON)
    (ADDRESS=(PROTOCOL=TCP) (HOST=rac1vip) (PORT=1521))
    (ADDRESS=(PROTOCOL=TCP) (HOST=rac2vip) (PORT=1521))
  )
(CONNECT_DATA=(SERVICE_NAME=HRSRV))
)
```

# Client-Side Connect-Time Load Balancing (cont)

- Defined by setting the parameter **LOAD\_BALANCE=ON** in **tnsnames.ora**
- Typically, you'd use the VIP names in the list
- Client randomly selects an address in the address list and connects to that node's listener.
- Using SCAN IP is irrelevant
- Regardless of the load balancing option in the server side
- Regardless on the load on the nodes



## LBA-enabled Service



# Overview of the Load Balancing Advisory

- Sends incoming work to the instances based on quality of service
- Recognizes the machine power differences
- Supports the following client technologies:
  - JDBC universal connection pool, OCI session pool, Oracle WebLogic Server Active, GridLink for Oracle RAC, and the ODP.NET Connection Pools.
  - Third party applications: JDBC and Oracle RAC FAN API or callbacks with OCI.
- If LBA is not enabled, connections are distributed equally to the instances.



# Enabling LBA in a Service

- To enable LBA in a service, set service-level goals for run-time connection load balancing (**rlbgoal**):

- **SERVICE\_TIME**: work requests distributed based on response time

```
srvctl modify service -db rac -service orders  
-rlbgoal SERVICE_TIME -clbgoal SHORT
```

- **THROUGHPUT**: work requests distributed based on throughput

```
srvctl modify service -db rac -service batchj  
-rlbgoal THROUGHPUT -clbgoal LONG
```

- If **rlbgoal** is not configured (or set to **NONE**), the LBA is disabled




# Transparent Application Failover (TAF) Overview

- OCI driver feature that can be used with Thick JDBC clients
- A failed connection is failed over to surviving instance
  - Opened transactions are rolled back
  - It can resume the **SELECT** statement
- Two methods supported:
  - **BASIC**: application establishes a new connection to a surviving instance
  - **PRECONNECT**: a shadow connection is initially made
- Can be configured in the client-side as well as in the server-side



# Configuring TAF Options



# TAF BASIC Configuration on Client-side

- In `tnsnames.ora` file configure:
  - **FAILOVER**: set it to ON
  - **FAILOVER\_MODE**
    - **TYPE**: specifies the type of failover. It accepts: `SESSION`, `SELECT`, or `NONE`
    - **METHOD**: speed of the failover. It accepts: `BASIC`, or `PRECONNECT`
    - **RETRIES**: how many times Oracle Net should try to reconnect
    - **DELAY**: how many seconds Oracle Net should wait before trying to connect again



Ahmed Baraka  
Oracle Database Administrator



# TAF BASIC Configuration on Client-side: Example



```
ctaf =  
  (DESCRIPTION =(FAILOVER=ON) (LOAD_BALANCE=ON)  
    (ADDRESS=(PROTOCOL=TCP) (HOST=rac1-vip) (PORT=1521))  
    (ADDRESS=(PROTOCOL=TCP) (HOST=rac2-vip) (PORT=1521))  
    (CONNECT_DATA =  
      (SERVICE_NAME = hrsrv)  
      (FAILOVER_MODE = (TYPE=SELECT)  
        (METHOD=BASIC)  
        (RETRIES=10)  
        (DELAY=10)))  
  )
```



# TAF BASIC Configuration on Server-side

- Use the following options in the **add service** command:

```
srvctl add service -d db_unique_name -service service_name
...
[-failovertype {NONE|SESSION|SELECT|TRANSACTION}]
[-failovermethod {NONE | BASIC}]
[-failoverretry failover_retries]
[-failoverdelay failover_delay]
```

```
srvctl add service -db racdb -service hrsrv -preferred rac1
-available rac2,rac3 -failovermethod BASIC
-failovertype SELECT -failoverretry 10 -failoverdelay 5
```

# TAF PRECONNECT Configuration on Client-side: Example



Ahmed Baraka  
Oracle Database Administrator

```
HRSRV =  
  (DESCRIPTION=  
    (ADDRESS=(PROTOCOL=tcp) (HOST=srv1-vip) (PORT=1521))  
    (CONNECT_DATA=  
      (SERVICE_NAME=hrsrv)  
      (FAILOVER_MODE=  
        (BACKUP=HRSRV2)  
        (TYPE=SELECT)  
        (METHOD=PRECONNECT)))  
  )  
  . . .
```

# TAF PRECONNECT Configuration on Client-side: Example (cont)



```
HRSRV2 =  
  (DESCRIPTION=  
    (ADDRESS=(PROTOCOL=tcp) (HOST=srv2-vip) (PORT=1521))  
    (CONNECT_DATA=  
      (SERVICE_NAME=hrsrv)  
      (FAILOVER_MODE=  
        (BACKUP=HRSRV)  
        (TYPE=SELECT)  
        (METHOD=PRECONNECT)))  
  )
```

# TAF PRECONNECT Configuration on Server-side: Example

- On the server side:

```
srvctl add service -db racdb -service hrsrv -preferred rac1  
-available rac2,rac3 -tafpolicy PRECONNECT
```

- An internal **hrsrv\_preconnect** service will be created
- In this example, TAF is actually not enabled, because **FAILOVER\_TYPE** is not defined.
- Cannot be configured in policy-managed RAC databases



Ahmed Baraka  
Oracle Database Administrator



## TAF PRECONNECT Configuration on Server-side: Example (cont)

```
# client side configuration for the server-side TAF PRECONNECT:
PRESRV =
  (DESCRIPTION=
    (ADDRESS=(PROTOCOL=tcp)(HOST=svr-scan)(PORT=1521))
    (CONNECT_DATA=
      (SERVICE_NAME=presrv)
      (FAILOVER_MODE=
        (BACKUP=PRESRV2)
        (TYPE=SELECT)
        (METHOD=PRECONNECT)))
  )
```


# TAF PRECONNECT Configuration on Server-side: Example (cont)



```
PRESRV2 =  
  (DESCRIPTION=  
    (ADDRESS=(PROTOCOL=tcp) (HOST=srv-scan) (PORT=1521))  
    (CONNECT_DATA=  
      (SERVICE_NAME=presrv_preconnect)  
      (FAILOVER_MODE=  
        (BACKUP=HRSRV)  
        (TYPE=SELECT)  
        (METHOD=PRECONNECT)))  
  )
```

# TAF Verification

- Current sessions attributes show if failover is enabled:



Ahmed Baraka  
Oracle Database Administrator

```
SELECT MACHINE, FAILOVER_METHOD, FAILOVER_TYPE,  
FAILED_OVER, SERVICE_NAME, COUNT(*)  
FROM GV$SESSION  
GROUP BY MACHINE, FAILOVER_METHOD, FAILOVER_TYPE,  
FAILED_OVER, SERVICE_NAME;
```

- Service attributes:

```
SELECT NAME, FAILOVER_METHOD, FAILOVER_TYPE  
FROM DBA_SERVICES
```

# About Fast Application Notification (FAN)

- The mechanism used by Oracle to notify the processes about the service level information and instances status, as UP or DOWN.
- Supported by the following technologies without programmatic changes:
  - Oracle JDBC Universal Connection Pool
  - ODP.NET connection pool
  - OCI session pool
  - Oracle WebLogic Server Active Gridlink
- Can be used by programming in JDBC, ODP .NET, and OCI



# About Fast Notification Application (FAN) (cont)

- Used by Fast Connection Failover (FCF)
- Used by Application Continuity or Transaction Guard
- To enable FAN in a service:



Ahmed Baraka  
Oracle Database Administrator

```
srvctl modify service -db rac -s hrsrv -notification TRUE
```

# About Fast Connection Failover (FCF)

- A failover feature that you can enable in the connection pool
- Supports the following failover features:
  - Planned outages: in-use connections are not interrupted, closed only after the work is done.
  - Unplanned outages: connections made to a failed instance automatically removed from pool
  - Is aware of adding a new node
- Oracle Notification Service (ONS) to propagate database events
- Recommended over TAF configuration

# Configuring FCF Overview

- FCF can be configured for the following clients:
  - JDBC OCI and JDBC Thin clients
  - OCI Clients (even if TAF is configured)
- .. in the following connection pooling technologies:
  - Universal Connection Pool or Implicit Connection Cache (*deprecated*)
  - Oracle WebLogic Server Active GridLink
  - OCI connection pool, and OCI session pools.
- Details provided in “*Universal Connection Pool Developer's Guide*” and “*Oracle Call Interface Programmer's Guide*”



Ahmed Baraka  
Oracle Database Administrator



# Summary

In this lecture, you should have learnt how to perform the following:

- Set up the following configurations:
  - Client-side connect-time load balancing
  - Server-side connect-time load balancing with and without having the Load Balancing Advisory (LBA) enabled
  - Transparent Application Failover (TAF) on client side
  - Basic TAF on server side
  - Preconnect TAF on the client side and on the server side.
- Describe Fast Connection Failover (FCF)
- Describe and enable Fast Application Notification (FAN)