

Windal Accounting

Client PC installation guide

Folder layout: `D:\WINDAL` · App: `D:\WINDAL\apptest`

Includes: Oracle, Node.js, Cloudflare tunnel, Git clone/setup, and updates

Document version: May 2026 · APPTTEST / Windal

Contents

1. Overview and folder layout
2. Prerequisites checklist
3. Install Git for Windows (one time)
4. First-time install — copy or clone from GitHub
5. Install Node.js and Cloudflare (cloudflared)
6. Configure Oracle and connection.config.json
7. Run setup-client.ps1
8. Cloudflare tunnel (config.yml)
9. Start services and verify
10. Scheduled tasks (auto-start after reboot)
11. Updating the app from Git (routine)
12. One-click desktop update
13. Troubleshooting

Windal — Client installation (D:\WINDAL)

This guide is for installing **Windal Accounting** (APPTTEST web app + API) on a **client PC**. Example paths use `D:\WINDAL` ; you may use another drive if needed.

1. Overview and folder layout

```
D:\WINDAL\  
  apptest\  
    server.cjs, package.json, SRC, scripts (.ps1, .cmd)  
    connection.config.json    ← Per-client Oracle + client key (secrets)  
    config.yml                ← Cloudflare tunnel ingress  
    xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx.json ← Tunnel credentials  
  oracle_bridge\  
    instantclient_23_0\  
      tnsnames.ora, sqlnet.ora    ← Optional TNS (if used)
```

The API reads Oracle from `..\oracle_bridge\instantclient_23_0` relative to `apptest` .

Service	Local URL	Public URL (example client <code>dal-pushkar</code>)
Web (Vite)	<code>http://localhost:5174</code>	<code>https://dal-pushkar.fasaccountingsoftware.in</code>
API	<code>http://localhost:5001</code>	<code>https://dal-pushkar-api.fasaccountingsoftware.in</code>

2. Prerequisites checklist

- Windows 10 or 11 (64-bit).
- **PowerShell as Administrator** for setup and scheduled tasks.
- Internet for first install (Git clone, npm, winget).
- Oracle database reachable from this PC; Instant Client at `D:\WINDAL\oracle_bridge\instantclient_23_0` .
- Cloudflare account access for zone `fasaccountingsoftware.in` (tunnel).

3. Install Git for Windows (one time per PC)

Git is required to **clone** the app the first time and to **pull updates** later.

3.1 Download and install

1. Open <https://git-scm.com/download/win>
2. Download **64-bit Git for Windows Setup**.
3. Run the installer → accept defaults (ensure **Git from the command line and also from 3rd-party software** is selected).
4. Finish and open a **new** PowerShell window.

3.2 Verify Git

```
git --version
```

Expected: `git version 2.x.x`

Optional — winget:

```
winget install --id Git.Git -e --accept-source-agreements --accept-package-agreements
```

Close PowerShell and open a new window, then run `git --version` again.

3.3 Configure Git (recommended once per PC)

```
git config --global user.name "Your Name"  
git config --global user.email "you@company.com"
```

For private GitHub repos, use a **Personal Access Token** as password when Git prompts during clone/pull, or set up SSH keys.

4. First-time install — get the app from GitHub

Repository: `https://github.com/DBHATIA182/MYFAS_WINDAL.git`

Branch: `main`

4.1 Option A — Fresh clone (recommended for new client PC)

1. Create parent folder if needed:

```
mkdir D:\WINDAL -Force
```

2. Clone the repository:

```
cd D:\WINDAL  
git clone https://github.com/DBHATIA182/MYFAS_WINDAL.git apptest  
cd D:\WINDAL\apptest
```

3. If you have an **old copy** of the app (not from Git), copy these files from the old folder into `D:\WINDAL\apptest` after clone:

- `connection.config.json`
- `config.yml`
- Tunnel credentials file: `<tunnel-uuid>.json` (same name as in `config.yml`)

4.2 Option B — Automated first-time Git install script

Copy `git_client_installation.ps1` to `D:\WINDAL` (parent folder, **not** inside `apptest`). Edit paths inside the script if your drive differs.

```
cd D:\WINDAL
Set-ExecutionPolicy -Scope Process -ExecutionPolicy Bypass -Force
.\git_client_installation.ps1
```

This script: renames existing `APPTTEST` to `APPTTEST_OLD` if needed, clones the repo, copies `connection.config.json` / tunnel files from backup, runs `npm ci` and `npm run build`.

4.3 What NOT to copy from dev PC

- Do **not** copy `node_modules` — install on client with `npm ci`.
- `dist` is optional — setup rebuilds the UI.

5. Install Node.js and Cloudflare (cloudflared)

5.1 Check if already installed

```
node --version
npm --version
cloudflared --version
```

Need **Node.js 18 or newer** (LTS recommended).

5.2 Automatic (recommended) — via setup-client.ps1

`setup-client.ps1` installs Node LTS and cloudflared using **winget** when missing (Step 7).

5.3 Manual install with winget (Administrator)

```
winget install --id OpenJS.NodeJS.LTS -e --accept-source-agreements --accept-package-agreements
winget install --id Cloudflare.cloudflared -e --accept-source-agreements --accept-package-agreements
```

Close PowerShell, open a **new** window, verify commands again.

5.4 Manual install from websites

- **Node.js:** <https://nodejs.org/> — download LTS, install with defaults.
- **cloudflared:** <https://developers.cloudflare.com/cloudflare-one/connections/connect-networks/downloads/> — Windows 64-bit.

5.5 Cloudflare login (one time per PC)

```
cloudflared tunnel login
```

Browser opens → log in → select zone **fasaccountingsoftware.in**.

6. Configure connection.config.json

Edit `D:\WINDAL\apptest\connection.config.json` for this client:

- `clientName` / `defaultClientKey` — e.g. `dal-pushkar` (use hyphens in DNS, not underscores)
- `oracle.primary` — user, password, connect string (e.g. `XE` or `HOST:1521/SERVICE`)

Setup script can write this file for you (next step).

7. Run setup-client.ps1 (one-time setup)

Open **PowerShell as Administrator**:

```
cd D:\WINDAL\apptest

powershell -ExecutionPolicy Bypass -File .\setup-client.ps1 `
  -ClientKey "dal-pushkar" `
  -OraclePrimaryUser "DAL" `
  -OraclePrimaryPassword "YOUR_PASSWORD" `
  -OracleConnectionString "XE" `
  -OracleSecondaryUser "DAL" `
  -OracleSecondaryPassword "YOUR_PASSWORD"
```

This typically:

- Updates `connection.config.json`
- Installs Node / cloudflared if missing
- Runs `npm install` and `npm run build`
- Creates scheduled task `FAS-dal-pushkar-API` (API auto-start on reboot)

After Node install, if `node` is not found, close PowerShell and open a new window.

8. Cloudflare tunnel (config.yml)

If tunnel **dal-pushkar** already exists in Cloudflare, you do **not** create it again. On this PC you need:

- `D:\WINDAL\apptest\config.yml`
- `D:\WINDAL\apptest\<tunnel-uuid>.json` (credentials)

8.1 Example config.yml

```
tunnel: YOUR-TUNNEL-UUID-HERE
credentials-file: ./YOUR-TUNNEL-UUID-HERE.json

ingress:
  - hostname: dal-pushkar.fasaccountingsoftware.in
    service: http://localhost:5174
  - hostname: dal-pushkar-api.fasaccountingsoftware.in
    service: http://localhost:5001
  - service: http_status:404
```

8.2 Regenerate config on client (same tunnel name)

```
cloudflared tunnel login
cd D:\WINDAL\apptest
powershell -ExecutionPolicy Bypass -File .\setup-new-client-tunnel.ps1 -ClientKey "dal-pushkar" -
SkipClientSetup
```

8.3 List tunnels

```
cloudflared tunnel list
```

9. Start services and verify

9.1 Option A — Script (three windows)

```
cd D:\WINDAL\apptest  
powershell -ExecutionPolicy Bypass -File .\start-apptest-services.ps1
```

9.2 Option B — Manual (three PowerShell windows)

Window 1 — API:

```
cd D:\WINDAL\apptest  
npm.cmd run server
```

Window 2 — Web:

```
cd D:\WINDAL\apptest  
npm.cmd run dev -- --host 0.0.0.0 --port 5174
```

Window 3 — Tunnel:

```
cd D:\WINDAL\apptest  
cloudflared tunnel --config .\config.yml run
```

9.3 Option C — Batch

```
cd D:\WINDAL\apptest  
.\run-all-services.cmd
```

9.4 Verification

Check	Expected
Local web	http://localhost:5174
Local API	http://localhost:5001
Public web	https://dal-pushkar.fasaccountingsoftware.in
Public API	https://dal-pushkar-api.fasaccountingsoftware.in
API log	D:\WINDAL\apptest\logs\server.log

10. Scheduled tasks (auto-start after reboot)

Task name	What starts	How to register
FAS-<client>-API	API only	Default from setup-client.ps1
FAS-<client>-AllServices	API + Vite + tunnel	setup-scheduled-task-all-services.ps1 (Admin)

Use only **one** auto-start method to avoid port conflicts on 5001 and 5174.

```
powershell -ExecutionPolicy Bypass -File .\setup-scheduled-task-all-services.ps1
```

11. Updating the app from Git (routine)

When developers publish changes to GitHub, update the client PC:

11.1 Stop services first

```
cd D:\WINDAL\apptest
powershell -ExecutionPolicy Bypass -File .\stop-apptest-services.ps1 `
-AppRoot "D:\WINDAL\apptest" -StopScheduledTasks -ReleaseApiPort5001 -ReleasePorts5174
```

11.2 Pull and rebuild

```
cd D:\WINDAL\apptest
powershell -ExecutionPolicy Bypass -File .\update-from-git.ps1 -Branch main
```

This runs: `git fetch` , `git pull origin main` , `npm ci` , `npm run build` .

11.3 Start services again

```
powershell -ExecutionPolicy Bypass -File .\start-apptest-services.ps1 -AppRoot "D:\WINDAL\apptest"
```

11.4 Manual Git commands (if scripts fail)

```
cd D:\WINDAL\apptest
git fetch origin
git checkout main
git pull origin main --autostash
npm.cmd ci
npm.cmd run build
```

Files Git must NOT overwrite: Keep local copies of `connection.config.json` , `config.yml` , and tunnel `*.json` . If pull changes them, restore from backup.

12. One-click desktop update

Use the desktop shortcut **Update APPTTEST** (or run):


```
cd D:\WINDAL\apptest
powershell -ExecutionPolicy Bypass -File .\run-desktop-update.ps1 -AppRoot "D:\WINDAL\apptest" -Branch
main
```

Log file: `D:\WINDAL\apptest\logs\desktop-update.log`

Steps: stop services → git pull + npm ci + build → start services.

13. Troubleshooting

Problem	Action
<code>node</code> / <code>npm</code> not found	Reopen PowerShell after install; or add <code>C:\Program Files\nodejs</code> to PATH.
<code>git</code> not found	Install Git for Windows; reopen PowerShell.
Not a Git repository	Run first-time clone (Section 4) or <code>git_client_installation.ps1</code> .
git pull failed	Run <code>git status</code> ; stash local changes: <code>git stash -u</code> , pull, then <code>git stash pop</code> .
File locked during update	Close API/Vite/tunnel windows; run stop script with <code>-StopScheduledTasks</code> ; do not open log files in Notepad while updating.
Oracle init error	Confirm <code>D:\WINDAL\oracle_bridge\instantclient_23_0</code> exists; check TNS files.
Tunnel credentials missing	Place <code>config.yml</code> + <code><uuid>.json</code> in apptest folder.
Wrong site on public URL	Vite must use port 5174 ; match <code>config.yml</code> ingress.

Quick reference — paths and commands

```
App folder:      D:\WINDAL\apptest
Git repo:        https://github.com/DBHATIA182/MYFAS_WINDAL.git
First clone:     cd D:\WINDAL && git clone ... MYFAS_WINDAL.git apptest
Setup:           .\setup-client.ps1 -ClientKey "..." -Oracle...
Update:          .\run-desktop-update.ps1 -AppRoot "D:\WINDAL\apptest"
Start:           .\start-apptest-services.ps1
```

Windal Accounting — Client installation guide · Rebuild PDF: run `build-windal-install-guide-pdf.ps1` from the apptest folder.