Row Pattern Matching in SQL Advanced SQL

Torsten Grust, Louisa Lambrecht

University of Tübingen

Summer Term 2024

SQL:2016 introduced an entirely new SQL construct for *row pattern matching* (MATCH_RECOGNIZE).










As of July 2024, not supported by •.

Key components of MATCH_RECOGNIZE:

- 1. ORDER BY: Order the rows of a table.
- 2. **DEFINE**: Tag rows that satisfy given predicates.
- 3. PATTERN: Specify a regular expression over row tags, find matches in the ordered sequence of rows.
- 4. MEASURES: For each match, evaluate expressions that measure its features (matched rows, length, ...).

```
SELECT *
FROM map MATCH_RECOGNIZE (
 ORDER BY x
 MEASURES MATCH_NUMBER() AS feature,
          PREV(FIRST(DOWN.x)) AS start,
          LAST(UP.x) AS term
 ONE ROW PER MATCH
 AFTER MATCH SKIP PAST LAST ROW
 PATTERN( DOWN (DOWN | EVEN) * (EVEN | UP) * UP)
 DEFINE
        UP AS UP.alt > PREV(UP.alt),
          DOWN AS DOWN.alt < PREV(DOWN.alt), row tags
          EVEN AS EVEN.alt = PREV(EVEN.alt)
```



⊞ map			
×	alt		
0	406		
7	404		
18	404		
22	401		
28	403		
31	403		
35	407		
44	402		
50	402		
56	403		
62	402		

DEFINE
NULL
DOWN
EVEN
DOWN
UP
EVEN
UP
DOWN
EVEN
UP
DOWN

```
SELECT *
      map MATCH_RECOGNIZE (
FROM
  ORDER BY x
 MEASURES MATCH NUMBER() AS feature,
          PREV(FIRST(DOWN.x)) AS start,
          LAST(UP.x) AS term
 ONE ROW PER MATCH
  AFTER MATCH SKIP PAST LAST ROW
 PATTERN( DOWN (DOWN | EVEN) * (EVEN | UP) * UP )
          UP AS UP.alt > PREV(UP.alt),
 DEFINE
          DOWN AS DOWN.alt < PREV(DOWN.alt),
          EVEN AS EVEN.alt = PREV(EVEN.alt)
```

⊞ ma	р
	alt
0	406
7	404
18	404
22	401
28	403
31	403
35	407
44	402
50	402
56	403
62	402





feature	start	term
1	0	35
2	35	56

