



Functional Programming

WS 2019/20

Benjamin Dietrich, Denis Hirn

Assignment #4

Submission Deadline: Thu, 21.11.2019

Exercise 1: Minesweeper

(10 Points)

The objective of Minesweeper is to clear a rectangular field which contains hidden *mines*. For each field cell the player steps on, he is given a hint about the number of mines in the direct neighborhood.

We want to implement a function to compute these numbers for a given field with visible mines:

```
minesweep :: [[Char]] -> [[Int]]
```

Example:

```
field = [ "oooooooo"
          , "***ooooo"
          , "*_*ooooo"
          , "***ooooo"
          ]
```

```
Main> minesweep field
[ [ 2, 3, 2, 1, 0, 0, 0, 0 ]
, [ 3, 5, 3, 2, 0, 0, 0, 0 ]
, [ 5, 8, 5, 3, 0, 0, 0, 0 ]
, [ 3, 5, 3, 2, 0, 0, 0, 0 ]
]
```

Follow these steps to solve the problem:

1. The actual algorithm shall be formulated as a combination of helper functions, you have to implement in advance:
 - (a) Write a function `num :: Char -> Int` which takes a field cell and returns 1, if it is mined ('*'), and 0, if it is safe (' ').
 - (b) Write a function `shiftL :: Num a => [a] -> [a]` which shifts a given list of numbers to the left, i. e. drops the first element and appends a new element 0 to the end of the list.
 - (c) Write a function `shiftR :: Num a => [a] -> [a]` which shifts a given list of numbers to the right.

(d) Write a function

```
zipWith3' :: (a -> b -> c -> d) -> [a] -> [b] -> [c] -> [d]
```

It takes a function $f :: (a \rightarrow b \rightarrow c \rightarrow d)$ that combines three elements, as well as three lists of equal length and returns a list where each element is the combination (using f) of the input lists' elements at the same position.¹

Example:

```
zipWith3' (\a b c -> a * b + c) [1,2] [3,4] [5,6]  $\equiv$  [8,14]
```

(e) Use functions `shiftL`, `shiftR` and `zipWith3'` to implement a function

```
addNeighbours :: [Int] -> [Int]
```

For each element of a given list of integers, the function returns the sum of the element itself, together with its left and right neighbour.

Example:

```
addNeighbours [1,1,1,0,1]  $\equiv$  [2,3,2,2,1]
```

(f) Write a function which transposes the rows and columns of a given matrix (list of lists of equal length).²

```
transpose :: [[a]] -> [[a]]
```

Example:

```
transpose [[1,2,3],[4,5,6]]  $\equiv$  [[1,4],[2,5],[3,6]]
```

2. Implement `minesweep` as a combination of `Prelude` function `map` and the helper functions `num`, `addNeighbours` and `transpose` defined in step 1.

Exercise 2: Regular Expressions

(10 Points)

Finite state machines aren't the only method to implement regular expression matching. Here, we will build a regular expression matcher using the *derivatives of a regular expression*.

To implement this approach, we first need a representation for regular expressions on a given alphabet of symbols.

1. Define a data type `RegExp a` for regular expressions, which are one of:

- the empty string ϵ ,
- a symbol of the alphabet (symbols have type a – typically $a \equiv \text{Char}$),
- a concatenation $r_1 r_2$ of two regular expressions r_1 and r_2 (r_1 followed by r_2),
- the *Kleene star* r^* of a regular expression r (r repeated zero or more times),
- an alternation $r_1 | r_2$ of two regular expressions r_1 and r_2 (r_1 or r_2),
- a special regular expression \emptyset which accepts no input at all.

2. Write an instance of type class `Show` for `RegExp a` to print a regular expression as string of characters ϵ , a , $*$, $+$, $|$, \emptyset . Use parentheses $()$ to group parts of the regular expression, if necessary.

The *derivative of a regular expression* r with respect to symbol a is another regular expression r' . If input s is accepted by r , then r' accepts s with the starting symbol a removed. For example, consider the regular expression $r = ab^*$. The derivative of r with respect to a is b^* and the derivative of b^* with respect to b is again b^* . However, the derivative of r with respect to b is the regular expression \emptyset .

These derivatives can be used to implement regular expression matching.

¹Obviously you shall implement this function on your own and must not use the `Prelude` function `zipWith3`.

²You must not use the `Data.List` function `transpose`, but implement the function on your own.

First we need a function $\nu(r)$ to test whether a regular expression r is nullable. We say that r is nullable, if r accepts the empty string ε :

$$\nu(\varepsilon) = \text{True}$$

$$\nu(a) = \text{False}$$

$$\nu(r^*) = \text{True}$$

$$\nu(r_1 r_2) = \nu(r_1) \wedge \nu(r_2)$$

$$\nu(r_1 | r_2) = \nu(r_1) \vee \nu(r_2)$$

$$\nu(\emptyset) = \text{False}$$

3. Write a function `nullable :: RegExp a -> Bool` implementing ν .

Now we can define a function $\partial_a(r)$ to compute the derivative of a regular expression r with respect to a symbol a :

$$\partial_a(\varepsilon) = \emptyset$$

$$\partial_a(b) = \begin{cases} \varepsilon & , \text{ if } a = b \\ \emptyset & , \text{ if } a \neq b \end{cases}$$

$$\partial_a(r^*) = \partial_a(r r^*)$$

$$\partial_a(r_1 r_2) = \begin{cases} \partial_a(r_1) r_2 | \partial_a(r_2) & , \text{ if } \nu(r_1) \\ \partial_a(r_1) r_2 & , \text{ if } \neg \nu(r_1) \end{cases}$$

$$\partial_a(r_1 | r_2) = \partial_a(r_1) \vee \partial_a(r_2)$$

$$\partial_a(\emptyset) = \emptyset$$

4. Write a function `derive :: Eq a => RegExp a -> a -> RegExp a` implementing ∂ .

Supposed we have a regular expression r and a string of symbols $s = a_1 \dots a_n$. To test whether r accepts s , we can make use of a successive application of ∂ to r with respect to the symbols of s . If and only if the final derivative with respect to a_n is nullable, i.e., matches the empty string ε , the regular expression r matches the whole string s :

$$r \text{ matches } s \iff \nu(\partial_{a_n}(\dots \partial_{a_1}(r)))$$

5. Write a function `match :: Eq a => RegExp a -> [a] -> Bool` implementing the regular expression matcher. Remember to provide some tests.

[Optional:] Extend your definitions of `RegExp a`, `nullable` and `derive` to also support the *Kleene plus*: A regular expression can also be r^+ (the regular expression r repeated one or more times).