Triple R

TRIPLE R
ELEMENT DATA SHEET

Article nr. NEW	Article nr. OLD	TYPE	Micron rating	Micron rating	Water absorption	Dirt capacity	Filter medium	Dimensions	Element Weight gr.	Flow rates (depends on viscosity)
EL10002	TR-20000	**D100-H114**	$\beta_2 > 75$	$\beta_3 > 400$	~400 ml	~170 gr.	cellulose	178 x H 114	700	2,0 l/m
EL30001	TR-20515	**D300-H114**	$\beta_2 > 75$	$\beta_3 > 400$	~1.100 ml	~470 gr.	cellulose	303 x H 114	1.960	5,5 - 8,5 l/m
EL03003	TR-20230	**M30-H114**	$\beta_2 > 75$	$\beta_3 > 600$	~60 ml	~35 gr.	cellulose	103 x H 114	250	1,0 l/m
EL05004	TR-20330	**M50-H114**	$\beta_2 > 75$	$\beta_3 > 600$	~130 ml	~50 gr.	cellulose	142 x H 114	490	1,5 l/m
EL10006	TR-20430	**M100-H114**	$\beta_2 > 200$	$\beta_3 > 900$	~200 ml	~95 gr.	cellulose	178 x H 114	770	2,0 - 3,0 l/m
EL30004	TR-20520	**M300-H114**	$\beta_2 > 200$	$\beta_3 > 900$	~560 ml	~260 gr.	cellulose	303 x H 114	2.150	5,5 - 8,5 l/m
EL30025	TR-20530	**M300-H80**	$\beta_2 > 200$	$\beta_3 > 900$	~560 ml	~260 gr.	cellulose	303 x H 80	1.510	7,0 - 11,0 l/m
EL03002	TR-20270	**E30-H114**	$\beta_3 > 75$	$\beta_5 > 500$	~50ml	~40 gr.	cellulose	103 x H 114	230	1,0 l/m
EL05002	TR-20370	**E50-H114**	$\beta_3 > 75$	$\beta_5 > 500$	~100 ml	~60 gr.	cellulose	142 x H 114	420	1,5 l/m
EL10003	TR-20470	**E100-H114**	$\beta_3 > 75$	$\beta_5 > 500$	~180 ml	~110 gr.	cellulose	178 x H 114	700	2,0 - 3,0 l/m
EL30003	TR-20510	**E300-H114**	$\beta_3 > 75$	$\beta_5 > 500$	~500 ml	~300 gr.	cellulose	303 x H 114	1.960	5,5 - 8,5 l/m
EL30007	TR-20540	**E300-H80**	$\beta_3 > 75$	$\beta_5 > 500$	~500 ml	~300 gr.	cellulose	303 x H 80	1.375	7,0 - 11,0 l/m
EL03004	TR-25250	**X30-H114**	$\beta_5 > 75$	$\beta_{10} > 140$	~60 ml	~55 gr.	cellulose	103 x H 114	210	1,0 l/m
EL05007	TR-25350	**X50-H114**	$\beta_5 > 75$	$\beta_{10} > 140$	~130 ml	~75 gr.	cellulose	142 x H 114	400	1,5 l/m
EL10010	TR-25450	**X100-H114**	$\beta_5 > 75$	$\beta_{10} > 140$	~200 ml	~130 gr.	cellulose	178 x H 114	630	2,0 - 3,0 l/m
EL30006	TR-20512	**X300-H114**	$\beta_5 > 75$	$\beta_{10} > 140$	~560 ml	~360 gr.	cellulose	303 x H 114	1.760	5,5 - 8,5 l/m
EL30019	TR-20550	**X300-H80**	$\beta_5 > 75$	$\beta_{10} > 140$	~560 ml	~360 gr.	cellulose	303 x H 80	1.230	7,0 - 11,0 l/m
EL10012	TR-25470	**WG-100**	$\beta_{10} > 75$	$\beta_{10} > 75$	0	data n/a	polyester	178 x H 114	680	1,0 - 1,4 l/m
EL10017	TR-25480	**DWG-100**	$\beta_5 > 75$	$\beta_5 > 75$	0	data n/a	polyester	178 x H 114	680	1,0 - 1.4 l/m
EL10013	TR-20450	**WE-100**	$\beta_{40} > 50$	$\beta_{40} > 50$	900 ml	low	synth. fibre	178 x H 114	630	2,0 l/m

IMPORTANT NOTICE!

Both the dirt absorption and water retention capacity are based on official and **certified testing methods**; not on commercial assumptions, like CJC and Kleenoil are doing.

The dirt absorption capacity is resulting from detailed measurements during an **ISO 16889 Multipass Test**. That's the only official test for measuring dirt absorption capacities.