Supporting information

Separating coverage gains from error targeting in molecular prediction sets

Siyuan Tong[†] and Yuechen Wang[†]

[†]Siyuan Tong and Yuechen Wang contributed equally to this work and share first authorship.

S1 Activation, ranking, and error–yield identities

S1.1 Exact weighted inclusion condition

Let a candidate label have finite calibration scores s_i with positive weights w_i, total $W = \sum_i w_i$, and query mass $w > 0$ placed at infinity. Let q be the lower $(1-\alpha)$ quantile of this discrete distribution, with $0 < \alpha < 1$. For a finite candidate score s, define $B(s) = \sum_{i:s_i<s} w_i$. Then

$$s \le q \quad \Longleftrightarrow \quad B(s) < (1-\alpha)(W+w). \tag{S1}$$

To see this, write $t = (1-\alpha)(W+w)$. The weighted quantile is the first ordered calibration score at which cumulative weight reaches t, or infinity when $t > W$. If the cumulative mass strictly below s reaches t, this first score lies below s, so the label is excluded. If that mass is less than t, no score below s can be the quantile, so $q \ge s$. The same argument includes tied scores. For an empty calibration class, $B = W = 0 < t$, giving inclusion and an infinite threshold.

The query-weight boundary is therefore $w > B(s)/(1-\alpha) - W$. Equality is excluded: replacing the strict sign with a weak inequality changes the decision when the cumulative mass below s is exactly t. For example, calibration scores 0.2 and 0.5 with weights 2 and 1, $\alpha = 0.5$, and query weight 1 give $t = 2$ and $q = 0.2$. The candidate score 0.5 is excluded even though $B(0.5) = t$.

For the two-view TAME intersection, both views must be eligible, the candidate label must be protected and absent from the repaired baseline, and this inequality must hold in each view. Membership of a label already in the baseline does not constitute a new intervention. An intervention rescues a wrong decision only if the observed outcome equals the added label.

S1.2 Constant-query-weight ranking identity

For a fixed calibration sample with positive weights, if the query weight in each view is constant across targets, each class-specific threshold is constant. Under binary LAC, inclusion of label y is $p_y(x) \ge 1 - q_{y,v}$. The intersection across views is an upper level set at the largest such cutoff; the union is an upper level set at the smallest. Restricting to the baseline singletons omitting y preserves that ordering. Ranking $p_y(x)$ and selecting the same number of members returns exactly the same subset. A threshold includes a complete

boundary tie, so matching the number selected does not split that tie. If too few views are eligible, both the reference expansion and its matched comparator have zero budget.

This identity holds for any fixed positive source weights under binary LAC, fixed active views, and constant query weights, independently of density-ratio accuracy.

S1.3 Comparing two rules with incomplete outcomes

Consider original singleton class c, with omitted label $y = 1 - c$. For rule $j \in \{A, P\}$, let R_j count expanded labeled decisions whose true class is y, let L_j count those with true class c, and let $m_j^{\text{obs}} = R_j + L_j$. Write $\delta R = R_A - R_P$ and $\delta m = m_A^{\text{obs}} - m_P^{\text{obs}}$. Then

$$E_y(A) - E_y(P) = -\delta R / N_y, \tag{S2}$$

$$\text{CSY}_c(A) - \text{CSY}_c(P) = (\delta R - \delta m)/N_c. \tag{S3}$$

At equal labeled budgets, greater error recovery implies less loss of correct singletons. Equal operational budgets do not ensure equal labeled budgets when missing outcomes occur in different selected subsets; the δm term is required. The mechanism tables preserve both counts. For minimum-class coverage, the exact effect is obtained after calculating both class coverages within the cell: averaging class minima cannot be replaced by taking the minimum of panel-averaged coverages.

S1.4 Executable checks

`check_activation_identity.py` compares the strict inequality with the executable weighted-quantile rule using empty and nonempty calibration classes, positive unequal weights, repeated score ties, and four alpha levels. It also checks the exact equality boundary and constant-query ranking. These checks verify the weighted boundary and ranking identities.

S2 Data, roles, and gates

Source preparation uses the versioned chemical-standardization contract and RDKit 2026.03.4. Tox21 missing labels are omitted only for the corresponding assay's labeled metric. Structure identity determines overlap exclusions and the shared molecular unit for inference. The five fitted repetitions may yield endpoint-specific eligible counts, while the fixed additional-family target lists do not change between fits. Table S1 gives the recorded target and calibration counts.

For the additional families, duplicate standardization leaves AMES with 3,304 negative and 3,951 positive structures; hERG with 193 negative and 414 positive; DILI with 238 negative and 236 positive; and CYP2D6 with 10,583 negative and 2,500 positive. The fixed random and scaffold target sizes are identical within each family. Scaffold groups remain intact. All four families are retained in the analysis, including those below the fixed gate thresholds.

The mean-gap condition compares the weighted gap with $\max(10^{-12}, 1.05 \times \text{unweighted gap})$. Class and overall effective sample size use the same fraction in each sensitivity, producing fourteen one-factor

Table S1: Target and calibration counts by assay and phase. Ranges span the five fit seeds. N_0, N_1 count observed target labels; calibration counts refer to the classical shared-predictor analysis.

Phase	Assay	Raw	Eligible	N_0	N_1	Calib.
development	NR_AR	296	291	284	3	1395
development	NR_AR_LBD	296	291	244	4	1307
development	NR_AhR	296	291	237	30	1258
development	NR_Aromatase	296	291	193	18	1120
development	NR_ER	296	293	235	27	1171
development	NR_ER_LBD	296	291	272	10	1338
development	NR_PPAR_gamma	296	291	247	15	1249
development	SR_ARE	296	292	183	47	1120
development	SR_ATAD5	296	291	242	25	1365
development	SR_HSE	296	291	252	10	1245
development	SR_MMP	296	292	196	38	1118
development	SR_p53	296	291	236	28	1310
random	AMES	1451	1451	662	789	1161
random	CYP2D6_Veith	2617	2617	2139	478	2094
random	DILI	95	95	47	48	76
random	hERG	122	122	42	80	97
scaffold	AMES	1451	1451	618	833	1161
scaffold	CYP2D6_Veith	2617	2617	2129	488	2094
scaffold	DILI	95	95	36	59	76
scaffold	hERG	122	122	38	84	97
epa	NR_AR	647	616	551	12	1395
epa	NR_AR_LBD	647	620	549	8	1307
epa	NR_AhR	647	616	511	70	1258
epa	NR_Aromatase	647	621	469	35	1120
epa	NR_ER	647	623	453	47	1171
epa	NR_ER_LBD	647	617	557	19	1338
epa	NR_PPAR_gamma	647	620	548	31	1249
epa	SR_ARE	647	623	442	91	1120
epa	SR_ATAD5	647	616	557	35	1365
epa	SR_HSE	647	619	564	19	1245
epa	SR_MMP	647	622	470	54	1118
epa	SR_p53	647	619	549	39	1310

Table S2: Fixed transport-gate settings and prespecified one-at-a-time sensitivity values. Each view must pass all applicable checks.

Quantity	Default	Sensitivities
Calibration sample size	≥ 100	50, 200
Eligible target sample size	≥ 100	50, 200
Calibration count in each class	≥ 20	10, 40
Overall effective sample size	$\geq 0.25n$	0.10, 0.50 fractions
Within-class effective sample size	$\geq \max(2, 0.25n_y)$	0.10, 0.50 fractions
Maximum of lower/upper clip fractions	≤ 0.30	0.10, 0.50
Domain-classifier AUC	≤ 0.99	0.95, 1.00
Weighted/unweighted mean-gap allowance	≤ 1.05	1.00, 1.20
Density-ratio clipping	$[0.05, 20]$	fixed

configurations across the seven adjustable settings. These operating settings were fixed before the revision outcome analysis. The physicochemical view comprises molecular weight, logP, topological polar surface area, hydrogen-bond donors and acceptors, rotatable bonds, ring count, fraction of sp^3 carbons, and heavy-atom count. Descriptor normalization is fitted on the source role. The score view uses component and stack logits; ratios are estimated from unlabeled domain membership.

S3 Reference systems and predictor sensitivity

S3.1 Shared-predictor comparisons

The shared-predictor experiment uses the same eligible compounds, source roles, probabilities, and calibration labels within each assay/seed/model. Table S3 reports the absolute baseline trade-offs before transport expansion. The full numerical supplement includes all levels, methods, and assay panels.

Table S3: Ordinary Mondrian LAC with empty-set repair, historical six-assay EPA panel at $\alpha = 0.10$. All entries are percentages.

Predictor	C_0	C_1	$C_{\min}$	MacroCSY	Deferral
Logistic	85.77	89.60	84.84	43.51	47.58
Stack	85.36	89.47	83.74	48.18	42.01
Equal-logit	86.19	90.96	84.82	46.70	44.37

S3.2 Recorded neural-reference configurations

The experiment uses independent paper-based implementations of CoDrug [3] and KMM-CP [4]. The configurations below specify their run settings and named variants. CoDrug combines classification loss with an energy-margin penalty, uses an auxiliary ZINC molecular pool filtered by source scaffolds, and estimates separate calibration and target densities in the model's logit space. The implementation uses a 512-dimensional graph representation, classifier hidden sizes 256 and 8, two message-passing layers, two readout iterations, Adam learning rate 0.001, batch size 64, at most 100 epochs, and router-role cross-entropy early stopping with patience 15. Gaussian-KDE bandwidths are selected separately by ten-fold cross-validation over twenty-five fixed candidates between $10^{-1.3}$ and 10. Weighted global and candidate-label Mondrian sets retain the query mass at infinity. The global construction follows the published CoDrug equations; the candidate-label Mondrian version is an explicitly named extension for the present class-specific comparison. The printed energy margins $m_{\text{in}} = -5$ and $m_{\text{out}} = -35$ are evaluated as written. Because their ordering may conflict with the intended in/out energy separation, a second predeclared implementation swaps them to -35 and -5. Both prespecified versions are reported in Table S4. The energy weight is 0.01 and the temperature is one.

KMM-CP uses an independently trained AttentiveFP backbone without CoDrug's energy penalty or auxiliary molecules. It uses a 512-dimensional graph representation, one 64-dimensional classifier hidden layer, three message-passing layers, inverse-frequency cross-entropy weighting, Adam learning rate 0.001, a per-epoch learning-rate factor 0.8, batch size 128, at most 50 epochs, and training-loss patience

five. The 64-dimensional penultimate representation is supplied to kernel mean matching. Five RBF bandwidth multipliers, 0.01, 0.1, 0.5, 1, and 2 times the cross-domain median distance, are compared using a permutation-standardized unbiased squared MMD with 100 fixed-seed permutations. Bounded KMM uses weight bound 30 and an exact mean-mass constraint. Selective KMM jointly estimates source weights and target selection weights, requires mean selection mass at least 0.5, retains target weights at least 0.2, and then refits ordinary KMM to the retained targets. Solver status and constraint residuals determine whether the optimization is accepted.

Before OSQP, the quadratic matrix P and linear term q are divided by $\lambda_{\max}(P) > 0$; constraint matrices and bounds retain their original scale. The reported objective is converted back to its original units, while solver residuals refer to the scaled problem.

The published KMM-CP pseudocode applies the predicted class's threshold to every candidate, whereas its class-conditional description implies a threshold selected by the candidate label. We therefore report both interpretations explicitly, together with the global version, for ordinary and selective KMM. Their empirical weighted quantiles have no query mass at infinity or $(n+1)$ rank correction, following the published procedure. The implementation records the mass tolerance and permutation settings for each configuration. For selective methods, unselected compounds defer in the common full-cohort analysis; accepted-only coverage is also reported with its own denominator.

Table S4: All ten neural reference configurations on the historical six-assay EPA panel at $\alpha = 0.10$. Values are percentages. E_1 and E_0 are false-inactive and false-active exposure, respectively. Each system uses its own predictor and native deferral budget. Candidate uses candidate-label thresholds; predicted uses the paper's predicted-group interpretation. The CoDrug candidate-class variants extend its global construction.

Reference configuration	E_1	E_0	$C_{\min}$	MacroCSY	Deferral
CoDrug, printed / global	62.80	2.17	30.51	56.92	6.44
CoDrug, printed / candidate	14.42	10.16	84.70	52.52	35.22
CoDrug, swapped / global	58.43	2.63	33.21	58.00	6.67
CoDrug, swapped / candidate	10.93	11.05	86.24	52.97	36.58
KMM / global	13.15	10.25	84.66	54.35	33.65
KMM / candidate	16.55	9.91	82.05	55.55	30.37
KMM / predicted	13.30	18.05	77.13	59.19	24.84
Selective KMM / global	10.88	6.68	87.73	38.93	48.11
Selective KMM / candidate	7.67	6.89	90.78	36.27	52.79
Selective KMM / predicted	11.00	8.22	84.31	38.56	46.39

The numerical supplement also retains selected-target metrics for selective KMM, alongside full-eligible-target metrics. In the latter, unselected targets are assigned full sets and count toward operational deferral. Outcomes use the observed-label denominator in the corresponding population.

S4 Sensitivity analyses and molecular inference

For every single-view, union, ungated, and gate-sensitivity expansion, the comparison matches its own two class-specific budgets. The reported intervals use 2,000 shared-structure bootstrap draws, retaining all seed-specific predictions and recomputing each cell metric before the equal-weight panel mean. The

primary contrast uses the historical six endpoints, stack, LAC, and $\alpha = 0.10$. The all-twelve panel and other predictors are separate analyses.

The probability range from zero to one is partitioned into five bins of width 0.2. Each bin includes its lower boundary; the final bin also includes one. Each of five query-weight controls permutes query weights within these bins, using the same permutation across views. Calibration weights, fitted target densities, and joint-view weight relationships remain fixed. The gated and ungated versions each have their own probability comparator. Across the declared 280 ablation/alignment contrasts, no pointwise error interval excludes zero. Within the primary stack panel, the ten alignment controls have no added deferrals. The nonzero primary physicochemical-only and union contrasts have a mean error difference of -0.0952 percentage points (95% interval, -0.3030 to 0.0000).

The 24 additional-family active-label comparisons combine four endpoints, two split regimes, and three predictors. Their false-negative differences are zero except for the CYP2D6 random split with the equal-logit predictor, at -0.0418 percentage points (95% interval, -0.1330 to 0.0000). This secondary comparison is retained with all endpoint-specific estimates and denominators in the machine-readable contrasts.

S5 Controlled shift mechanisms

The fixed source posterior is $p_1(x) = \text{logit}^{-1}(2x_1 + 0.5x_2 - 1)$. Thirty replicates, seeds beginning at 73000, use 400 calibration and 800 target observations each at $\alpha = 0.10$. The two transport views are the raw two-dimensional covariates and those covariates augmented with their elementwise squares.

The no-shift condition uses standard Gaussian covariates. An overlapping covariate shift moves the first target coordinate's mean by one while retaining the source outcome law. Its known marginal density ratio is $\exp(x_1 - 1/2)$. The support-loss condition places half the targets beyond bounded calibration support. Finally, the changed-conditional condition reuses the no-shift calibration data, target covariates, predictions, and diagnostics, but changes the target posterior to $1 - p_1(x)$. The paired observable inputs match in all thirty replicates. For TAME, mean class-1 coverage is 90.36% under no shift and 39.74% under the changed conditional, at identical deferral. The archived synthetic replicate table also reports minimum-class coverage, MacroCSY, and deferral for all included rules.

S6 Rebuilding and numerical files

`build_results.py` reads the frozen aggregate inputs, rebuilds every manuscript table and figure, and checks thirty EPA predictor/method/panel combinations against the underlying assay–seed metrics for seven numerical outcomes. `rebuild.py` then checks the activation identity and compiles the main text, supporting information, response, and cover letter twice each.

The complete numerical supplement includes `all_cell_metrics.csv.gz` (343,680 rows), `all_panel_metrics.csv.gz` (77,328 rows), and `all_paired_contrasts.csv.gz` (7,700 metric rows, covering 770 comparison specifications). Compression preserves the returned CSV bytes. The source manifest records hashes and transformations. The compact repository inputs preserve the

columns required for manuscript rebuilding, all paired contrasts, every shared-predictor gate record, and mechanism-count tables.

The numerical supplement supports fixed-input reconstruction of tables and figures and inspection of archived intervals. Retraining and molecule-cluster resampling require the model and row-level exports stored on the execution machine. Missing assay outcomes are excluded from the corresponding labeled metrics.

References

[1] V. Vovk, Conditional validity of inductive conformal predictors, Proceedings of Machine Learning Research 25 (2012) 475–490. https://proceedings.mlr.press/v25/vovk12.html.

[2] R. J. Tibshirani, R. F. Barber, E. J. Candès, A. Ramdas, Conformal prediction under covariate shift, Advances in Neural Information Processing Systems 32 (2019). https://proceedings.neurips.cc/paper/2019/hash/8fb21ee7a2207526da55a679f0332de2-Abstract.html.

[3] S. Laghuvarapu, Z. Lin, J. Sun, CoDrug: Conformal drug property prediction with density estimation under covariate shift, Advances in Neural Information Processing Systems 36 (2023). https://proceedings.neurips.cc/paper_files/paper/2023/hash/7691484a7a35d5e2742279c1d926b778-Abstract-Conference.html.

[4] S. Laghuvarapu, R. Deb, J. Sun, KMM-CP: Practical conformal prediction under covariate shift via selective kernel mean matching, Proceedings of Machine Learning Research 337 (2026) 3237–3261. https://proceedings.mlr.press/v337/laghuvarapu26a.html.

[5] Y. Romano, M. Sesia, E. Candès, Classification with valid and adaptive coverage, Advances in Neural Information Processing Systems 33 (2020). https://proceedings.neurips.cc/paper_files/paper/2020/hash/244edd7e85dc81602b7615cd705545f5-Abstract.html.

[6] R. Huang, M. Xia, D.-T. Nguyen, T. Zhao, S. Sakamuru, J. Zhao, S. A. Shahane, A. Rossoshek, A. Simeonov, Tox21Challenge to build predictive models of nuclear receptor and stress response pathways as mediated by exposure to environmental chemicals and drugs, Frontiers in Environmental Science 3 (2016) 85. https://doi.org/10.3389/fenvs.2015.00085.

[7] C. Xu et al., In silico prediction of chemical Ames mutagenicity, Journal of Chemical Information and Modeling 52 (2012) 2840–2847. https://doi.org/10.1021/ci300400a.

[8] S. Wang et al., ADMET evaluation in drug discovery. 16. Predicting hERG blockers by combining multiple pharmacophores and machine learning approaches, Molecular Pharmaceutics 13 (2016) 2855–2866. https://doi.org/10.1021/acs.molpharmaceut.6b00471.

[9] Y. Xu et al., Deep learning for drug-induced liver injury, Journal of Chemical Information and Modeling 55 (2015) 2085–2093. https://doi.org/10.1021/acs.jcim.5b00238.

[10] H. Veith et al., Comprehensive characterization of cytochrome P450 isozyme selectivity across chemical libraries, Nature Biotechnology 27 (2009) 1050–1055. https://doi.org/10.1038/nbt.1581.

[11] R. El-Yaniv, Y. Wiener, On the foundations of noise-free selective classification, Journal of Machine Learning Research 11 (2010) 1605–1641. https://www.jmlr.org/papers/v11/el-yaniv10a.html.