EXP NO:- 9 Date:-

Aim:-

To design and configure an simple network transmitting of one router, two switches & multiple PCs in cisco packet tracer, & enables communication b/w PCs

Equipments Required:-

1) Cisco packet Tracer Software.
2) 1 Router
3) 2 switches.
4) 4 PCs.
5) Appropriate cable.

Procedure:-

1) open cisco packet tracer.
2) Add devices to workshop.
3) connect devices with cables.
4) configure Router Interface.
5) configure PC IP addresses.
6) Source and Test connectivity.

```
Cisco Packet Tracer PC Command Line 1.0
C:\>ping 192.168.1.10

Pinging 192.168.1.10 with 32 bytes of data:

Reply from 192.168.1.10: bytes=32 time=3ms TTL=128
Reply from 192.168.1.10: bytes=32 time<1ms TTL=128
Reply from 192.168.1.10: bytes=32 time=6ms TTL=128
Reply from 192.168.1.10: bytes=32 time=4ms TTL=128

Ping statistics for 192.168.1.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 6ms, Average = 3ms

C:\>
```

Result :-

The PCs connected to different switches on communicate with each other via router the successfully ping replies Verify the network is properly configured.