

Table 2 — Sensitivity: Wake Convection Speed a_w (TSR=8)

a_w input	CT	CP	$\square$ [-]	dCT	dCP	iters	conv.
0.05	0.6860	0.4949	0.2181	+0.0269	+0.0405	267	✓
0.10	0.6800	0.4859	0.2251	+0.0209	+0.0315	107	✓
0.15	0.6736	0.4762	0.2327	+0.0145	+0.0218	57	✓
0.20	0.6667	0.4657	0.2411	+0.0076	+0.0113	46	✓
0.25	0.6591	0.4544	0.2503	+0.0000	+0.0000	49	✓
0.30	0.6515	0.4428	0.2611	-0.0076	-0.0116	54	✓
0.35	0.6427	0.4295	0.2727	-0.0164	-0.0248	39	✓
0.40	0.6322	0.4145	0.2847	-0.0270	-0.0399	27	✓
0.45	0.6203	0.3979	0.2979	-0.0388	-0.0565	28	✓
0.50	0.6071	0.3797	0.3125	-0.0520	-0.0747	24	✓

Note: a_w sensitivity always uses fixed input values. Reference: $a_w=0.25$. Other params: $N=20$, $N_{wake}=5$, $dpsi=10.0$ deg. $\bar{a}$ = span-averaged axial induction.