

Table 3 — Sensitivity: Blade Discretisation (TSR=8)

N	dist.	CT	CP	■ [-]	dCT	dCP	iters	conv.
5	Cosine	0.6714	0.4743	0.2279	+0.0123	+0.0199	19	✓
5	Constant	0.6789	0.4849	0.2240	+0.0198	+0.0305	19	✓
8	Cosine	0.6674	0.4658	0.2415	+0.0082	+0.0114	21	✓
8	Constant	0.6712	0.4747	0.2265	+0.0121	+0.0203	22	✓
10	Cosine	0.6638	0.4615	0.2420	+0.0047	+0.0072	29	✓
10	Constant	0.6696	0.4715	0.2297	+0.0105	+0.0171	19	✓
13	Cosine	0.6625	0.4591	0.2462	+0.0034	+0.0047	68	✓
13	Constant	0.6681	0.4683	0.2343	+0.0090	+0.0139	19	✓
15	Cosine	0.6608	0.4568	0.2476	+0.0016	+0.0024	47	✓
15	Constant	0.6676	0.4667	0.2371	+0.0084	+0.0123	26	✓
18	Cosine	0.6597	0.4553	0.2490	+0.0006	+0.0009	32	✓
18	Constant	0.6664	0.4644	0.2413	+0.0073	+0.0100	27	✓
20	Cosine	0.6591	0.4544	0.2503	+0.0000	+0.0000	49	✓
20	Constant	0.6651	0.4625	0.2420	+0.0060	+0.0081	30	✓
25	Cosine	0.6583	0.4532	0.2516	-0.0008	-0.0012	102	✓
25	Constant	0.6631	0.4596	0.2440	+0.0040	+0.0052	21	✓
30	Cosine	0.6573	0.4520	0.2528	-0.0018	-0.0024	109	✓
30	Constant	0.6622	0.4581	0.2458	+0.0031	+0.0037	24	✓

N	dist.	CT	CP	■ [-]	dCT	dCP	iters	conv.
50	Cosine	0.6552	0.4493	0.2549	-0.0039	-0.0051	183	✓
50	Constant	0.6593	0.4537	0.2503	+0.0002	-0.0006	421	✓

Reference: N=20, cosine. Other params: N_wake=5, dps=10.0 deg, a_w mode=iterated. a-bar = span-averaged axial induction.