

Table 4 — Sensitivity: Azimuthal Step (TSR=8)

dpsi [deg]	N_steps	CT	CP	■ [-]	dCT	dCP	iters	conv.
1.0	360	0.6606	0.4566	0.2495	+0.0015	+0.0023	65	✓
2.5	144	0.6604	0.4564	0.2496	+0.0013	+0.0020	60	✓
5.0	72	0.6600	0.4558	0.2498	+0.0009	+0.0014	47	✓
10.0	36	0.6591	0.4544	0.2503	+0.0000	+0.0000	49	✓
15.0	24	0.6582	0.4530	0.2509	-0.0009	-0.0014	92	✓
20.0	18	0.6570	0.4512	0.2516	-0.0021	-0.0032	500	✗
25.0	14	0.6559	0.4500	0.2512	-0.0032	-0.0044	163	✓
30.0	12	0.6541	0.4474	0.2519	-0.0050	-0.0070	149	✓
40.0	9	0.6512	0.4430	0.2539	-0.0079	-0.0114	42	✓
50.0	7	0.6530	0.4462	0.2510	-0.0061	-0.0082	42	✓
60.0	6	0.6437	0.4320	0.2602	-0.0154	-0.0224	41	✓
70.0	5	0.6506	0.4448	0.2512	-0.0085	-0.0096	44	✓
80.0	4	0.6522	0.4470	0.2494	-0.0069	-0.0074	39	✓
90.0	4	0.6534	0.4479	0.2477	-0.0057	-0.0065	63	✓

Reference: dpsi=10.0 deg. Other params: N=20, N_wake=5, a_w mode=iterated. a-bar = span-averaged axial induction.