

Table 3 — Sensitivity: Blade Discretisation (TSR=8)

N	dist.	CT	CP	■ [-]	dCT	dCP	iters	conv.
5	Cosine	0.6680	0.4692	0.2322	+0.0089	+0.0148	23	✓
5	Constant	0.6753	0.4791	0.2292	+0.0162	+0.0247	19	✓
8	Cosine	0.6661	0.4639	0.2432	+0.0070	+0.0095	21	✓
8	Constant	0.6679	0.4695	0.2310	+0.0088	+0.0151	23	✓
10	Cosine	0.6626	0.4597	0.2436	+0.0035	+0.0054	28	✓
10	Constant	0.6666	0.4669	0.2335	+0.0075	+0.0125	22	✓
13	Cosine	0.6620	0.4584	0.2469	+0.0029	+0.0040	59	✓
13	Constant	0.6658	0.4647	0.2372	+0.0066	+0.0103	23	✓
15	Cosine	0.6605	0.4564	0.2480	+0.0014	+0.0020	47	✓
15	Constant	0.6656	0.4638	0.2396	+0.0065	+0.0094	27	✓
18	Cosine	0.6597	0.4553	0.2490	+0.0006	+0.0009	32	✓
18	Constant	0.6652	0.4624	0.2430	+0.0060	+0.0080	26	✓
20	Cosine	0.6591	0.4544	0.2503	+0.0000	+0.0000	49	✓
20	Constant	0.6640	0.4607	0.2436	+0.0049	+0.0063	33	✓
25	Cosine	0.6585	0.4536	0.2514	-0.0006	-0.0008	122	✓
25	Constant	0.6623	0.4584	0.2450	+0.0032	+0.0040	21	✓
30	Cosine	0.6577	0.4525	0.2524	-0.0014	-0.0019	99	✓
30	Constant	0.6616	0.4572	0.2465	+0.0025	+0.0028	23	✓

N	dist.	CT	CP	■ [-]	dCT	dCP	iters	conv.
50	Cosine	0.6558	0.4503	0.2541	-0.0033	-0.0041	231	✓
50	Constant	0.6593	0.4537	0.2503	+0.0002	-0.0006	421	✓

Reference: N=20, cosine. Other params: N_wake=5, dps=10.0 deg, a_w mode=fixed=0.25. a-bar = span-averaged axial induction.