

Table 5 — Sensitivity: Wake Length (TSR=8)

N_wake	N_fil.	CT	CP	■ [-]	dCT	dCP	iters	conv.
1	36	0.7029	0.5257	0.1858	+0.0438	+0.0713	61	✓
2	72	0.6780	0.4841	0.2233	+0.0189	+0.0297	50	✓
3	108	0.6676	0.4673	0.2392	+0.0085	+0.0129	92	✓
4	144	0.6621	0.4590	0.2464	+0.0030	+0.0046	42	✓
5	180	0.6591	0.4544	0.2503	+0.0000	+0.0000	49	✓
6	216	0.6575	0.4518	0.2528	-0.0016	-0.0026	47	✓
7	252	0.6565	0.4502	0.2545	-0.0026	-0.0042	62	✓
8	288	0.6559	0.4492	0.2556	-0.0033	-0.0052	79	✓
9	324	0.6554	0.4484	0.2564	-0.0037	-0.0060	62	✓
10	360	0.6550	0.4478	0.2569	-0.0041	-0.0066	58	✓
11	396	0.6547	0.4474	0.2573	-0.0044	-0.0070	57	✓
12	432	0.6545	0.4471	0.2576	-0.0046	-0.0073	56	✓
13	468	0.6543	0.4468	0.2579	-0.0048	-0.0076	53	✓
14	504	0.6542	0.4466	0.2581	-0.0049	-0.0078	55	✓
15	540	0.6540	0.4464	0.2582	-0.0051	-0.0080	55	✓

Reference: N_wake=5. Other params: N=20, dpsi=10.0 deg, a_w mode=fixed=0.25. a-bar = span-averaged axial induction.