

**Table 3 — Sensitivity: Blade Discretisation (TSR=8)**

| N  | dist.    | CT     | CP     | dCT     | dCP     | iters | conv. |
|----|----------|--------|--------|---------|---------|-------|-------|
| 10 | Cosine   | 0.6626 | 0.4597 | +0.0035 | +0.0054 | 28    | ✓     |
| 10 | Constant | 0.6666 | 0.4669 | +0.0075 | +0.0125 | 22    | ✓     |
| 20 | Cosine   | 0.6591 | 0.4544 | +0.0000 | +0.0000 | 49    | ✓     |
| 20 | Constant | 0.6640 | 0.4607 | +0.0049 | +0.0063 | 33    | ✓     |
| 30 | Cosine   | 0.6577 | 0.4525 | -0.0014 | -0.0019 | 99    | ✓     |
| 30 | Constant | 0.6616 | 0.4572 | +0.0025 | +0.0028 | 23    | ✓     |
| 50 | Cosine   | 0.6558 | 0.4503 | -0.0033 | -0.0041 | 231   | ✓     |
| 50 | Constant | 0.6593 | 0.4537 | +0.0002 | -0.0006 | 421   | ✓     |

Reference: N=20, cosine. Other params: N\_wake=5, dps=10.0 deg, a\_w=0.25.