

Table 4 — Sensitivity: Azimuthal Step (TSR=8)

dpsi [deg]	N_steps	CT	CP	■ [-]	dCT	dCP	iters	conv.
1.0	360	0.6606	0.4566	0.2495	+0.0015	+0.0023	65	✓
2.5	144	0.6604	0.4564	0.2496	+0.0013	+0.0020	60	✓
5.0	72	0.6600	0.4558	0.2498	+0.0009	+0.0014	47	✓
10.0	36	0.6591	0.4544	0.2503	+0.0000	+0.0000	49	✓
15.0	24	0.6582	0.4530	0.2509	-0.0009	-0.0014	92	✓
20.0	18	0.6573	0.4515	0.2516	-0.0018	-0.0029	550	✓
25.0	14	0.6561	0.4502	0.2510	-0.0030	-0.0042	170	✓
30.0	12	0.6544	0.4477	0.2516	-0.0047	-0.0067	225	✓
40.0	9	0.6517	0.4437	0.2533	-0.0074	-0.0107	42	✓
50.0	7	0.6530	0.4462	0.2510	-0.0061	-0.0082	42	✓
60.0	6	0.6452	0.4342	0.2583	-0.0139	-0.0202	41	✓
70.0	5	0.6507	0.4450	0.2511	-0.0084	-0.0094	45	✓
80.0	4	0.6522	0.4470	0.2494	-0.0069	-0.0074	39	✓
90.0	4	0.6531	0.4477	0.2480	-0.0060	-0.0067	58	✓

Reference: dpsi=10.0 deg. Other params: N=20, N_wake=5, a_w mode=fixed=0.25. a-bar = span-averaged axial induction.