

Table 5 — Sensitivity: Wake Length (TSR=8)

N_wake	N_fil.	CT	CP	■ [-]	dCT	dCP	iters	conv.
1	36	0.7075	0.5329	0.1805	+0.0484	+0.0785	52	✓
2	72	0.6814	0.4893	0.2193	+0.0223	+0.0349	48	✓
3	108	0.6693	0.4699	0.2372	+0.0102	+0.0155	80	✓
4	144	0.6627	0.4598	0.2457	+0.0036	+0.0054	46	✓
5	180	0.6591	0.4544	0.2503	+0.0000	+0.0000	49	✓
6	216	0.6571	0.4512	0.2534	-0.0020	-0.0032	37	✓
7	252	0.6557	0.4490	0.2557	-0.0034	-0.0054	73	✓
8	288	0.6548	0.4475	0.2572	-0.0043	-0.0068	58	✓
9	324	0.6541	0.4465	0.2581	-0.0050	-0.0079	56	✓
10	360	0.6536	0.4457	0.2588	-0.0055	-0.0087	56	✓
11	396	0.6532	0.4452	0.2593	-0.0059	-0.0092	56	✓
12	432	0.6529	0.4447	0.2597	-0.0062	-0.0097	56	✓
13	468	0.6527	0.4444	0.2601	-0.0064	-0.0100	56	✓
14	504	0.6525	0.4441	0.2603	-0.0066	-0.0103	55	✓
15	540	0.6523	0.4438	0.2605	-0.0068	-0.0105	54	✓

Reference: N_wake=5. Other params: N=20, dpsi=10.0 deg, a_w mode=iterated. a-bar = span-averaged axial induction.