Material Safety Data Sheet

Version 3.4 Revision Date 09/03/2012 Print Date 01/07/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name Sodium cacodylate Buffer pH 6.5; 50 mM – Isopropanol 15% solution

Product Number 97068 Brand Sigma

Supplier Sigma-Aldrich

> 3050 Spruce Street SAINT LOUIS MO 63103

USA

+1 800-325-5832 Telephone Fax +1 800-325-5052 Emergency Phone # (For (314) 776-6555

both supplier and manufacturer)

Preparation Information

Sigma-Aldrich Corporation

Product Safety - Americas Region

1-800-521-8956

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Flammable liquid, Carcinogen, Target Organ Effect, Irritant

Target Organs

Nerves., Kidney, Cardiovascular system., Gastrointestinal tract, Liver

GHS Classification

Flammable liquids (Category 3)

Acute toxicity, Inhalation (Category 3)

Skin irritation (Category 3) Eye irritation (Category 2A)

Acute aquatic toxicity (Category 2)

Chronic aquatic toxicity (Category 3)

GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H226 Flammable liquid and vapour. H316 Causes mild skin irritation. H319 Causes serious eye irritation.

H331 Toxic if inhaled. H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P273 Avoid release to the environment.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P311 Call a POISON CENTER or doctor/ physician.

HMIS Classification

Health hazard: 2
Chronic Health Hazard: *
Flammability: 3
Physical hazards: 0

NFPA Rating

Health hazard: 2 Fire: 3 Reactivity Hazard: 0

Potential Health Effects

InhalationSkinMay be harmful if inhaled. Causes respiratory tract irritation.May be harmful if absorbed through skin. Causes skin irritation.

Eyes Causes eye irritation.

Ingestion May be harmful if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : Crystallization solution 8/Fluka kit no 18839

Component		Classification	Concentration
2-Propanol			
CAS-No. EC-No. Index-No.	67-63-0 200-661-7 603-117-00-0	Flam. Liq. 2; Eye Irrit. 2; STOT SE 3; H225, H319, H336	10 - 30 %
CAS-No. EC-No. Index-No.	124-65-2 204-708-2 033-002-00-5	Acute Tox. 3; Aquatic Acute 1; Aquatic Chronic 1; H301 + H331, H410	0.1 - 1 %

For the full text of the H-Statements and R-Phrases mentioned in this Section, see Section 16

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIREFIGHTING MEASURES

Conditions of flammability

Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous combustion products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature: 2 - 8 °C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
2-Propanol	67-63-0	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
Remarks	Eye & Uppe human carci	•	ory Tract irritation (Central Nervous System impairment Not classifiable as a
		STEL	400 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Eye & Uppe human carci	•	ory Tract irritation (Central Nervous System impairment Not classifiable as a
		TWA	400 ppm 980 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		STEL	500 ppm 1,225 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	400 ppm 980 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	The value in	mg/m3 is	approximate.	
		TWA	400 ppm 980 mg/m3	USA. NIOSH Recommended Exposure Limits
		ST	500 ppm 1,225 mg/m3	USA. NIOSH Recommended Exposure Limits

Sigma - 97068 Page 3 of 8

Sodium dimethylarsinate	124-65-2	TWA	0.01 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.01 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	0.01 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
Remarks	Confirmed h	uman card	inogen	
		TWA	0.5 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.5 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form clear, liquid Colour colourless

Safety data

pH 6.4

Melting no data available

point/freezing point

Boiling point no data available

Flash point 37.0 °C (98.6 °F) - closed cup

Ignition temperature no data available
Autoignition no data available

temperature

Lower explosion limit no data available
Upper explosion limit no data available
Vapour pressure no data available
Density 0.985 g/cm3
Water solubility no data available

Sigma - 97068 Page 4 of 8

Partition coefficient: no data available

n-octanol/water

Relative vapour no

density

no data available

Odour no data available
Odour Threshold no data available
Evaporation rate no data available

10. STABILITY AND REACTIVITY

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Vapours may form explosive mixture with air.

Conditions to avoid

Heat, flames and sparks.

Materials to avoid

Strong bases

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - no data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral LD50

no data available

Inhalation LC50

no data available

Dermal LD50

no data available

Other information on acute toxicity

no data available

Skin corrosion/irritation

no data available

Serious eye damage/eye irritation

Eyes: no data available

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Propanol)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

Sigma - 97068 Page 5 of 8

Teratogenicity

no data available

Specific target organ toxicity - single exposure (Globally Harmonized System)

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System)

no data available

Aspiration hazard

no data available

Potential health effects

Inhalation May be harmful if inhaled. Causes respiratory tract irritation.

Ingestion May be harmful if swallowed.

Skin May be harmful if absorbed through skin. Causes skin irritation.

Eyes Causes eye irritation.

Signs and Symptoms of Exposure

Nausea, Headache, Vomiting, narcosis, Central nervous system depression, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects

no data available

Additional Information

RTECS: Not available

12. ECOLOGICAL INFORMATION

Toxicity

no data available

Persistence and degradability

no data available

Bioaccumulative potential

no data available

Mobility in soil

no data available

PBT and vPvB assessment

no data available

Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toxic to aquatic life.

13. DISPOSAL CONSIDERATIONS

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

Sigma - 97068 Page 6 of 8

UN number: 1992 Class: 3 (6.1) Packing group: III

Proper shipping name: Flammable liquids, toxic, n.o.s. (2-Propanol, Sodium dimethylarsinate)

Reportable Quantity (RQ): Marine pollutant: No

Poison Inhalation Hazard: No

IMDG

UN number: 1992 Class: 3 (6.1) Packing group: III EMS-No: F-E, S-D

Proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (2-Propanol, Sodium dimethylarsinate)

Marine pollutant: No

IATA

UN number: 1992 Class: 3 (6.1) Packing group: III

Proper shipping name: Flammable liquid, toxic, n.o.s. (2-Propanol, Sodium dimethylarsinate)

15. REGULATORY INFORMATION

OSHA Hazards

Flammable liquid, Carcinogen, Target Organ Effect, Irritant

SARA 302 Components

The following components are subject to reporting levels established by SARA Title III, Section 302:

CAS-No. Revision Date 124-65-2 1993-04-24

SARA 313 Components

Sodium dimethylarsinate

The following components are subject to reporting levels established by SARA Title III, Section 313:

 CAS-No.
 Revision Date

 2-Propanol
 67-63-0
 1987-01-01

 Sodium dimethylarsinate
 124-65-2
 1993-04-24

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

2-Propanol	CAS-No. 67-63-0	Revision Date 1987-01-01
Sodium dimethylarsinate	124-65-2	1993-04-24

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Water	7732-18-5	
2-Propanol	67-63-0	1987-01-01
Sodium dimethylarsinate	124-65-2	1993-04-24

New Jersey Right To Know Components

	CAS-No.	Revision Date
Water	7732-18-5	
2-Propanol	67-63-0	1987-01-01
Sodium dimethylarsinate	124-65-2	1993-04-24

California Prop. 65 Components

WARNING! This product contains a chemical known to the State of	CAS-No.	Revision Date
California to cause cancer.	124-65-2	1987-02-27
Sodium dimethylarsinate		

16. OTHER INFORMATION

Text of H-code(s) and R-phrase(s) mentioned in Section 3

Acute Tox. Acute toxicity
Aquatic Acute Acute aquatic toxicity
Aquatic Chronic Chronic aquatic toxicity

Sigma - 97068 Page 7 of 8

Eye Irrit. Eye irritation Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapour.
H301 + H331 Toxic if swallowed or if inhaled
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.
STOT SE Specific target organ toxicity - single exposure

Further information

Copyright 2012 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Sigma - 97068 Page 8 of 8