Release 14.7 - xst P.20131013 (nt64)

--> Parameter TMPDIR set to xst/projnav.tmp

Total REAL time to Xst completion: 0.00 secs
Total CPU time to Xst completion: 0.10 secs

--> Parameter xsthdpdir set to xst

Total REAL time to Xst completion: 0.00 secs
Total CPU time to Xst completion: 0.10 secs

--> Reading design: mux_proper.prj

TABLE OF CONTENTS

===
*   Synthesis Options Summary   *
===
---- Source Parameters
Input File Name   : "mux_proper.prj"
Ignore Synthesis Constraint File   : NO

---- Target Parameters
Output File Name   : "mux_proper"
Output Format   : NGC
Target Device   : xc7a100t-3-csg324

---- Source Options
Top Module Name   : mux_proper
Automatic FSM Extraction   : YES
FSM Encoding Algorithm   : Auto
Safe Implementation   : No
FSM Style   : LUT
RAM Extraction   : Yes
RAM Style   : Auto
ROM Extraction   : Yes
Shift Register Extraction   : YES
ROM Style   : Auto

```
Resource Sharing                    : YES
Asynchronous To Synchronous         : NO
Shift Register Minimum Size         : 2
Use DSP Block                       : Auto
Automatic Register Balancing        : No

---- Target Options
LUT Combining                       : Auto
Reduce Control Sets                 : Auto
Add IO Buffers                      : YES
Global Maximum Fanout               : 100000
Add Generic Clock Buffer(BUFG)      : 32
Register Duplication                : YES
Optimize Instantiated Primitives    : NO
Use Clock Enable                    : Auto
Use Synchronous Set                 : Auto
Use Synchronous Reset               : Auto
Pack IO Registers into IOBs         : Auto
Equivalent register Removal         : YES

---- General Options
Optimization Goal                   : Speed
Optimization Effort                 : 1
Power Reduction                     : NO
Keep Hierarchy                      : No
Netlist Hierarchy                   : As_Optimized
RTL Output                          : Yes
Global Optimization                 : AllClockNets
Read Cores                          : YES
Write Timing Constraints            : NO
Cross Clock Analysis                : NO
Hierarchy Separator                 : /
Bus Delimiter                       : <>
Case Specifier                      : Maintain
Slice Utilization Ratio             : 100
BRAM Utilization Ratio              : 100
DSP48 Utilization Ratio             : 100
Auto BRAM Packing                   : NO
Slice Utilization Ratio Delta       : 5

=========================================================================


=========================================================================
*                           HDL Parsing                                 *
=========================================================================
Analyzing Verilog file "D:\BRB\dds-mini\W8_0.v" into library work
Parsing module <mux_proper>.

=========================================================================
*                            HDL Elaboration                            *
=========================================================================

Elaborating module <mux_proper>.

=========================================================================
*                           HDL Synthesis                               *
=========================================================================

Synthesizing Unit <mux_proper>.
    Related source file is "D:\BRB\dds-mini\W8_0.v".
```

```
    Summary:
        no macro.
Unit <mux_proper> synthesized.

=========================================================================
HDL Synthesis Report

Found no macro
=========================================================================

=========================================================================
*                       Advanced HDL Synthesis                          *
=========================================================================


=========================================================================
Advanced HDL Synthesis Report

Found no macro
=========================================================================

=========================================================================
*                         Low Level Synthesis                           *
=========================================================================

Optimizing unit <mux_proper> ...

Mapping all equations...
Building and optimizing final netlist ...
Found area constraint ratio of 100 (+ 5) on block mux_proper, actual ratio is 0.

Final Macro Processing ...

=========================================================================
Final Register Report

Found no macro
=========================================================================

=========================================================================
*                           Partition Report                            *
=========================================================================

Partition Implementation Status
-------------------------------

  No Partitions were found in this design.

-------------------------------

=========================================================================
*                            Design Summary                             *
=========================================================================

Top Level Output File Name         : mux_proper.ngc

Primitive and Black Box Usage:
------------------------------
# BELS                             : 4
#      GND                         : 1
#      INV                         : 1
```

```
#      LUT2                        : 2
# IO Buffers                       : 12
#      IBUF                        : 3
#      OBUF                        : 9

Device utilization summary:
---------------------------

Selected Device : 7a100tcsg324-3


Slice Logic Utilization:
 Number of Slice LUTs:                    3  out of  63400     0%
    Number used as Logic:                 3  out of  63400     0%

Slice Logic Distribution:
 Number of LUT Flip Flop pairs used:      3
   Number with an unused Flip Flop:       3  out of      3   100%
   Number with an unused LUT:             0  out of      3     0%
   Number of fully used LUT-FF pairs:     0  out of      3     0%
   Number of unique control sets:         0

IO Utilization:
 Number of IOs:                          12
 Number of bonded IOBs:                  12  out of    210     5%

Specific Feature Utilization:

---------------------------
Partition Resource Summary:
---------------------------

  No Partitions were found in this design.

---------------------------


================================================================================
Timing Report

NOTE: THESE TIMING NUMBERS ARE ONLY A SYNTHESIS ESTIMATE.
      FOR ACCURATE TIMING INFORMATION PLEASE REFER TO THE TRACE REPORT
      GENERATED AFTER PLACE-and-ROUTE.

Clock Information:
------------------
No clock signals found in this design

Asynchronous Control Signals Information:
----------------------------------------
No asynchronous control signals found in this design

Timing Summary:
---------------
Speed Grade: -3

   Minimum period: No path found
   Minimum input arrival time before clock: No path found
   Maximum output required time after clock: No path found
   Maximum combinational path delay: 0.761ns
```

```
Timing Details:
---------------
All values displayed in nanoseconds (ns)

=========================================================================
Timing constraint: Default path analysis
  Total number of paths / destination ports: 10 / 8
-------------------------------------------------------------------------
Delay:               0.761ns (Levels of Logic = 3)
  Source:            I0 (PAD)
  Destination:       out<7> (PAD)

  Data Path: I0 to out<7>
                                Gate     Net
    Cell:in->out      fanout   Delay   Delay  Logical Name (Net Name)
    ----------------------------------------  ------------
     IBUF:I->O             2   0.001   0.383  I0_IBUF (out_0_OBUF)
     LUT2:I0->O            1   0.097   0.279  out<7>1 (out_7_OBUF)
     OBUF:I->O                 0.000          out_7_OBUF (out<7>)
    ----------------------------------------
    Total                      0.761ns (0.098ns logic, 0.663ns route)
                                       (12.9% logic, 87.1% route)

=========================================================================

Cross Clock Domains Report:
---------------------------

=========================================================================


Total REAL time to Xst completion: 11.00 secs
Total CPU time to Xst completion: 11.23 secs

-->

Total memory usage is 4616492 kilobytes

Number of errors   :    0 (   0 filtered)
Number of warnings :    0 (   0 filtered)
Number of infos    :    0 (   0 filtered)
```