

DBMS Practical 6 Program Code:

```
CREATE TABLE o_rollcall(roll_no NUMBER, name VARCHAR2(25), div VARCHAR2(5));
```

```
CREATE TABLE n_rollcall(roll_no NUMBER, name VARCHAR2(25), div VARCHAR2(5));
```

```
INSERT INTO o_rollcall VALUES(1,'ASHUTOSH','A');
```

```
INSERT INTO o_rollcall VALUES(2,'ARYAN','A');
```

```
INSERT INTO o_rollcall VALUES(3,'SANKET','B');
```

```
INSERT INTO o_rollcall VALUES(1,'ASHUTOSH','A');
```

```
INSERT INTO o_rollcall VALUES(5,'ROHAN','B');
```

```
INSERT INTO o_rollcall VALUES(1,'ASHUTOSH','B');
```

```
CREATE OR REPLACE PROCEDURE cursor_imp AS
```

```
c_r NUMBER;
```

```
c_n VARCHAR2(25);
```

```
c_d VARCHAR2(5);
```

```
cursor c1 (roll NUMBER , n VARCHAR2 , d VARCHAR2) IS SELECT roll_no , COUNT  
(roll_no),name ,COUNT (name), div, COUNT (div) FROM o_rollcall GROUP BY  
roll_no,name,div HAVING (COUNT(roll_no)>1) AND (COUNT(name)>1) AND (COUNT(div)>1) ;
```

```
temp c1%rowtype;
```

```
BEGIN
```

```
    DELETE FROM n_rollcall;
```

```
    INSERT INTO n_rollcall SELECT * FROM o_rollcall;
```

```
    OPEN c1(c_r,c_n,c_d);
```

```
    LOOP
```

```
        FETCH c1 INTO temp;
```

```
        EXIT WHEN c1%NOTFOUND;
```

```
        DELETE FROM n_rollcall WHERE roll_no = temp.roll_no AND name =  
temp.name AND div = temp.div;
```

```
        INSERT INTO n_rollcall VALUES (temp.roll_no,temp.name,temp.div);
```

```
        dbms_output.put_line(temp.roll_no || temp.name || temp.div);
```

```
    END LOOP;
```

```
END;
```

```
/
```

```
BEGIN
```

```
    cursor_imp;
```

```
END;
```

```
/
```

```
select *from o_rollcall;
```

```
select *from n_rollcall;
```